A-A-58014
29 March 1993

COMMERCIAL ITEM DESCRIPTION

MOTOR GRADER, DED

This commercial item description covers a diesel-engine-driven pneumatic tired motor grader.

Salient characterics:

A. Operating weight (approximate). The operating weight shall be not less than 45,000 pounds. Weight includes lubricants, coolant, full fuel tank, operator, 14 foot blade, 20.50 - 25 inch, 12 PR (L2) traction tires, and full height ROPS cab. Ripper and push plate included.

B, Engine. The diesel engine shall have a 24-volt starting system with at least a 50 amp alternator, a heavy-duty starter, heavy-duty batteries and an ether starting aid of the measured shot type. The engine shall produce a minimum of 200 flywheel HP at 2000 RPM and shall be capable of operating on JP-8, Jet A or Jet A1 without being adversely affected. An engine coolant heater and compartment doors shall be provided.

C. Transmission. A direct-drive power shift eight speed transmission is required. A transmission guard shall be provided.

D. Brakes. Fully sealed, four wheel air actuated oil disc brakes with air dryer shall be provided.

E. Axles. Front - solid steel. Rear - full floating, forged, heat-treated steel.

F. Tandems. Tandems shall have a minimum sidewall thickness of .79", wheel axle spacing of at least 5'5", and a drive chain pitch of 2.24". Tandem drive train differential (lock-unlock).

G. Frame. Box-sectioned, articulated.

Beneifical comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: WR-ALC/LZMB Robins AFB, GA 31098-5609.

AMSC N/A FSC 3805

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:58Z
Check the source to verify that this is the currenversion before use.

H. Moldboard. Wear-resistant, high-carbon steel. Dimensions shall be no less than 14' X 27" X 1". Cutting edge shall be hardend steel with reversible overlay end bits.

I. Wheels. Interchangeable rim and wheel assemblies. Tubeless tires, six 20.50 - 25", 12 PR (L2) traction tires.

J. Cab. A sound suppressed, full height cab with ROPS and the following features:

1. Defroster fans, front and rear.
2. Heater and pressurizer.
3. Mirrors shall be located outside, on the left and right side of cab.
4. Windshield wipers, front and rear.
5. Adjustable control console.
6. Seat belt.

K. Blade range.

1.	Maximum blade position, angle, both sides	90°.
2.	Maximum lift above ground	16.5".
3.	Maximum depth of cut	17.25".
4.	Hydraulic blade tip	40° forward; 5° rearward

L. Drawbar. Box-sectioned, .5" thick A-frame with six widely spaced shoes to support the circle.

M. Circle. Hydraulically driven worm and gear with 360° circle rotation and circle drive slip clutch.

N. Hydraulics. Closed center, load-sensing hydraulic system with full hydraulic controls. A hydraulic arrangement shall be provided with one or more additional hydraulic valves available for rear mounted ripper or wing blade.

O. Steering. Full two cylinder hydraulic steering system for front wheels. Frame steering shall be hydraulically actuated.

P. Lights. Lights shall be furnished as follows:

1. Working lights center and rear.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

2. Cab directional and cab headlights.

3. Bar mounted flood lights.

4. Cab mounted emergency beacon.

Q. Capacities.(as a minimum)

1. Fuel tank - - - 75 gallons.

2. Radiator - - - 11 gallons.

3. Hydraulic system - 25 gallons.

R. Additional equipment.

1. Push plate.

2. Ripper-scarifier.

3. Articulation indicator.

S. Instrumentation. Contractor's standard.

T. Safety. The grader shall conform to Federal Laws and Regulations governing noise, air pollution and other health and safety requirements which are in effect for this type of equipment at the time of contract award. The grader shall have a horn and backup alarm.

U. The vehicle furnished must be the latest model as of the date of award (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-39(f)(2)(ii)(A)) for at least three years immediately preceding the issuance date of the solicitation. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements.

NOTE TO OFFERORS: Offerors shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years immediately preceding the issuance date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:58Z
Check the source to verify that this is the currentversion before use.

(2) Total sales of the item to the general public during the three years immediately preceding the issuance date of the solicitation.

(3) Length of time the item has been sold in the commercial market place.

(4) Points of contact and phone numbers of customers to which the item has been sold in the commercial market place.

(5) Other pertinent information necessary to determine that the item is an established commercial item.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements.

Recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, and as implemented by Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities, labeling, and marking shall be as specified in the contract and/or order. Data plates shall be in accordance with MIL-STD-1223.

NOTES

a. Unless otherwise specified the grader(s) shall be painted dark green, 24052 of FED-STD-595.

b. Commercial manuals to include parts manual, and operation and maintenance manuals shall be supplied with each grader. (Two copies of each shall be supplied).

c. Type tires required, if not as specified.

d. Rustproofing, if required shall be as specified.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:58Z
Check the source to verify that this is the currentversion before use.

e. Equipment/features/requirements if different, shall be as specified.

f. Markings/identification information, if required shall be as specified.

Custodian:
AIR FORCE-99

Preparing Activity:
AIR FORCE-84

Project number 3805 - 0154

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.