MILITARY SPECIFICATION

AMPLIFIER, ELECTRONIC CONTROL ASU-3/A

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for one type of remote attitude amplifier, designated ASU-3/A.

2. REFERENCED DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards of the issue in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	Boxes, Wood, Cleated Plywood
PPP-B-636	Box, Shipping, Fiberboard

MILITARY

MIL-P-116	Preservation-packaging, Methods Of
MIL-C-5541	Chemical Conversion Coatings On Aluminum And Aluminum Alloys
MIL-I-6181	Interference Control Requirements, Aircraft Equipment
MIL-S-6872	Soldering Process, General Specification For
MIL-S-7742	Screw Threads, Standard, Optimum Selected Series, General Specification For
MIL-A-8625	Anodic Coatings, For Aluminum And Aluminum Alloys
MIL-I-26359	Indicator, Attitude, Remote ARU-4/A
MIL-C-83488	Coatings, Aluminum, Ion Vapor Deposited

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODS, Federal Center, Battle Creek MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

DOD-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking For Shipment And Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-143	Standards And Specifications, Order Of Precedence For The Selection Of
MIL-STD-794	Parts And Equipment, Procedures For Packaging And Packing Of
MIL-STD-810	Environmental Test Methods
MIL-STD-889	Dissimilar Metals

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Materials.

3.3.1 Fungus-proof materials. Materials that are nutrients for fungi shall not be used where it is practical to avoid them. Where used and not hermetically sealed, they shall be treated with a fungicidal agent acceptable to the procuring activity. However, if they will be used in a hermetically sealed inclosure, fungicidal treatment will not be necessary.

3.3.2 Nonmagnetic materials. Nonmagnetic materials shall be used for all parts except where magnetic materials are essential.

3.3.3 Metals. Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to fuels, salt spray, or atmospheric conditions likely to be met in storage or normal service.

3.3.4 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

3.3.5 Corrosive fumes. The materials, as installed in the amplifier and under the service conditions specified herein, shall not liberate deleterious fumes.

3.3.6 Protective treatment. When materials are used in the construction of the amplifier that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the performance requirements of this specification. The use of any protective coating that will crack, chip, or scale with age or extremes of climatic and environmental conditions shall be avoided.

3.4 Design and construction.

3.4.1 The amplifier shall consist of two channels of tubeless construction and associated power supply. The amplifier covered by this specification is intended for use with the ARU-4/A remote attitude indicator in accordance with MIL-I-26359. The amplifier shall be hermetically sealed and in accordance with figure 1.

3.4.2 Means shall be included in the amplifier for a locking type roll trim adjustment. This installation adjustment shall be available from the outside of (and on the connector end of) the amplifier case and provide for ±3° minimum trim of the ARU-4/A remote indicator. The letter "R" shall be stamped directly above the adjustment and painted color No. 37038 of FED-STD-595.

3.4.3 Electrical power requirements. The power supplied to the amplifier shall be single phase, 115V ±10 percent 400 Hz. The power consumption shall not exceed 20 va.

3.4.4 Electrical Connector. The electrical connector shall be a Bendix Part No. PT02H-14-19P, or equal, for a hermetically sealed application. The electrical connections shall be as shown on table I.

3.5 Performance. The amplifier shall be capable of operating satisfactorily when subjected to the following conditions:

a. Pitch and roll null. Pitch and roll null output not to exceed 8V

b. Voltage outputs. Not to exceed the limits specified in 4.4.5

c. Low voltage operation. Satisfactory operation when operated at 103V and 380 Hz

d. Environmental

(1) Temperature. Temperature ranging from -54°C to +71°C

(2) Low Temperature Exposure. After prolonged exposure at -62.5°C

(3) Temperature Shock. Temperature shock fluctuating from 85°C to -40°C

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

TABLE I

Amplifier Connections

Function	Connector Pin
Reference +90° (motor fixed phase)	C
Ground (Power)	A
115V ±10% rms, 400 Hz	B
Signal ground	V
INPUTS	
Roll	G
Pitch	M
Rate, damping - pitch	U - T
Rate, damping - roll	S - N
Trim, pitch (8V 400 Hz, phase B to 4V 400 Hz, phase B +180°)	K
OUTPUTS	
Roll	E
Pitch	P
Rate, gen. excitation - 30V 400 Hz phase B	R
18V 400 Hz, phase B	H
8V 400 Hz, phase B	L
4V 400 Hz, phase B +180°	J

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

(4) Altitude. Altitude ranging from sea level to 100,000 feet

(5) Humidity. Relative humidity up to 100 percent including conditions wherein condensation takes place in the form of both water and frost

(6) Fungus. Fungus growth as encountered in tropical climates

(7) Rain. Rainfall as encountered in any locale

(8) Salt Spray. Exposure to salt sea atmosphere

(9) Vibration. Vibration incident to service use

(10) Acceleration. When subjected to an acceleration of 20g.

3.5.1 Dielectric. The amplifier shall withstand a potential of 500V dc when applied between any electrical pin contact and any part of the case for a period of 10 seconds.

3.5.2 Hermetic seal. The leak rate shall not exceed 10 percent after 1000 hours of operation at 1 atmosphere differential pressure.

3.5.3 Radio interference suppression. Radio interference suppression requirements shall conform to MIL-I-6181.

3.5.4 Life. The amplifier shall operate satisfactorily for 1000 hours without interruption.

3.6 Interchangeability. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The item identification and part number requirements of DOD-STD-100 shall govern the manufacturer's part numbers and changes thereto.

3.7 Filling medium. The filling medium shall be of at least 98 percent purity, free of dust particles and containing not more than 0.006 milligrams of water vapor per liter (dew point -65°C) at the filling pressure. The filling medium shall be 100 percent helium, a mixture of 88 percent nitrogen and the remainder helium or 95 percent helium and 5 percent CO_2. The absolute pressure of the filling medium in the case shall be approximately 1 atmosphere. Where practicable the 100 percent helium filling medium shall be utilized.

3.8 Weight. The weight of the amplifier shall not exceed 2.0 pounds.

3.9 Soldering. Soldering shall be accomplished in accordance with MIL-S-6872.

3.10 Screw threads. Unless otherwise specified, the threads of all machine screws shall conform to MIL-S-7742.

3.11 Finishes and protective coatings.

3.11.1 Aluminum alloy parts. Aluminum alloy parts shall be covered with an anodic film conforming to MIL-A-8625 except as follows:

3.11.1.1 Dials, small holes, and case inserts need not be anodized.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

3.11.1.2 Aluminum alloys which do not anodize satisfactorily shall be coated with a chemical film in accordance with MIL-C-5541.

3.11.1.3 Where the primary purpose of the treatment is to afford a suitable paint base, chemical treatments in accordance with MIL-C-5541 may be used in lieu of anodizing.

3.11.1.4 Castings containing nonaluminum alloy integral inserts may be treated with a chemical film in accordance with MIL-C-5541 in lieu of anodizing.

3.11.1.5 When abrasion resistance is a factor, chemical films in accordance with MIL-C-5541 shall not be used in lieu of anodizing.

3.11.1.6 Parts in a hermetically sealed container need not be anodized.

3.11.1.7 When the part is plated with tin over a copper flash, the part need not be anodized.

3.11.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the cognizant engineering activity. Cadmium plating must be avoided when satisfactory alternative processes can be used.

3.12 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.13 Workmanship.

3.13.1 General. The amplifier, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness and thoroughness of soldering, wiring, impregnation or coils, marking or parts and assemblies, welding, and brazing, painting, riveting, machine-screw assemblies, and freedom of parts from burrs and sharp edges.

3.13.2 Dimensions. Dimensions and tolerances not specified shall be as close as is consistent with the best shop practices. Where dimensions and tolerances may affect the interchangeability, operation, or performance of the amplifier, they shall be held or limited accordingly.

3.13.3 Screw assemblies. Assembly screws and bolts shall be tight. The word "tight" means that the screw or bolt cannot be appreciably tightened further without damage or injury to the screw or bolt or threads.

3.13.4 Riveting. Riveting operations shall be carefully performed to insure that the rivets are tight and satisfactorily headed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Classification of tests. The inspection and testing of the amplifier shall be classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T08:28Z
Check the source to verify that this is the current version before use.

a. Acceptances tests. See 4.2

b. Preproduction tests. See 4.5

4.2 Acceptance tests. Acceptance tests shall consist of:

a. Individual tests

b. Sampling plans and tests

4.2.1 Individual tests. Each amplifier shall be subjected to the following tests as described under 4.4 Test methods:

a. Examination of product

b. Pitch and roll null

c. Sensitivity and phasing

d. Rate signal and mixing

e. Voltage outputs

4.2.2 Sampling plans and tests.

4.2.2.1 Sampling plan A. One amplifier selected at random from each 100 amplifiers or less produced on the contract or order shall be subjected to the following tests as described under 4.4 Test methods:

a. Individual tests

b. Low voltage operation

c. Low temperature operation

d. High temperature operation

e. Dielectric

f. Hermetic seal

4.2.2.2 Sampling plan B. Unless otherwise specified, three amplifiers selected at random from the first 15 items of the contract or order shall be subjected to the following tests as described under 4.4 Test methods, and as specified in the following schedule.

a. Sampling plan A tests

b. Radio noise interference

c. High temperature exposure

d. Altitude-low temperature

e. Temperature shock

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

f. Humidity

g. Fungus

h. Rain

i. Salt spray

j. Sand and dust

k. Vibration failure

l. Acceleration

m. Life

NOTE: At the option of the procuring activity the tests may be divided into three groups as follows, to be conducted on three amplifiers, if a need exists to expedite tests. Each amplifier shall meet the requirements of all the individual tests after completing the group of specific tests to which submitted.

Group I	Group II	Group III
Radio noise interference	Humidity	Vibration failure
High temperature exposure	Fungus	Acceleration
Low temperature	Rain	Life
Temperature	Salt spray	
	Sand and dust	

4.2.2.3 Rejection and retest. When one item selected from a production run fails to meet the specification, no items still on hand or later produced shall be accepted until the extent and cause of failure are determined. After corrections have been made, all necessary tests shall be repeated.

4.2.2.3.1 Individual tests may continue. For operational reasons, individual tests may be continued pending the investigation of a sampling test failure. But final acceptance of items on hand or produced later shall not be made until it is determined that the items meet all the requirements of the specification.

4.2.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.3 Test conditions.

4.3.1 Standard atmospheric conditions. Whenever the pressure and temperature existing at the time of the test are not specified definitely, it is understood that the test is to be made at atmospheric pressure (approximately 29.92 inches Hg) and at room temperature (approximately +25°C). When tests are made with atmospheric pressure or room temperature differing materially from the above values, proper allowance shall be made for the difference from the specified condition.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

4.3.2 Connections. Whenever it is specified that the amplifier shall be properly connected, it shall be understood that the amplifier shall be connected to a standard piece of test equipment.

4.3.3 Test equipment. When reference is made to standard test equipment, it shall be understood to mean a panel simulating signals from Eclipse-Pioneer AY-200-1 transmitters, or equal, (source impedance of less than 100 ohms) and loads simulating the ARU-4/A remote indicator, or equivalent.

a. Load the pitch and roll outputs with an impedance 69.7 +J149.3 at 400 Hz.

b. Short K to A, G to A, M to A.

4.4 Test methods.

4.4.1 Examination of product. The amplifier shall be inspected to determine compliance with this specification with respect to materials, workmanship, and marking.

4.4.2 Pitch and roll null. Supply power to the amplifier under conditions of test a and b of 4.3.3. Adjust the roll trim pot for minimum roll output. The pitch and roll output shall be a maximum of 4.5V.

4.4.3 Sensitivity and phasing. Remove short from M to A and inject a pitch signal of 150 mv ±2 percent ØB. The pitch output (pin P) shall be 14v minimum ØB ±20°. Repeat the same tests for roll removing short from G to A and reading roll output on pin E. The voltages and tolerances shall be the same as for pitch.

4.4.4 Rate signal and mixing. Re-establish the test conditions of 4.4.3. Supply a signal of 100 mv ±5 percent ØB to terminals U and T (pitch rate). Then apply the same signal to terminals S and N (roll rate). In each case the pitch and roll outputs (P and E) shall be 14V minimum, ØB +180° ±20°. Note: The roll trim pot must be on its electrical zero during this test.

4.4.5 Voltage outputs. With the amplifier energized with 115 ±2V 400 Hz; the following outputs shall be present:

Pin	Voltage and Phase
R	30 ±6 percent, 400 Hz phase B
H	18 ±8.5 percent 400 Hz phase B
L	8 ±3 percent 400 Hz phase B
J	4 ±3 percent 400 Hz phase B +180°

4.4.6 Low voltage operation. The amplifier shall be properly connected. The alternating current shall be reduced to 103V and 380 Hz. The amplifier shall meet the requirements as specified in 4.4.2, 4.4.3 and 4.4.4.

4.4.7 Low temperature operation. The amplifier shall be properly connected, except that no power shall be applied, and placed in a chamber at a temperature of -54°C for a period of 4 hours. At the end of this period, and while the amplifier is at the reduced temperature, power shall be applied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

The amplifier shall meet the requirements of 4.4.2 and 4.4.3 except the inputs shall be 300 mv and the output shall be 12V minimum, ØB±30°. The amplifier shall meet the requirements of 4.4.4 except the inputs shall be 200 mv and output shall be 12V minimum.

4.4.8 High temperature operation. The amplifier shall be properly connectd and placed in a chamber at a temperature of 71°C and operated for a period of 4 hours. The inputs during this soak period shall be 100 mv, 400 Hz to both the pitch and roll channels. At the end of this period and while the amplifier is at the high temperature, it shall meet the requirments specified in 4.4.2, 4.4.3, and 4.4.4.

4.4.9 Dielectric. A potential of 500V dc shall be applied between isolated pins and between pins and the case for a period of 10 seconds. There shall be no breakdown of insulation.

4.4.10 Hermetic seal test. The maximum allowable leak rate shall not result in more than 10 percent loss of contamination of the filling gas mixture after 1000 hours at approximately 1 atmosphere differential pressure.

4.4.11 Radio noise interference. The radio noise interference test shall be in accordance with MIL-I-6181.

4.4.12 Environmental. The amplifier shall be subjected to the following tests, conducted in accordance with the specified procedures of MIL-STD-810 and as specified herein.

4.4.12.1 High temperature exposure. Method 501.1, Procedure I, except delete steps 4 through 7, for a period of 24 hours and properly connected, except that no power shall be applied. At the end of this period and while still at the high temperature, the amplifier shall meet the requirments specified in 4.4.2 and 4.4.4.

4.4.12.2 Altitude and low temperature exposure tests. Low temperature test shall be in accordance with Method 502.1, Procedure I, except that the temperature in step 2 shall be -62°C (-80°F) and the exposure period shall be 72 hours. The temperature for step 4 shall be -54°C (-65°F). At the conclusion of step 5 and while still at -54°C (-65°F) temperature, the pressure within the chamber shall be reduced to the equivalent of 100,000 ± 500 feet altitude. At these conditions, the amplifier shall meet the requirements specified in 4.4.7.

4.4.12.3 Temperature shock. The amplifier shall be tested in accordance with Method 503.1, Procedure I, except that the chamber temperature in steps 1 and 4 shall be 85°C (185°F) and the chamber temperature of step 2 shall be -40°C (-40°F). After the test, the amplifier shall meet the requirements of all individual tests.

4.4.12.4 Humidity. The amplifier shall be tested in accordance with Method 507.1, Procedure I, except in step 2, delete 65°C (149°F) and substitute 71°C (160°F), in step 4, delete 85 percent relative humidity and 30°C (86°F) and substitute 95 percent relative humidity and 20°C to 38°C (68°F to 100°F); in step 5, delete the last sentence; delete steps 6 and 7 and substitute: Step 6 at the end of the tenth cycle, the equipment shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

returned to standard conditions. There shall be no evidence of corrosion or rusting of the internal or external parts of the amplifier, except for the electrical connector.

4.4.12.5 Fungus. The amplifier shall be tested in accordance with Method 508.2, Phase I and Phase II for a period of 28 days. The amplifier shall be suspended in the test chamber simulating its normal mounting configuration.

There shall be no deterioration which would adversely effect subsequent operation and fungus growth shall not be supported.

4.4.12.6 Rain. The amplifier shall be tested in accordance with Method 506.1, Procedure II except that the rate of falling rain in step 2 shall be 4 + 1 inches per hour. Upon removal from the chamber, the amplifier shall meet the requirements specified in 4.4.2.

4.4.12.7 Salt fog. The amplifier shall be subjected to the salt fog test, Method 509.1, Procedure I. The salt fog exposure shall be for a period of 50 hours. At the end of the 50-hour period, the amplifier shall be subjected to the individual tests specified herein. No damage shall result from this test, and the tolerances specified under the individual tests shall apply.

4.4.12.8 Dust (fine sand). The amplifier shall be subjected to the dust test, Method 510.1, Procedure I, except in step 1, delete the second sentence and substitute: Adjust the air velocity to 300 ± 200 feet per minute. Delete steps 2 and 3 and substitute: After 6 hours at the above conditions, the temperature shall be raised to and maintained at 71°C(160°F). These conditions shall be maintained for 6 hours.

4.4.12.9 Vibration. The amplifier shall be subjected to the vibration tests of Method 514.2, Procedure I, Part I; equipment category b.1; table 514.2-II; figure 514.2-2, curve D except that, the amplitude shall be as follows: between 5 and 10 Hz it shall be 0.080 inch double amplitude, between 10 and 15 Hz, it shall be ± 0.41g, between 15 and 75 Hz, it shall be 0.036 inch double amplitude and between 75 and 500 Hz, it shall be ± 10g. The cycling test frequency shall be 5 to 500 Hz and back to 500 Hz. The entire cycling and resonant testing shall be conducted at a temperature of 71°C(160°F). During the entire test, the amplifier shall be energized with standard electrical power and shall be connected to the standard test equipment. After the vibration tests, the amplifier shall meet the requirements specified in the individual tests. No damage to any part of the amplifier shall result from the vibration.

4.4.13 Acceleration. The amplifier not operating shall be mounted in its normal operating position and accelerated first along its vertical axis and then along each of two axes that are perpendicular to the vertical axis and to each other. The amplifier shall be subjected to an acceleration of 20g in each of the above axes for a period of 1 minute. At the end of this acceleration the amplifier shall meet the requirements for the individual tests. No damage to the amplifier shall result from this test.

4.4.14 Life. The amplifier shall be properly connected and operated for a period of 1000 hours. There shall be no failure during the test. After the test, the amplifier shall meet the requirements specified for individual

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

tests. The procuring activity shall reserve the right to perform this test as a 1000-hour continuous life test without interruption, or a 1000-hour life test with cycling, with the system operating continuously for a 22-hour period, then shut off for a 2-hour period. The test time of the life test shall then be computed from the summation of the 22-hour operation periods.

4.5 Preproduction testing.

4.5.1 Preproduction test sample. The preproduction test samples shall consist of three amplifiers. Samples shall be identified with the manufacturer's own part number and any additional information required by the letter of authorization.

4.5.2 Preproduction required. Prior to actual procurement, the product which this specification covers shall pass the preproduction tests specified herein. If the product is later modified in any way, the modified form shall be subjected to and shall pass the same preproduction tests.

4.5.3 Preproduction tests. The preproduction tests shall consist of all the tests specified in 4.4 Test methods.

4.6 Packaging inspection.

4.6.1 Quality conformance. The inspection of the preservation-packaging and interior package marking shall be in accordance with group A and B quality conformance requirements, Section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of applicable container specification and the marking requirements of MIL-STD-129.

4.6.2 First article. When the unit container is capable of serving as the shipping container, first article inspection and rough handling tests as outlined in Section 4 of MIL-P-116, shall be accomplished followed by a functional test of the unit to insure freedom from operational malfunction.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be Level A or C as specified by procuring activity.

5.1.1 Level A .

5.1.1.1 Cleaning. Unit shall be cleaned in accordance with Process C-1 of MIL-P-116.

5.1.1.2 Drying. Immediately after cleaning, the unit shall be dried following any one or combination of the drying procedures of MIL-P-116.

5.1.1.3 Preservation application. Not required.

5.1.1.4 Unit packaging. Unless otherwise specified by the procuring activity, each unit shall be packaged in quantity unit packs of one each in accordance with method IC-1 of MIL-P-116. Overbox each completed pack in a PPP-B-636 fiberboard, weather-resistant class box. Cushioning material between bag and container shall be of a type, density and thickness that will

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

protect the unit from impact shock damage when tested as specified in paragraph 4.6 of this specification.

5.1.2 Level C. Unit shall be packaged as indicated for Level A except that a PPP-B-636 domestic class box shall be used as the unit container.

5.2 Packing. Packing shall be level A, B, or C as specified.

5.2.1 Level A. Unless otherwise specified by procuring agency, units packaged as specified in 5.1 shall be packed in shipping containers conforming to specification.

5.2.2 Level B. Unless otherwise specified, units packaged as in 5.1 shall be packed in shipping containers conforming to PPP-B-636.

5.2.3 Level C. Packaged units shall be packed in shipping containers that afford adequate protection against damage during direct domestic shipment from supply source to first receiving activity. Packs shall conform to applicable carrier rules and regulations.

5.3 Marking. In addition to any special marking required by the contract, each unit package and shipping container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The ASU-3/A amplifier covered by this specification is intended for use in aircraft in conjunction with a ARU-4/A remote attitude indicator.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Levels of packaging and packing required and reinspection date marking

c. When sampling plan B tests will not be conducted

6.3 Changes from the previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Air Force - 99

Preparing activity:
Air Force - 99

Reviewer:
Air Force - 11

Project No:
6610-F330

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 PREVIOUS EDITION WILL BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:29Z
Check the source to verify that this is the current version before use.