SUPERSEDING
MIL-C-26339B
25 May 1967

MILITARY SPECIFICATION

CARRIER, PASSENGER, CARGO, UTILITY, FULL TRACKED, OVER-THE-SNOW TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers five sizes of cargo, utility and passenger carrying, full tracked, arctic tracklaying vehicles.

1.2 Classification. Cargo carriers shall be of the size specified (see 6.2).

Size 1 - Carrier, Cargo, Flatbed, With Cab, 2 Passenger
Size 2 - Carrier, Cargo, Flatbed, With Cab, 4 Passenger
Size 3 - Carrier, Cargo, Flatbed, With Cab, 6 Passenger
Size 4 - Carrier, Combination Cab and Cargo Type Body, 10 Passenger
Size 5 - Carrier, Utility, With Cab, With Snow Plow Blade (see 3.12).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

F-P-666	Primer, Pressure, Internal Combustion Engine (Cold Starting Aid) and Primer, Cartridges
W-B-131	Battery, Storage; Vehicular, Ignition, Lighting and Starting
O-E-915	Extinguisher, Fire, Dry-Chemical (Hand Portable)

Military

MIL-A-11755	Antifreeze, Arctic Type
MIL-A-27302	Arrestor, Spark, Exhaust, Internal Combustion Engine
MIL-C-1283	Can, Gasoline, Military, 5-Gallon
MIL-P-514	Plate, Identification and Plate, Identification Transportation Data

STANDARDS

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODSAC, Federal Center, Battle Creek, MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

Military

MIL-STD-810	Environmental Test Methods
MIL-STD-1223	Administrative Wheeled Vehicle Treatment, Painting and Data Plate Standard
MIL-STD-1472	Human Engineering Design Criteria for Military Systems, Equipment and Facilities
MS 51335	Pintle Assembly, Towing

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Standards and Recommended Practices

J551	Measurement of Electromagnetic Radiation from Motor Vehicles (20-1000 Mhz)
J552	External Electromagnetic Radiation Suppressors
J537	Storage Batteries

(Information as to the availability of this handbook may be obtained from the Society of Automotive Engineers, Inc., Two Pennsylvania Plaza, New York, NY 10001.)

THE TIRE AND RIM ASSOCIATION, INC. (TRA)

Yearbook

(Application for copies should be addressed to the Tire and Rim Association, Inc., 200 W. Market St., Akron, OH 44313.)

DEPARTMENT OF TRANSPORTATION (DOT)

Federal Motor Carrier Safety Regulations (FMCSR)

(Application for copies should be addressed to the US Department of Transportation, Federal Highway Administration, Washington, DC 20591.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish a carrier for first article inspection (see 4.2.1).

3.2 Standard chassis components and accessories. Except as specified in this specification, the chassis components, assemblies, and accessories to be delivered under this contract shall be standard or optional items which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data. All chassis items considered standard equipment on the vehicle model to be supplied under applicable contract shall be furnished except when optional equipment is required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

3.3 Rustproofing. The vehicle shall be rustproofed in accordance with the requirements of MIL-STD-1223.

3.4 Drain plugs. All drain plugs installed throughout the vehicle for the purpose of draining lubricants shall be the permanent/magnet type and shall be readily accessible. Lubrication system shall permit use of arctic lubricants.

3.5 Design and construction. The carrier shall be a gasoline or diesel engine driven tracklaying vehicle designed for carrying cargo and passengers and shall be capable of meeting the requirements specified herein.

3.5.1 Weights and dimensions. The vehicle shall provide for weights and dimensions as follows:.

	Size 1	Size 2	Size 3	Size 4	Size 5
a. Curb weight, lbs (Max)	8,660	8,660	8,660	8,660	11,000
lbs (Min)					9,500
b. Ground Pressure, lbs per sq inch (Max) at curb wt.	.98	.98	.98	.98	.98
c. Overall Width, Inches (Max)	118	118	118	118	150
d. Overall Height, Inches (Max)	102	102	102	102	102
e. Overall Length in (Max)	190	190	190	190	190
f. Ground Clearance, Inches (Min)	11	11	11	11	11
g. Inside Body Height, Inches (Min)	44	44	44	44	44
h. Inside Body Width, Inches (Min)	70	70	70	70	30
i. Load Space:					
Width, Inches (Min)	70	70	70	70	N/A
Length, Inches (Min)	70	48	48	96	N/A

3.5.2 Maintainability. The carrier shall be designed so that normal adjustments, repairs, lubrication and overhaul can be readily accomplished by the use of general purpose tools with a minimum removal of or disturbance of other elements of the carrier.

3.6 Performance. The carrier shall meet the load carrying, load towing and mobility requirements under the environmental conditions specified herein with the engine derated to 6,000 feet altitude (engine manufacturer's data shall be furnished.

3.6.1 Environmental conditions. The carrier shall be capable of satisfactory operation and storage in ambient temperatures ranging from -30°F to +65°F and shall be capable of withstanding rain as encountered in any locale. When winterization is specified (see 3.13), the carrier shall be capable of satisfactory operation and storage in ambient temperatures ranging from -70°F to +65°F.

3.6.2 Load carrying and towing capability. The carrier shall be capable of

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

carrying the following cargo and passengers.

Size 1 - Operator, one passenger, and cargo load of 2000 pounds minimum evenly distributed over the cargo space.

Size 2 - Operator, three passengers, and cargo load of 1650 pounds minimum evenly distributed over the cargo space.

Size 3 - Operator, 5 passengers and a cargo load of 1300 pounds minimum evenly distributed over the cargo space.

Size 4 - Operator and 9 passengers and operator and a cargo load of 1575 pounds minimum evenly distributed over the cargo space.

Size 5 - Operator only.

The carriers shall be capable of towing a trailer and cargo sled having a gross weight of 1500 pounds. Full load consists of curb weight, operator, passengers, and payload. For purposes of this specification, operator weight is equivalent to 175 pounds.

3.6.3 Mobility. When fully loaded, the carrier shall be capable of operating satisfactorily over hard packed level snow and smooth level ground at a speed of not less than 15 miles per hour (mph) (11 mph for size 5 vehicles) and not more than 25 mph for at least 120 miles without damage or refueling. Vehicle shall be capable of being operated at medium speeds (4-10 mph) for extended periods of time in mountainous terrain without overheating the engine and without failure. The vehicle shall develop a drawbar pull of not less than 13,000 pounds on snow surface, for size 5.

3.6.3.1 Turning. Carrier turning radius for left and right turns shall not exceed 15 feet and shall be measured from the pivot point to inside edge of inner track.

3.6.3.2 Gradeability. The fully loaded carrier shall be capable of ascending and descending continuous grades of not less than 80 percent (%). The fully loaded carrier shall be capable of operating, stopping and starting on a side slope of not less than 60%.

3.7 Chassis.

3.7.1 Engine. The engine, complete with all necessary components and accessories, shall be a commercial industrial class, liquid cooled, internal combustion, four-stroke cycle, gasoline type or a liquid cooled, internal combustion four-stroke cycle, diesel type. If gasoline engine is furnished, it shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at engine speed not more than the manufacturer's recommended operating speed. The engine shall have not less than 6 cylinders if gas type and four cylinders if diesel type and shall incorporate a crankcase ventilation system. The engine shall meet the operational requirements contained herein, including the side slope ability. The engine shall be equipped with a locking hand throttle located on the instrument panel. The engine shall start within five minutes and be ready for full load operation within fifteen minutes in any ambient temperature specified in 3.6.1. When specified (see 6.2), a fluid priming system, conforming to F-P-666, Type

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

I, size 2, shall be completely installed; only steel clad, corrosion-resistant cartridges shall be used. A lubricating oil filter of the full flow type shall be furnished. The engine shall be furnished with an intake air cleaner and when the cleaner is of the oil bath type, its oil capacity shall be not less than one pint. The thermostat furnished for the engine cooling system shall be of the range from 170°F to 195°F.

3.7.2 Fuel tank. The fuel tank furnished shall be located rearward of the cab on sizes 1, 2, 3 and 5 and rearward of the operator's seat on size 4 vehicles, and shall provide capacity necessary to conform to 3.6.3. The tank vent and filler lines shall be conveniently located so as to prevent gasoline fumes and leakage inside the vehicle.

3.7.3 Transmission. An automatic or hydrostatic transmission shall be provided. The automatic transmission shall have a minimum of three forward speeds and 1 reverse speed and shall provide for driver selection of individual gears and ranges of gears. The hydrostatic transmission shall provide speeds that are infinitely variable for the entire speed range in forward and reverse direction. The transmission shall have a torque capacity adequate to transmit the maximum gross torque of the engine through all gear reductions.

3.7.4 Heater and defroster. Vehicle cab shall be provided with a 12 volt hot water heater with fresh air intakes and discharge outlets to the floor and to the windshield defroster louvers. Heater shall be complete with blower and mounted controls convenient to the driver. Heater shall be capable of maintaining the temperature of the cab air at the carrier floor above 40°F when the ambient temperature is -25°F with no solar input. When winterization is specified (see 3.13), the heater shall be capable of maintaining the temperature of the cab air at the carrier floor above 40°F when the ambient temperature is -60°F with no solar input.

3.7.5 Track control assembly. The track control shall consist of a lever(s), or steering wheel and column which shall be suitable located for left hand drive.

3.7.6 Drive line assembly. The drive line components shall be of adequate strength to transmit the maximum torque developed through all gear train reductions.

3.7.7 Tracks. The carrier shall be equipped with two full driving tracks designed to provide continuous support to the carrier at all ground contact points. The track assemblies shall operate in varied terrain such as sand, mud, snow, ice and bare ground without excessive wear and breakage. The track design shall provide for repair of track, and for removal and replacement of track cleats. The track width and the length of the track contacting the ground shall provide a ground pressure not more than that specified in 3.5.1. Track mounting shall provide for not less than 4 inches of track tension adjustment or shall be continuous spring tension type providing self adjustment of track tension. Track design shall provide independent control of each track.

3.7.8 Suspension system. The suspension system shall consist of axles and automotive tire assemblies independently mounted on each side of the carrier to avoid lateral stresses through the frame. The design of the linkage assembly shall permit the articulation in a vertical plane of the wheel and

Source: https://assist.dla.mil Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

tire assemblies so that a constant downward pressure is applied when the vehicle is operated on uneven surfaces and the track guides are retained in one vertical plane.

3.7.8.1 Axles. The axles shall provide for mounting of the wheel and tire assemblies. The axles shall be adequate for the loads imposed by the fully equipped and fully loaded carrier under the operating conditions specified herein.

3.7.8.2 Wheel and tire assemblies. The wheel and tire assemblies furnished shall be the Manufacturers recommended wheel and tire assemblies. Tires serving as track tensioning surfaces shall be hard rubber. Tires shall provide adequate support for the vehicle and to the tracks when the vehicle is fully loaded to rated GVM. Pneumatic tires shall be Urethane foam filled type. Tires and rims shall be in accordance with the requirements of the Tire and Rim Association recommendations.

3.7.9 Braking system. The braking system furnished shall be capable of completely locking the tracks under all conditions of use. A separate emergency brake shall be incorporated in the drive system and shall be capable of holding the fully loaded carrier stationary on a slope headed either direction equal to its grade climbing ability. The emergency brake handle shall be located so as to be easily operated by the driver.

3.7.10 Exhaust system. Exhaust system shall conform to Vehicle Motor Carrier Safety Regulation 393.83. Exhaust tailpipe shall extend to the rear of the vehicle or at least ten inches above the cab and be so located as to minimize the possibility of exhaust fumes entering the body of the vehicle. A spark arrestor, conforming to the material and performance requirements of MIL-A-27302, shall be furnished.

3.7.11 Seat belts. The contractor shall install lap safety belts and necessary fastenings for the driver and all passengers.

3.7.12 Towing devices. Adequate hooks, loops or pins for towing the vehicle shall be mounted on the front of the vehicle.

3.7.13 Pintle assembly. When specified (see 6.2), a pintle assembly conforming to MS 51335 shall be furnished on the chassis frame. Rear edge of the pintle shall be installed not more than four inches forward of the rearmost part of the vehicle. Mounting shall include reinforcement to transfer loads directly to the chassis.

3.7.14 Winch. When specified (see 6.2), a winch assembly shall be provided on the front or rear of the vehicle. Winch shall be powered by the 12 volt electrical system on the vehicle, and shall be wound with one-hundred-fifty feet of commercial preformed, steel core, galvanized cable. Winch line pull rating on the bare drum, and the normal breaking strength of the wire rope shall be not less than 8000 pounds. Winch shall have forward and reverse drum-drive and a drum clutch to permit free spooling of the cable.

3.7.15 Export package. When specified (see 6.2), manufacturer's export package shall be furnished. Export package shall be designed for continuous vehicle operation on regular grade leaded gasoline without vehicle modification and adjustment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

3.8 Vehicle types.

3.8.1 Vehicle body. Sizes 1, 2 and 3 carriers shall be equipped with a flat-bed cargo type body with cab and shall include stake pockets. For sizes 1, 2, and 3, removable front, rear and side stake assemblies at least three feet in height shall be provided. Size 4 carrier shall be equipped with a combination cab and cargo type body (e.i., cab with seats installed is used for transporting personnel and with seats removed is used for transporting cargo). Size 5 carrier shall be equipped with an operator's cab.

3.8.2 Tarpaulin and frame. When specified (see 6.2), carrier cargo area shall be furnished with a fitted tarpaulin and necessary metal frame and tiedown devices for installation. The tarpaulin shall be fabricated from 10 ounce/square yard duck. Color shall be as specified (see 6.2).

3.8.3 Cab. Carrier shall be equipped with a cab. The cab exterior surfaces shall be insulated and of weather-tight construction. The cab structural members shall be of sufficient strength and have adequate bracing to provide occupant protection in the event of roll-over of the vehicle. The cab floor shall be capable of withstanding the specified loads and shall provide a non-skid surface. The cab shall be equipped with a front sloping windshield of sufficient height to permit complete visibility from the operator's position. Weatherstripping and attaching cement for doors and windows shall be suitable for cold weather requirements contained herein. For Size 4, the body shall provide a minimum width of 21 inches between the rear passenger seats for foot room.

3.8.4 Doors. The carrier shall be equipped with two doors minimum, one located on each side of the cab, for size 1; three doors minimum, one located on each side of the cab and another one located for the rear passengers, for size 2 and 3; three doors minimum, one located on each side of the cab and one double located at the rear of the cab (rear opening shall be at least 36 inches high by 54 inches wide in size), for size 4; one door located on the side of the cab, for size 5. When rear door is provided, a suitable rear step(s) shall be furnished. Each door shall be equipped with striker plates and cam or slam type locks for the door latches. Door openings shall conform to MIL-STD-1472.

3.8.5 Windows. The carrier shall be equipped with a crank or sliding style window in the front door(s). Window shall be provided in each remaining door(s) and in the rear of the cab. Rear window size shall permit sufficient visibility of area rearward of vehicle from operator's position. For sizes 3 and 4, one additional window shall be located in each side of the cab. All windows shall be 160 square inches minimum size and shall be constructed of safety glass.

3.8.6 Seating. The carrier shall provide seating for an operator and its passengers (see 3.6.2).

3.8.6.1 Operator's seat. The operator's seat shall be located on the front left side of the vehicle and shall provide for fore and aft multi-position adjustment. The seat shall be located so as to provide maximum comfort for the operator when the carrier is in use for extended periods of time. The seat shall have a cushioned seat and cushioned back rest.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

3.8.6.2 Passenger seat(s). Except for size 5, one passenger seat shall be located on the front right side of the vehicle and shall be similar to the operator's seat with respect to size, design, comfort and adjustment. For size 2, the remaining seats shall be located across the width of the rear of the cab. For size 4, the remaining passenger seats shall be located on each side of the carrier and shall be easily removable or shall fold up out of the way for cargo space. For size 3, the remaining passenger seats shall be located across the width of the rear of the cab and along the left side of the cab. All seats shall provide sufficient capacity and size for passengers dressed in artic clothing. All seats shall have padded seats and padded backs.

3.9 Instruments. The instruments furnished shall be of the standard automotive type, flush mounted and lighted on the instrument panel, and shall consist of but not be limited to a fuel gauge, speedometer (except size 5 vehicles), exhaust pyrometer (diesel engine only), voltmeter, hour meter, engine oil pressure gauge, ammeter, tachometer, engine coolant temperature gauge, hydraulic system oil temperature gauge (when applicable) and air system air pressure gauge (when applicable). All instrument wiring and cable shall be suitably protected and attached so as to eliminate chafing and damage due to normal carrier operation.

3.9.1 Instrument panel. The instrument panel shall be the manufacturer's standard. The panel shall be easily removable to permit access to instruments for maintenance purposes. All instruments and switches located on the instrument panel shall be adequately marked to assure positive identification. The switches located on the instrument panel shall consist of but not be limited to ignition starter switch, cab heater control switch, windshield wiper switch and headlamp switch.

3.10 Electrical system. Electrical system shall be in accordance with FMSCR 393.27 through 393.31 and 393.33. Wiring insulation shall be suited for the cold weather application required herein.

3.10.1 Ignition system. For gasoline-engine-driven vehicles 12 volt DC ignition system shall be furnished. Alternator of not less than 55 amperes rated capacity which provides not less than 7 amperes DC output at normal engine idle speed, shall be furnished. Battery(s) shall be 12 volt potential. The total reserve capacity shall be not less than 110 minutes and the total cold cranking ampere rating at 0°F shall be not less than 450 amperes. Reserve capacity and cold cranking ratings shall be in accordance with SAE J537. Battery(s) shall be of the maintenance free type having the maintenance free characteristics listed in W-B-131.

3.10.2 Starting system. For diesel-engine-driven vehicles, battery(s) shall be maintenance free type having the maintenance free characteristics listed in W-B-131 and shall be of 12 volt potential. The total reserve capacity shall be not less than 400 minutes and the total cold cranking ampere rating at 0°F shall not be less than 1200 amperes. Reserve capacity and cold cranking ratings shall be in accordance with SAE J537. Twelve or 24-volt DC starting system with 12-volt lighting system, and with not less than a 55 ampere alternator, shall be furnished.

3.10.3 Lighting. The lighting shall include two high and low sealed beam headlamps, two combination stoplight/tail lamps, back-up light(s), two adjustable spotlights and interior lights. The two headlamps, stoplight/tail

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

lamps and spotlights shall conform to SAE standards. Lights on rear shall be within the plan outline of the vehicle. Two flush-mounted interior lights shall be furnished in the body and shall be located so that the driver and passenger positions are illuminated. Switches for operating and dimming headlamps shall be located on the instrument panel. Back-up lights shall be operated from a dash mounted switch or shall be an integral part of the transmission (automatic operation in reverse gear). The spotlights shall be mounted within the plan outline of the vehicle with one mounted aft and the other forward. The control switch (on-off) and control handle (position) of the forward spotlight shall be conveniently located to the driver and for the rear spotlight shall be convenient to a passenger. All exterior lights shall be rigidly mounted and shall be protected by means of guards against damage from brush and tree limbs.

3.11 Accessories. At least the following accessories shall be provided:

a. Horn with button located accessibly to the driver.

b. Electric operated dual windshield wipers.

c. One inside rearview mirror, rectangular configuration, minimum area of 15 sq in.

d. Two outside rearview mirrors, rectangular configuration, minimum area of 30 sq in each.

e. Two sets of keys.

f. Tools for track adjustment and tire change.

g. Fire extinguisher, in accordance with Fed Spec O-E-915, Type I, Class I, Size 5.

3.12 Special accessories. As specified (see 6.2), the following additional accessories shall be furnished.

a. Track repair kit.

b. Manually controlled radiator shutters.

c. An installed kit consisting of suitable bracket assembly for mounting military type gas can conforming to MIL-C-1283 on the vehicle. Quantity and location of can(s) shall be specified in 6.2.

d. Spare wheel and tire assembly mounted on the side of the vehicle. Quantity shall be specified in 6.2.

e. Hydraulic snow plow blade, full U, 6 directional control.

f. Hydraulic snow plow blade, full U, 6 directional control with wings hydraulically folded for service and transport and angled back for windrowing.

g. Hydraulic snow plow blade, straignt, 6 directional control.

h. Rear mounted compactor bar/drag assembly with lift assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

i. Other accessory equipment.

3.13 Winterization. When specified (see 6.2), winterization shall be provided.

3.13.1 Heater and defroster. See 3.7.4.

3.13.2 Power plant heaters. Coolant, engine oil and battery heaters shall be provided. Heaters shall operate on 110 volt AC and shall be wired through a junction block to a single three-pronged (male) weatherproof, slave receptacle for receiving external power and grounding vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to -60°F) without cracking and loss of dielectric capacity. All heater lead wires shall be installed without interferring with vehicle component operation and without loose, excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

a. Coolant heater, 1500-watt minimum rating, shall be installed in the engine block or lower, coolant, inlet hose. A coolant circulating pump, driven by a 110-volt AC motor, shall be provided. A check valve shall be installed in the system to prevent reverse flow when the engine is running.

b. Immersion type engine oil heater, 300 watt minimum rating with 170 to 195°F thermostat shall be installed in oil pan through any convenient opening.

c. Battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as -70°F and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.

3.13.3 Cooling system. The cooling system shall contain artic-type antifreeze (ethylene glycol) conforming to MIL-A-11755 filled to capacity for protection down to -70°F; a warning tag bearing the information:

"Cooling System Filled with Artic-Type Antifreeze (Ethylene Glycol) For Protection Down to -70 degrees F; DO NOT DRAIN"

shall be securely attached to the radiator filler neck.

3.14 Interchangeability. All parts having the same manufacturer' part number shall be functionally and dimensionally interchangeable.

3.15 Radio interference suppression. Vehicle shall be suppressed for radio interference in accordance with SAE Standard J551. Suppressors used shall conform to SAE Recommended Practice J552.

3.16 Cleaning, treatment and painting. Treatment, cleaning, painting, marking and data plates shall be in accordance with Air Force requirements of MIL-STD-1223. Exterior color shall be as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

3.17 Transportation data plate. A transportation data plate conforming to MIL-P-514 shall be provided. The transportation data plate shall be securely attached as near as practicable to the nameplate and shall contain the following information:

Overall length	Inches
Overall height	Inches
Overall width	Inches
Shipping cubage	Cubic Feet
Shipping weight	Pounds
Shipping tonnage	Tons
Center of Gravity Location	Inches (longitudinal), Inches (traverse)

3.18 Workmanship. The carrier, including all parts and accessories, shall be fabricated and finished in a workmanlike manner. Particular attention shall be given to neatness and thoroughness of soldering, welding, brazing, painting, riveting, wiring and fitting of the hydraulic and mechanical systems. Parts and assemblies shall be free from burrs and sharp edges.

3.19 Servicing and adjusting. Prior to acceptance of the vehicles by the Government inspector, contractor shall service and adjust each vehicle for operational use including at least the following: focusing of lights; adjustment of the engine, electrical and brake system; filling and charging of battery; alignment of front wheels and inflation of all tires; complete lubrication of chassis, engine and running gear with the grades of lubrication recommended for the ambient temperature at delivery point; unless otherwise specified (see 3.13), servicing of cooling system with antifreeze solution, filled to capacity; and servicing of windshield washer reservoir with antifreeze solution, if so equipped.

4. QUALITY ASSURANCE

4.1 Responsibility for Inspection. Unless otherwise specified in the contract, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the purchase description where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article inspection (see 4.2.1)

b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. First article inspection shall be performed on one carrier when required (see 3.1). First article inspection shall consist of the examination in 4.3 and all tests in 4.4. Failure of the first article to pass the examination or any of the first article tests shall be cause for rejection.

4.2.2 Quality conformance inspection. Quality conformance inspection shall be applied to each vehicle prior to being prepared for delivery under terms of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

4.3 Examination. The vehicle shall be examined to determine compliance with the requirements of section 3. Particular attention shall be given to materials, dimensions, weight, markings, finish and workmanship. This examination shall be accomplished with a checklift showing the results after each requirement.

4.4 Tests. Malfunction, permanent deformation or failure shall be cause for rejection.

4.4.1 Gradeability. The fully loaded carrier shall be tested ten times without stopping to show conformance to the requirements of 3.6.3.2.

4.4.2 Mobility. The fully loaded carrier shall be driven over level dirt surface in an ambient temperature of not less than 60°F for not less than 120 consecutive miles (100 consecutive miles for size 5 vehicles) in not more than ten hours without overheating the engine and without refueling. Fuel consumption (gallons) shall be recorded. Test vehicle to show conformance to the maximum speed requirement (see 3.6.3) and when applicable, drawbar pull requirement (see 3.6.3).

4.4.3 Braking. The fully loaded carrier shall be driven at maximum speed. Apply brakes at same speed to lock track movement. Application of brakes to lock tracks shall not require more than 120 pounds force at the brake pedal (not applicable to hydrostatic drive type vehicles). Failure of tracks to lock shall be cause for rejection. Test carrier to show conformance to the emergency brake requirements of 3.7.9.

4.4.4 Turning. The fully loaded carrier shall be tested to show conformance to the requirements of 3.6.3.1.

4.4.5 Night operation. The carrier shall be operated at night to determine the adequacy of carrier interior and road illumination.

4.4.6 Road test. The first article vehicle shall be driven 500 miles minimum over snow or ground and shall be conducted at an average speed of 10 mph minimum (8 mph minimum for size 5 vehicles) without any failures. Failure for the purpose of this test is defined as any malfunction which cannot be remedied within one manhour by adjustment, repair or replacement using ordinary tools and parts, and which will cause: (a) degradation of performance capabilities, (b) serious damage to the carrier by continued operation and/or (c) serious personnel safety hazard. Evidence of any of the following shall also constitute failure of this test: (a) engine coolant temperature in excess of boiling point, (b) transmission oil temperature in excess of 250°F, (c) engine oil temperature in excess of 230°F and (d) drive axle oil temperature in excess of 250°F. The road test shall include the following: (1) 100 engine starts, (2) 100 progressions through all forward gear ratios, (3) 20 progressions in reverse gear ratio, from standing still position to three mph minimum, (4) 100 normal stops, (5) 25 panic stops, (6) 250 right circle turns and 250 left circle turns. Total miles and total testing time shall be recorded. Average speed shall be calculated using the following formula:

Avg Speed = Total miles ÷ total time

4.4.7 Ground pressure. Carrier, at curb weight, shall be examined to determine conformance to the ground pressure requirements of 3.5.1.b. Ground

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

pressure shall be calculated using the following formula:

GP = Curb Wt ÷ Track area in contact with ground.

4.4.8 Environmental tests.

4.4.8.1 Low temperatures. The carrier shall be subjected to low temperature test in accordance with MIL-STD-810. Standard ambient conditions shall be ambient conditions of first article test site. While exposed to low temperature, the heater shall be operated until carrier interior temperature stabilizes. A maximum of 30 minutes shall be required to raise cab temperature above 40°F, measured at one foot above floor. The Government shall select position of temperature measuring device. The defrosting system shall be operated and shall maintain clear vision through the windshield.

4.4.8.2 Rain. Delete and substitute 4.4.8.3 rain test. All window, windshield and closure seals shall be subjected to 90 degree and 45 degree impact from a 2 ft diameter spray from a one and one half inch hose at 35 psi pressure. No leaks shall occur.

4.4.9 Track replacement. Carrier tracks shall be interchanged by two men in not more than 30 minutes to determine ease of repair, replacement and adjustment.

5. PACKAGING

5.1 Preservation, packaging, and packing. Unless otherwise specified (see 6.2), the preservation, packaging and packing shall be in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The carrier covered by this specification is intended for use in the transport of passengers and cargo, and towing sleds and trailers over terrains and in environments encountered in artic regions and swamp areas. The terrains encountered shall include swampy and frozen muskeg, hummocks, rocks, sand, light and deep snows, narrow trenches, slopes, small tree and bush areas, mud and vertical objects.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this purchase description.

b. Size of vehicle required (see 1.2)

c. First article inspection, when required (see 3.1)

d. Fluid priming system required (see 3.7.1)

e. Pintle assembly, when required (see 3.7.13)

f. If winch is required (see 3.7.14)

g. If export package is required (see 3.7.15)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

h. If a tarpaulin and frame are required (see 3.8.2)

i. Color of tarpaulin required (see 3.8.2)

j. If special accessories are required (see 3.12)

k. Winterization required (see 3.13)

l. Color of finish coat (see 3.16)

m. Preparation for delivery required (see 5.1).

Custodians:
Army - AT
Navy - YD
Air Force - 99

Preparing Activity:
Air Force - 84

Project Number:
2320-1069

☆U.S. GOVERNMENT PRINTING OFFICE: 1982—605-034/146

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-26339C Carrier, Passenger, Cargo, Utility, Full Tracked, Over the Snow Type

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   [ ] YES [ ] NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE AIR FORCE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

HQ AFLC CASO/LODS
Federal Center
Battle Creek, MI 49016

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:28Z
Check the source to verify that this is the current version before use.