MIL-I-26299F
AMENDMENT 2
10 JULY 1981
SUPERSEDING
AMENDMENT 1
22 April 1980

MILITARY SPECIFICATION

INDICATOR, RATE OF FLOW, 0-5000 PPH,
INTEGRALLY LIGHTED

This amendment forms a part of Military Specification MIL-I-26299F, dated 30 January 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under SPECIFICATIONS, Federal: Delete "QQ-P-416".

Add boxed paragraph to bottom center of page.

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

PAGE 2

2.1, under SPECIFICATIONS, Military: Add:

"MIL-C-83488 Coating, Aluminum, Ion Vapor Deposited"

PAGE 3

3.1: Delete paragraph and substitute the following:

"3.1 First article. When specified (see 6.4), the contractor shall furnish sample units(s) for first article inspection and approval (see 4.4)".

PAGE 13

3.8.3: Delete and substitute the following:

"3.8.3 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

FSC 6620

Source: https://assist.dla.mil -- Downloaded: 202610-20T09:24Z
Check the source to verify that this is the current version before use.

PAGE 14

Add new paragraph 3.12 as follows:

"3.12 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible without jeopardizing the intended end use of the item."

4.2.a: Delete "Qualification tests" and substitute "First article tests".

PAGE 15

4.4: Delete "Qualification testing" and substitute "First article testing".

4.4.3, title and line 1: Delete references to "Qualification tests" in both places, and substitute "First article tests".

PAGE 25

4.7: Delete and substitute the following:

"4.7 Inspection and test. Tests of methods of preservation and packaging shall be accomplished in accordance with Section 4 of MIL-P-116, to insure compliance with Section 5 of this specification."

5.: Delete paragraphs 5 through 5.2.3 and substitute the following:

"5. Packaging.

5.1. Preservation-packaging. Preservation-packaging shall be Level A or C as specified. (See 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Indicator shall be cleaned in accordance with Process C-1 of MIL-P-116.

5.1.1.2 Drying. Indicator shall be dried in accordance with Process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the procuring activity, each Indicator, Rate of Flow, 0-5000 PPH, integrally lighted, shall be packaged in quantity unit packs of one each in accordance with Method 1C-1 of MIL-P-116. Overbox in PPP-B-636 carton large enough to allow for application of

Source: https://assist.dla.mil -- Downloaded: 202610-20T09:24Z
Check the source to verify that this is the current version before use.

sufficient cushioning material between container and bag, of a type, density, and thickness to insure shock transmission does not exceed peak values in Gs established for the item, when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Same as Level A except Method III of MIL-P-116 applies in lieu of specified method.

5.2 Packing. Packing shall be Level A, B or C as specified (see 6.2).

5.2.1 Level A. Indicator packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, weather-resistant class, unless otherwise specified by the procuring activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, or minimum tare and cube consistent with the protection required. Table II of MIL-STD-794 applies for Army use.

5.2.2 Level B. Indicator packaged as specified in 5.1.1 shall be packed in domestic class exterior shipping containers conforming to PPP-B-636. Other requirements as specified in 5.2.1 above shall apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first domestic receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations and may be the contractor's commercial practice, provided the latter meets the requirements of this level."

PAGE 27

6.4: Delete paragraph and substitute the following:

"6.4 First article. A first article is required for inspection and it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Aquisition Requlation. First article tests are described in 4.4. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test and approval of the first article."

Custodian:
Air Force - 99
Navy - AS

Preparing activity:
Air Force - 99

Project number:
6620 - 0342

Source: https://assist.dla.mil -- Downloaded: 202610-20T09:24Z
Check the source to verify that this is the current version before use.