INCH-POUND

MIL-T-26225B(USAF)
1 MARCH 1995
SUPERSEDING
MIL-T-26225A(USAF)
3 September 1959

MILITARY SPECIFICATION

TRAILER, LIFT, AIRCRAFT - MISSILE ENGINE ETU-8/E

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an aircraft and missile engine lift trailer, designated ETU-8/E.

* 2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specification and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (6.2).

SPECIFICATIONS

MILITARY

MIL-P-116	Preservation, Method of
MIL-T-704	Treatment and Painting of Materiel
MIL-H-5606	Hydraulic Fluid, Petroleum Base, Aircraft, Missile, and Ordinance
MIL-V-62038	Vehicles, Wheeled: Preparation for Shipment and Storage of

STANDARDS

MILITARY

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: The Resources and Logistics Services Division, SA-ALC/TILDD, Bldg. 171, Post C-12, 485 Quentin Roosevelt Rd., Kelly AFB, TX 78241-6425 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1730

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

MIL-STD-129 Marking for Shipment and Storage (Part 1 of 4 Parts)
MIL-STD-130 Identification Marking of U.S. Military Property
MIL-STD-1186 Cushioning, Anchoring, Bracing, Blocking and Waterproofing, with Appropriate Test Methods

* (Unless otherwise indicted, copies of the federal and military specifications and standards are available from the Defense Printing Service, Detachment Office, 700 Robbins Ave., Bldg 4D, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

AIR LOGISTICS CORPORATION

100628T Trailer Assembly Model 4000A Heavy Duty Positioning

* (Copies of specifications, standards, drawings, publications and other Government documents required by contractors in connection with specified acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issues of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIAL (ASTM)

ASTM D-3951 Standard Practice for Packaging, Commercial

* (Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY (AWS)

AWS D1.1 Structural Welding Code Steel Twelfth Edition

* (Applications for copies of AWS publications should be addressed to the American Welding Society, 2501 NW 7th Street, P.O. Box 351040, Miami, FL 33135-3030.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specifications sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specified exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.2 Design and construction

3.2.1 Assembly drawing. The requirements of drawing 100628A apply as requirements of this specification with the exceptions and additions specified herein. When the drawing and this specification conflict, this specification shall govern (see 6.2).

3.2.2 Commercial items. Components proposed for use in lieu of commercial parts specified on the drawings shall be functionally and dimensionally interchangeable with the parts specified and are subject to the approval of the procuring activity.

3.2.3 Welding. Welding shall be accomplished by welders certified in accordance with Class A of AWS D1.1.

3.3 Performance

3.3.1 Static load. The trailer shall withstand a static load of 16,000 pounds applied as specified in 4.6.2 herein.

3.3.2 Tilt, roll, yaw, and transverse operations. Under an 8,000 pound load, the adjusting mechanism for tilt, roll, yaw, and transverse operations shall be operable by hand. The transverse operations shall require not more than 26 pounds load on the handle (see 4.6.3). Under a 16,000 pound load, the adjusting mechanism shall be operable by a standard .5 inch drive wrench and shall require not more than 600 pound-inches torque with the load in any position on the rails (see 4.6.3.1).

3.3.3 Side load. While under a static load of 8,000 pounds, the trailer shall withstand a side load of 1,200 pounds (see 4.6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

3.3.4 Endurance. When subjected to a 5 cycle, 8,000 pound endurance test (a cycle consists of raising the trailer from collapsed to fully extended heights), the hydraulic systems shall require no more than 75 pounds force on the pump handle(s) to raise the 8,000 pounds at the end of the test, nor shall the cylinder settling rate exceed .0625 inch per hour (see 4.6.5).

3.4 Hydraulic servicing. The hydraulic system shall be bled of air and filled with hydraulic fluid conforming to MIL-H-5606.

3.5 Finish. The trailer shall be finished in accordance with type A of MIL-T-704.

3.6 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.7 Workmanship. The trailer, including all parts and accessories, shall meet all requirements of this specification. Particular attention shall be given to neatness and thoroughness of marking of parts and assemblies; welding and brazing, painting, riveting, machine screw assemblies; and freedom of parts from burrs and sharp edges.

3.7.1 Riveting. Riveting operations shall be performed to ensure that the rivets are tight and satisfactorily headed.

3.7.2 Cleaning. The trailer shall be thoroughly cleaned of loose, spattered or excessive weld scale and flux, rust and metal chips, oil, grease, oxides, and other foreign matter after assembly. Burrs and sharp edges, as well as resin finish that may crumble or crack shall be removed.

3.7.2.1 Multiple-pass welds. When a weld is built up by two or more beads or passes, proceeding beads shall be cleaned free of scale and flux by chipping or scraping and brushing.

* 4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection. First article inspection shall be performed on one trailer representative of the final production item (see 3.1 and 6.3).

4.3.1 First article test sample. The first article test sample shall consist of one trailer representative of the production equipment. It shall be tested at a laboratory designated by the contractor's plant under the supervision of the procuring activity.

* 4.3.2 First article tests. The first article tests shall consist of all tests as specified in paragraph 4.6.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the individual tests as specified in paragraph 4.6.

4.5 Packaging inspection. The preservation, packaging, packing, and marking of the equipment shall be subjected to inspection and test to determine compliance with the requirements of section 5 of this specification. The contractor shall provide the necessary facilities and supplies for inspections and tests made prior to final acceptance.

4.6 Test methods.

4.6.1 Examination of product. The trailer shall be visually inspected to determine compliance with the requirements specified herein with respect to material, workmanship, applicable drawings, preparation of trailers and application of protective finishes and markings.

4.6.2 Static load tests. The trailer shall be subjected to a static load of 16,000 pounds. The center of gravity of the load shall be 18 inches above the center of the parallel rails and applied to two points on each rail which are 60 +/-2 inches apart. The load shall be raised to maximum height with spacers and lowered to the low position while loaded. The lifts provided on the wheels shall also be subjected to this static load and operated through their entire range. No damage shall result from the static load. The lift cylinders shall show no leaks around their seals and the hydraulic system shall be capable of handling these entire loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

* 4.6.3 Tilt, roll, yaw and transverse tests (8,000 lb.). The tilt, roll, yaw, and transverse mechanism shall be operated through their entire ranges and shall be tested under an 8,000 pound load. The adjusting mechanism shall be operated by hand without the use of tools or auxiliary support mediums. The winch drive shall be demonstrated by rolling this from each end of the rails. The maximum load on the handle that is required to perform transverse operations shall not exceed 26 pounds.

* 4.6.3.1 Tilt, roll, yaw and transverse tests (16,000lb.). The tilt, roll, yaw and transverse mechanisms shall be operated through their entire ranges and shall be tested under a 16,000 pound load. The winch drive shall be demonstrated by rolling this load from each end of the rails. The adjusting mechanism shall be operable by a standard .5 inch drive wrench and shall require not more than 600 pound-inches or torque with the load in any position on the rails.

4.6.4 Side load test. The trailer shall be raised to its maximum height. The trailer shall be subject to a static load of 8,000 pounds. A side load of 1,200 pounds shall be applied at the side of the rails. The trailer shall not show permanent deformation, tip, or overturn when the 1,200 pound side load is applied. The trailer shall not be tied down during this test.

4.6.5 Endurance test. An endurance test shall be conducted on the hydraulic system of the trailer. The test shall consist of 5 cycles of raising 8,000 pounds. One cycle shall consist of raising the trailer from collapsed height to the fully extended height and return to the collapsed position. At the end of the endurance test, the force required at the end of the pump handle(s) to raise the 8,000 pound shall not exceed 75 pounds each.

4.6.6 Settling test. After the endurance test, the cylinder settling rate shall not exceed .0625 inch per hour. The settling rate shall be measured at 10, 50, and 90 percent of the height adjustment.

5. PACKAGING

* 5.1 Preservation. Preservation shall be level A, C or Commercial as specified (see 6.2).

* 5.1.1 Level A. The trailer shall be preserved and packaged in accordance with MIL-V-62038.

* 5.1.2 Level C. The trailer shall be preserved and packaged in such a manner as to provide protection from deterioration and damage during shipment to the initial receiving activity in accordance with MIL-V-62038.

* 5.1.3 Commercial. The trailer shall be preserved in accordance with ASTM-D-3951.

* 5.2 Packing. The trailer, packaged in accordance with 5.1, shall be packed level A, B, C or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

* 5.2.1 Level A. The trailer shall be packed in accordance with the requirements of MIL-V-62038 for level A.

* 5.2.2 Level B. The trailer shall be shipped boxed or unboxed mobile in accordance with the requirements for level B in MIL-V-62038.

* 5.2.3 Level C. The trailer shall be shipped unboxed mobile in accordance with MIL-V-62038. Items which require overpacking for acceptance by the carrier shall be packed in domestic grade containers in a manner that will ensure safe transportation at the lowest rate to the point of delivery. Containers shall meet consolidated freight classification rules or regulations of other common carriers as applicable to the mode of transportation.

* 5.2.4 Commercial. The trailer shall be shipped unboxed mobile in accordance with the requirements of ASTM D-3951.

* 5.3 Physical condition. All cushioning, blocking, bracing, and bolting shall be in accordance with MIL-STD-1186. The drop tests of MIL-STD-1186 shall be waived when preservation, packaging and packing of the stand is for immediate use or when the drop tests of MIL-P-116 are applicable.

* 5.4 Marking. In addition to any special marking required by the contractor or order, shipping containers shall be marked in accordance with MIL-STD-129, or ASTM D-3951 as applicable. The shipment marking nomenclature shall be as follows:

TRAILER, LIFT, AIRCRAFT - MISSILE ENGINE ETU-8/E

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The ETU-8/E trailer covered by this specification is intended for use in installing or removing aircraft engines and other components from aircraft and missiles and for the ground transportation and handling of these components. Also it is indented for use in some forms of field maintenance or aircraft engines.

* 6.2 Ordering data.

* 6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. In the event it becomes necessary to change the drawings in order to achieve the performance requirements of the specification, the contractor will immediately notify the contracting officer with

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

recommendations for drawing changes to obtain the required performance. To the extent approved, such changes shall be processed in accordance with the provisions of the changes clause of this contract.

c. Issue of the DoDISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2)

d. When first article is required (see 3.1).

e. Required levels of preservation and packaging, and packing (see section 5).

* 6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a first article sample, a first production item or a standard production item from the contractor's current inventory and the number of items to be tested as specified in 4.3.1 The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article tests results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirements for samples for the first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and the bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

* 6.4 Subject term (key word) listing.

Lift trailer, aircraft - missile engine, ETU-8/E

Engine, lift trailer, aircraft - missile, ETU-8/E

ETU-8/E aircraft - missile engine lift trailer

* 6.5 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issues were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the past previous issues.

Custodian:
Air Force - 99

Preparing activity:
Air Force - 82

(Project No. 1730-F276)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-26225B(USAF)	2. DOCUMENT DATE (YYMMDD)

3. DOCUMENT TITLE
Trailer, Lift, Aircraft - Missile Engine ETU-8/E

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*)	d. TELEPHONE (*Include Area Code*) (1) Commercial (2) AUTOVON (*If applicable*)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (*Include Area Code*) (1) Commercial	(2) AUTOVON
SA-ALC/TILDD	(210) 925-6314	DSN 945-6314
c. ADDRESS (*Include Zip Code*) 306 Tinker Drive Kelly AFB, Texas 78241-5916	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:21Z
Check the source to verify that this is the current version before use.