MIL-T-26310A(USAF)
AMENDMENT 1
2 July 1962

MILITARY SPECIFICATION

TRAILER, LIFT, AIRCRAFT - MISSILE ENGINE ETU- 9/E

This amendment forms a part of Military Specification MIL-T-26310A(USAF) dated 8 July 1959

Page 2, paragraph 2.1: Under STANDARD add:

"*MIL-STD-143* *Specification and Standards, Order of Precedence for the Selection of*".

Page 2, paragraph 2.1: Delete reference to Bulletin 143.

Page 3, paragraph 3.3, line 3 and 4: Delete "Bulletin 143 except as specified in 3.3.1 and 3.3.2" and substitute "MIL-STD-143".

Page 3, paragraphs 3.3.1 and 3.3.2: Delete

Page 5, paragraph 3.6.2, first sentence: Delete "3.7.1" and substitute "3.6.1".

Page 11 paragraph 3.9, third sentence: Delete "lbs" and substitute "foot-pounds".

Page 11, paragraph 3.9.3, last sentence: Delete "1,600 to 1,700" and substitute "2,400 to 2,700".

Page 15, paragraph 4.5.4.3 last two sentences: Delete and substitute "The winch drive shall be demonstrated by rolling this load from each end of the rails in a level position. If the torque required to perform any of the adjustments exceeds 700 inches-pounds, the trailer shall be rejected".

FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:26Z
Check the source to verify that this is the current version before use.

Page 17, paragraph 4.5.6.2: Delete and substitute:

"4.5.6.2 Winch. - An endurance test shall be conducted on the winch. The test shall consist of 50 cycles (25 complete cycles in compression and 25 complete cycles in tension) of rolling a 10,000-pound load on the rails tilted 10° from the horizontal. Twenty-five cycles shall be performed with the rails permanently tilted at 10° placing the load in compression and tension. The rails shall then be permanently tilted 10° in the opposite direction and 25 cycles conducted with the load in tension and compression. No further movement of the rails . . shall be permitted during these winch tests. One cycle shall consist of rolling the load from one end of the rails to the opposite end and return to the starting position. At the end of the endurance test, the maximum load on the handle shall not exceed 25 foot-pounds. During the endurance testing, the overload protection device shall demonstrate satisfacory operation in compliance with 3.9.3. The winch overload protection device shall be tested to determine that the overload clutch disengages between 2,400 and 2,700 pounds chain load output".

Page 17, paragraph 4.6.2, line 2: Delete "4.4" and substitute "4.5".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:26Z
Check the source to verify that this is the current version before use.