INCH-POUND

MS27055D
25 September 2003
SUPERSEDING
MS27055C
30 June 1972

DETAIL SPECIFICATION SHEET

# ADAPTER ASSEMBLY, FLARED, 45° ELBOW, TUBE TO HOSE - WITH SWIVEL NUT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-27272.




NOTES:
1. Dimension A is measured between the hose end of the socket and the free end of the insert at its centerline when the socket is assembled on the elbow subassembly.
2. If required, lockwire holes to be drilled in accordance with SAE AS1043 and suffix L added to the Part of Identifying Number (PIN) (e.g., MS27055-10CL).

FIGURE 1. Adapter assembly illustration.

.


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:14Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Intended use. This adapter is intended for use with hose conforming to MIL-DTL-27267.

Dimensions. Dimensions are in inches.

Material. PIN suffix C: Corrosion-resistant steel.
No PIN suffix: Combination of aluminum alloy and corrosion-resistant steel.
See applicable specification sheet for other components identified in table I for their material requirements.

Identification of product. The PIN and the manufacturer's Commercial and Government Entity (CAGE) Code shall be marked on a removable tag securely attached to the adapter. The PIN for this part shall be as specified in table I (e.g., MS27055-10C).

Order of precedence. This specification takes precedence over the documents referenced herein. Unless otherwise specified, referenced documents shall be of the issue in effect on the date of solicitation.

Adapter assembly illustration. See figure 1.

TABLE I. Adapter assembly composition.

| PIN 1/ | Elbow subassembly PIN | Sleeve PIN | Socket PIN | A 2/ max |
|---|---|---|---|---|
| MS27055 | MS27063 | MS27070 | MS27069 | |
| -10C | -10C | -10C | -10C | 2.43 |
| -10 | -10 | | | |
| -12C | -12C | -12C | -12C | 2.89 |
| -12 | -12 | | | |
| -16C | -16C | -16C | -16C | 3.02 |
| -16 | -16 | | | |
| -20C | -20C | -20C | -20C | 3.52 |
| -20 | -20 | | | |
| -24C | -24C | -24C | -24C | 3.80 |
| -24 | -24 | | | |

1/ If required, lockwire holes to be drilled in accordance with SAE AS1043 and suffix L added to the PIN (e.g., MS27055-10CL).
2/ Dimension A is measured between the hose end of the socket and the free end of the insert at its centerline when the socket is assembled on the elbow subassembly.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:14Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Review activities:
Army - AR, AT, MI
Navy - MC, SA, SH
Air Force - 71

Preparing activity:
DLA - CC

(Project 4730-0868-005)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:14Z
Check the source to verify that this is the current version before use.