MIL-C-10922G
20 February 1985
SUPERSEDING
MIL-C-10922F
25 November 1980

MILITARY SPECIFICATION

CASE, PARACHUTIST'S INDIVIDUAL WEAPONS,

M-1950, ADJUSTABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of padded adjustable individual weapons case, fabricated from olive drab cotton duck and webbing, with a slide fastener flap closure. The case is equipped with a snap link, V-ring and quick release snap hook for attachment to the T-10 parachute harness worn by the parachutist.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

UU-P-268	-	Paper, Kraft, Wrapping
PPP-B-591	-	Boxes, Shipping, Fiberboard, Wood-Cleated
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-2-114	-	Case, Parachutists' Individual Weapons, M-1950, Adjustable Assembly
2-2-115	-	Sections
2-2-116	-	Body Details and Sections
2-2-117	-	Details

(Copies of documents required by contractor in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Materials and construction. Materials (see 6.5) and construction shall conform to requirements specified on Drawing 2-2-114, to subsidiary documents applicable thereto, and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026l0-17T14:35Z
Check the source to verify that this is the current version before use.

3.1.1 Slide fastener tape. The slide fastener tape shall be water-resistant and mildew-resistant treated and shall show good fastness to weathering.

3.1.2 Hardware. All metal hardware components shall be free of burrs, sharp edges, corroded areas and shall not be broken or bent.

3.2 Stitching. Stitching defects such as skipped or broken stitches and runoffs shall be overstitched not less than 1 inch past ends of the defect in accordance with the required stitch pattern. Thread ends shall be trimmed throughout to a length of 1/4 inch or less. Thread tension shall be maintained so that there will be no loose stitching and the lock will be imbedded in the materials sewn.

3.2.1 Stitching, automatic machinery. Stitching patterns produced by automatic machines may be utilized in lieu of those specified, providing seam strength efficiency and functions are equal to, or better than, the specified pattern (see 6.4).

3.2.2 Setting of end clip. The webbing shall be inserted the full depth of the clip. The clip shall be attached without cutting the webbing. The webbing shall be flat at the point of entry.

3.2.3 Setting of snap fasteners. If a hole is punched before inserting the male and female part of the fastener, the hole shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. The fastener shall be securely clinched.

3.2.4 Mating of V-ring with link. The 1-3/4 inch quick release snap link shall have sufficient clearance when inserted through V-ring to allow attachment of quick release snap hook.

3.3 Workmanship. The workmanship shall conform to the quality established by this document.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection . Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:35Z
Check the source to verify that this is the current version before use.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.2.2 In-process inspection. Examination shall be made to determine that holes punched to receive snap fasteners are in compliance with 3.2.3. Whenever nonconformance is noted, correction shall be made to the items affected and the process.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of cases. The sample unit shall be one case. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 15.0 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric (duck and felt)	Hole (except drill hole), cut, or tear	X	
Webbing	Any hole, cut, or tear	X	
	Edge frayed or scalloped	X	
Hardware	Broken or bent; corroded areas; burrs or sharp edges.	X	
	Any required component not specified type or size	X	
	Any required component malfunctioning, improperly set, or reversed	X	
	End clip improperly clinched, i.e., webbing not flat at point of entrance into clip		X
	Snap link does not fit into V-ring as specified	X	
Open seams	1/2 inch or less		X
	More than 1/2 inch	X	

NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more skipped or run-off stitches occur. On double stitching seams, a seam shall be considered open when either one or both sides of the seam are open.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Raw edges (except where required)	More than 1/2 inch when securely caught in other stitching		X
NOTE:	Raw edges not securely caught in stitching shall be classified as open seams.		
Run-offs	(See open seams)		
Seam and stitch type	Wrong seam or stitch type	X	
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in excessive tightness of fabric on seams	X	
Stitches per inch	One stitch less than minimum specified		X
	Two or more stitches less than minimum specified	X	
	One or two stitches in excess of maximum specified		X
	More than two stitches in excess of maximum specified	X	
NOTE:	Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams or in turning corners, shall be classified as follows: a. Within the major defect classification - Minor defect b. Within the minor defect classification - No defect		
Stitching margins	Larger than specified by more than 3/16 inch for more than 2 inches		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Thread breaks	Overstitched less than 1 inch		X
	NOTE: Thread breaks not overstitched shall be classified as open seams.		
Stitching ends	Ends of stitching backstitched less than 1/2 inch (except where ends are turned under in a hem or held down by other stitching)		X
	Ends of stitching not backstitched	X	
Stitching	Any required row of stitching omitted (except on WW stitching)	X	
	WW stitching:		
	One row of stitching omitted		X
	Two or more rows of stitching omitted	X	
	Stitching extends off chapes		X
	Length of stitching less than specified by more than 1/4 inch	X	
	Any operation requiring size No. 5 thread performed with size F-F thread	X	
Components and assembly	Any component or required operation omitted or not as specified (unless otherwise classified herein)	X	
	Needle chews	X	
	Mends, darns, or patches	X	
	Any turn under on stitched ends of webbing not securely caught in WW stitching	X	
	Turn under on ends of straps, chapes, and loops less than specified by more than 1/8 inch		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Snap fasteners	Male or female portion misplaced, failing to effect a secure closure	X	
	Not securely clinched or clinched excessively, cutting surrounding fabric	X	
	Fail to snap closed or to remain in a secure closed position	X	
Chape A	Any part of chape single ply construction	X	
Body (including flap)	Any splice, i.e., made of more than one piece of duck	X	
	Body pad not caught in hem stitching or flap hem	X	
Slide fastener	Not specified type, style and size	X	
	Slider jams or fails to interlock chain: tapes improperly applied causing failure of fastener to effect a smooth and secure closure	X	
	Quick release device defective or functioning improperly, failing to release when slider is pulled fully	X	
	Thong omitted		X
Tab	Not stitched through a slide fastener tape and flap, or not attached to end of a slide fastener assembly as specified		X
Lowering strap pocket on flap	Construction or formation of pocket not as indicated on drawings	X	
End piece	Top edge of end piece uneven with edge of body opening by more than 1/8 inch		X
End pad	Any part of end pad not stitched to end piece		X
	Top end of pad not caught in hem at top end of end piece		X

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:35Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Body pad	Ends or edges of pad not caught in closing seams or in flap hem		X
Leather reinforcement	Misplaced, i.e., set on open end of case in lieu of closed end	X	
	Reversed, i.e., set with grain side facing felt pad		X
	Top edge of reinforcement not stitched through felt and body	X	
Marking, "US" and identification	Omitted, incorrect, illegible, misplaced, or size characters not as specified		X
Cleanness	Noticeable spots or stains, i.e., grease, oil, ink, dirt not removed; thread ends not trimmed as specified throughout		X

* 4.2.4 End item dimensional examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of cases. The sample unit shall be one case. The inspection level shall be S-4 and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:35Z
Check the source to verify that this is the currentversion before use.

TABLE II. End item dimensional defects

Examine	Defect	Classification Major	Minor
Overall dimensions	Smaller than specified dimensions, less applicable minus tolerance, but not smaller than twice the applicable minus tolerance		X
	Smaller than specified dimensions, less twice the applicable minus tolerance	X	
	Larger than specified dimensions and applicable plus tolerance		X
Component and location dimensions (not otherwise classified herein)	Not within specified tolerance		X

* 4.2.5 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with table III. The sample unit shall be one shipping container fully packaged. The lot shall be expressed in units of shipping containers. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE III. Packaging defects

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Polyethylene bag seams and closure crooked, non-continuous, or not parallel to each other
Contents (exterior container)	Number per container not as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

* 4.2.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with table IV. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

TABLE IV. Palletization defects

Examine	Defect
Finished dimensions	Length,width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. All areas of the felt pad shall be lightly and uniformly sprinkled with naphthalene flakes. The quick release snap shall be removed and completely wrapped in 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. The wrap shall be secured with 2-inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45. The wrapped quick release snap shall be placed within the case. The case shall be closed, laid out flat, front down, and the end opposite the slide fastener folded over onto the body of the case, resulting in a bundle measuring approximately 32-1/2 inches in length by 10-1/2 inches in width. The quick release snap shall be adjusted within the case to fit up against the fold. Each folded case shall then be securely cross-tied at the folded end with cotton tape or twine. The folded and tied case shall be unit packed in a snug-fitting, clear polyethylene film bag of 0.003 inch thickness (± 20 percent tolerance). The polyethylene bag shall be formed with heat sealed seams that are straight and continuous and parallel to each other and the formed edges of the bag. Prior to or during heat sealing the closure operation, excess air within the bag shall be expelled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

* 5.1.2 Commercial. Each case shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Ten cases, preserved as specified in 5.1, shall be packed in a shipping container conforming to class II, style A or I, type 2 load of PPP-B-591; or overseas type, style A or I, grade A or B, type 2 load of PPP-B-601, as specified (see 6.2). Level A unit packs shall be packed flat, alternated end to end and nested in each stack, one in length, two in width, and five in depth within a shipping container. Inside dimensions of each shipping container shall approximate 32-1/2 inches in length, 21 inches in width, and 12-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed and reinforced in accordance with the appendix of the applicable container specification.

* 5.2.2 Level B packing. Ten cases, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, class domestic, variety DW, grade 350, of PPP-B-636. The inside of each container shall be fitted with a box liner conforming to class domestic, variety DW, grade 275 of PPP-B-636. The inside dimension of each container shall be approximately 32-1/2 inches in length, 21 inches in width, and 12-1/2 inches in depth. Level A unit packs shall be packed flat, alternated end to end, and nested in each stack, one in length, two in width and five in depth within the shipping container. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

* 5.2.3 Commercial packing. Cases, preserved as specified in 5.1 shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), cases, packed as specified in 5.2.1, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia, as applicable, of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:35Z
Check the source to verify that this is the currentversion before use.

5.4.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required information listed below legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall only indicate the following information:

STOCK NUMBER
ITEM DESCRIPTION
QUANTITY

6. NOTES

6.1 Intended use. The weapons case is intended for use by airborne personnel as a protective carrying container for individual or crew served weapons. The case is not furnished with a lowering line.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
c. Type of shipping container desired for level A packing (see 5.2.1).
d. When palletization is required (see 5.3).

6.3 Methods of repair. Cuts in felt of the case which do not intersect the stitches of a stitch pattern attaching any of the web straps to the case may be repaired with type 304 stitch. The cut edges of the felt shall be firmly butted and the cut sewed with a size E nylon thread, color Olive Drab, S-1, CA 66022, 7 to 11 stitches per inch, stitch width of 1/4 inch, plus 1/16 inch, minus 1/32 inch. The stitches shall extend a minimum of 1/2 inch beyond both ends of the cut edges. Cuts in the felt adjacent to a stitch pattern which attaches a web strap to the case may be repaired with a type 304 stitch, size E nylon thread, color Olive Drab, S-1, CA 66022, 7 to 11 stitches per inch. The stitches shall be as close as permitted to the original stitches but shall not intersect these. Cuts in the felt within a stitch pattern shall be repaired by hand stitching using size E nylon thread. Where necessary to prevent further damage, the additional stitches may extend around two or three sides of the stitch pattern.

6.4 Automatic stitching. Stitching patterns produced by automatic machines may be used upon approval by the contracting activity. Certification of equivalency, supported by engineering data, may be required.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on tne entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - Nu
Air Force - 99

Review activities:

Air Force - 82
DLA - CT

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8465-0899

☆ U.S. GOVERNMENT PRINTING OFFICE: 1985—505-038/21203

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-10922G	Case, Parachutist's Individual Weapons, M-1950, Adjustable

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:35Z
Check the source to verify that this is the current version before use.