MILITARY SPECIFICATION

CAPACITORS, FIXED, MICA DIELECTRIC, BUTTON STYLE,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-10950C, dated 8 July 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE II, delete and substitute:

TABLE II. Characteristic.

"

Symbol	Temperature coefficient (ppm/°C)	Capacitance drift (% of pF)
B	Not specified	Not specified
D	-100 to +100	0.3 percent or 0.3 pF, whichever is greater.
E	-20 to +100	±(0.1 percent +0.1 pF)
F	-60 to +60	±(0.1 percent +0.1 pF)

"

2.1: In list of Military Standards, delete "MIL-STD-456" (with corresponding title). Also add the following:

"MIL-STD-1285 - Marking of Electrical and Electronic Parts."

PAGE 4

* 3.10, delete and substitute:

"3.10 Shock (specified pulse). When capacitors are tested as specified in 4.6.7, there shall be no intermittent contacts of 0.5 milliseconds (ms) or greater duration, or arcing or other indication of breakdown, nor shall there be any open- or short-circuiting or evidence of mechanical damage."

3.12, title: Delete "Temperature cycling" and substitute "Thermal shock". Make this change wherever "Temperature cycling" appears in this specification.

PAGE 6

3.17.1, line 3: Delete "MIL-STD-456" and substitute "MIL-STD-1285".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:38Z
Check the source to verify that this is the current version before use.

TABLE IV, delete and substitute:

TABLE IV. Color code.

"

Color	Capacitance (pF)		Capacitance tolerance	Characteristic
	First and second significant figures	Multiplier 1/	Percent (±)	
Black	0	1	---	---
Brown	1	10	1 (F)	B
Red	2	100	2 (G)	---
Orange	3	1,000	---	D
Yellow	4	---	---	E
Green	5	---	---	F
Blue	6	---	---	---
Purple (Violet)	7	---	---	---
Gray	8	---	---	---
White	9	---	---	---
Gold	---	---	5 (J)	---
Silver	---	---	10 (K)	---

1/ The multiplier is the factor by which the two significant figures are multiplied to yield the nominal capacitance (see 1.2.1.4)."

PAGE 8

* TABLE V, group II: Delete "Shock (medium impact)" and substitute "Shock (specified pulse)".

PAGE 9

4.5.1.1, delete and substitute:

"4.5.1.1 Inspection lot. An inspection lot shall consist of all capacitors of the same group and shall consist of one or more styles as indicated in table VI, produced under the same conditions, and offered for inspection at one time. The sample selected from the lot shall be representative of the styles in the lot."

TABLE VI, delete and substitute:

" TABLE VI. Inspection lot groups.

Group	Styles
1	CB11 through CB50
2	CB55 through CB67

"

PAGE 10

* TABLE VIII: Delete "Shock (medium impact)" and substitute "Shock (specified pulse)".

TABLE IX: In first column: Delete "(every month)" for subgroups 1 and 2 and substitute "(every 2 months)" for both deletions. Subgroup 3: Delete "(every 3 months)" and substitute "(every 6 months)".

4.5.1.4.1.1., line 1: Delete "once each calendar month for subgroups 1 and 2 and every 3 months" and substitute "Once every 2 calendar months for subgroups 1 and 2 and every 6 months".

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:38Z
Check the source to verify that this is the current version before use.

PAGE 12

* 4.6.7, delete and substitute:

"4.6.7 Shock (specified pulse). Capacitors shall be tested in accordance with method 213 of MIL-STD-202. The following details and exceptions shall apply:

(a) Method of mounting: Normal mounting means.
(b) Test condition letter: I (100 G's).
(c) Electrical load during shock: Rated voltage shall be applied.
(d) Examination during and after shock: During the test, observation shall be made for momentary or intermittent arcing of 0.5 ms or greater duration. After the test, capacitors shall be visually examined for evidence of breakdown, arcing, fractures, loosening of parts, or other visible mechanical damage."

* 4.6.7.1: Delete in its entirety.

PAGE 13

4.6.9.1, line 1: Delete "method 102" and substitute "method 107".

4.6.9.1(a), line 1: Delete "Test condition letter - D" and substitute "Test condition letter - A".

PAGE 18

TABLE XI, delete and substitute:

" TABLE XI. Combined-style submittal data.

Styles	Type designation	Sample size
CB11 and	CB11NE152F	18
CB14	CB14SE512F	18
CB21 and	CB21TE242F	18
CB31	CB31QE242F	18
CB60 and	CB60RF471F	18
CB62	CB62RF242F	18
CB55 and	CB55RF471F	18
CB57	CB57RF242F	18
CB65 and	CB65PF471F	18
CB67	CB67PF242F	18

"

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:38Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - SH
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, CG, OS
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1600)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:38Z
Check the source to verify that this is the current version before use.