MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, MICA DIELECTRIC, BUTTON STYLE,

(FEED THRU) STYLES CB11, CB13, CB14

This amendment forms a part of MIL-C-10950/1E, dated 8 July 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* Shock (medium impact), delete in its entirety and substitute:

"Shock (specified pulse): Method 213 of MIL-STD-202, condition I (100 G's)."

* Temperature cycling and immersion, delete in its entirety and substitute:

"Thermal shock: Method 107 of MIL-STD-202, condition A.

"Immersion: Method 104 of MIL-STD-202, condition A.

"Insulation resistance: Not less than 5,000 megohms.

"Capacitance change: Within 1 percent of the initial value or 0.5 pF, whichever is greater."

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - SH
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, CG, OS
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1600-1)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:38Z
Check the source to verify that this is the current version before use.