MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, MICA DIELECTRIC, BUTTON STYLE (FEEDTHRU)
STYLE CB50

This amendment forms a part of MIL-C-10950/4D, dated 8 July 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Shock (medium impact), delete in its entirety and substitute:

"Shock (specified pulse): Method 213 of MIL-STD-202, condition I (100 G's)."

Temperature cycling and immersion, delete in its entirety and substitute:

"Thermal shock: Method 107 of MIL-STD-202, condition A.

"Immersion: Method 104 of MIL-STD-202, condition A.

"Insulation resistance: Not less than 5,000 megohms.

"Capacitance change: Within 1 percent of the initial value or 0.5 pF, whichever is greater."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - SH
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, CG, OS
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1600-4)


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:39Z
Check the source to verify that this is the current version before use.