MILITARY
SPECIFICATION

MIL-P-10952B(SigC)
28 April 1953
Superseding
MIL-P-10952A(SigC)
31 July 1952

PILOT BALLOON TARGET KIT MX-1265( )/AP

1. SCOPE

1.1 This specification covers Pilot Balloon Target Kit MX-1265( )/AP (see 6.3). The kit as listed in 1.1.1 consists of Pilot Balloon Target ML-307( )/AP, the principal component and the associated items. Pilot Balloon Target ML-307( )/AP is a target made of aluminum-foil backed paper on a balsa wood frame which when carried aloft by a balloon provides a reflective target for ground based radars.

1.1.1 Pilot Balloon Target Kit MX-1265( )/AP is composed of the following, packaged as indicated in Section 5.

24 each Pilot Balloon Target ML-307( )/AP
4 each Bracing Sticks (spares)
1 each Wind Data Pad
1 each Twine, in Tube
1 each Technical Bulletin
1 each Assembly Instruction Sheet

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND DRAWINGS

2.1 Specifications.- The following specifications, standards, and drawings of the issue in effect on the date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

NN-B-591	Boxes; Fiberboard, Wood-Cleated (For Domestic Shipment).
NN-B-601	Boxes; Wood-Cleated-Plywood, For Domestic Shipment.
NN-B-621	Boxes; Wood, Nailed and Lock-Corner.
UU-T-111	Tape; Paper, Gummed (Sealing and Securing).
LLL-B-631	Boxes, Fiber Corrugated (For Domestic Shipment).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:39Z
Check the source to verify that this is the current version before use.

MILITARY

JAN-P-105	Packaging and Packing for Overseas Shipment - Boxes, Wood Cleated, Plywood.
JAN-P-106	Packaging and Packing for Overseas Shipment - Boxes; Wood, Nailed.
MIL-B-107	Boxes, Wood, Wire Bound, (Overseas Type).
MIL-P-116	Preservation, Methods of.
JAN-P-117	Packaging and Packing for Overseas Shipment - Bags, Interior Packaging.
JAN-P-125	Packaging and Packing for Overseas Shipment - Barrier Materials, Waterproof, Flexible.
MIL-A-140	Adhesive, Water-Resistant, Waterproof Barrier Material.
JAN-T-713	Twine, Lacing and Tying, Electrical and Electronic Equipment.

U. S. ARMY

19-10	Filler, Interior, Packing, Fiberboard, Corrugated, Single and Double Faced, For General Packing Purposes.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection By Attributes.
MIL-STD-129	Marking of Shipments.

DRAWINGS

SIGNAL CORPS

460-12	Group B-2 Sampling Plans.
SC-DL-20560	Drawing List - Pilot Balloon Target ML-307( )/AP.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer. Both the title and identifying symbol should be stipulated when requesting copies.)

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:39Z
Check the source to verify that this is the currentversion before use.

3. REQUIREMENTS

3.1 Preproduction samples.-

3.1.1 Quantities.- After award of contract, two preproduction samples of collapsed pilot balloon targets shall be furnished (See 6.5).

3.1.2 Compliance with specified requirements.-

3.1.2.1 Preproduction samples shall meet specified requirements, shall be made and assembled by tools and methods that will be used for quantity production, and shall be accompanied by a statement to that effect. (See 3.1.2.3 for exception.)

3.1.2.2 Approval of preproduction samples shall not be construed as a waiver of any specified requirement. After being released to the contractor (see 3.1.2.4), preproduction samples to be offered as units on contract shall be refabricated by the contractor if necessary to meet specified requirements.

3.1.2.3 When deviation from 3.1.2.1 is unavoidable, the preproduction samples may be submitted for approval provided that the accompanying statement describes in detail each nonconforming feature, reason therefor, and manner in which it will be corrected in production of equipment on contract.

3.1.3 Test data.- The preproduction samples shall be accompanied by test data showing compliance with specified performance. The test data shall comprise an engineering report giving test procedure, observations and other data, calculations, test results, and essential details of the testing equipment (manufacturer's model, serial number, date of calibration, and the like).

3.1.4 Reference standards.- After preproduction samples have been approved and returned to the contractor's plant, they shall be kept intact in custody of the Government inspector until released by him. They shall be used as reference standards to resolve any differences of opinion regarding interpretation of specified requirements.

3.1.5 Preproduction inspection.- Preproduction samples may be submitted by the Government to the group A inspection and to the group B inspection specified in tables I, and II, respectively. Unlisted nondestructive inspection on preproduction samples of equipment and unlisted destructive or nondestructive inspection on separate preproduction samples of parts or materials may be performed to determine compliance with specified requirements.

3.2 Construction.- Pilot Balloon Target ML-307( )/AP shall be constructed in accordance with drawings listed on Drawing List SC-DL-20560.

3.2.1 Parts, materials and processes.- Parts, materials, and processes for Pilot Balloon Target ML-307( )/AP shall be in accordance with Drawing List SC-DL-20560.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:39Z
Check the source to verify that this is the current version before use.

3.3 Facsimiles.- Two facsimile copies of the Ravin Data Sheet Form R-424 (wind data pad) and the assembly instruction sheet shall be submitted for approval to the contracting officer.

3.4 Associated items.- The items listed in the following subparagraphs shall be furnished and packaged in accordance with Section 5.

3.4.1 Assembly instructions.- An assembly instruction sheet shal be printed in black ink on unglazed paper. It shall be set forth, a step by step procedure, for assembling the end item from its collapsed, packaged state.

3.4.2 Wind data pad.- One wind data pad (Ravin Data Sheet Form R-424, 48 sheets to the pad, shall be supplied with each 24 targets on order.

3.4.3 Waxed twine (tube).- One (1/2 lb.) tube of twine, (type N or composition VCR of type 5) class I in accordance with Specification JAN-T-713 shall be supplied with each group of 24 targets.

3.5 Workmanship.- The equipment shall be manufactured and assembled in a thoroughly workmanlike manner.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:39Z
Check the source to verify that this is the current version before use.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Inspection, general.- Inspection shall consist of group A, and group B inspection as specified in 4.1.1 through 4.1.2.1 (see 6.6.). Group B inspection shall normally be performed on lots that have passed group A inspection and on samples selected from units that have been subjected to and met the group A inspection. However, the order may be varied when the Government considers it more practical to select separate samples for group B inspection.

4.1.1 Group A inspection.- Group A inspection shall be in accordance with table I and Standard MIL-STD-105.

4.1.2 Group B inspection.- Group B inspection shall be in accordance with table II.

Table I - Government group A inspection

Inspection	Requirement paragraph	Test paragraph	AQL
Visual and mechanical - major	3.2 thru 3.5	4.2	1%
Visual and mechanical - minor		4.2	4%

Table II - Government group B inspection

Inspection	Requirement paragraph	Test paragraph	Group B plans	Drawing
Adhesion	3.2.1	4.3	B-2	460-12

4.1.2.1 Sampling procedure.- Samples shall be selected in an unbiased manner by the Government inspector. Unless otherwise specified, inspection shall be started using level II of the specified drawing. If the number of defective sample units from a lot exceeds the acceptance number specified on the drawing, the lot shall be rejected. Disposition of rejected product (sample units and lots) shall be in accordance with Standard MIL-STD-105 and 4.1.3.

4.1.2.2 Procedure in case of failure.- When a lot is rejected, the contractor shall immediately investigate the cause of failure and shall report to the Government inspector the results thereof and proposed corrective action. If the contractor and Government inspector cannot agree on the corrective action to be taken, the matter shall be referred to the contracting officer for resolution.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:39Z
Check the source to verify that this is the current version before use.

4.1.2.3 Reinspection of conforming group B sample units.- Unless otherwise specified, sample units which have been subjected to and passed group B inspection, may be accepted in contract, provided that all visible damage incurred during group B inspection is repaired and the units are then subjected to and pass group A inspection.

4.1.3 Disposition of nonconforming product.- When defective sample units or rejected lots are resubmitted for acceptance, such items shall be suitably tagged or identified by equivalent means to indicate the cause of failure and means employed to correct the fault. The record shall be presented to the Government when the items are resubmitted and shall become the property of the Government.

4.2 Visual and mechanical inspection.- The part or component shall be given a thorough inspection for mechanical fit, markings, poor workmanship, and other defects. Pilot Balloon Target ML-307( )/AP shall be inspected to see that it has been assembled according to drawings so that there are no foil-to-foil seams. Devices shall be checked for proper functioning. Visual and mechanical defects shall be classified by the Government as major or minor in accordance with definitions of Standard MIL-STD-105.

4.3 Adhesion tests.- Random targets, as determined by the Government, shall be tested for good adhesion by prying the balsa wood from the aluminum foil, the aluminum foil from the paper, and the paper from the wood. This test shall ascertain that the glued surfaces do not separate.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:39Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-

5.1.1 For domestic shipment.- Pilot Balloon Target Kit MX-1265( )/AP shall be packaged in accordance with method III of Specification MIL-P-116 (See 6.4).

5.1.2 For export shipment.- Preserve and package Pilot Balloon Target Kit MX-1265( )/AP in accordance with procedures specified for the designated methods as prescribed in Specification MIL-P-116, and further described in the following paragraphs. (See 6.4)

5.1.2.1 Technical bulletin, instruction sheets, wind data pad and twine.- Package each item method IC-3, as follows: Inclose each item, together within a close-fitting type II class b bag, conforming to Specification JAN-P-117. Properly seal closure.

5.1.2.2 Unit package.- Pilot Balloon Target Kit MX-1265( )/AP shall be packaged method IC-2, and shall consist of the following items:

1 package packaged as specified in 5.1.2.1
24 pilot balloon targets (collapsed)
52 bracking sticks

Collapse each balloon target to its minimum dimensions. Stack the balloon targets together with bracing sticks side by side to form a uniform square: cushion the targets by wrapping in a conforming wrap of flexible corrugated fiberboard conforming to Specification 19-10. Seal entire closure with gummed kraft tape, conforming to Specification UU-T-111. Overwrap each cushioned unit with waterproof barrier material, complying with Specification JAN-P-125, for case liners. Completely seal all seams and closures of the waterproof barrier with a continuous seam at least 2 inches wide of water resistant adhesive, complying with Specification MIL-A-140.

5.2 Packing.-

5.2.1 For domestic shipment.- Pilot Balloon Target Kit MX-1265( )/AP, shall be packed in wood cleated fiberboard, wood cleated plywood, nailed wood, or corrugated fiberboard boxes conforming to Specification NN-B-591, NN-B-601, NN-B-621, and LLL-B-631, respectively. Closures shall be made in accordance with the applicable box specification. (See 6.4)

5.2.2 For export shipment.- Place 2 unit packs packaged as specified in 5.1.2.2 stacked to form a square package within a wood cleated plywood, nailed wood or wirebound wood box conforming to the requirements of Specification JAN-P-105, JAN-P-106 and MIL-B-107 respectively. Fabricate the boxes to fit contents snugly. The approximate gross weight of any exterior shipping container shall not exceed 150 pounds. Close the shipping container as specified in the appendix of the applicable box specification. (See 6.4)

5.2.2.1 Shipping containers shall be strapped in conformance with the requirements of the appendix of the applicable container specification only for direct shipment to ports.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:39Z
Check the source to verify that this is the current version before use.

5.3 Marking for shipment.- Interior packages and exterior shipping containers shall be marked in accordance with applicable provisions of Standard MIL-STD-129.

6. NOTES

6.1 Intended use.- Pilot Balloon Target ML-307( )/AP, the principal item of this kit, is a lightweight, expendable target for use with Pilot Balloons ML-159, ML-160 and ML-161 which when tracked by ground based radars such as Radar Set AN/CPS-10 or Radio Set SCR-584, determines the upper wind direction and speed.

6.2 Pilot Balloon Target Kit MX-1265( )/AP.- Kit MX-1265( )/AP provides a basis whereby the principal component, Pilot Balloon Target ML-307( )/AP may be issued in lots of 24 each with the necessary white pine bracing sticks and with one each assembly instruction sheet, technical bulletin, tubes of twine and wind data pad per lot of 24 targets.

6.3 Nomenclature.- The parenthesis in the nomenclature will be deleted or replaced by a letter identifying the particular design, for example ML-307W/AP or MX-1265W/AP. As soon as possible after award of the contract, the contractor should apply to the contracting officer for such information. (See 1.1)

6.4 Ordering data.- Procurement documents should specify the following:

a. Title, number and the date of this specification.
b. Samples required. (See 3.1.1)
c. Marking and shipping of samples.
d. Whether domestic or overseas shipment is required. (See 5.1.1, 5.1.2, 5.2.1, and 5.2.2)
e. Place of final inspection.
f. Acceptable quality level (see 4.1).
g. Facsimiles required. (See 3.3).

6.5 Waiver of preproduction samples.- When items for which preproduction samples are required are currently in production on a Government order, the contractor may apply to the contracting officer for waiver of preproduction samples on the new order. Any request for waiver should include a statement indicating that the specified samples have been submitted and approved on the current contract; production of the item under the new order will be concurrent with, or follow without interruption, production on the current order; and current production is in strict compliance with specified requirements for the new equipment, or describing any deviations authorized on the current order. Waiver of preproduction samples may be contingent on renegotiation of the contract to reflect the saving in cost to the contractor.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:39Z
Check the source to verify that this is the current version before use.

6.6 Additional testing.- It should be understood that additional inspection and non-destructive test of equipment may be performed by the Government inspector when considered necessary to determine compliance with this specification and other applicable documents. The Government inspector, therefor, may withdraw materials, parts, or assemblies temporarily from production for such inspection and testing, performed either at a Government or the contractor's plant.

NOTICE: When a Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission or manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:39Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:39Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING GENERAL
U.S. ARMY ELECTRONICS COMMAND
ATTN: AMSEL-PP-E-SED
FORT MONMOUTH, N.J. 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:39Z
Check the source to verify that this is the current version before use.