MIL-S-10926G
10 June 1986
SUPERSEDING
MIL-S-10926F
5 March 1979

MILITARY SPECIFICATION

SUSPENDERS, TROUSERS, M-1950

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers elastic webbing suspenders of one type and size.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-276	- Thread, Cotton
JJ-W-155	- Webbing, Textile, (Cotton, Elastic)
QQ-B-613	- Brass, Leaded and Nonleaded: Flat Products (Plate, Bar, Sheet, and Strip)
QQ-S-766	- Steel Plates, Sheets, and Strip - Corrosion Resisting

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8440

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

QQ-W-321	- Wire, Copper Alloy
QQ-W-423	- Wire, Steel, Corrosion-Resisting
UU-B-36	- Bags, Paper (Grocers)
DDD-L-20	- Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-T-45	- Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-F-495	- Finish, Chemical, Black, for Copper Alloys
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

2-4-48 - Suspenders, Trousers, M-1950

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

COLOR ASSOCIATION OF THE UNITED STATES

Standard Color Reference of America

(Application for copies should be addressed to the Color Association of the United States, 343 Lexington Avenue, New York, NY 10016.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Guide samples. Guide samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variation from this document may appear in the sample, in which case this document shall take precedence.

3.2 Materials. (See 6.4.)

3.2.1 Basic material. The material for the shoulder straps and shoulder loops shall be cotton elastic webbing, 1 1/2 inches wide, Olive Drab 7, conforming to type I, class 11 of JJ-W-155, except that the requirements for colorfastness to accelerated weathering shall not apply.

3.2.2 Webbing. The material for the hook tabs shall be cotton webbing, 1 1/2 inches wide, Olive Drab 7, conforming to type IIa, class 3 of MIL-W-530, except that the requirement for colorfastness to accelerated weathering shall not apply.

3.2.3 Thread. The thread for seaming and stitching shall be cotton type IA3 or IB3, ticket No. 30, 3 ply, and 24, 4 ply, Olive Drab S-1 (C.A. 66022), conforming to V-T-276.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

3.2.3.1 Colorfastness. The dyed thread shall show fastness to perspiration and laundering equal to or better than the standard sample. When no standard sample is available, the colored thread shall show "good" colorfastness to perspiration and laundering.

3.2.4 Slide buckles. The buckles shall be made from corrosion-resistant steel sheet, finish No. 2D, or steel strip, finish No. 1, conforming to class 430 of QQ-S-766; or quarter-hard or half-hard brass, sheet or strip, conforming to copper alloy No. 268 of QQ-B-613. The buckles shall conform to the design and dimensions shown on Drawing 2-4-48. The steel buckles shall have a dull black finish, produced chemically or by a fused salt bath, when tested as specified in 4.2.1. The brass buckles shall have a black chemical finish conforming to MIL-F-495.

3.2.5 Hooks. The hooks shall be made from corrosion-resistant steel wire conforming to form 1, composition 430, condition A of QQ-W-423; or quarter-hard round brass wire conforming to alloy No. 270 of QQ-W-321. The hooks shall conform to the design and dimensions shown on Drawing 2-4-48. The steel hooks shall have a dull black finish, produced chemically or by a fused salt bath, when tested as specified in 4.2.1. The brass hooks shall have a black chemical finish conforming to MIL-F-495.

3.2.6 Ferrule. If steel wire is used for the hooks, the ferrules shall be formed from stainless steel strips composition 430, condition A, 0.025-inch thick, conforming to QQ-S-766. The steel ferrules shall have the same finish as the steel hooks. If brass hooks are used, the ferrules shall be formed from brass strips, copper alloy No. 260 or 268, quarter-hard, 0.025-inch thick, conforming to QQ-B-613. The brass ferrules shall have the same finish as the brass hooks. The design of the ferrules shall be as shown on Drawing 2-4-48.

* 3.2.7 Labels. Each pair of suspenders shall have an identification label conforming to type IV, class 2 of DDD-L-20. The fastness to laundering requirements of DDD-L-20 shall apply. The label color shall be medium green. The following cable numbers of the Standard Color Reference of America are furnished for information and guidance as to the intensity of the shade desired for the labels:

Cable No. 70034
Cable No. 70130
Cable No. 70131

* 3.3 Design. The design is a scissor-back type as shown on Drawing 2-4-48.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

* 3.4 Drawing 2-4-48. Drawing 2-4-48 establishes dimensional requirements for the hardware and shows the desired end item. If there are any inconsistencies between the written document and the drawing, the document shall control.

3.5 Construction.

* 3.5.1 Stitches, seams, and stitching. All stitches, seams, and stitching shall conform to FED-STD-751. The type of seam, stitching, and stitches per inch shall be as specified in table I. Where two or more methods for seams or stitch types are given for the same part of the operation, any one of them may be used.

* 3.5.1.1 Automatic stitching. Any of the stitching operations cited in this document may be performed with an automatic machine, provided that the requirements for stitch pattern, stitches per inch, size, and types of thread are met, and that at least three tying, overlapping, or back stitches are used to secure the ends of stitching.

* 3.5.1.2 Type 301 stitching. Ends of all stitching shall be backstitched or bartacked not less than 1/2 inch except where ends are caught in other seams and stitching. Thread tension shall be maintained so that there will be no loose or tight stitching and the lock will be embedded in the sewn material.

3.5.1.2.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1/2 inch in back of the end of stitching.1/

b. Thread breaks, or two or more consecutive skipped or run-off stitches, noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1/2 inch in back of the defective area, continue over the defective area, and continue a minimum of 1/2 inch beyond the defective area onto the existing stitching.1/

c. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner.1/

1/ When making the above repairs, the ends of stitching are not required to be backstitched.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

3.5.1.3 Repairs of types 502, 503, and 504 stitching. All repairs shall be in accordance with 3.5.1.2.1 except for substituting 3/4 inch wherever 1/2 inch appears.

3.5.1.4 Thread ends. All thread ends shall be trimmed to a maximum length of 1/4 inch.

3.6 Manufacturing operation requirements. The suspenders shall be manufactured as specified by the operations in table I. The contractor is not required to follow the exact sequence of operations listed. Any additional tacking or holding stitching used to facilitate manufacture is permissible, provided that the thread is removed or does not show on the finished suspenders.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing operations requirements

No.	Requirements	Stitch type	Seam and stitching type	Stitches per inch	Thread	
					Needle	Bobbin/ Looper
1.	Cut webbing					
	a. Cut elastic webbing for shoulder straps (two each) and shoulder loops (two each) in sufficient lengths to conform to finished measurements specified in 3.7.					
	b. Cut cotton webbing for hook tabs (two each) in sufficient lengths to conform to finished measurements specified in 3.7.					
	c. The shoulder loops and hook tabs may be cut from short lengths and, when so cut, they shall approximate the shade of the basic material.					
2.	Labeling					
	Apply the identification label so that on the finished suspenders the label will be on the inside of the left shoulder strap (when worn), not less than 3 inches from the diagonal end (point A on Drawing 2-4-48).					
3.	Make elastic shoulders straps					
	a. Overedge stitch one end of each shoulder strap.	502 or 503 or 504	EFd-1 EFd-1 EFd-1	8-12 8-12 8-12	30-3 30-3 30-3	30-3 30-3 30-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing operations requirements - Continued

No.	Requirements	Stitch type	Seam and stitching type	Stitches per inch	Thread	
					Needle	Bobbin/ Looper
3.	Make elastic shoulder straps (continued)					
	b. Position each shoulder loop to each shoulder strap so the ends of the shoulder loops nearest the overedged ends of the shoulder straps are 22 inches ± 3/8 inch from the overedged ends.					
	c. Attach one shoulder loop by turning in the raw ends of the shoulder loops not less than 3/8 inch, and box stitch to shoulder straps, catching the turned in ends in the stitching. The box pattern shall be 1 3/8 to 1 1/2 inches long and 1/8 to 3/16 inch wide. Insert the other loop through the opening between the attached loop and shoulder strap, then box stitch the ends of loop to shoulder strap as indicated above. This will allow the scissor action of shoulder straps.	301	LSd-2	10-14	24-4	24-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing operations requirements - Continued

No.	Requirements	Stitch type	Seam and stitching type	Stitches per inch	Thread Needle	Thread Bobbin/ Looper
4.	Make hook tabs and attach shoulder straps					
	a. Overedge stitch one end of each cotton webbing.	502 or 503 or 504	EFd-1 EFd-1 EFd-1	8-12 8-12 8-12	30-3 30-3 30-3	30-3 30-3 30-3
	b. Lace the webbing as shown on Drawing 2-4-48 through the adjustment loop and the eye of the hook forming a tab of three plies.					
	c. Insert the raw edge of the elastic shoulder strap, at a 60 ± 5 degree angle, between the second and third ply of the hook tab webbing, the full width of webbing (but not beyond the outside edge). Box stitch through the three thicknesses of webbing, with the inserted end of the shoulder strap caught in the stitching of the inside edge and partially caught in the diagonal stitching. Stitch across the width of the webbing at each end of tab with a double row of stitches. The first row shall be 1/4 ± 1/8 inch from each folded end and the second row within 1/8 inch of the first row. Then stitch along the sides of webbing with a single row of stitches 1/8 to 3/16 inch from edge. The diagonal stitching shall be from corner to corner, crossing at center.	301		10-14	24-4	24-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

TABLE I. Manufacturing operations requirements - Continued

No.	Requirements	Stitch type	Seam and stitching type	Stitches per inch	Thread	
					Needle	Bobbin/ Looper
5.	Attach shoulder straps to slide buckles					
	Attach the free end of each shoulder strap to the slide buckle as shown on Drawing 2-4-48 (see side view).					
6.	Clean suspenders					
	a. Trim all thread ends to a length of not more than 1/4 inch.					
	b. Remove all loose threads, spots, and stains.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

* 3.7 Finished measurements. The finished suspenders shall conform to the measurements in table II (see also Drawing 2-4-48).

TABLE II. Size of finished suspenders

Dimension	Inches	Tolerance inches
Length of each shoulder strap from "A" to overedged end 1/	38 3/4	± 1/2
Length of each shoulder loop	6 3/8	± 1/4
Length of each hook tab	2 3/8	± 1/4
Length of free end of hook tab	2	± 1/2
Finished position of shoulder loops from overedged ends of straps 1/	22 3/4	± 3/8

1/ This measurement shall be made with the shoulder strap laid out flat, without tension, and the end of the strap not attached to the slide buckle.

3.8 Replacement of defective components. During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in 4.2.2 and 4.2.3 shall be removed from production and replaced with nondefective and properly matched components.

3.9 Workmanship. The finished suspenders shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in the document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document. In addition, testing shall be performed on components listed in table III for characteristics noted. The lot sizes shall be expressed in terms of "gross slide buckles" or "gross hooks", as applicable, and the sample unit for testing shall be one slide buckle or one hook as applicable. The lot shall be unacceptable if one or more sample units fail to meet the specified requirements and tolerances. The sample size shall be in accordance with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

Lot size	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

TABLE III. Test methods

Component	Characteristic	Requirement paragraph	Test method	Determinations per sample unit	Results reported as
Slide buckle	Dimensions	3.2.4	Scale	1	To the nearest 1/32 inch
	Finish on steel	3.2.4	1/		
Hook and ferrule	Dimensions	3.2.5 and 3.2.6	Scale	1	To the nearest 1/32 inch
	Finish on steel and brass	3.2.5 and 3.2.6	1/		

1/ A certificate of compliance is required and will be acceptable for the stated requirements.

* 4.2.2 End item visual examination. The finished suspenders shall be examined for the defects listed in table IV. The lot size shall be expressed in units of suspenders. The sample unit shall be one suspender. The inspection level shall be II, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 major defects and 15.0 for total (major and minor) combined defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of visual defects

Defect	Classification	
	Major	Minor
Material defects and damages		
Webbings:		
Hole, cut tear, neddle chew, smash, multiple float, loose slub, or frayed scalloped edges	X	
Large exposed drill hole	X	
Visible mend		X
Hardware:		
Broken or malformed	X	
Corroded area, burr, or sharp edge	X	
Finish partially omitted		X
Finish omitted	X	
Size or type not as specified	X	
Cleanness		
Spot or stain		X
Thread ends not trimmed or loose threads not removed throughout suspenders		X
Any tacking or holding thread visible on the finished suspenders		X
Component and assembly		
Any component part or required operation omitted (unless otherwise classified herein)	X	
Any operation not performed as specified (unless otherwise classified herein)		X
Seams and stitching		
Part of material caught in unrelated operation or stitching		X
End of stitching when not caught in other seams or stitching backtacked less than 1/2 inch	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of visual defects - Continued

Defect	Classification	
	Major	Minor
Seams and stitching (continued)		
Stitching overlapping the end(s) of thread break less than 1/2 inch		X
Ends of a continuous line of stitching overlapped less than 1/2 inch		X
Gage of stitching and seam allowances:		
Irregular, i.e., unevenly gaged or corresponding stitchings not uniformly gaged (to be scored only when condition exists along major portion of seam)	X	
Width not as specified, or not within range of gage specified, or varies more than 1/16 inch when no range is specified		X
Stitches broken or missing		
-up to 1/2 inch (inclusive)		X
-more than 1/2 inch	X	
Skipped stitches		
-1/4 inch up to 1/2 inch (inclusive)		X
-more than 1/2 inch	X	
Run-offs		
-1/4 inch up to 1/2 inch (inclusive)		X
-more than 1/2 inch	X	
Raw edge more than 1/4 inch		X
Seam or stitch type not as specified		X
Stitches per inch less than minimum or more than maximum specified		X
Stitch tension:		
Loose tension		
-resulting in a loose seam	X	
-resulting in exposed loops of top or bottom thread for a distance of more than 1 inch		X
Tight tension (stitches break where strain is applied in the direction of the seam or stitching)		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of visual defects - Continued

Defect	Classification	
	Major	Minor
Identification label		
Omitted, incorrect, illegible		X
Not positioned as specified		X

* 4.2.3 End item dimensional examination. The end item shall be examined for dimensional defects in table V. Any dimension that varies from that specified in 3.7 shall also be classified as a defect. The inspection level shall be S-3, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

TABLE V. Dimensional defects

Examine	Defect
Angle between shoulder straps	Less than 55° or more than 65°
Component and location dimensions	Not within specified tolerance

4.2.4 Packaging examination. The fully packaged end items shall be examined for the defects listed on the following page. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2, and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and unit packs)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components such as incomplete closure of container flap, improper taping, loose strapping, inadequate stapling Bulged or distorted container
Content	Number of unit packs per container is more or less than required Number of suspenders per unit packs is more or less than required 1/

1/ For this defect, one unit pack from each container in the sample shall be examined.

4.2.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted, incorrect, illegible, or of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each pair of suspenders shall be folded in half to an approximate length of 10 inches and tied at the center with cotton tape or twine. Ten pairs of folded suspenders, stacked in two tiers of five pairs each, with every other pair reversed, shall be unit packed in a close-fitting clear polyethylene film bag of 0.00125-inch thickness (± 25 percent tolerance). The polyethylene bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and to the formed edges of the bag. The polyethylene bag closure shall be effected by heat sealing with the heat seal made as close as possible to the open end or by means of a mechanical tie (e.g., paper or vinyl plastic covered soft steel wire, aluminum band). Prior to or during the heat seal closure operation, excess air within the bag shall be expelled. Alternatively, the suspenders may be unit packed in a kraft paper bag conforming to type II, grade A, number 10 of UU-B-36. The open end of the paper bag shall be folded over and secured with 2-inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45. The unit pack shall measure approximately 10 inches in length, 5 inches in width and 3 3/8 inches in depth.

* 5.1.2 Commercial. Suspenders shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. One hundred and twenty pairs of suspenders, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed flat, four in length, one in width (against one side panel), and two in depth, and the remaining four shall be placed flat, two in length, and two in depth, in the space at the opposite side panel of the shipping container. Inside dimensions of each container shall approximate 23 1/2 inches in length, 15 1/2 inches in width, and 6 3/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.2.4. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B packing. One hundred and twenty pairs of suspenders, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275, of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, four in length, one in width (against one side panel), and two in depth, and the remaining four shall be placed flat, two in length and two in depth, in the space at the opposite side panel of the shipping container. Inside dimensions of each container shall approximate 23 1/2 inches in length, 15 1/2 inches in width and 6 3/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.2.4.

* 5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that inspection shall be in accordance with 4.2.4.

* 5.2.3 Commercial packing. Suspenders, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), suspenders, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be No. 3 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged packages. Polyethylene bagged unit packs shall have the required identification information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit easy identification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The suspenders are intended to be worn with combat and field trousers worn by personnel of the Department of Defense.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
c. Type and class of unit load required (see 5.2.1).
d. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
e. When palletization is required (see 5.3).

6.3 Samples. For access to samples address the contracting activity issuing the invitation for bids.

6.4 Recycled material. The contractor is encouraged to use recycled material for nontextile components, provided that it meets the requirements of this document (see 3.2).

6.5 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

User activities:

Navy - CG
Air Force - 45

Preparing activity:

Army - GL

Project No. 8440-0169

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-10929G	Suspenders, Trousers, M-1950

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:36Z
Check the source to verify that this is the current version before use.