MILITARY SPECIFICATION

FITTINGS AND FLANGES. CAST BRONZE, SILVER-BRAZING

SUITABLE FOR ULTRASONIC INSPECTION

This amendment forms a part of Military Specification MIL-F-24227 (SHIPS), 18 May 1966

Page 1, paragraph 1.2: Delete

"FITTINGS	Figure	Table
Caps:	17	XX
Reducer (reducing one size)	7	X
Reducer (reducing two sizes)	8	X
Straight coupling	6	X'

and substitute:

"FITTINGS	Figure	Table
Caps:	17	XX
Couplings and reducers:		
Reducer (reducing one size)	7	X
Reducer (reducing two sizes)	8	X
Straight coupling	6	X"

Page 2, paragraph 2.2, under American Society for Testing and Materials, B61: Delete "Stem" and substitute "Steam".

Page 2, paragraph 3.1.1, first sentence: Delete and substitute: "Castings produced by continuous melt process and not identified with a heat no. or code may be accepted provided the controls are approved by the procuring activity and cognizant inspector."

Page 4, table V: Delete "Tolerances on angles to be ± 0° - 3 inches" and substitute "Tolerances on angles to be ± 0° - 30 minutes"

Page 5, paragraph 3.3.18, line 2: Delete "cuts of"

Page 5, paragraph 3.3.19, second sentence: Delete and substitute: "Drilled flanges shall be spot-faced on the black parallel to the face of the flange for the bolt-heads and nuts."

Page 5, table VI, column 1: Delete "1-5/16" and substitute "15/16"

Page 5, paragraph 3.4.1, line 1: Delete "fitting" and substitute "fitting, union"

Page 5, paragraph 3.4.1, item (c)(1): Delete "200S" and "150S"

Page 9, table VIII, change as follows:

(a) Column 1, Outside diameter of tube: Delete "0.504" and substitute "0.540"
(b) Column M, opposite 3 inch iron pipe size: Delete "3.206" and substitute "3.286"
(c) Column G: Delete "Minimum"

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:08Z
Check the source to verify that this is the current version before use.

Page 23, table XVIII, column Y: Delete and substitute:

Y
Inches
0.831
.904
1.049
1.219
1.369
1.604

Page 23, table XVIII, column f: Delete and substitute:

f	
Pitch diameter	
Maximum	Minimun
Inches	Inches
1.4492	1.4420
1.7801	1.7720
2.1102	2.1020
2.5407	2.5320
2.8609	2.8520
3.4610	3.4520

Page 26, table XX, change as follows:

(a) Column F, minimum, opposite 6 inch iron pipe size: Delete "6.670" and substitute "6.630".
(b) Column F, maximum, opposite 6 inch iron pipe size: Delete "6.720" and substitute "6.730".
(c) Column G_2: Delete "Maximum" and substitute "Minimum".
(d) Column H_1: Delete "H_1" and substitute "H"
(e) Last column, opposite 1-1/2 inch iron pipe size: Delete "2.28" and substitute "2.38".
(f) Last column, opposite 6 inch iron pipe size: Delete "7.42" and substitute "7.56".

Preparing activity:
Navy-SH
(Project 4730-N658)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:08Z
Check the source to verify that this is the current version before use.