MIL-C-14968(MU)
5 November 1968
SUPERSEDING
(See 6.6)

MILITARY SPECIFICATION

CARTRIDGE, 57MM, SMOKE, WP, M308A1 ASSEMBLING, MARKING AND PACKING

1. SCOPE

1.1 This specification covers the assembling, marking and packing for one type of cartridge designated as Cartridge, 57MM, Smoke, WP, M308A1, for use with the 57MM rifle, M18.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ARMY

9215427 - Cartridge, 57MM: Smoke, WP, M308A1 w/Fuze, PD, M503A2 for 57MM Rifle, M18, M18A1

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

8796471 - Box, Packing Ammunition for 57MM Rifle, Ammunition in Fiber Container M167A2, Assembly, Details and Packing
9215018 - Ammunition Container, Fiber, 57MM, M167A2 Assembly, Details, Packing and Marking.

PUBLICATIONS

ARMY

ET-9215427 - Equipment Tabulation

(Copies of specifications, standard, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Cartridge.-The cartridge shall comply with all requirements specified on Drawing (dwg.) 9215427 and with all requirements specified in applicable specifications.

3.3 Propellant weight.-The weight of the propellant shall not differ by more than plus or minus 0.02 ounce from that designated by the loading authorization for the particular lot of propellant used.

3.4 Cartridge case crimp

3.4.1 Torque.-The projectile shall withstand a torque of 100 inch-pounds minimum (min.), without rotating in the cartridge case, when tested as specified in 4.3.1.1.

3.4.2 Bullet pull.-The cartridge case shall separate from the projectile at a load between 1000 pounds, min., and 2500 pounds, maximum (max.), when tested as specified in 4.3.1.2.

3.5 Proving ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.2.

3.5.1 Muzzle velocity.-The corrected muzzle velocity of the projectile at ambient temperature shall be not more than 1236 feet per second (fps) nor less than 1164 fps and the standard deviation of the lot shall not exceed 13 fps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

3.5.2 Projectile functioning.-There shall be visible evidence of functioning upon impact as indicated by the presence of a smoke cloud.

3.5.3 Premature burst and security of parts.-There shall be no premature burst or indication of metal parts failure in the gun bore or in flight before impact.

3.5.4 Safety.-There shall be no premature burst or indication of metal parts failure in the gun bore or in flight when fired with propellant adjusted to give 112 percent of the rated maximum pressure of a new gun.

3.6 Workmanship

3.6.1 Cartridge.-All manufacturing, processing and assembly operations of the cartridge shall be correctly performed in a thoroughly workmanlike manner. Parts shall be free of burrs, chips, dirt, cracks, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The cartridge or components shall not be damaged in any manner during the loading operation.

3.6.1.1 Painting and marking shall be restored by the loading and assembling contractor on any component furnished him when such painting or marking has been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specification referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection provisions

4.2.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specifications, or drawings, not affecting safety, performance interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

a. Propellant charge from not more than one lot.

b. Loaded primers from one lot interfix number from one manufacturer.

c. Cartridge cases from one manufacturer with one lot interfix number.

d. Loaded fuzes from one lot interfix number from one manufacturer.

e. WP loaded filling assemblies from one manufacturer in accordance with the same drawing, same drawing revision, same specification and same specification revision of one loading lot interfix number.

f. Burster charges from not more than one lot.

4.2.2 Examination.-Inspection for Critical defects (and Major defects, when so specified) shall be 100 percent. Sampling plans and procedures shall be in accordance with Standard MIL-STD-105 or MIL-STD-414 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100% inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with para. 4.2.4.

4.2.2.1 Primer, prior to assembly to cartridge case (see dwg. 8839466 covering a detail of dwg. 9215427)

Categories	Defects	Method of Inspection	Code No.
Critical:			
	1. One or more flash holes missing	Visual	01001
Major: None defined.			
Minor:	AQL 0.65 percent		
	201. Evidence of poor workmanship (see 3.6)	Visual	01002

4.2.2.2 Cartridge case prior to assembling to propelling charge (see dwg. 10535911 covering a detail of dwg. 9215427)

Categories	Defects	Method of Inspection	Code No.
Critical:			
	1. Primer obviously loose	Manual	02001

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Primer damaged	Visual	02002
Minor:	AQL 1.5 percent		
201.	Foreign matter on interior of liner	Visual	02003
202.	Foreign matter in charge	Visual	02004
203.	Evidence of poor workmanship (see 3.6.1.2)	Visual	02005

4.2.2.3 Cartridge case with propelling charge, prior to assembling to projectile (see dwg. 10535911 covering a detail of dwg. 9215427)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Propellant charge missing ...	Visual	03001
102.	Liner improperly closed	Visual	03002
103.	Liner perforated or torn	Visual	03003
Minor:	AQL 1.0 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	03004

4.2.2.4 Projectile as received from WP loading facility (see dwg. 9223510 covering a detail of dwg. 9215427)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	WP leakage or evidence of leakage	Visual	04001
Major:	AQL 0.40 percent		
101.	Foreign matter in burster tube	Visual	04002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	04003

4.2.2.5 Projectile loading assembly prior to inserting burster (see dwg. 9223510 covering a detail of dwg. 9215427)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Burster pad missing or inadequate	Visual	05001

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

Major: None defined.

Minor: None defined.

4.2.2.6 Projectile loading assembly prior to assembly with cartridge case (see dwg. 9233510 covering a detail of dwg. 9215427)

Categories	Defects	Method of Inspection	Code No.
Major:	AQL 0.40 percent		
101.	Burster charge missing or below flush	Visual	06001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	06002

4.2.2.7 Cartridge assembly, prior to assembly of fuze (see dwg. 921547)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Foreign matter in fuze well.	Visual	07001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	07002

4.2.2.8 Cartridge assembly with fuze (see dwg. 9215427)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Burster charge loose	Manual	08001
2.	Damage to liner which would allow propellant to escape	Visual	08002
3.	Primer above flush	Gage	08003
Major:	AQL 1.0 percent		
101.	Torque test failure of fuze.	Test	08004
102.	Primer percussion element below flush, max.	Gage	08005
103.	Fuze not staked	Visual	08006

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

104.	Fuze not fully seated	Visual	08007
105.	Rotating band missing or damaged	Visual	08008
106.	Overall length, max.	Gage	08009
Minor:	AQL 1.5 percent		
201.	Marking missing, misleading or unidentifiable	Visual	08010
202.	Exterior of cartridge with an aggregate of bare spot in excess of 1/4 square inch (see 3.6.1.1)	Visual	08011
203.	Evidence of poor workmanship (see 3.6)	Visual	08012

4.2.2.9 Unsealed fiber container (see dwg. 9215018)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Packing component missing ...	Visual	09001
Minor:	AQL 1.0 percent		
201.	Round excessively tight in container	Manual	09002
202.	Evidence of poor workmanship (see 3.6)	Visual	09003

4.2.2.10 Sealed fiber container (see dwg. 9215018)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Container cut or damaged through all impregnated asphalt layers	Visual	10001
102.	Tape incomplete or badly wrinkled	Visual	10002
103.	Metal end loose or distorted.	Visual	10003

Source: https://assist.dla.mil -- Downloaded: 20261O-18T05:13Z
Check the source to verify that this is the currentversion before use.

Minor:	AQL 2.5 percent		
201.	Tear tab missing or improper .	Visual	10004
202.	Gap between cover and body of container	Visual	10005
203.	Color of tape incorrect	Visual	10006
204.	Marking missing, misleading or unidentifiable	Visual	10007
205.	Contents loose	Manual	10008

4.2.2.11 Sealed wood packing box (see dwg. 8797671)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Box damaged	Visual	11001
102.	Hardware or strapping missing, broken or loose	Visual	11002
103.	Boards loose or nails protruding	Visual	11003
Minor:	AQL 2.5 percent		
201.	Hardware improperly engaged ..	Visual-Manual	11004
202.	Strapping improperly assembled	Visual-Manual	11005
203.	Car seal missing, unsealed or improperly positioned	Visual-Manual	11006
204.	Contents loose	Manual	11007
205.	Handle missing or insecure ...	Visual	11008
206.	Marking missing, misleading or unidentifiable	Visual	11009

4.2.3 Testing

4.2.3.1 Check test for possible deterioration of the primer-Major defect - Code No. 01003.-If the total elapsed time between original acceptance of any primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in the applicable primer loading specification immediately before the primer lot is assembled into the cartridges. The test shall be performed by the contractor on primers selected by the government inspector at the facility assembling the primers into the cartridges (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.2.3.2 Profile and alignment (see dwg. 9215427) Major defect - Code No. 08012.-The cartridges, including those which have had the bourrelet repainted (see 3.6.1.1), shall be gaged 100 percent for profile and alignment. Any cartridge which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.3 Propellant weight (see 3.3) Critical defect - Code No. 02006.-The propellant shall be weighed and check-weighed 100 percent. The check-weighing shall be accomplished independently of the original weighing and, if performed manually, shall be performed by another operator. Any charge which fails to comply with the applicable requirement shall be classed defective and removed.

4.2.3.4 Cartridge case crimp

4.2.3.4.1 Torque (see 3.4.1) Major defect - Code No. 08013-The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter F and AQL 1.5 percent. The test shall be performed as specified in 4.3.1.1. Equipment shall be in accordance with 4.2.4.

4.2.3.4.2 Bullet pull (see 3.4.2) Major defect - Code No. 08014.-The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter F and AQL 1.5 percent. The test shall be performed as specified in 4.3.1.2. Equipment shall be in accordance with 4.2.4.

4.2.3.5 Proving ground.-The proving ground tests shall be performed as specified in 4.3.2.

4.2.3.5.1 Muzzle velocity (see 3.5.1) Major defect - Code No. 08015.

4.2.3.5.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter I and AQL of 1.0 percent. In addition, if the standard deviation of the projectile sample multiplied by the factor 0.75 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.5.1.2 After three consecutive lots have met the criteria of 4.2.3.5.1.1, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter F, and AQL 1.0 percent. In addition if

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

the standard deviation of the projectile sample multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.5.2 Projectile functioning (see 3.5.2) - Major defect - Code No. 08016.

4.2.3.5.2.1 Beginning with the first lot produced and continuing until three or consecutive lots have complied with the applicable requirements specified, the sample cartridge used in the muzzle velocity test (see 4.2.3.5.1.1) shall be observed for projectile functioning. If three or more projectiles fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.2.2 After three consecutive lots have met the criteria of 4.2.3.5.2.1, the sample cartridges in the muzzle velocity test (see 4.2.3.5.1.2) shall be observed for projectile functioning. If two or more projectiles fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.3 Safety (see 3.5.4) - Critical defect - Code No. 08017.

4.2.3.5.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, fifteen sample cartridges shall be selected at random from each lot for this test. If any cartridge fails to comply with the safety requirements, the lot shall be rejected.

4.2.3.5.3.2 After three consecutive lots have met the criteria of 4.2.3.5.3.1, five sample cartridges shall be selected at random from each lot for this test. If any cartridge fails to comply with the safety requirements, the lot shall be rejected.

4.2.3.5.4 Premature burst and security of parts (see 3.5.3) - Critical defect - Code No. 08018.-If any of the sample cartridges used in any of the proving ground tests fails to comply with the applicable requirements for premature burst and security of parts, the applicable lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-9215427 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection equipment. The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures

4.3.1 Cartridge case crimp

4.3.1.1 Torque.-The security of the crimp of the cartridge case to the projectile shall be determined by applying a torque load at a rate of travel not to exceed 10 degrees per minute. Observation shall be made for compliance with the applicable requirement.

4.3.1.2 Bullet pull.-The security of the crimp of the cartridge case to the projectile shall be determined by applying a load in the axial direction at the rate of 0.125 inch per minute. Observation shall be made for compliance with the applicable requirement.

4.3.2 Proving ground tests.-These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedure. The sample cartridges shall be fired from a rifle for which the cartridge is standard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.3.2.1 Muzzle velocity.-The sample cartridges shall be fired as specified in 4.3.2.2 and the muzzle velocity shall be measured.

4.3.2.2 Projectile functioning.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, fifteen sample cartridges shall be fired for impact against a 1-inch wood bursting screen placed not less than 400 feet from the muzzle of the rifle and ten sample cartridges shall be fired for impact on firm ground with the rifle elevated at not less than 320 mils. After three consecutive lots have met the criteria of 4.2.3.5.1.1, five sample cartridges shall be fired for impact against a 1-inch wood bursting screen placed not less than 400 feet from the muzzle of the rifle and five sample cartridges shall be fired for impact on firm ground with the rifle elevated at not less than 320 mils.

4.3.2.3 Safety.-The sample cartridges shall be fired with propelling charges adjusted to give 112 percent of the rated maximum pressure for a new gun. In addition for the first three production lots from each manufacturer (loading facility) a smear camera shall be used to observe the projectile in flight, in order to record any possible malfunctioning.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A.-The cartridges shall be preserved and packaged in accordance with dwg. 9215018.

5.2 Packing

5.2.1 Level A.-The containers shall be packed in accordance with dwg. 8796471.

5.3 Marking.-Marking of the wood box shall be in accordance with dwg. 8796471. The fiber container shall be marked in accordance with dwg. 9215018.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the currentversion before use.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Cost of check test.-The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

6.5 Submission of test data.-In addition to the normal distribution of records, when the cartridge is procured by the Department of the Army, one copy of all ballistic test data will be forwarded to the following:

Commanding Officer
Picatinny Arsenal
Dover, New Jersey
ATTN: SMUPA-ND2 and SMUPA-DA2

6.6 Supersession data.-This specification includes in part the requirement of MIL-C-12825A dated 14 February 1955.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1310-A-091

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.