MIL-C-14972B (MU)
10 October 1972
SUPERSEDING
MIL-C-14972A
30 April 1971

MILITARY SPECIFICATION

CLIP, SHORTING ASSEMBLY, FOR 2.75 INCH ROCKET MOTOR

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for one type of shorting clip designated as Clip, Shorting Assembly, for 2.75 Inch Rocket Motor Mark 4 and 40.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling procedure and tables for inspection by attributes
MIL-STD-109 - Quality Assurance Terms & Definitions
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1169- Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235- Single and Multilevel continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

9260007 - Clip, Shorting

FSC: 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

ET-9260007 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with the specified drawings and specifications.

3.2 Workmanship.-All parts shall be fabricated and assembled in accordance with best practices. Metal parts shall be free of rust and all other foreign matter. Any cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

3.3 First Article Inspection.-This specification makes provisions for first article inspection. Requirement for the submission of first article sample by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein.

4.1.1 Submission of Product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

b. Drawing, specification number and date, together with an identification and date of changes.

c. A statement that all material purchased by the contractor meets requirements when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Sample

4.2.1 Submission.-The contractor shall submit a First Article Sample to a government approved facility as designated by the Contracting Officer (see para. 6.4) for evaluation in accordance with the provisions of 4.2.2. The First Article sample shall consist of thirty (30) Shorting Clips which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings, certificates of conformance for materials (see 4.1.1c). A sample containing known defects will not be submitted unless specifically authorized, by the Contracting Officer. A First Article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material is used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Parts will be subjected by the Government to any or all of the examinations or tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any part fails to comply with any of the requirements and inspections, the First Article Sample shall be rejected. The Government reserves the right to terminate its

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

inspection upon any failure of a part in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and/or submit a new First Article Sample or portion thereof. Until a First Article Sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless directed by the Contracting Officer.

4.3 Inspection Provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirement. Inspection lots for the inspection of the item being procured and deliverable under the contract shall comply with MIL-STD-105, and shall be numbered with a unique lot number which shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-The examinations listed in the following subparagraph shall be performed on inspection lots (see 4.2.1) of the components or assemblies in the applicable paragraph heading. Inspection for critical defects (and Major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect, if approved by the procuring activity, to apply the AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspection listed shall be in accordance with 4.3.3.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:14Z
Check the source to verify that this is the current version before use.

4.3.2.1 Clip, Shorting (see dwg. 9260007)

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		
Major:	AQL 1.5 percent		
101.	Overall outside length	Gage	01001
102.	Distance, parallel to shaft, from outside edge of bend in aft hook nearest to shaft to bend in center of aft hook	Gage	01002
103.	Radius of curvature, bend in aft hook nearest to shaft	Gage	01003
104.	Distance, perpendicular to shaft, between center of radius of bend nearest to shaft and center of radius of bend farthest from shaft in aft hook	Gage	01004
105.	Distance, perpendicular to shaft between center of radius of bend in center of aft hook and center of radius of bend farthest from shaft in aft hook	Gage	01005
106.	Radius of curvature, bend in aft hook farthest from shaft	Gage	01006
107.	Length of straight portion of aft hook between bend farthest from shaft and end of aft hook	Gage	01007
108.	Distance, parallel to shaft, from outside edge of bend in aft hook nearest to shaft to outside edge of bend in aft hook farthest from shaft	Gage	01008
109.	Radius of bend in forward hook nearest to shaft	Gage	01009
110.	Length of forward hook	Gage	01010
111.	Radius of bend in forward hook farthest from shaft	Gage	01011
112.	Distance, end of forward hook to shaft	Gage	01012
113.	Angle between engaging portion of forward hook and shaft	Gage	01013

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:14Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Minor:	AQL 2.5 percent		
201.	Diameter of shaft	Gage	01014
202.	Radius of center bend in aft hook	Gage	01015
203.	Angle of center bend in aft hook	Gage	01016
204.	Width of forward hook	Gage	01017
205.	Material improper	Visual	01018
206.	Evidence of poor workmanship (see 3.2)	Visual	01019
207.	Radius of bend between shaft and forward hook	Gage	01020

4.3.3 Inspection Equipment. - Equipment tabulation number ET-9260007 identifies inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.3.1 Government Rights to Documentation. - Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, construction, survery and whenever inspection equipment drawings are needed.

5. PREPARATION FOR DELIVERY

5.1 Packing and Marking

5.1.1 Level C. - The Shorting Clips shall be packed and marked in accordance with MIL-STD-1169(MU).

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

6.2 These code numbers are used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor, (see 6.3.5).

6.3 Inspection Equipment.-The contractor shall design inspection equipment as required by the referenced inspection Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

6.3.1 Inspection Equipment Lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection Equipment List Codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment
MU - Army designs, mandatory for use

6.3.3 Army Designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor Designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of Contractor Designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-R. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Submission of First Article Samples.-Instructions as to the location for the evaluation of the First Article Sample shall be obtained from the Contracting Officer. Upon receipt of such request the Contracting Officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-NI.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

CUSTODIAN:
ARMY-MU

PREPARING ACTIVITY:
ARMY-MU

PROJECT NUMBER: 1340-A323

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:14Z
Check the source to verify that this is the currentversion before use.

FOLD

Department of the Army
Headquarters, Picatinny Arsenal
Dover, New Jersey 07801

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:14Z
Check the source to verify that this is the current version before use.