INCH-POUND

MIL-C-14972C (MI)
25 March 1992
SUPERSEDING
MIL-C-14972B (MU)
10 October 1972

MILITARY SPECIFICATION

CLIP, SHORTING ASSEMBLY, FOR 2.75 INCH ROCKET MOTOR

This specification is approved for use by the U.S. Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the quality assurance provisions and special requirements not covered by the drawings for one type of shorting clip designated as Clip, Shorting Assembly, for 2.75 Inch Rocket Motor, Mark 4 and 40.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Missile Command, ATTN: AMSMI-RD-SE-TD-ST, Redstone Arsenal, AL 35898-5270 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1340
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition, General Specification for

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Ammunition Lot Numbering
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

(Unless otherwise indicated, copies of the federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Ave., Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

ARMY

9260007 - Clip, Shorting

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ARMY

ET-9260007 - Equipment Tabulation

(Copies of the drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with the specified drawings and specifications.

3.2 Workmanship. All parts shall be fabricated and assembled in accordance with best practices. Metal parts shall be free of rust and all other foreign matter. Any cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

3.3 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 in order to define terms used herein. The provisions of MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4).

4.2.1 Submission of product. At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing, specification number and date, together with an identification and date of changes.

c. A statement that all material purchased by the contractor meets requirements when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample to a government approved facility as designated by the contracting officer (see para. 6.3) for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of 30 shorting clips which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment including packaging and packing, and shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample including statements of findings and certificates of conformance for materials (see 4.2.1c). A sample containing known defects will not be submitted. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.3.2 Inspections to be performed. Parts will be subjected by the Government to any or all of the examinations or tests specified in this specification and any or all requirements of the applicable drawings.

4.3.3 Rejection. If any part fails to comply with any of the requirements and inspections, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure or a part in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and/or submit a new first article sample or portion thereof. Until a first article sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless directed by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Lot formation. The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with re-requirement. Inspection lots for the inspection of the item being procured and deliverable under the contract shall comply with the inspection plan shown in table I, and shall be numbered with a unique lot number which shall be in accordance with MIL-STD-1168.

4.4.2 Examination. The examinations listed in the following subparagraph shall be performed on inspection lots (see 4.4.1) of the components or assemblies in the applicable paragraph heading. Inspection for critical defects shall be 100%. Sampling plans for major defects shall be in accordance with table I. Equipment necessary for the performance of the inspection listed shall be in accordance with 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

TABLE I. Sampling plan.

Lot Size	Sample Size
2 to 8	100%
9 to 90	8
91 to 150	12
151 to 280	19
281 to 500	21
501 to 1200	27
1201 to 3200	35
3201 to 10,000	38
10,001 to 35,000	46
35,001 to 150,000	56
150,001 and over	64
In all cases: Acceptance number is zero. Rejection number is one.	

4.4.2.1 Examination of clip, shorting (see drawing 9260007).

Categories	Defects	Method of Inspection	Sampling Plan (Table)
Critical	None defined		
Major:			
101.	Overall outside length	Gage	Table I
102.	Distance, parallel to shaft, from outside edge of bend in aft hook nearest to shaft to bend in center of aft hook	Gage	Table I
103.	Radius of curvature, bend in aft hook nearest to shaft	Gage	Table I

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Sampling Plan (Table)
104.	Distance, perpendicular to shaft, between center of radius of bend nearest to shaft and center of radius of bend farthest from shaft in aft hook	Gage	Table I
105.	Distance, perpendicular to shaft between center of radius of bend in center of aft hook and center of radius of bend farthest from shaft in aft hook	Gage	Table I
106.	Radius of curvature, bend in aft hook farthest from shaft	Gage	Table I
107.	Length of straight portion of aft hook between bend farthest from shaft and end of aft hook	Gage	Table I
108.	Distance, parallel to shaft, from outside edge of bend in aft hook nearest to shaft to outside edge of bend in aft hook farthest from shaft	Gage	Table I
109.	Radius of bend in forward hook nearest to shaft	Gage	Table I
110.	Length of forward hook	Gage	Table I
111.	Radius of bend in forward hook farthest from shaft	Gage	Table I
112.	Distance, end of forward hook to shaft	Gage	Table I
113.	Angle between engaging portion of forward hook and shaft	Gage	Table I

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection equipment. Equipment tabulation number ET-9260007 identifies inspection equipment required to perform the examinations and tests prescribed in this section.

4.5 Inspection of packaging. The sampling and inspection of the preservation, packaging, and container marking shall be in accordance with the requirements of MIL-STD-1169.

5. PACKAGING

5.1 Preservation, packing, palletization and marking. Preservation, packing, palletization and marking shall be either Level A or B, as specified (see 6.2).

5.2 Level A or B. Preservation, packing, palletization and marking shall be in accordance with MIL-STD-1169.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This specification describes the quality assurance provisions and other special requirements not covered by the drawings for one type of shorting clip used in the 2.75 inch rocket motor.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1)

c. Whether a first article is required (see 3.3)

d. Whether packaging requirements are Level A or B (see 5.1).

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerers whether the item(s) should be a first article sample, a first production item, or a number of items to be tested as specified in 4.3. The contracting officer should include specific

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Metrication. Metric equivalents in accordance with FED-STD-376 are acceptable for use in this specification.

6.5 Subject term (keyword) listing.

Ammunition
Arming devices
Firing sequence
Fuzes
Short circuits

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - MI

Preparing activity:
Army - MI

(Project 1340 - A766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-14972C(MI)	920325

3. DOCUMENT TITLE
CLIP, SHORTING ASSEMBLY, FOR 2.75-INCH ROCKET MOTOR

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
COMMANDER U.S. ARMY MISSILE COMMAND	(205)876-6980	746-6980
c. ADDRESS (Include Zip Code) ATTN: AMSMI-RD-SE-TD-ST REDSTONE ARSENAL, AL 35898-5270	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2020-10-16T05:14Z
Check the source to verify that this is the current version before use.