INCH-POUND

MIL-D-14951A (AR)
AMENDMENT 3
26 August 1992
SUPERSEDING
AMENDMENT 2
8 February 1990

MILITARY SPECIFICATION

DELAY ELEMENT M53
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-D-14951A (AR) dated 8 September 1982, and is approved for use by the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of Department of Defense.

PAGE 1

Add MIL-Q-9858 cited in 4.1.5

PAGE 2

* Add new paragraph:

"3.1.1 Control environment. Mixing of the chemical ingredients, loading of the chemical composition and sealing of the M53 delay shall be performed in an environment of 45%-60% RH and 70-80 degrees F."

* Add new paragraph:

"3.1.2 Mixing time. The minimum mixing time requirement for the M53 delay mix shall be one (1) hour and thirty (30) minutes."

* Add new paragraph

"3.1.3 Burn time. The bottom (Slow) delay composition shall be varied to achieve the proper burn time. Burn time STD. DEV shall not exceed 0.2 seconds. The top (Fast) delay composition shall have an average burn time of 1 to 1.5 seconds. Burn time STD. DEV shall not exceed 0.2 seconds. The two delay compositions shall be stored in containers of different colors and each container shall be labeled."

* Add new paragraph:

"3.1.4 Column range. The acceptable column height range value for each delay charge shall be included in the contractor process document."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-01-16T15:41Z
Check the source to verify that this is the current version before use.

* Add new paragraph:

"3.1.5 Final control. "The delays shall be put into their final pack within five days after lot acceptance. The LAT sample of delays shall be selected after the sub lot of delays has been x-rayed. Sealed M53 delays shall not sit unpacked more than five (5) days in an uncontrolled environment."

PAGE 3

* 3.8: Delete "shall not exceed 0.50 percent max" and substitute "shall not exceed 0.10 percent max by weight."

* Add new paragraph:

"3.11 Process control. The contractor shall submit a process control document to the Government specifying the entire process for the production of the M53 delay element. The Process Control Document shall be submitted in accordance with paragraph 4.1.5."

* Add new paragraph:

"4.1.5 Submission of entire process control document. The contractor shall submit a process control document which details all the specific procedures involved in the entire processing operations. This document shall be a part of the contractor's quality program requirement in accordance with MIL-Q-9858. It shall be submitted to the contracting officer for review by the technical agency. The contractor shall not initiate production without written approval of the entire procedures from the contracting officer. Once approved the contractor shall not change the process without written approval from the contracting officer."

PAGE 6

* Delete Table I first article inspection page 2 of 2 and substitute new page 6 included:

PAGE 12

4.4.2.5, Major Defect 104: Delete "Primer below flush surface of holder" and substitute "Depth of primer below surface of holder, max."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.

Table I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Delay Element M53	2 OF 2	9246248
			NEXT HIGHER ASSEMBLY 9246246

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Delay Element Assembly, M53 (Dwg. 9246248)			
	Examiniation for defects	10	3.2	4.4.2.7
	Arming and delay function test at 145 F.	315	3.3	4.5.2
	Arming and delay functioning test at 70 F.	315	3.3	4.5.2
	Arming and delay functioning test at -50 F.	315	3.3	4.5.2
	Waterproofness test	50	3.4	4.5.3
	Arming pin pull test	25	3.2	4.5.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.

PAGE 14

4.4.2.7:

Major 103: Delete the phrase "primer holder cavity or".

Major 104: Delete in its entirety.

4.4.2.8.1:

Critical 1: Change "160 degrees F" to "145 degrees F".

Critical 3: Change "-65 degrees F" to "-50 degrees F".

Major 101: Change "160 degrees F" to "145 degrees F".

Major 103: Change "-65 degrees F" to "-50 degrees F".

Major 104: Change "160 degrees F" to "145 degrees F".

Major 106: Change "-65 degrees F" to "-50 degrees F".

PAGE 16

4.4.2.8.1: In the column marked no. of sample units, add the number "105" for the following defect categories:

Critical 1, 2, 3:

Major 101, 102, 103, 104, 105.

PAGE 17

Delete footnote #3 in its entirety and substitute:
"The lot shall be rejected if three (3) or more samples fail to meet the requirement."

PAGES 16 & 17

* Delete paragraph 4.4.2.8.1 (pages 16 & 17) in its entirety and substitute new pages 16 and 17 included:

PAGE 19

* Add new paragraph:

"4.5.1.2 In process test. The loading machine shall not be altered in any way as a result of the in-process

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4.4.2.8.1	Delay Element, M53 (Testing)		9246248
			NEXT HIGHER ASSEMBLY: 9246246

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Delay functioning, short time at 145 F	105		3.3.2	4.5.2
2	Delay functioning, short time at 70 F	105		3.3.2	4.5.2
3	Delay functioning, short time at -50 F	105		3.3.2	4.5.2
4	Arming pin pull test, below minimum load	500	2/	3.2	4.5.4
Major					
101	Arming functioning, non-functioning at 145 F	1/	4/	3.3.1	4.5.2
102	Arming functioning, non-functioning at 70 F	1/	4/	3.3.1	4.5.2
103	Arming functioning, non-functioning at -50 F	1/	4/	3.3.1	4.5.2
104	Delay functioning, above max. time at 145 F	1/	4/	3.3.1	4.5.2
105	Delay functioning, above max. time at 70 F	1/	4/	3.3.1	4.5.2
106	Delay functioning, above max. time at -50 F	1/	4/	3.3.1	4.5.2
107	Arming pin pull test, failure to move above maximum load	500	2/	3.2	4.5.4
108	Waterproofness test	60	3/	3.4	4.5.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.8.1	Delay Element, M53 (Testing)				9246248
					NEXT HIGHER ASSEMBLY 9246246
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
1/ The number of units samples used in the critical category # 101 to 106. Except the criticals shall have no defects permitted. 2/ Compute pull load mean (x) and the standard deviation (unbiased) (s). Rejection criteria is as follows: a. $\bar{x} - 5s < 22$ b. $\bar{x} + 2.5s > 80$ c. $x \leq 40$ d. Any individual (xi) less than 30. e. Any two (2) individuals (xi) greater than 80. 3/ The lot shall be rejected if three (3) or more samples fail to meet the requirements. 4/ After combining the three (3) phases of the critical category # 1 to 3, the sublot shall be rejected if three (3) or more samples fail to meet the requirements.		# 1 to 3 shall be		the same	as for major category

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.

test (i.e. testing five (5) units for time/function every five hundred that are produced). This data should be recorded and used for information only. Corrective action-readjust process to original plan. Record the reason or reasons for the process deviation."

* Add new paragraph:

"4.5.1.3 After screening. After screening, test for burning time five (5) samples from each new fast and slow delay mix bucket to evaluate mixture uniformity. Each thirty (30) pound mix yields 5-6 buckets of delay composition. If the burning time standard deviation of any mix does not meet the requirements of paragraph 3.1.3, the composition shall be rejected and ARDEC shall be notified immediately for disposition of the delay composition batch. The delays will be loaded by hand weighing and tamping each increment. Consolidation may be performed by hand or machine loader at the contractor's option. The fast burn mix will be evaluated by loading delays with 244 mg (181 + 63) of that delay composition only. Once uniformity of the faster burning composition is established, the slower burn composition will be loaded as the first increment (181 mg) and the qualified fast burn mix from one bucket utilized as the second increment (63 mg) to load up the test samples of five (5) from each bucket of slow burn composition. The identity of samples to buckets shall be retained and all data forward to ARDEC for evaluation."

4.5.2, line 3: Change "160" to "145" and "-65" to "-50".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A768)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.