MIL-C-14944A(AR)
18 November 1981
SUPERSEDING
MIL-C-14944 (MU)
8 August 1969

MILITARY SPECIFICATION

GRENADE, HAND, PRACTICE, DELAY: M69, BODY ASSEMBLY FOR

This specification is approved for use by the U. S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the body assembly for one type of grenade designated as Grenade, Hand, Practice, Delay: M69.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.1), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:10Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

U. S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKAGING DRAWINGS

9235207	-	Body Assembly. (2 sheets)
9251421	-	Box, Fiberboard for Body Assembly for Grenade, Hand, Practice, Delay, M69.
9251422	-	Box, Packing, for Body Assembly for Grenade, Hand, Practice, Delay, M69.

INSPECTION EQUIPMENT DRAWINGS

8801484	-	Torque Test.
8801487	-	Gage, Receiver. (3 sheets)
8841017	-	Adapter.

(Copies of specifications, standards and drawings required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with the applicable drawings, specifications and standards.

3.2 Body Assembly. The body assembly shall comply with all requirements specified on Drawing (Dwg) 9235207, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Strength of weld of body assembly. The equatorial weld line of the metal parts assembly shall not exhibit visible cracks when crushed to a dimension of 2.000 + 0.125 inches in the plane of the weld when tested as specified in 4.5.2.

3.4 First Article Inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:10Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table 1.

Part Description	Drawings	Quantity
Insert	8810746	10
Top cup	9235207-1	20
Bottom cup	9235207-2	20
Body Assembly (unpainted)	9235207	50

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:10Z
Check the source to verify that this is the current version before use.

TABLE 1. FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-14944A(AR)

PARAGRAPH	TITLE: Body Assembly		SHEET 1 OF 1		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: -
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Insert Dwg. 8810746 Examination for Defects	10		3.2	4.4.2.1
	Assembly, Top Cup Dwg. 9235207-1 Examination for Defects	20		3.2	4.4.2.2
	Cup, Bottom Dwg. 9235207-2 Examination for Defects	20		3.2	4.4.2.3
	Body Assembly Dwg. 9235207 Examination for Defects	50		3.2	4.4.2.4
NOTES:					

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-14944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Insert				8810746
					NEXT HIGHER ASSEMBLY 9235207
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Minor diameter, min		0.40%	3.2	Gage
Minor 201	Poor workmanship		1.0 %	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-14944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Assembly, Top Cup				9235207 (Sh.1)
					NEXT HIGHER ASSEMBLY
					-
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wall thickness of cup, min.		0.40%	3.2	Gage
102	Torque test of insert	20(a)		3.2	4.5.1
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES: (a) The twenty (20) assemblies shall be selected from each four (4) hours of production. If any assembly fails to comply with the requirement specified on the drawing, the four (4) hour's production represented by the sample shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-14944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Cup, Bottom				9235207 (Sh.1)
					NEXT HIGHER ASSEMBLY
					-
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Wall thickness, min		0.40%	3.2	Gage
Minor 201	Poor workmanship		1.0%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-14944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Body Assembly (prior to painting)				9235207
					NEXT HIGHER ASSEMBLY
					-
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight incorrect		0.40%	3.2	Balance
102	Pitch diameter of thread for depth specified in note		0.40%	3.2	Gage
103	Concentricity of stopper hole with thread (see optional - one-piece design when applicable)		0.40%	3.2	Gage
104	Stopper hole missing		0.40%	3.2	Visual
Minor					
201	Outside diameter, max		0.65%	3.2	Gage
202	Total height		0.65%	3.2	Gage
203	Mismatch over max		0.65%	3.2	8801487
204	Poor workmanship		1.0%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-14944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Body Assembly				9235207
					NEXT HIGHER ASSEMBLY: -
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Strength of equatorial weld	1(a)		3.3	4 5.2
Minor 201	Protective finish damaged (Bare spot on exterior surface)		0.65%	3.2	Visual
202	Marking misleading, unidentifiable or missing		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.5	Visual

NOTES: (a) One (1) body assembly shall be selected from each four (4) hours of production. If the assembly fails to comply with the requirements specified on the drawing or in 3.3, the four (4) hour's production represented by the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection.

4.5.1 Torque test of weld of insert. The body assembly shall be placed in the fixtures shown on Dwgs 8801484 and 8841017 and the torque specified on Dwg. 9235207 shall be applied.

4.5.2 Strength of equatorial weld of body assembly. The body assembly shall be placed in a suitable test fixture (see 6.7) and a load shall be applied in the plane of the weld in order to crush the assembly to a dimension of 2.000 + 0.125 inch.

5. PACKAGING

5.1 Packaging requirements. Packaging shall be as specified on Dwg. 9251421.

5.2 Packing. Packing shall be as specified on Dwg. 9251422.

5.3 Marking. Marking of the fiber box and wood box shall be as specified on Dwgs. 9251421 and 9251422, respectively.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U. S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraph number.

6.3 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commander, U. S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading "US Army Armament Research and Development Command" (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.5 Data cards. (See (MIL-A-48078). Distribution of data cards shall include the address specified in 6.3.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.7 Test fixture No. 1300 AB Specimen Mount Press, product of Adolph I. Buehler Co., Chicago, Illinois, was found to be satisfactory in conducting the strength of equatorial weld test.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1330-A163

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAT-M
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-G-14944A(AR) - Grenade, Hand, Practice, Delay: M69, Body Assembly For

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:10Z
Check the source to verify that this is the current version before use.