MIL-G-14971A (PA)
10 April 1974
SUPERSEDING
MIL-G-14971
7 October 1968

MILITARY SPECIFICATION

GRENADES, HAND, M33, M59, M67 AND M68,

METAL PARTS ASSEMBLY FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the metal parts assembly for four types of grenades designated as Grenades, Hand, M33; Grenade, Hand, M59; Grenade, Hand, M67 and Grenade, Hand, M68.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-T-45	- Tape, Paper Gummed (Sealing and Securing)
TT-C-490	- Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

MILITARY

MIL-A-2550	- Ammunition, General Specification for

STANDARDS

FEDERAL

FED-STD-141	- Paint, Varnish, Lacquer and Related Materials, Methods of Inspection Sampling and Testing

FSC: 1330

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

MIL-STD-109 - Quality Assurance Terms and Definitions

MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

8810743 - Metal Parts Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

. Title 49 - Transportation 0-190

(The Code of Federal Regulations is available from the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402. Orders should specify, "49 CFR 0-190 (latest revision)".)

Source: https://assist.dla.mil -- Downloaded: 202640-18T05:13Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly.-The assembly shall comply with all requirements specified on Drawing (Dwg) 8810743, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Strength of weld of metal parts assembly.-The equatorial weld line of the metal parts assembly shall not exhibit visible cracks when crushed to a dimension of 1.500 ± .125 inches in the plane of the weld when tested as specified in 4.4.3. "This paragraph does not apply to the optional one piece construction of the body assembly. (See Dwg. 8810743 Sh. 2)".

3.4 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.5 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (see 6.4).

3.6 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements when such material is purchased by the contractor or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificates shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.

4.2.1 Submission.-The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2. (See 6.1.) The first article sample shall consist of the following:

a. Seventy (70) metal parts assemblies (fifty (50) not painted).
b. Twenty (20) inserts.
c. Twenty (20) top cup assemblies.
d. Four (4) test panels or four (4) metal parts assemblies for salt spray.
e. Two (2) stock specimens, each comprised of the width of the stock to be used for production, and the length, equivalent to the circumference of the tool to be utilized for production, shall be selected from the coil of stock prior to forming the top cup and bottom cup. One sample shall be taken from the beginning of the coil; the other sample shall be taken from the end of the coil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

Each specimen shall be identified for the direction of rolling and identified with an index position of the tool. The first article sample shall be submitted and approved prior to initiation of regular production.

All parts and completed assemblies submitted shall have been produced by the Contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. A first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process (including heat treatment procedures and equipment, material used, drawing specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 Inspection to be performed.-All parts and assemblies shall be subjected by the Government to any or all of the examinations or tests specified in this specification and any or all requirements of the applicable drawing. In addition, any or all of the following examinations and tests will be performed.

4.2.2.1 Quantities for first article tests.-After classification of defects inspection and other inspections have been completed as specified in 4.2.2, the following quantities shall be subjected to the following tests:

4.2.2.1.1 Internal air pressure of metal parts assembly, prior to painting.-The fifty (50) assemblies shall be subjected to this test.

4.2.2.1.2 Torque test of weld of insert.-The fifty (50) top cup assemblies shall be subjected to this test. This paragraph does not apply to the optional one piece construction of the body assembly (See Dwg. 8810743 Sh. 2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.2.2.1.3 Strength of weld of metal parts assembly.-The fifty (50) assemblies shall be subjected to this test. This paragraph does not apply to the optional one piece construction of the body assembly (See Dwg. 8810743 Sh. 2).

4.2.2.1.4 Dimensional inspection of stock specimens.-The two (2) stock specimens shall be subjected to the dimensional inspection specified in 4.4.1.

4.2.2.1.5 Salt spray.-The four (4) test panels or four (4) metal parts assemblies shall be subjected to this test.

4.2.3 Rejection.-If any assembly, component or stock specimen fails to comply with any of the applicable requirements the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure to any assembly, component, or stock specimen in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions.-

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Change to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 202640-18T05:13Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plan for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Individual defects shall have an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Insert (See Dwg. 8810746 covering a detail of Dwg. 8810744).-

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined		
Major			
101.	Concentricity of O.D. with P.D. of thread	8828094	01004
102.	Perpendicularity of fuze seating surface with P.D. of thread	Gage	01005
103.	Diameter max. and length max. of counterbores. (when applicable)	Gage	01003
Minor			
201.	Evidence of poor workmanship (See 3.4)	Visual	01002

4.3.2.2 Metal parts assembly, prior to painting (See Dwg. 8810743 Sh. 2).-

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined		
Major			
101.	Outside diameter maximum	Gage	02001
102.	Pitch diameter of thread	8810486	02002
103.	Minor diameter of thread	Gage	02003

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

104.	Length of thread, minimum	8810486	02004
105.	Concentricity of pitch diameter of thread with O.D. of base	8810488	02011
106.	Outside diameter of insert, max.	Gage	02006
107.	Concentricity of pitch diameter with O.D. of insert (when applicable)	Gage	02010
108.	Perpendicularity of pitch diameter to fuze seating surface (when applicable)	Gage	02012
Minor			
201.	Height	Gage	02007
202.	Mismatch	8810487	02008
203.	Evidence of poor workmanship (See 3.4)	Visual	02009

4.3.2.3 Metal parts assembly (See Dwg. 8810743).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor			
201.	Bare spots on exterior surface	Visual	03001
202.	Paint pools on interior surface	Visual	03002
203.	Evidence of poor workmanship (See 3.4)	Visual	03003

4.3.2.4 Metal Parts assembly, prior to painting (optional one piece body construction) (See Dwg. 8810743).-

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined		
Major			
101.	Outside diameter maximum	Gage	09001
102.	Pitch diameter of thread	Gage	09002
103.	Minor diameter of thread	Gage	09003

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the current version before use.

104.	Length of thread, maximum	Gage	09004
105.	Concentricity of pitch diameter of thread with O.D. of base	Gage	09005
106.	Outside diameter of neck for length specified	Gage	09006
107.	Concentricity of pitch diameter with O.D. of neck	Gage	09007
108.	Perpendicularity of pitch diameter with fuze seating surface	Gage	09008
109.	Concentricity of minor diameter with O.D. of neck	Gage	09009
110.	Concentricity of minor diameter with O.D. of body	Gage	09010
111.	Perpendicularity of minor diameter with fuze seating surface	Gage	09011
Minor			
201.	Height	Gage	09012
202.	Location of datum points	Gage	09013
203.	Weight, maximum	Gage	09014
204.	Evidence of poor workmanship (See 3.4)	Visual	09015

4.3.3 Testing.-

4.3.3.1 Dimensional inspection of stock specimen (See Dwg. 8810745 and 8810747) Major defects, Code No. 04001.-Two (2) stock specimens shall be taken from each coil of finished stock just prior to forming the top cup and bottom cup. The width of each specimen shall be the width of the stock, and the length shall be as necessary to obtain the total surface area of the tool to be used in production. One (1) specimen shall be taken from the beginning of the coil and the other specimen shall be taken from the end of the coil. An additional specimen shall be taken whenever a new, repaired, or altered tool is entered into production. Each specimen shall be identified with an index position on the tool and for the direction of travel of the stock with respect to the tool. The specimens shall also be identified as being from the beginning or end of the coil. If, for any specimen, the average value of fifteen (15) measurements for the total thickness dimension and the depth dimension fails to comply, or if the direction of tool travel does not comply with the applicable drawing requirements, the coil, or portion thereof, from which the specimen was taken, shall be rejected. In addition, the tool which produced the rejected specimen shall be removed from production. All cups produced from the rejected coil shall be rejected. The dimensional inspection shall be performed as specified in 4.4.1 using gage design 8827906 and other equipment as approved by the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the current version before use.

The specimen from a new, repaired, or adjusted tool entering production shall be subjected to dimensional inspection of all stock dimensions specified on the applicable drawings. Fifteen (15) readings shall be taken for each dimension. The tool shall not be used in production until dimensional compliance with the drawing requirements has been determined from the specimen produced by the tool.

4.3.3.2 Torque test of weld of insert (See Dwg. 8810744) Major defect, Code No. 05001.-Twenty (20) top cup assemblies shall be selected from each four (4) hours production and subjected to this test. If any assembly fails to comply with the requirement specified on the applicable drawing, the four (4) hour's production represented by the sample shall be rejected. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4. This paragraph does not apply to the optional one piece construction of the body assembly (see dwg. 8810743 Sh. 2).

4.3.3.3 Strength of weld of metal parts assembly (see paragraph 3.3), Major Defect, Code No. 06001.-Twenty (20) metal parts assemblies shall be selected from each four (4) hours production and subjected to this test. If any assembly fails to comply with the applicable requirement, the four (4) hour's production represented by the sample shall be rejected. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4. This paragraph does not apply to the optional one piece construction of the body assembly (see dwg. 8810743 Sh. 2).

4.3.3.4 Internal air pressure of metal parts assembly, prior to painting (see dwg. 8810743), Major defect, Code No. 07001.-Fifty (50) metal parts assemblies shall be selected from each lot and subjected to this test. If two (2) or more assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4.

4.3.3.5 Salt spray (see dwg. 8810743), Major defect, Code No. 08001.-Sampling and rejection shall be in accordance with specification TT-C-490 except drying shall be in forced air at 220°F for 24 hours.

4.3.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.3.2 and in 4.3.3 (See 6.3).

4.4 Test methods and procedures.-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.4.1 Dimensional inspection of stock specimen.-Fifteen (15) measurements shall be taken on each sample specimen for the total thickness dimension and the depth dimension. There shall be three (3) points of measurement across the width of the specimen at five (5) places along the length. The spacing of the readings shall be approximately uniform. One measurement for each characteristics shall be performed at each of the fifteen (15) measuring points on the specimen. An average value for each characteristic shall be computed for each specimen for which these measurements were obtained. In addition to the above stock specimens from a new, repaired, or adjusted tool entering production shall have the following characteristics measured: groove radius, spherical radius, and the center distance dimension.

4.4.2 Torque test of weld of insert.-The metal parts assembly shall be placed in an approved fixture and the torque specified on Dwg. 8810744 shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot. This paragraph does not apply to the optional one piece construction of the body assembly (see dwg. 8810743 Sh. 2).

4.4.3 Strength of weld of metal parts assembly.-The metal parts assembly shall be placed in an approved test fixture (See 6.5) and a load shall be applied in the plane of the weld in order to crush the assembly to a dimension of 1.500 ± .125 inches. This test is a distructive test. Parts so tested may not be returned to the lot. This paragraph does not apply to the optional one piece construction of the body assembly (see dwg. 8810743 Sh. 2).

4.4.4 Internal air pressure of metal parts assembly prior to painting.-The metal parts assembly shall be placed in an approved fixture and the air pressure specified on Dwg. 8810743 shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.4.5 Salt spray.-This test shall be conducted in accordance with FED-STD-141. Salt solution shall be 5 percent. Parts or panels shall not be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging .-

5.1.1 Level C.-One hundred twenty-five (125) metal parts assemblies shall be packed in cells formed by half slotted fiberboard corrugated partitions in five (5) layers, each layer in a 5X5 cell arrangement. The inside dimensions of the carton shall be 14 3/8 X 14 3/8 X 14 5/8 high. The outside dimensions of the separators shall be 14 1/4 X 2 3/4 to form cells measuring 2 3/4 X 2 3/4 inches. A pad 14 1/4 X 14 1/4 shall be placed on each layer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level C.-See 5.1.1

5.3 Marking.-Marking of the carton shall comply with MIL-STD-1169.

5.4 Shipping.-When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types: Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is catalogued and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirement Lists (DD Form 1423).

The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design.

6.3.3 Submission of designs for approval.-Contractor designs shall be approved by the Government prior to fabrication or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423). Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Submission of results of contractor-conducted examination and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, Attn: SARPA-QA-A-S.

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the current version before use.

6.5 Test fixture No. 1300 AB Specimen Mount Press, product of Adolph 1, Buehler Co., Chicago, Illinois, was found to be satisfactory in conducting the strength of weld test.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1330-A031

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-713-155/6385

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the current version before use.