INCH-POUND
MIL-G-14971A (AR)
AMENDMENT 4
27 March 1998
SUPERSEDING
AMENDMENT 3
9 July 1975

MILITARY SPECIFICATION

GRENADE, HAND, M33, M59, M67 AND M68
METAL PARTS ASSEMBLY FOR

This amendment forms a part of MIL-G-14971A (AR), dated 10 April 1974, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1, SPECIFICATIONS, FEDERAL: Delete “PPP-T-4S” and substitute “PPP-T-45”.

PAGE 2

2.1:

Under Specification Federal change “PPP-T-4S” to “PPP-T-45”.

Under Drawings change “U.S. Army Munitions Command” to “U.S. Armament Command” and add the following drawings:

“8828094 - Concentricity Gage
8801486 - Special Go Thread Plug
8801487 - Gage, Receiver
8801488 - Concentricity Gage
8827906 - Special Micrometer Caliper”

AMSC N/A FSC 1330
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.2.2:

Major 102: Change “8810486” to “8801486”.
Major 104: Change “8810486” to “8801486”.
Major 105: Change “8810488” to “8801488”.
Minor 202: Change “8810487” to “8801487”.

PAGE 10

4.3.3.2: Delete this paragraph and substitute a new paragraph to read:

“4.3.3.2 Torque test of weld of insert (See Dwg. 8810744) Major Defect, Code No. 05001.-Forty (40) top cup assemblies shall be selected from each four (4) hours production. Twenty (20) top cup assemblies shall be tested as specified in paragraph 4.4.2 using equipment in accordance with paragraph 4.3.4. If none of the twenty top cup assemblies fails to meet the applicable requirement, the quantity of production represented by the sample shall be acceptable. If two (2) of the twenty top cup fail to meet the applicable requirement, the quantity of production represented by the sample shall be rejected. If one (1) of the twenty top cup assemblies fails to meet the specified requirement, the additional 20 top cup assemblies shall be subjected to this test. If one or more of these second twenty fail to meet the applicable requirement, the quantity of production represented by the sample shall be rejected.”

4.3.3.3: Delete this paragraph and substitute a new paragraph to read:

“4.3.3.3 Strength of weld of metal parts assembly (See paragraph 3.3), Major Defect, Code No. 06001.-Forty (40) metal parts assemblies shall be selected from each four (4) hours production. Twenty (20) metal parts assemblies shall be tested as specified in paragraph 4.4.3 using equipment in accordance with paragraph 4.3.4. If none of the twenty metal parts assemblies fails to meet the applicable requirement, the quantity of production represented by the sample shall be acceptable. If two (2) of the twenty metal parts assemblies fail to meet the applicable requirement, the quantity of production represented by the sample shall be rejected. If one (1) of the twenty metal parts assemblies fails to meet the

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

specified requirement, the additional 20 metal parts assemblies shall be subjected to this test. If one or more of these second twenty fail to meet the applicable requirement, the quantity of production represented by the sample shall be rejected.

4.3.3.5: Add the following sentences to the end of this paragraph: "This test shall be conducted for 96 hours. Salt spray test not required for inside surface. The test shall be performed as specified in 4.4.5."

PAGE 11

5.1.1: Delete in its entirety and substitute the following:

"5.1.1 Level C.-One hundred twenty-five (125) metal part assemblies shall be packed in cells formed by half slotted chip-board 0.040 thick commercial, No. 2 finish partitions, in five (5) layers, each layer in a 5 x 5 cell arrangement. The inside dimension of the carton shall be 13 1/8 x 13 1/8 x 13 ¾ high. The outside dimensions of the separators shall be 13 x 2 5/8 inches to form cells measuring 2 9/16 x 2 9/16 inches. A "B" flute corrugated fiberboard pad 13 x 13 shall be placed on each layer."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-0403)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.