MIL-W-14960B (MU)
30 June 1971
Superseding
MIL-W-14960A (MU)
2 January 1969

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE HE, XM155E1, AND WARHEAD, GUIDED MISSILE, TRAINING, XM237E1, PARTS FOR

1. SCOPE

1.1 This specification covers quality assurance provisions and special requirements not covered by the drawings for the fabrication of the inert parts for Warhead, Guided Missile, HE, XM155E1 and for Warhead, Guided Missile, Training, XM237E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-D-1000 - Drawing, Engineering and Associated List

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167 - Ammunition Data Cards
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITION COMMAND

9226302 - Warhead, Guided Missile, HE, XM155E1, Inert Parts Assembly
9230608 - Warhead, Guided Missile, Training, XM237E1, Inert Parts Assembly
9211595 - Crate, Packing, Ammo, Dual for Whd, GM, HE XM155 or Whd, GM, Training, XM237
9211596 - Crate, Packing, Ammo, Single, for Whd, GM, HE, XM155 or Whd, GM, Training, XM237
9233456 - Crate, Packing, Ammo, Dual, Modified for Whd, GM, HE, XM155 or Whd, GM, Training, XM237

PUBLICATIONS

US ARMY MUNITION COMMAND

ET-9226302 - Equipment Tabulation
ET-9230608 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Inert Parts Assemblies.-The Inert Parts Assemblies shall comply with all requirements specified on Drawing (dwg.) 9226302 or 9230608, whichever applies, and with all requirements specified in applicable specifications.

3.3 Mounting Insert Pin.-The Mounting Insert Pin shall be present in each mounting insert.

3.4 Leakage Test of Inert Parts.-The Inert Parts Assembly (dwg. 9226302 or dwg. 9230608, whichever applies) and the Safety and Arming Housing Assembly (dwg. 9226308) shall withstand an internal air pressure test of 2.0 pounds per square inch, minimum, for 60 seconds, minimum, with no evidence of leakage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

3.5 Workmanship

3.5.1 Molded Parts.-The Molded Parts shall be free of porosity, warpage in excess of drawing dimensions, checks, cracks chipped edges, blisters, scratches, and other defects which would affect their serviceability. Small chips at the end of the machined cavities will be disregarded.

3.5.2 Foreign Matter.-All parts shall be free of chips, dirt, grease, excess flash, rust, silicone products and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few slight scratches not exposing base material.

3.5.3 Marking.-All marking shall be neat and sharply defined.

3.6 First Article Inspection.-This specification makes provisions for First Article Inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Inserts.-The liner inserts (dwg. 9226311) in the safety and arming housing assembly shall be capable of accepting mating screws for a minimum depth of .36 inches.

3.8 Fragment Weight.-A quantity of 15,000 fragments (dwg. 9226307) shall weigh 64.3 pounds minus 1 pound, plus 2 pounds.

3.9 Component and Assembly Lot Information.-Data cards prepared for each lot shall include specific component and assembly lot information defined in 6.1.b.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets the requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required by subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of two assemblies, one dual packing crate, and four complete sets of parts (i.e., four each of every component and every subassembly, except fragments, 20 of which shall be submitted) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings/certificates of conformance for materials (see 4.1.1.c). A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.2.2 Inspections to be Performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.3 Inspection Provisions

4.3.1 Lot Formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4...4.

4.3.2.1 Insert, forward (see dwg. 8800268 covering a detail of dwg. 9226303).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Pitch diameter of internal thread	Gage	01001
102.	Major diameter of external thread, minimum (min)	Gage	01002
Minor:	AQL 1.00 percent		
201.	Operation missing	Visual	01003
202.	Evidence of poor workmanship (see 3.5.2)	Visual	01004

4.3.2.2 Insert, mounting (see dwg. 8861590 covering a detail of dwg. 9226303).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Pitch diameter of thread	Gage	02001
102.	Thickness of flange	Gage	02002
103.	Diameter over knurl	Gage	02003
104.	Knurl incomplete or not sharp	Visual-Manual	02004
Minor:	AQL 1.50 percent		
201.	Minor diameter of thread, maximum (max)	Gage	02005
202.	Diameter of flange, min.	Gage	02006
203.	Operation missing	Visual	02007
204.	Evidence of poor workmanship (see 3.5.2)	Visual	02008

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.3.2.3 Insert, safety and arming (see dwg. 9226311 covering a detail of dwg. 9226308).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Pitch diameter of internal thread	Gage	03001
102.	Diameter over knurl	Gage	03002
103.	Knurl incomplete or not sharp	Visual-Manual	03003
Minor:	AQL 1.00 percent		
201.	Operation missing	Visual	03004
202.	Evidence of poor workmanship (see 3.5.2)	Visual	03005

4.3.2.4 Housing, safety and arming (see dwg. 9226309 covering a detail of dwg. 9226308).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Location and orientation of bolt holes	Gage	04001
102.	Location of booster node slot	Gage	04002
103.	Molding defects (see 3.5.1)	Visual	04003
104.	Diameter of bolt holes on flange	Gage	04004
105.	Inside dimensions of S&A housing	Gage	04005
106.	Depth of counterbore in bolt holes	Gage	04006
107.	Diameter of counterbore in bolt holes	Gage	04007
Minor:	AQL 0.65 percent		
201.	Foreign matter (see 3.5.2)	Visual	04008

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.3.2.5 Assembly, housing safety and arming (see dwg. 9226308 covering a detail of dwg. 9226302 or dwg. 9230608 whichever applies).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Location and orientation of inserts	Gage	05001
102.	Insert missing	Visual	05002
103.	Insert above flush	Visual	05003
104.	Spring pin missing	Visual	05004
105.	Spring pin protrudes into cavity	Visual	05005
106.	Cracks around inserts	Visual	05006
107.	Booster node missing	Visual	05007
108.	Booster node protrudes into cavity	Visual	05008
Minor:	AQL 0.65 percent		
201.	Foreign matter (see 3.5.2)	Visual	05009

4.3.2.6 Cup, warhead, aft (see dwg. 9226306 covering a detail of dwg. 9226305).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Depth of cup, inside, min.	Gage	06001
102.	Inside diameter, min.	Gage	06002
103.	Depth of cut-out for trough, min.	Gage	06003
104.	Knurl missing	Visual	06004
105.	Trough cut-out offset	Gage	06005
Minor:	AQL 0.65 percent		
201.	Foreign matter (see 3.5.2)	Visual	06006

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.3.2.7 Assembly, body, inner, aft (see dwg. 9226305 covering a detail of dwg. 9226303).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Cup missing or loose	Visual-Manual	07001
102.	Sidewall thickness, min.	Gage	07002
103.	Molding defects (see 3.5.1)	Visual	07003
104.	Inside diameter of aft cup, min.	Gage	07004
105.	Depth of cup, min.	Gage	07005
106.	Depth of trough, min.	Gage	07006
Minor:	AQL 0.65 percent		
201.	Foreign matter (see 3.5.2)	Visual	07007

4.3.2.8 Assembly, body, inner, forward (see dwg. 9226304 covering a detail of dwg. 9226303).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Location and orientation of nut holes	Gage	08001
102.	Sidewall thickness, min.	Gage	08002
103.	Molding defects (see 3.5.1)	Visual	08003
104.	Diameter of nut holes	Gage	08004
105.	Nut missing	Visual	08005
Minor:	AQL 0.65 percent		
201.	Foreign matter (see 3.5.2)	Visual	08006

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.3.2.9 Assembly, inner body (see dwg. 9226303 covering a detail of dwg. 9226302 or dwg. 9230608 whichever applies).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Location of mounting inserts ...	Gage	09001
102.	Diameter across mounting inserts, max.	Gage	09002
103.	Forward insert above flush or loose	Visual	09003
104.	Location of aft trough with Lug X	Gage	09004
Minor:	AQL 0.65 percent		
201.	Foreign matter (see 3.5.2)	Visual	09005

4.3.2.10 Assembly, warhead, inert parts, prior to assembly of outer body (see dwg. 9226302 or dwg. 9230608 whichever applies).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Void not filled	Visual	10001
Minor: None defined.			

4.3.2.11 Assembly, warhead, inert parts prior to painting (see dwg. 9226302 or dwg. 9230608 whichever applies).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Mounting flange cracked or damaged	Visual	11001
102.	Mating surfaces of S&A housing and inner body assembly flange not clean prior to application of adhesive	Visual	11004

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

103.	Excessive adhesive after torquing screws	Visual	11005
104.	Screws loose or not seated properly	Visual-Manual	11006
Minor:	AQL 1.00 percent		
201.	Outer body improperly applied	Visual	11002
202.	Evidence of poor workmanship (see 3.5)	Visual	11003

4.3.2.12 Assembly, warhead, inert parts (see dwg. 9226302 or dwg. 9230608 whichever applies).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Total length, max.	Gage	12001
102.	Outside diameter, max.	Gage	12002
103.	Weight marked on the assembly incorrect	Visual	12003
104.	Safety and arming assembly, retainer, or closing cover missing	Visual	12004
105.	Paint or foreign matter in threaded holes, aft cup, safety and arming cavity or closing plug surface	Visual	12005
Minor:	AQL 0.65 percent		
201.	Marking incomplete or inadequate	Visual	12007

4.3.2.13 Shipping container, prior to sealing, with warhead (see dwg. 9211595, dwg. 9211596, or dwg. 9233456 whichever applies)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Holding plate missing or loose	Visual	13001
102.	Warhead not seated properly	Visual	13002

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

103.	Hold down strap missing, broken or insecure	Visual-Manual	13003
Minor:	AQL 1.00 percent		
201.	Foreign matter inside crate	Visual	13004
202.	Strapping improperly assembled .	Visual	13005

4.3.2.14 Shipping container, sealed (see dwg. 9211595, dwg. 9211596, or dwg. 9233456 whichever applies).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Strapping missing, broken or loose	Visual-Manual	14001
102.	Board broken, split or curled ..	Visual	14002
103.	Skid missing or damaged excessively	Visual	14003
104.	Contents exposed	Visual	14004
105.	FSN number misleading or identifiable	Visual	14005
Minor:	AQL 1.50 percent		
201.	Fastener missing or loose	Visual-Manual	14006
202.	Strapping improperly assembled .	Visual	14007
203.	Nail protruding	Visual	14008
204.	Marking missing, misleading or unidentifiable	Visual	14009

4.3.2.15 Cup Booster (see dwg. 9247335 covering a detail of dwg. 9226302 whenever applicable).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Cylindrical wall thickness, max.	Gage	16001
102.	Inside diameter, min.	Gage	16002

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.00 percent		
201.	Foreign matter inside cup	Visual	16003
202.	Evidence of poor workmanship (see 3.5)	Visual	16004

4.3.3 Testing

4.3.3.1 First Article Inspection (see 4.2.1).-The sample submitted as the first article quantity shall be tested as specified below after having been examined for all other drawing requirements. Rejection and resubmission shall be in accordance with 4.2.3.

4.3.3.1.1 Mounting Insert Pin (see 3.3 and 4.3.3.2.1).

4.3.3.1.2 Assembly Weight (see 4.3.3.2.2 and dwg. 9226302).

4.3.3.1.3 Leakage Test of Inert Parts Assembly (see 3.4 and 4.3.3.2.3).

4.3.3.1.4 Molded Components (see 3.5.1 and 4.3.3.2.4).

4.3.3.1.5 Inserts (see 3.7 and 4.3.3.2.5).

4.3.3.1.6 Fragment Weight (see 3.8 and 4.3.3.2.6).

4.3.3.2 Production Testing

4.3.3.2.1 Mounting Insert Pin (see 3.3 and 4.4.1) - Major Defect - Code No. 09007.-This determination shall be performed 100 percent, as specified in 4.4.1, using the applicable inspection equipment of 4.3.4. Any assembly from which one or more pins are missing shall be classed defective and removed from the lot pending repair and re-submission to test.

4.3.3.2.2 Assembly Weight (see dwg. 9226302 or dwg. 9230608 whichever applies) - Major Defect - Code No. 12008.-This determination shall be performed 100 percent. Any assembly which fails to comply with requirements of the drawing shall be classed defective and removed from the lot. The test shall be performed as specified in 4.4.2.

4.3.3.2.3 Leakage Test of Inert Parts (see 3.4) - Inert Parts Assembly - Major Defect - Code No. 11004 - Safety and Arming Housing Assembly - Major Defect - Code No. 05010.-This test shall be performed 100 percent, as specified in 4.4.3, using the test equipment specified in 4.3.4. Any assembly which fails to comply with the requirements shall be classed defective and shall be removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.3.3.2.4 Molded Components (see dwg. 9226309, 9226305, and 9226304).-At the start of production from a new mold, or after adjustment or repair to a mold, consecutively produced units from each mold shall be dimensionally examined until four (4) consecutive units meet all applicable drawing requirements. After adjustment or repair, those dimensions affected by the adjustment or repair shall be examined. During production, the molding procedures shall be monitored for uniformity of molding practices. Suspected deviations in mold product shall be examined to determine if corrective action or mold repair is required. All dimensions for the thin body sections of the forward and aft bodies may be measured while under restraint to control the inherent out-of-round condition.

4.3.3.2.5 Inserts - Safety and Arming Inserts (see dwg. 9226308) - Major Defect - Code No. 12010.-This determination shall be performed 100 percent, as specified in 4.4.4, using the test equipment specified in 4.3.4. Any assembly which fails to comply with the requirement shall be classed defective and shall be removed from the lot pending repair and re-submission to test.

4.3.3.2.6 Fragment Weight (see dwg. 9226307) - Major Defect - Code No. 15001.-This determination shall be made on each lot of 15,000 fragments as specified in 4.4.5. Any quantity of 15,000 fragments which fails to comply with the requirements shall be classed defective and shall be rejected.

4.3.4 Inspection Equipment.-Equipment Tabulation Number ET-9226302 or ET-9230608 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in Paragraph 6.3.

4.3.4.1 Government Rights to Documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving of inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

4.4 Test Methods and Procedures

4.4.1 Mounting Insert Pins.-The cavity of each mounting insert shall be examined using the gage specified in 4.3.4. If the shoulder of the gage contacts one or more inserts of a unit, that unit shall be classed defective.

4.4.2 Weight of Inert Parts Assembly.-The inert parts assembly shall be weighed using equipment accurate to within 0.01 pounds.

4.4.3 Leakage of Inert Parts.-The inert parts assembly, prior to painting and the safety and arming housing assembly, shall be subjected to the internal air pressure specified in 3.4 while submerged under 1 inch of water. Any assembly exhibiting leakage, as evidenced by the escape of a stream of bubbles, of any frequency shall be classed defective. Acceptable units shall be identified by a 1/2 inch letter "A" stamped on the recess for the safety and arming flange and between the booster slot and flange on the safety and arming housing assembly.

4.4.4 Inserts.-The four safety and arming inserts shall be examined, after painting, using the gages specified in 4.3.4. If the gage does not screw in for the specified length in one or more inserts of any assembly, that unit shall be classed defective.

4.4.5 Fragment.-The specified quantity of fragments shall be weighed using equipment accurate to within 0.01 pound

5. PREPARATION FOR DELIVERY

5.1 Packing and Marking

5.1.1 Level C - Parts Assembly (dwg. 9226302 or dwg. 9230608 whichever applies).-The assemblies shall be packed and marked in accordance with dwg. 9211595, dwg. 9211596 or dwg. 9233456 whichever applies.

5.2 Data Cards.-Data cards shall be prepared for each lot (see 6.1).

6. NOTES

6.1 Ordering Data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data Cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167. Data cards shall include, as a minimum, the following components and assembly information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

COMPONENTS

Component	Drawing	Model	Manufacturer	Date Manufactured	Lot No.	Quantity
Safety & Arming Housing Assembly	9226308	NA	Required	Required	If Applicable	Required
Booster Cup	9247335	NA	"	"	"	"
Fragment	9226307	NA	"	"	"	NA
Mounting Insert	8861590	NA	"	"	"	Required
Aft Cup	9226306	NA	"	"	"	"
Liner Insert	9226311	NA	"	"	"	"
Self-Locking Screws	.9238885	NA	"	"	"	"
Nut	MS-27131	24K	"	"	"	"

NA - Not Applicable.

REMARKS:
List all unit serial numbers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

6.2 Inspection Code Numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection Equipment.-The contractor shall design inspection equipment as required by the referenced inspection Equipment Lists (EL) in accordance with the instructions of Paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection Equipment Lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number column" of the list of inspection equipment (Form SMUPA 1010) the number of drawings or Federal Stock numbers of existing equipment designs or codes as indicated in Paragraph 6.3.2. Design action required of the contractor is described in Paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection Equipment List Codes.-The inspection equipment, as defined in 6.3.3 and 6.3.4, will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army Designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide design when an army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

6.3.4 Contractor Designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of Contractor Designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND14. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Shipping Containers.-The procuring agency should notify the parts contractor of the possible availability of used wood shipping containers.

6.5 Quality Assurance Provisions of Other Documents.-The Quality Assurance Provisions of Other Documents of the contract, which are required to be part of the contractor's written description, include but are not limited to those which relate to plating or other protective coating, physical, chemical and other properties when specific quality assurance or inspection provisions are included in the applicable material or process specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

6.6 Submission of First Article Samples.-Instructions as to the location for the evaluation of the first article sample shall be obtained from the contracting officer. Upon receipt of such request, the contracting officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-NI, Dover, New Jersey.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1336-A-160

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 61 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:12Z
Check the source to verify that this is the current version before use.