INCH-POUND

MIL-W-14960B (AR)
AMENDMENT 3
10 March 1994
SUPERSEDING
AMENDMENT 2
05 July 1990

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE
HE, M155, AND WARHEAD GUIDED MISSILE, TRAINING M237
PARTS FOR

This Amendment forms a part of Military Specification MIL-W-14960B (PA), dated 30 June 1971, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Change heading identification number:

From: "MIL-W-14960B (MU)"

To: "MIL-W-14960B (PA)".

PAGE 3

* 3.8 Change from:

"Fragment Weight.-A quantity of 15,000 fragments (dwg. 9226307) shall weigh 64.3 pounds minus 1 pound, plus 2 pounds."

Change to:

"Fragment weight. A quantity of 2,500 fragments (dwg. 9226307) shall weigh 64.3 pounds minus 1 pound, plus 2 pounds."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.

4.3.2.14 Change Major:

From: "Major AQL 1.00%"

To: "Major AQL 0.65%"

4.3.2.14 Change Major 102:

From: "102 Board broken, split or curled Visual 14002"

To: "102 Board broken, split full length Visual 14002"

4.3.2.14 Delete Major:

"105 FSN number misleading or unidentifiable Visual 14005"

Page 14

* 4.3.3.2.6 Change from:

"4.3.3.2.6 Fragment Weight (see dwg. 9226307) - Major Defect - Code No. 15001.-This determination shall be made on each lot of 15,000 fragments as specified in 4.4.5. Any quantity of 15,000 fragments which fails to comply with the requirements shall be classed defective and shall be rejected."

Change to:

"4.3.3.2.6 Fragment weight (see dwg. 9226307) - Major Defect - Code No. 15001. This determination shall be made on each lot of 2,500 fragments as specified in 4.4.5. Any quantity of 2.500 fragments which fails to comply with the requirements shall be classed defective and shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.

4.4.3 Change from:

"4.4.3 Leakage of Inert Parts. The inert parts assembly prior to painting and the safety and arming housing assembly shall be subjected to the internal air pressure specified in 3.4 while submerged under 1 inch of water. Any assembly exhibiting leakage as evidenced by the escape of a stream of bubbles, of any frequency shall be classed defective. Acceptable units shall be identified by a 1/2 inch letter "A" stamped on the recess for the safety and arming flange and between the booster slot and flange on the safety and arming housing assembly."

Change to:

"4.4.3 Leakage of Inert Parts. The inert parts assembly prior to painting and the safety and arming housing assembly shall be subjected to the internal air pressure specified in 3.4 while submerged under 1 inch of water. Any assembly exhibiting leakage as evidenced by the escape of a stream of bubbles of any frequency shall be classed defective. Acceptable units shall be identified by a 1/2 inch letter "A" stamped on the interior surface of aft body P/N 9226305 in molded area covering cup P/N 9226306."

The margins of this amendment are marked with asterisks to indicate where the changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 1336-A639)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:11Z
Check the source to verify that this is the current version before use.