PURCHASE DESCRIPTION

WARHEAD, 2.75 INCH ROCKET XM229, (Two PIECE)
PARTS FOR

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings, for one type of warhead designated as Warhead, 2.75 Inch Rocket, XM229, (Two Piece).

2. APPLICABLE DRAWINGS

2.1 The following documents of the issue In effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coating

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of
MIL-STD-105 - Sampling procedures and tables for inspection by attributes

STANDARDS

FEDERAL

FED-STD-151 - Metals, Test Methods

FSC: 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

9238883 - Warhead, 2.75 Inch Rocket, XM229 Metal Parts Assembly (Two Piece)

PUBLICATIONS

ORDNANCE CORPS

ET-9238883 - Equipment Tabulation

(Conies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications, - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated? the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing Materials (ASTM)

A 445- Ferritic Ductile (Nodular) Iron Castings for Valves, Flanges, Pipe Fittings, and Other Piping Components.

(Application for copies should be addressed to The American Society for Testing Materials 1916 Race Street, Philadelphia 3, Pa.

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Warhead assemblies. - The warhead assemblies shall comply with all requirements specified on Drawing (dwg,) 9238883, and with all requirements specified in applicable specifications.

3.3 Metal defects. - The components shall be free of surface defects, cracks, cracklike imperfections, pits, cold shuts, hot tears, blow holes, scaling, and other similar defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

3.4 Microexamination. - For ductile iron the microstructure test described in ASTM-A-445 shall be performed for each ladle.

3.5 Salt Spray Test. - The finished assemblies after painting shall comply to an accleerated corrosion test as described in this document.

3.6 Each warhead shall be capable of withstanding a 5 ft. drop test as prescribed in this document.

3.7 Workmanship, - The components and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, unblended radii, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few slight scratches not exposing phosphate coating or base material. All required markings shall be neat and sharply defined.

3.8 First Article Inspection. - This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such Inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product. - At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

A statement that the lot Complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all Inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4,2 First Article Inspection

4.2.1 Submission. - The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 5 sets of the component parts (unpainted) , 5 unpainted assemblies, and 5 painted assemblies which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production

Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of' the contract and submit a record of this inspection with the sample, including statements of findings/certificates of conformance for materials (see 4.1.l.e). A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed? - Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in this, specification and any or all requirements of the applicable drawings.

4.2.3 Rejection. - If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.3 Inspection provisions for production

4.3.1 Lot formation. - The term “lot” as used throughout this specification refers to an Inspection lot, which 3.s defined as an essentiality homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, specification, or revision thereof. Changes to either the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105 and shall be numbered in accordance with MIL-STD-1168.

Unless otherwise approved by the contracting officer, the inspection lot size of major assemblies or end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest quantity contractually scheduled for delivery during any month of the contract period. Inspection lots for components or sub-assemblies, other than the items of delivery, shall be homogeneous and of a size convenient to the contractor.

4.3,2 Examination, - Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL’s and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent foe each minor defect. Once agreement has been reached as to which method will be used (group or individual) that method will be used for all of the CD’S listed in this specification. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Nose, Elongated (see dwg. 9238882 covering a detail of dwg. 9238883).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Metal defective (see 3.3).....	Visual	01001

Minor: None defined.

4.3.2.2 Base (see dwg. 8889404 covering a detail of dwg. 9238883).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Diameter inside at front.....	Gage	02001
102.	Diameter inside.....	Gage	02002
103.	Metal defective (see 3.3).....	Visual	02003
Minor:	AQL 1.50 percent		
201.	Improper forward radii or chamfer.....	Visual-Measure	02004
202.	Improper surface finish.....	Visual	02005
203.	Evidence of poor workmanship (see 3.7).....	Visual	02006

4.3.2.3 Warhead, 2.75 Inch Rocket, XM229, Metal Parts Assembly, (Two Piece) before painting (see dwg. 9238883).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Hydrostatic stamp missing.....	Visual	03001
2.	Air pressure stamp missing....	Visual	03002
Major:	AQL 2.50 percent		
101.	Concentricity of pitch diameter of fuze thread with outside diameter between the bourrelets including perpendicularity of front face.....	Gage	03003
102.	Concentricity of counterbore at front of fuze thread with pitch diameter of thread.....	Gage	03004
103.	Concentricity of diameter at rear of fuze thread undercut (if applicable) with pitch diameter of threads.....	Gage	03005
104.	Concentricity of ogive with outside diameter between the bourrelets.....	Gage	03006

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

105.	Concentricity of base at rear of thread with pitch diameter of base thread.....Gage	03007
106.	Concentricity of base at rear of threads with outside diameter between the bourrelets.....Gage	03008
107.	Concentricity of the rear bourrelet with outside diameter between the bourrelets.....Gage	03009
108.	Concentricity of the forward bourrelet with outside diameter between the bourrelets.....Gage	03010
109.	Motor body seat not perpendicular to outside diameter between the bourrelets.....Gage	03011
110.	Length of fuze thread (if applicable).....Gage	03012
111.	Diameter of rear of fuze thread.....Gage	03013
112.	Outside diameter forward & aft of forward bourrelet.....Gage	03014
113.	Diameter of rear bourrelet....Gage	03015
114.	Diameter of forward bourrelet.Gage	03016
115.	Diameter of base at rear of thread.....Gage	03017
116.	Thickness of wall between the forward bourrelet and ogive...Gage	03018
117.	Thickness of wall between the bourrelets.....Gage	03019
118.	Variation of wall thickness excessive.....Gage	03020
119.	Profile of ogive.....Gage	03021
120.	Thickness through base.....Gage	03022
121.	Metal defective (see 3.3).....Visual	03023
122.	Length from front face to motor housing seat.....Gage	03024
123.	Length from motor housing seat to rear of base.....Gage	03025
Minor:	AQL 2.50 percent	
201.	Depth of counterbore at front.Gage	03026
202.	Improper forward radii or chamfer.....Visual	03027
203.	Improper surface finish.....Visual	03028
204.	Location of rear thread.....Gage	03029
205.	Evidence of poor workmanship (see 3.7.....Visual	03030

4.3.2.4 Warhead, 2.75 Inch Rocket, XM229, Metal Parts Assembly, (Two Piece) after painting (see dwg. 9238883).

Source: https://assist.dla.mil -- Downloaded: 20260-18T05:13Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Pitch diameter of fuze thread.	Gage	04001
102.	Minor diameter of fuze thread, max.	Gage	04002
103.	Pitch diameter of rear thread.	Gage	04003
104.	Major diameter of rear thread, min.	Gage	04004
105.	Thread damaged or not full.	Visual	04005
106.	Foreign matter in cavity.	Visual	04006
Minor:	AQL 2.50 percent		
201.	Protective coating inadequate or damaged.	Visual	04007
202.	Paint in cavity inadequate.	Visual	04008
203.	Paint not dry.	Tactile	04009
204.	Paint adhesion.	Tape Test	04010
205.	Marking missing, incorrect, or illegible.	Visual	04011

4.3.3 Testing

4.3.3.1 Microexamination. - Major Defect - Code No. 01002 (see Dwg. 9238882). For ductile. iron, a test lug shall be cast representing the last metal poured from each ladle treated with the modularizing agent. The test casting and microexamination shall be in accordance with ASTM-A-445. Failure of the test lug to conform to the microstructure requirements of ASTM-A-445 shall be cause for rejection of the castings from the ladle represented by the test lug.

4.3.3.2 Hardness Test

4.3.3.2.1 Ductile Iron Nose Casting Hardness Test - Major Defect - Code No. 01003. - To insure compliance with the mechanical properties requirements, each nose casting from a sample shall be subjected to a hardness test with a Brinell Hardness Tester. The sample, 10 per cent minimum, representative of extreme furnace environment , shall be selected from each heat treat batch when a batch type furnace Is used for final heat treatment. When a continuous type furnace Is used for final heat treatment, from which a 10% min. sample will also be selected, a heat treat batch will be considered a quantity of castings not to exceed 4 hours production. The castings which constitute the sample shall be collected at regular continuous intervals throughout the 4 hour cycle. The heat treat batch thus constituted shall form the basis for selecting castings for the tension test hereinafter prescribed. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.3,3.2.2 Malleable Iron Base Casting Hardness Test - Major Defect - Code No. 02007. - To insure compliance with the mechanical properties requirements, each base casting from a sample shall be subjected to a hardness test with a Brinell Hardness Tester. The sample, a 10% minimum, representative of extreme furnace environment, shall be selected from each heat treat batch of 1000 or fraction thereof when a batch type furnace is used for the final heat treatment. When a continuous type furnace is used for final heat treatment, from which a 10% min. sample will also be selected, a heat treat batch will be considered a quantity of castings not to exceed 4 hours production. The castings which constitute the sample shall be collected at regular continuous intervals throughout the 4 hour cycle. The heat treat batch thus constituted shall form the basis for selecting sample castings for the tension test here-in-after prescribed. The hardness test shall be performed on the approximate center of the bottom of the castings, The test shall be performed as specified in 4.4.1 using equipment in accordance with 4.3.4.

4.3.3.3 Tension Test

4.3,3.3.1 Tension Test on Nose (Ductile Iron) - Major Defect - Code No. 01004. - The hardest and softest casting representing the days' heat treat production as determined in 4.3.3.2.1 shall be subjected to the test specified in 4.4.3 using equipment in accordance with 4.3.4. Failure of any test specimen to comply with the applicable physical properties requirements shall be cause for rejection of the days' heat treat production represented by the specimens.

4,3.3.3.2 Tension Test on Base. Major Defect - Code No. 02008. When malleable iron is used two base castings from each heat treat batch; one of the hardest and one of the softest as determined by 4.3.3.2.2 shall be subjected to the tension test In accordance with 4.4.4, to determine compliance with the mechanical properties requirements of the applicable drawing. When steel bases are used, two bases from each heat treatment or stress relieved batch of 5000 or fraction thereof shall be subjected to the tension test. Failure of any specimen to comply shall be cause for rejection of the batch represented by the specimen. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3,4.

4.3.3.4 Hydrostatic Test, - Critical defect - Code No. 03031 - Each metal parts assembly shall be subjected to the required constant internal hydrostatic pressure to determine compliance with requirements specified on dwg. 9238883. Failure of any assembly to comply shall be cause for rejection of the assembly. Metal parts assemblies which comply shall be stamped with the letter "H" as indicated on the assembly drawing. The test shall be performed as specified in 4.4.5 using equipment in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.3.3.5 Air pressure - Critical defect - Code No. 03032. - Each shell assembly that has passed the hydrostatic pressure test, as indicated by the letter "H" stamped on the body, shall, after completion of the drying cycle be subjected to a submerged air pressure test. Any shell assembly failing to comply with requirements specified on Dwg. 9238883 as evidenced by air bubbles rising to surface of water shall be rejected. Air bubbles caused by entrapped air on the outside of the shell shall not be cause for rejection of the shell assembly. Shell assemblies which comply with the requirements of Dwg. 9238883 shall be stamped with the letter "A" as indicated on the assembly drawing. The test shall be performed as specified in 4.4.6 using equipment in accordance with 4.3.4.

4.3.3.6 Salt Spray Test - Major defect (see 3.5) Code No. 04012. - The sample size for this test shall be as follows: During production, one warhead from each days production, shall be subjected to the salt spray test as specified in 4.4.8, until five consecutive days production have successfully passed the test. Sampling shall then be reduced to one sample twice per week, upon reduced sampling if one failure occurs, corrective action shall be taken and sampling shall revert to one specimen from each days production until five consecutive days' production have again successfully passed the test. If two consecutive failures occur after the contractor has been notified to take corrective action in either the original sampling plan or the reduced sampling plan, inspection for acceptance shall be stopped until necessary corrective action has been taken. Any specimen (warhead) which does not comply with any of the following test criteria shall be considered a failure. The specimen, when subjected to the salt spray test as specified in 4.4.8, shall show no more than 1/8 inch creepage, blistering, or loss of adhesion of the paint as measured from the scribe mark. At all other points there shall be no more than a trace of film failure such as blistering, or corrosion, and not more than twenty scattered blisters, none larger than 3/16 inch in diameter on the painted surface of the warhead. This is intended that the maximum amount of corrosion in the salt spray test be comparable to photograph 8-1 in ASTM Standard Method of Evaluation Degree of Resistance to Rusting obtained with paint or iron and steel surfaces, D610-43. This test shall be performed as specified in 4.4.8 using equipment in accordance with 4.3.4.

4.3.3,7 Drop Test - Major Defect - Code No. 04013 - Beginning with the first lot and continuing until five consecutive lots have been tested a sample from each lot shall be subjected to a drop test as specified in 4.4.7 using equipment in accordance with 4.3.4, Upon satisfactory results from five consecutive lots the contractor may reduce testing to a sample from one randomly selected lot per month. The contractor shall return to the five lot requirement upon failure of any lot. The sample shall consist of 23 randomly selected painted assemblies which have passed all other requirements of this specification. The lot represented by the sample shall be rejected if two (2) or more warheads fail to

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the current version before use.

comply with the inspection criteria. If only one (1) warhead fails, a retest is permissible as follows: For retest, a new sample, consisting of 46 warheads randomly selected from the lot shall be subjected-to the drop test in accordance with 4.4.7. If one or more warheads fail to comply with the inspection criteria, the lot shall be rejected. Inspection Criteria - The warheads shall be subjected to and comply with a Hydrostatic and Air test in accordance with 4.3.3.4 and 4.3.3.5. There shall be no visual evidence of cracklike discontinuities on the surface of the warheads after the Hydrostatic and Air tests, This Is considered to be a destructive test.

4.3.4 Inspection Equipment, - Equipment Tabulation Number ET-9238883 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.4.1 Government rights to documentation. - Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, Identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.4.2. Supply and Maintenance. - Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.4 Test Methods and Procedures

4.4.1 Hardness Test on Base. - After final heat treatment, the hardness test shall be performed on the base. Procedures for this test are as prescribed by Federal Test Method Standard No. 151 Method 242.1,

4.4.2 Hardness Test on Nose, Elongated, - After final heat treatment, the hardness test shall be performed on the nose, elongated, between the bourrelets. Procedures for this test are as prescribed by Federal Test Method Standard No. 151. Method 242.1.

4.4.3 Tension Test on Nose, Elongated, - Two tension test specimens conforming to a standard “R” type specimen as prescribed by Federal Test Method Standard No. 151 shall be taken longitudinally from each sample. Samples shall be taken 1.800 apart between bourrelets. The criteria for determining yield strength and elongation shall be as prescribed by Federal Test Method Standard No. 151 Method 211.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.4,4 Tension Test on Base, - From the samples provided in accordance with 4.3.3.3.2 one tensile test specimen conforming to a standard "R" type specimen as prescribed by Federal Test Method Standard No. 151 shall be taken from the bottom of each base. The criteria for determining yield strength and elongation shall be as prescribed by Federal Test Method Standard No. 151, Method 211.1.

4.4.5 Hydrostatic Test - (see 4.3.3.4). - The metal parts assembly shall be hydrostatically tested using equipment capable of performing the test accurately and consistently. In performing the test, the pressure will be applied gradually until the required minimum pressure is reached, after which the pressure will be held for a minimum of 5 seconds. The equipment shall be calibrated prior to the start. of each day's operation, at intervals of not over 2 hours of continuous operation, and prior to restarting the operation after a layoff of 1 hour or more.

4.4,6 Air Pressure Test - (see 4,3.3.5). - Body assemblies that have passed the hydrostatic test shall be mounted in an approved fixture in such a manner that the body assembly will be completely submerged in water. The air pressure shall be applied and held for a minimum of 15 seconds.

4.4.7 Drop Test. - Warheads from a sample as provided in accordance with 4.3.3.7 shall be dropped from a height of 5 feet onto a steel plate having a minimum thickness of 3 inches and a brinell hardness of at least 207. The steel plate shall be solidly supported in a horizontal plane over its entire bearing area by a minimum thickness of 24 inches of concrete. The steel plate shall have a smooth flat surface and shall have a length and width of at least 36 inches. The plate shall be surrounded on all four sides by a heavy steel enclosure of sufficient height and strength to contain the warheads during rebounds. The 5 foot height necessary to perform this test can be obtained by using a special steel tower or derrick. The warheads will be dropped individually with their longitudinal axis at 45 degrees to the horizontal base down. The warhead shall be inert loaded to conform to the weight and center of gravity of a HE warhead. An inert loaded 423 fuze shall be attached to the inert warhead. The combined weight of the inert warhead and fuze shall be 16.75 ± 0.2 lbs. The center of gravity is 14.25 ± 0.5 from the forward end of the fuze.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

4.4.8 Salt Spray Test (see 4.3.3.6), - An accelerated corrosion test shall be performed utilizing the equipment and procedures prescribed by the Federal Test Method Standard No. 151, Method 811. A 20 percent concentration of sodium chloride solution shall be used and length of the test shall be for 144 hours. Actual production warhead assemblies only shall be subjected to this test. Test panels shall not be substituted for the warhead assemblies. The test specimen shall be air dried for a minimum of 96 hours before testing. The painted specimen shall be scored through using a sharp knife. The specimens shall then be exposed to the 20 percent salt spray as specified in Federal Test Method Standard No. 151, Method 811.

5. PREPARATION FOR DELIVERY

5.1 Packaging and marking-Level C. - The warhead shall be packaged and marked in accordance with Drawing 7548604.

5.2 Packing and marking-Level C. - The packaged warheads shall be packed and marked in accordance with Military Specification MIL-P-10025,

6. NOTES

6.1 Ordering data. -Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers. -The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. - The contractor shall design inspection equipment required by the referenced inspection Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists. - Inspection equipment lists indicate the availability of inspection equipment designs by showing in the “number” column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor Is described in paragraphs 6.3.3 and 6.3.4, The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as “Contractor Design” in the number column. These contractor designs must

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes. - The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
Mu - Army design, mandatory for use.

6.3.3 Army designs. - Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing of Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs. - Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

6.3.5 Submission of contractor designs. - All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification. Unless otherwise specified on the (EL) Equipment List, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND9. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Submission of First Article Samples. - Instruction as to the location for the evaluation of the First Article sample shall be obtained from the Contracting Officer. Upon receipt of such request, the Contracting Officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-NI.

6.5 Defect Reporting. - Beginning with the first lot and continuing until 25 lots have been produced and accepted by the Government, the contractor shall submit a defect report to the Commanding Officer, Picatinny Arsenal, Dover, New Jersey, ATTN: SMUPA-ND9. After 25 lots have been produced and accepted, the contractor shall submit a defect report for every fifth lot for the remainder of the contract. The defect report shall contain the results of the inspections and tests as per paragraphs 4.3.2 and 4.3.3 of this specification, The inspections and tests shall be identified in the report by Defect Code Numbers as shown In para. 4,3.2 and 4.3.3.

NOTICE: When Government drawing, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever: and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may In any way be related thereto.

Custodian:
Army - MU

Preparing Activity:
Army - MU

Project No. 1340-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 61 1426

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:13Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

343-221 (A-593)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:13Z
Check the source to verify that this is the current version before use.