[METRIC]
A-A-2082D
December 3, 1993
SUPERSEDING
A-A-2082C
October 24, 1989

COMMERCIAL ITEM DESCRIPTION

STANDS, OFFICE MACHINE (TRADITIONAL STYLE)

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification AA-S-00680E which is canceled.

1. Scope. This commercial item description covers office machine stands which are a part of a traditional line of gray metal furniture for heavy duty office use.

2 Salient characteristics.

2 1 Classification The stands shall be classified by the following types

Type I - Stationary stand with a drawer or compartment for paper. Minimum overall dimensions are 914 mm W x 610 mm D x 660 mm H (maximum height 686 mm).

Type II - Portable stand with drop leaves and retractable casters. Minimum top dimensions are 254 mm W x 394 mm D Minimum drop leaf dimensions are 216 mm W x 394 mm D. Minimum overall height with casters retracted is 660 mm (maximum height 686 mm)

3 Requirements.

3 1 Tops

3 1 1 Type I top The Type I top shall have a 19 mm minimum radius on the corners The top shall be HP plastic laminate with a backing sheet on the bottom. The backing sheet is not required with steel core tops. The edging shall be plastic or metal (self-edging is not allowed). The overhang shall be a maximum of 51 mm beyond the apron. overall thickness shall be a minimum of 19 mm.

3.1.2 Type II top. The Type II top shall be HP plastic

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

laminate with a backing sheet on the bottom The backing sheet is not required with steel core tops. The sides of the top shall be sealed or self-edged. Overall thickness of the top shall be a minimum of 19 mm. Alternatively, the top and drop leaves may be five ply hardwood lumber core or seven ply hardwood veneer, properly sealed on both sides and finished with semi-gloss lacquer.

3 1 3 Plastic laminate. When a HP plastic laminate is used, the color shall be white leather in accordance with GSA Standard FSS-L-01001. Alternatively, the manufacturer may provide his equivalent commercial white leather HP plastic laminate subject to the contracting officer's approval.

3.2 Legs.

3.2.1 Type I legs. The Type I legs shall have be a minimum 50 mm square (with or without a taper) formed steel and shall be KD construction.

3 2.2 Type II legs The Type II legs shall be tubular or formed steel The base shall have retractable casters, minimum 50 mm diameter with ball bearing swivels, the retracting mechanism shall have a means of locking the casters in the down or operating position

3.3 Drawer or compartment. On the Type I stand, there shall be either a drawer or an open compartment located on the right facing the stand. Either shall accommodate 216 mm by 279 4 mm paper The sides of the open compartment shall be closed and shall be equally accessible from the front or back of the stand. Exposed corners shall have a minimum 12 7 mm radius minimum inside clearance height of the drawer or compartment shall be 50 mm The drawer shall have in and out stops

3 4 Finish The stand shall have a baked enamel finish The color shall be in accordance with Fed Std No 595, gray (26134' Alternatively, the manufacturer may provide his commercial, baked enamel, gray finisr subject to the contracting officers approval

3.5 Identification label The identification label shall have the contractor's name or trademark, contract number and year and month of manufacture legibly marked with permanent ink The label shall not be removable by hand without defacement after being affixed for four hours.

3.6 Workmanship. The stands shall be free from sharp

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:19Z
Check the source to verify that this is the currenversion before use.

corners, edged, burrs, and design features which could cause injury to personnel or damage to their clothes. The baked enamel finish shall be smooth, without runs, grit, wrinkles, tackiness, or separation of color. There shall be no defects that affect the appearance or serviceability of the stand

3.7 Performance The stands shall comply with the following requirements. Failure to comply with these requirements shall be cause for rejection.

3.7 1 Type I. The Type I stands shall comply with the following tests cited in ANSI/BIFMA X5.5· 4 - Top Loading, 5 - Top Load Ease, 8 - Out Stop, 10 - Racking, 11 - Drop, 12 - Leg Impact, and 14 - Tables Stability.

3.7 2 Type II The Type II stands shall comply with the following tests.

3.7.2.1 Dropleaf test. The casters shall be retracted. The leaves shall be raised to the horizontal and supported by the leaf supports. A straight edge shall be placed across the stand top and extending to the outside edge of the drop leaf. The vertical measurement from the bottom of the straight edge to the top of the outside of the leaf shall not be greater than 3.8 mm nor shall the leaf support hold the leaf in a position higher than the stand top. The test shall be performed on both the right and left leaves After this portion of the test is performed, a test load of 9.1 Kg shall then be applied to each leaf for a period of five minutes. The load shall be evenly distributed in the area in the area extending from the side edge of the top up to 51 mm of the end of the leaf. The entire load shall be concentrated on the leaf. Upon removal of the load and with the leaves still in the horizontal position, the vertical measurement shall be repeated Any difference in the measurements taken before and after the weight was applied in excess of 1 6 mm shall be cause for rejection

3 7.2.2 Static load test. The casters shall be retracted and the leaves dropped. Apply a weight of 90 6 kg for a minimum time of 5 minutes to an area not to exceed 304.8 mm in diameter in the center of the top. Deflection of the top in excess of 3 8 mm during the test or a permanent set in excess of 1.6 mm of any part of the stand shall be cause for rejection.

3.8 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.

4 Quality Assurance Provisions

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:19Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. The contractor shall be responsible for the performance of all inspection and testing in fulfillment of all requirements specified herein. Unless otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities approved by the Government as suitable for the performance of inspections and tests required by this CID The Government reserves the right to perform any or all of the inspections and/or tests set forth in this CID, as deemed necessary to provide assurance of supply conformance to prescribed requirements.

4.2 First article requirements The first article requirements shall be as specified in the solicitation.

4.3 Quality conformance inspection A sample of the finished product shall be selected in accordance with paragraph 5 6 of this CID for quality conformance verification The sample shall be examined to verify that the requirements referenced in sections 1 and 2 have been met. Any non-conformance with the above requirements shall be considered a defect All defects found shall be classified as major/minor in accordance with paragraphs 4 4 and 4.5 of this CID.

4 4 Major defects The following conditions of non-conformance with the stated requirements of the CID shall be considered as major defects which may potentially affect the safety, functionality, durability, usability, and life of the purchased items

No acceptable evidence Types I and II tables are in conformance with ANSI/BIFMA standard X5.5.
No evidence of Type II tables meeting the dropleaf and static load test
Parts fractured, buckled, bent, punctured, or malformed
Rivets loose or not set properly Sharp edges
Preservation, packaging, and packing not in accordance with the requirements of the contract or purchase order
Identification marking missing, wrong, or illegible

4.5 Minor defects. Non-conformance listed below shall be considered as minor defects affecting the appearance of the finished item

Rough or slivered surface.
Burrs.
Rough tool markings
Oversized holes

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:19Z
Check the source to verify that this is the currentversion before use.

Pitted, stained, or blistered surfaces.
Foreign matter embedded in the finish.
Painted surfaces contain sags or runs.
Components and parts covered with film.
Parts, components, overall covered, not free of grease, dirt dust, epoxy, stains, etc

4 6 Sampling The sampling plan shall be in accordance with MIL-STD-105 with an inspection level II, Acceptable Quality Level (AQL) of 6 5 percent defective for minor defects and an inspection level of S-2, AQL of 2 5 percent defective for major defects.

5 Preservation, packaging, packing, labeling, and marking The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

6. Standards. The latest issues of ANSI/BIFMA Standard No X5.5, MIL-STD 105 and Fed. Std 595 in effect on the date of the solicitation shall be used to determine compliance with the stated requirements.

7 Notes

7 1 Ordering data Purchasers shall specify the type

7.2 Plastic laminate sample. A sample of the decorative plastic laminate is obtainable from the General Services Administration Federal Supply Service, Furniture Commodity Center, Engineering Division, Washington, DC 20406

7 3 Color sample. A sample panel of the enamel finish is obtainable from the General Services Administration, Federal Supply Service, Business Service Center, Washington, DC 20407 or the Business Service Center in the nearest General Services Administration Regional Office

7 4 ANSI/BIFMA Standard Copies of the ANSI/BIFMA Standard X5 5 can be obtained from the American National Standards Institute, Inc , 1430 Broadway, New York, NY 10018

7.5 MIL-STD-105 Copies of MIL-STD-105 can be obtained from the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

7.6 Federal standards. Federal Standard No. 595 is available from General Services Administration Business Service Centers in Boston, MA, New York, NY; Philadelphia, PA; Washington, DC,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle WA.

PREPARING ACTIVITY
GSA - FSS/3FNE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.