[INCH-POUND]
A-A-2824
October 13, 1993

COMMERCIAL ITEM DESCRIPTION

KITCHEN UTENSILS

The General Services Administration has authorized the use of this commercial item description (CID) as a replacement for CID's A-A-395, A-A-464, A-A-858, and A-A-1754 which have been canceled.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This commercial item description covers four kitchen utensils.

1.2 Classification. The kitchen utensils shall be of the following items, as specified (see 6.1):

Items:
1 - Masher, Potato, Hand
2 - Egg Beater
3 - Dredger, Kitchen
4 - Sieve, Flour

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of issuance of the invitation for bids or request for proposal unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102

DISTRIBUTION STATEMENT A : Approved for public release; distribution is unlimited.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

Federal Standard:

FED-STD-376 - Preferred Metric Units For General Use By The Federal Government.

Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA, and the GSA Specifications Unit (3FBP-W), Suite 8100, L'Enfant Plaza, S.W., Washington, DC 20407.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM Standard:

E 29 - Standard Practice For Using Significant Digits In Test Data To Determine Conformance With Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

NSF International:

Standard Number 2 - Food Service Equipment.
Criteria C-2 - Special Equipment and/or Devices.
Annual Listing - Food Service Equipment and Related Products, Components and Materials.

Application for NSF International documents should be addressed to NSF International, 3475 Plymouth Road, P.O. Box 130140, Ann Arbor, MI 48113-0140.

3. SALIENT CHARACTERISTICS

3.1 Design and construction.

3.1.1 Item 1 - Masher, Potato, Hand. The overall length of the masher shall be 17 to 20 inches (431.8 to 508.0 mm). The wire base of the masher shall measure 3 X 4 inches minimum (76.2 to 101.6 mm). The wire shall be either corrosion-resisting steel or plated (nickel or chromium) carbon steel with a diameter of not less than 3/16 inch (4.8 mm). The wire shall be bent in a serpentine shape and the ends of the wire bent at right angles to the base, brought together and inserted into the handle.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:26Z
Check the source to verify that this is the current version before use.

The handle shall be tubular and fabricated of corrosion-resisting steel, brass, carbon steel, plastic, or other material in accordance with NSF International standards.

3.1.2 Item 2 - Egg Beater. The egg beater shall be constructed from metal die cast components. Ferrous parts shall be nickel or chromium plated. The egg beater shall be hand operated and consist of double agitators which are operated by a hand-crank with drive and pinion gears. The egg beater shall have a handle at the top of the frame for grasping while operating the hand crank. The double agitators shall have a minimum of four wings each. A suitable plastic may be used for the pinion gear and bushings. The overall length of the egg beater shall be from 10-7/8 to 13-1/2 inches (276.2 to 342.9 mm). The beater shall operate smoothly without gear or pinion crumbling, deformation, slipping, or binding.

3.1.3 Item 3 - Dredger, Kitchen. The kitchen dredger may be fabricated from either aluminum or corrosion-resisting steel. The body shall be formed seamless from a single piece of aluminum, 0.028 inch minimum thickness (0.71 mm), or corrosion-resisting steel, 0.022 inch minimum thickness (0.56 mm). The top edge of the body shall be threaded to accommodate the cover. The cover shall be made from the same material as the body and may be up to two gauges thinner than the body. The cover shall be threaded to match the body and shall contain 100 holes (minimum) with a minimum diameter of 0.060 inch (1.5 mm). The body shall include a handle of the same thickness. The height of the dredger shall be 3-7/8 inches ± 1/4 inches (98.4 mm ± 6.35 mm) and the diameter shall be 2-7/8 inches, + 1/8 inch, - 5/16 inch (73.0 mm, + 3.18 mm, - 7.94 mm). Aluminum dredges shall have a bright anodized finish and corrosion-resisting steel dredges shall have a polished finish.

3.1.4 Item 4 - Sieve, Flour. The flour sieve shall have a top inside diameter of 16 inches ± 1/8 inch (406.4 mm ± 3.2 mm) and inside depth of 3-1/2 inches ± 1/8 inch (88.9 mm ± 3.2 mm). The body shall be formed from 0.064 inch minimum (1.6 mm) thick aluminum and shall have vertical sides with rolled groves. The bottom shall be blanked out and shall be covered with 14-mesh screen cloth (aluminum, tinned steel, or corrosion-resisting steel). If aluminum screen cloth is used it shall be protected by a heavier reinforcing screen. The screen cloth shall be locked in place by a clamping band. The clamping band shall be formed from a single piece of aluminum.

3.2 NSF International compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the items offered meet the applicable requirements of NSF International Standard No. 2 or Criteria C-2. Satisfactory evidence of this compliance may be any of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

(1) A listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished item, or

(2) A certification issued by NSF International under this special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory, acceptable to the contracting officer and the medical authority of the service for which the items are being procured, indicating that the item has been tested and conforms to NSF International Standard No. 2 or Criteria C-2. Acceptability of the testing laboratory by the medical authority shall be determined prior to initiation of procurement actions.

NSF International compliance will not be required for the items 2 and 4.

3.3 Marking for identification. The manufacturer's name, trade name or trademark shall be applied to each utensil.

3.4 Workmanship. The finished utensils shall be clean and smooth and shall not contain any burrs, rough die, tool, gouge, or grind marks or burn marks. The finished items shall not be fractured, dented, bent, punctured, or malformed. There shall be no defects which may impair serviceability, durability or appearance.

3.5 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.6 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The values stated in parentheses are for information purposes only.

3.7 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document.

3.8 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor certification. The contractor shall certify that the utensil meets the salient characteristics and the requirements of this commercial item description, and, except for any government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace, or is the same product that has been successfully been delivered to the government on a previous contract or purchase order. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.3 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.4 Lot formation. All utensils from the same manufacturer of the same item offered for delivery at one time shall be considered a lot for purposes of inspection.

4.5 Sampling for visual and dimensional examination. A random sample of utensils shall be selected from each lot in accordance with inspection level S-4, AQL 4.0 expressed in terms of defects per hundred units. The sample unit shall be one finished utensil. The sample utensil shall be visually and dimensionally examined to verify compliance with table I and the remainder of this commercial item description. All dimensions are absolute as defined in ASTM E 29.

4.6 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate and shipping containers (as applicable) for conformance with the packaging, packing, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, AQL 6.5, expressed in terms of defects per hundred units. The sample unit shall be one shipping container.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:26Z
Check the source to verify that this is the current version before use.

TABLE I - Classification of defects

Examine	Defect
Finish	Area of corrosion Stained or discolored
Construction and Workmanship	Any burrs, slivers, sharp edges, rough die marks, or tool gouge. Any part missing, or not specified size Any component fractured, split, bent, buckled, punctured or otherwise impaired
Marking	Missing, incomplete, or illegible.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable):

a. Title, number and date of this commercial item description.
b. Item required (see 1.2).
c. The packaging, packing, and marking required.

6.2 CID based part identification numbering. Utensils conforming with this commercial item description shall be identified by a part number configuration consisting of identification of a portion of the CID number and item. An example of the part identification number configuration is shown below. This part identification numbering system is intended for identification and cross-indexing of the item within the Federal cataloging system. Part identification numbers are not required to be placed on the product or container.

Part Identification Numbering System for CID A-A-2824

AA2824-1 Example - Item 1, Masher, Potato, Hand

- Item (1, 2, 3, or 4).
- General commercial item description number

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

6.3 Supersession data. The kitchen utensils were previously defined by the commercial item descriptions listed below:

Item 1 - CID A-A-395
Item 2 - CID A-A-464, Type I
Item 3 - CID A-A-858
Item 4 - CID A-A-1754

6.4 National Stock Numbers (NSN's). The following is a list of NSN's assigned which correspond to this CID. The list may not be indicative of all possible NSN's associated with this CID.

NSN	Item	Item Name
7330-00-205-3093	1	Masher, Potato, Hand
7330-00-243-3408	2	Egg Beater
7330-00-266-7454	3	Dredger, Kitchen
7330-00-815-1455	4	Sieve, Flour

Military Coordinating Activity:

Army - GL

Custodians:
Army - GL
Navy - SA
Air Force - 99

Civil Agency Coordinating Activity:

VA - OSS

Review Activities:
Army - MD, QM
Air Force - 84, 50

PREPARING ACTIVITY:

GSA - FSS

User Activity:
Navy - MC

(DoD Project 7330-0675)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.