A-A-50124
June 29, 1987

COMMERCIAL ITEM DESCRIPTION

OVENS, BAKING AND ROASTING, CONVECTION, ENERGY EFFICIENT, GAS

The General Services Administration has authorized the use of this commercial item description.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers two types of energy efficient gas convection ovens as follows:

Type I - One oven compartment

Type II - Two oven compartment

2. SALIENT CHARACTERISTICS

2.1 Type I.

2.1.1 Design and construction. The type I oven front and door exterior surfaces shall be stainless steel with the remaining exterior surfaces finished in accordance with the manufacturer's commercial practice. The oven compartment and door lining shall be stainless steel. The minimum usable oven interior shall be 26-1/2 inches wide by 21-1/4 inches deep by 19 inches high. The type I oven shall preheat from an ambient temperature of 70°F to an inner oven temperature of 350°F within 15 minutes, and shall maintain an oven temperature of 350°F for 1 hour with a gas input of not more than 14,000 BTU. Type I ovens shall be equipped with removable rack supports and five racks, a two-speed oven fan (750 to 1140 RPM for low speed and 1725 RPM for high speed), an oven light, an oven indicator light, and a 60-minute timer (minimum) with alarm. The type I oven shall also have a separate switch to operate the oven fan when the oven doors are opened for cooling purposes. Oven doors shall be vertically split, side opening type with heat resistant viewing windows. A handle shall be provided on each door or one handle to open and close the doors simultaneously. Type I ovens shall be equipped with stainless steel legs with leveling devices. Type I ovens shall be equipped for operation and venting under a canopy. The exterior dimensions of the type I oven shall not exceed 40 inches wide by 38-1/2 inches deep. The type I ovens shall have the capability of being stacked.

FSC 7310

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

2.1.2 Fuel system. The oven shall be designed to burn natural gas. The oven shall be rated at 49,000 BTU/hour minimum. The oven shall be equipped with a gas pressure regulator and gas burner(s) with automatic gas ignition system. The oven burner shall be equipped with a constant burning pilot or electrically ignited pilot or direct spark ignition. An ANSI approved quick disconnect (socket and plug) and a 5-foot minimum flexible metal connector consisting of a male pipe thread fitting on one end and union with female thread on the opposite end shall be supplied with each oven.

2.1.3 Thermostat. The oven shall be equipped with a thermostat to automatically control oven temperature from 200°F to 475°F minimum.

2.1.4 Electrical characteristics. The electrical controls, lights, switches, and blower shall operate on a nominal 120 volt, 60 Hertz, single phase power source. Each oven shall be equipped with a 6-foot minimum UL approved 3-wire power supply cord with NEMA 5-15P plug. The oven blower shall be rated at not more than 3/4 horsepower.

2.2 Type II. The type II oven shall consist of two type I ovens stacked and secured, with each oven compartment operating independently of the other. Type II ovens shall come equipped with only one set of stainless steel legs with leveling devices.

2.3 Standards compliance. The ovens shall comply with American National Standard Institute (ANSI) Z83.12 and the National Sanitation Foundation Standard No. 4.

2.4 Data name plate (Government unique requirement (see 5.4)). The oven shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the oven by rivets, screws, or welding in such a manner as to meet the applicable NSF requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (See 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the oven.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace, except for those additional requirements/characteristics specified herein. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export, as specified (see 5.2).

4.2 Commercial packaging and packing. Each oven shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each oven shall be disassembled to the extent determined by the supplier to protect the parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be identified. The oven parts shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration, and physical damage during shipping and storage. Disassembled parts may be packaged in a class weather-resistant fiberboard box conforming to PPP-B-636 or placed within the oven or directly into the shipping container with the oven.

4.3.2 Export packing. One oven shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, grade B of PPP-B-621. The contents of the box shall be cushioned, blocked, and braced to prevent movement while the box is in transit. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

4.3.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with MIL-STD-147.

4.4 Marking (commercial and export). Marking of unit pack, shipping container and unit load shall be in accordance with MIL-STD-129, or ASTM D 3951, as applicable.

5. NOTES

5.1 Intended use. The energy efficient baking and roasting gas convection ovens are for use in kitchen and bakeries where combined use and time savings are required.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:39Z
Check the source to verify that this is the current version before use.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Type required (see 1.1).
c. Government approved manual number to be included on data name plate (see 2.4).
d. Selection of applicable packaging and packing required (see 4.1).
e. When palletization of shipping containers is required (see 4.3.3).

5.3 Sources of documents.

5.3.1 Sources for nongovernment association documents.

NEMA 5-15P plug, is available from:

National Electrical Manufacturers Association (NEMA)
155 East 44th Street
New York, NY 10017

ANSI Z83.12 - American National Standard for Commercial Gas Baking and Roasting Ovens, is available from:

American National Standards Institute (ANSI)
1430 Broadway
New York, NY 10018

or

The American Gas Association, Inc.
8501 East Pleasant Valley Road
Cleveland, OH 44131

NSF Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:39Z
Check the source to verify that this is the currentversion before use.

5.3.2 Sources of governmental documents.

Military documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD, TS
Navy - MC, SA
Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0720

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:39Z
Check the source to verify that this is the current version before use.