A-A-50140
December 16, 1987

COMMERCIAL ITEM DESCRIPTION

MIXER, FLUID, ELECTRIC

The General Services Administration has authorized the use of this commercial item description in preference to MIL-M-40600.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers mixers of the following types:

Type	
I	Single-spindle mixer with one cup
II	Three-spindle mixer with three cups
III	Five-spindle mixer with five cups

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The mixers shall be furnished with a one-quart, stainless steel, mixing cup for each mixing spindle on the machine. The mixer shall be furnished with a support stand consisting of a metal base and upright section. The upright section shall be equipped with a metal support bracket for holding the mixing cup(s) in place while in operation. The mixers shall be turned on and off by placement and removal of the mixing cup. The mixers shall provide for various speeds using either a variable speed motor or interchangeable spindle agitators on a single speed motor. Mixers with variable speed motors shall be capable of speed adjustment by a manual switch. Agitators shall be furnished with the mixers. The mixers shall operate smoothly and without excessive vibrations and noise.

2.2 Electrical. Types I and II mixers (Single and triple spindles), shall be supplied with a 6-foot electric cord with a NEMA 5-15P plug assembled at one end of the cord. Unless otherwise specified, (see 5.2), types I and II shall operate on 120 AC or DC volts, as specified. Unless otherwise specified (see 5.2), the type III mixer (five-spindle), shall operate on 220 AC volts, 50 hertz, single phase power source.

2.3 Standards compliance. Mixers shall comply with the requirements of UL Standard No. 73 and NSF Standard No. C-2.

FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

2.4 Identification plate. In addition to the identification marking required by UL 73, the identification plate shall include the contract number and national stock number.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. When specific quality assurance provisions are specified for any commercial characteristic, the contractor shall furnish data resulting from inspection conducted in accordance with the specific quality assurance provisions. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export, as specified (see 5.2).

4.2 Commercial.

4.2.1 Commercial packaging and packing. Each mixer shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Export.

4.3.1 Export packaging. Each mixer shall be packaged in a snug-fitting fiberboard box constructed and closed using method II in accordance with style RSC, class domestic of PPP-B-636. At the option of the contractor, cups may be packaged separately in a fiberboard box as specified above. Each mixer, cups and agitators shall be cleaned, preserved, cushioned, and immobilized to afford protection against corrosion, deterioration, and physical damage during shipment and storage.

4.3.2 Export packing. Twelve single-spindle mixers, 6 three-spindle mixers, or 6 five-spindle mixers of one description only, shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, type 2 load of PPP-B-621. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

4.4 Marking (commercial and export). Marking of unit pack and shipping container shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:39Z
Check the source to verify that this is the currentversion before use.

5. NOTES

5.1 Intended use. The fluid mixer is intended for use in preparing beverages at soda fountains.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Type of mixer required (see 1.1).
c. Electrical requirements (see 2.2).
d. Type of packaging and packing required (see 4.1).

5.3 Sources for nongovernment association documents.

NEMA 5-15P - National Electrical Manufacturers Association, 155 East 44th Street, New York, NY 10017.

NSF Standard No. C-2 - National Sanitation Foundation, 3475 Plymouth Road, P. O. Box 1468, Ann Arbor, MI 48106.

UL Standard No. 73 - Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062

ASTM D 3951 - Standard Practice for Commercial Packaging (Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

5.4 Supersession data. The types of fluid mixers covered by this commercial item description replace the items covered by MIL-M-40600 as indicated below.

CID A-A-50140		MIL-M-40600	
Type		Type	Style
I	Single-spindle mixer	1	1
II	Three-spindle mixer	3	1
III	Five-spindle mixer	5	1

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 50

Review activities

Army - MD, TS
Navy - SA, SH, MC

User activity

Army - CE

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0806

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.