MILITARY SPECIFICATION

CONNECTOR SETS, ELECTRICAL, HERMETICALLY SEALED, SUBMARINE

This amendment forms a part of Military Specification MIL-C-22249A(SHIPS), dated 19 April 1968, and is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

Page 1

2.1: Delete reference to Federal Specifications "QQ-N-290" and "QQ-S-634" and Military specification "MIL-P-19833", and add the following specifications:

SPECIFICATIONS

FEDERAL
"L-P-410 - Plastic, Polyamide (Nylon), Rigid: Rods, Tubes, Flats, Molded and Cast Parts."

MILITARY
"MIL-M-14 - Molding Plastics and Molded Plastic Parts, Thermosetting."

2.1: Military specification MIL-G-45204, delete "Electric" and substitute "Electrically".

2.1: Under Military standards, delete reference to "MIL-STD-167" and substitute the following:

"MIL-STD-167-1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited)."

Page 2

2.2: Under UNIFORM CLASSIFICATION COMMITTEE, delete "202 Union Station, 516 West Jackson Blvd." and substitute "Room 1106, 222 South Riverside Plaza".

2.2: Add the following:

"SOCIETY OF AUTOMOTIVE ENGINEERS
AMS 5764 - Steel Bars, Forgings, Extrusions and Rings, Corrosion-Resistant 22CR-12.5NI-5.0.

(Application for copies should be addressed to the Society of Automotive Engineers, 485 Lexington Avenue, New York, New York 10017.)"

3.2, line 3: Delete "6.5" and substitute "6.4".

3.3.6 and 3.3.7: In title, delete "body" and in line 1, delete "bodies".

3.3.8: Delete and substitute:

"3.3.8 Header insert body. Header insert bodies shall be fabricated from corrosion-resisting steel in accordance with class 316L of QQ-S-763 or ARMCO 22-13-5 in accordance with AMS 5764."

1/ THE MARGINS OF THIS AMENDMENT ARE MARKED "#" TO INDICATE WHERE CHANGES (ADDITIONS, MODIFICATIONS, CORRECTIONS, DELETIONS) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS WAS DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:34Z
Check the source to verify that this is the current version before use.

Page 2 (cont'd)

3.3.9, line 5: Delete "0.0005" and substitute "0.00005".

3.3.10, line 2: Delete "herein" and substitute "in 4.7".

Page 3

3.3.13, line 2: Delete "DG1-30 of MIL-P-19833" and substitute "GDI-30 of MIL-M-14".

3.3.17 and 3.3.21, line 2: After "steel" add "in accordance with QQ-S-763".

3.3.25, line 2: Delete "IIb" and substitute "2b".

3.3.26, title: Delete "lock" and substitute "locking".

3.3.27 and 3.3.28: After "steel" add "in accordance with QQ-S-763".

3.4, line 2: Delete "seets" and substitute "sheets".

3.4.1(b): Delete "rounded" and substitute "broken".

Page 4

3.4.1(f): Add as last sentence: "The first and last partial thread of both internal and external threads shall have the initial portions removed for an extent of 110 to 120 degrees."

3.4.1(i): Add as last sentence: "Non-machined surfaces shall have a 250 rms maximum finish."

3.4.2.2, line 5: Delete "prod" and substitute "probe".

3.4.2.3, line 2: After "with", add "type C of".

3.4.3: In line 3, delete "gaskets", and in line 6, delete "seals".

3.4.3.1: In line 1, delete "to" and substitute "of"; in line 2, delete "in the plug" and "in", and in line 3, delete "the header".

3.4.4.1, line 2: Delete "0.031" and substitute "0.070".

Page 5

3.6.5: Add as first sentence: "Connectors shall be in accordance with the requirements of type I of MIL-STD-167-1, and in line 2, delete "4.7.4" and substitute "4.7.5".

3.6.6: Add as first sentence: "Mated connectors and unmated headers shall be in accordance with the type A, grade A, class I, lightweight requirements of MIL-S-901."

Page 6

3.8, line 6: Add "being" after the word "as".

Page 9

4.7.5: In line 2, delete "MIL-STD-167" and substitute "MIL-STD-167-1".

4.7.6: In line 2, delete "grade B, class II" and substitute "type A, grade A, Class I", and in line 7, delete "than" and substitute "that".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:34Z
Check the source to verify that this is the current version before use.

Page 9 (cont'd)

5.1.1.1: Add as last sentence: "Where plug to header seals are also used as protective cover seals, one additional seal shall be provided and separately packaged for use as a plug to header seal."

Page 10

5.1.1.1.2, line 2: Delete "rear" and substitute "cable", and delete "cable" after "plug".

Preparing activity:
Navy - SH
(Project 5935-N917)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-603-112/3057

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:34Z
Check the source to verify that this is the current version before use.