MIL-C-63521 (AR)
AMENDMENT 7
18 AUGUST 1987
SUPERSEDING
AMENDMENT 6
18 May 1986

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, FOR
CARTRIDGE 105mm, APFSDS-T, M833

This Amendment forms a part of Military Specification MIL-C-63521 (AR), dated 14 June 1982, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Title: Delete in its entirety and substitute: "CONTAINER, AMMUNITION, METAL, FOR CARTRIDGE, 105MM, TANK AMMUNITION,"

* 1.1, Delete "Kinetic energy tank ammunition" and substitute "105mm tank ammunition, M456A2, M735, M774, M833."

* 2.1.1 Specifications and standards. Under STANDARDS MILITARY, delete "1188 - Commericla packaging of suplies and equipment."

PAGE 2

2.1.2 Other Government documents, drawings, and publications. Under drawings, add:

"9378187 - Container, Ammo, Metal for Ctg. 105mm, APFSDS-T; M735 or M774"

* "12551938 - Container, Ammo, Metal for Ctg, 105mm HEAT-T-MP: M456A2."

* 2.2 Other publications. UNDER AMERICAN SOCIETY FOR TESTING MATERIALS, add

"ASTM-D3951 - Commercial packaging, standard practice for."

PAGE 3

* 3.2 Containers. First sentence, delete: "9345252" and substitute: "9345252, 9378187 or 12551938"

AMSC N/A FSC 8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

PAGE 7

Table I, Spring, unpainted: Deleted in its entirety.

PAGE 10

* 4.4.2.2, Spring: Next higher assembly block, add "9344044"
Delete Major defect 103 in its entirety.

NOTES: Delete Note (b) in its entirety.

PAGE 11

4.4.2.3 Support, shaft: Delete Major defects 105, 107, and 108 in their entireties.

PAGE 13

4.4.2.5 Handle:

Delete Major defects 103 and 104 in their entireties.

Delete Major defect 106 in its entirety and substitute:

"106 Distance from center of shaft hexhole to outer edge of tabs (Dim. B) 0.40% 3.2 Gage".

Delete Minor defect 201 in its entirety.

PAGE 16

4.4.2.8 Retainer, washer:

Delete Major defect 103 in its entirety and substitute:

"103 Material certification (a) 3.2 Certification".

Delete Major defect 104 in its entirety.

Add Note (a) as follows:

"(a) With each lot of material submitted".

PAGE 17

4.4.2.9 Cover:

Delete Major defect 105 in its entirety and substitute:

"105 Depth from rim to inside of cover base 0.40% 3.2 Gage".

Major defect 107: Delete "rib" and substitute "rim".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

PAGE 22

4.4.2.14, Rim: Delete in its entirety and substitute new Page 22, included.

PAGE 23

4.4.2.15, Ring: Delete in its entirety and substitute new Page 23, included.

PAGE 26

4.4.2.18 Plug, stacking:

Delete Major defects 101, 102, 103, and 104 in their entireties and substitute:

"101	Length of plug	0.40%	3.2	Gage
102	Width of plug	0.40%	3.2	Gage
103	Length of indexing projection	0.40%	3.2	Gage
104	Width of indexing projection	0.40%	3.2	Gage".

PAGE 27

4.4.2.19 Body Weldment (body assembly), prior to painting:

Major defect 101: Delete Paragraph Reference "4.5.8.2" and substitute "4.5.8.1".

Major defect 102: Delete "Weld of rings to body" and substitute "Weld of rim to body".

PAGE 28

4.4.2.20 Container, ammo, metal:

Add new major defect 104 as follows:

"104 Screw torque test (a) 0.40% 3.2 4.5.10.

Add Note (a) as follows:

"(a) The screw torque test shall be performed after the air pressure test has been performed and the screw has been reassembled."

PAGE 29

4.4.2.21 Support, sabot: Delete in its entirety and substitute new page 29, included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Rim		9344028
			NEXT HIGHER ASSEMBLY
			9344032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth from edge of rim to inside flat		0.40%	3.2	Gage
102	Length of larger slot on side of rim		0.40%	3.2	Gage
103	Length of smaller slot on side of rim		0.40%	3.2	Gage
104	Location of larger slot from inside flat		0.40%	3.2	Gage
105	Location of smaller slot from inside flat		0.40%	3.2	Gage
106	Location of bayonet slot, 4 places		0.40%	3.2	Gage
107	Inside dimension across flats, 2 places (Dim. A)		0.40%	3.2	Gage
108	Inside dimension across corner, 2 places (Dim. D)		0.40%	3.2	Gage
109	Width of larger slot		0.40%	3.2	Gage
110	Width of smaller slot		0.40%	3.2	Gage
111	Inside diameter of rim		0.40%	3.2	Gage
Minor					
201	Drainage hole missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9344029
4.4.2.15	Ring				NEXT HIGHER ASSEMBLY 9344032
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance from edge of ring to outside flat		0.40%	3.2	Gage
102	Length of larger slot on side of ring		0.40%	3.2	Gage
103	Length of smaller slot on side of ring		0.40%	3.2	Gage
104	Location of smaller slot from inside flat		0.40%	3.2	Gage
105	Location of larger slot from inside flat		0.40%	3.2	Gage
106	Inside dimensions across flats, 2 places (Dim. A)		0.40%	3.2	Gage
107	Width of larger slot		0.40%	3.2	Gage
108	Width of smaller slot		0.40%	3.2	Gage
109	Inside diameter of ring		0.40%	3.2	Gage
Minor					
201	Drainage hole missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)
AMENDMENT 7

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.21	Support Assembly		9362624
			NEXT HIGHER ASSEMBLY
			9345252

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		1.0%	3.2	Gage
202	Length		1.0%	3.2	Gage
203	Presence of chamfer		1.0%	3.2	Visual
204	Large inside diameter		1.0%	3.2	Gage
205	Small inside diameter		1.0%	3.2	Gage
206	Material certification	(a)		3.2	Certification
207	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:
(a) With each lot of material submitted

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

PAGE 30

4.4.2.22 Spacer. Under next higher assembly: Delete "9345284" and substitute "9345252".

PAGE 32

4.4.2.24 Cushion. Under next higher assembly: Add "9332584".

PAGE 33

4.4.2.25 Cushion assembly. Under next higher assembly: Add "9345252".

PAGE 34

4.4.2.26 Cushion. Under next higher assembly: Delete "9332584" and substitute "9345252".

PAGE 35

4.4.2.27 Support: Delete in its entirety.

PAGE 36

4.4.2.28:

Lift collar assembly. Under drawing number: Delete "9345282" and substitute "9378280".

Delete Minor Defect 201 in its entirety.

Minor Defect 202, delete in its entirety and substitute:

"202 Strap missing or improper 1.0% 3.2 Visual".

PAGE 37

Add new paragraphs: 4.4.2.30, Page 37A (included)
4.4.2.31, Page 37B (included)
4.4.2.32, Page 37C (included)
* 4.4.2.33, Page 37D (included)
* 4.4.2.34, Page 37E (included)
* 4.4.2.35, Page 37F (included)

PAGE 39

4.5.5 Deflection load of spring: Delete in its entirety.

4.5.8.1 Air pressure of unpainted cover assembly and unpainted body assembly. First sentence: Delete "core assemblies" and substitute "cover assemblies."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.30	Spacer (M735 and M774)		9378189
			NEXT HIGHER ASSEMBLY
			9378187

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

(a) With each lot of material submitted

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil/ (37 A) Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)
AMENDMENT 7

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.31	Support Assembly, Alt. (M735 and M774)				9378188
					NEXT HIGHER ASSEMBLY 9378187
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		1.0%	3.2	Gage
202	Length		1.0%	3.2	Gage
203	Presence of chamfer		1.0%	3.2	Visual
204	Large inside diameter		1.0%	3.2	Gage
205	Small inside diameter		1.0%	3.2	Gage
206	Material certification	(a)		3.2	Certification
207	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:
(a) With each lot of material submitted

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.32	Container, Ammo, Metal, for Ctg 105mm, APFSDS-T; M735 or M774		9378187
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any component missing or damaged		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.33	Adapter (M456A2)		12551936
			NEXT HIGHER ASSEMBLY 12551938

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Outside diameter		1.0%	3.2	Gage
203	Thickness		1.0%	3.2	Gage
204	Size of recess		1.0%	3.2	Gage
205	Poor workmanship		1.0%	3.7	Visual

NOTES:

(a) With each lot of material submitted.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.34	Support, Nose, Plastic (M456A2)	1	1	12551937
				NEXT HIGHER ASSEMBLY: 12551938

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Distance from end to inside shoulder		1.0%	3.2	Gage
203	Presence of 30° chamfer inside end		1.0%	3.2	Gage
204	Large inside diameter		1.0%	3.2	Gage
205	Large diameter on front protusion		1.0%	3.2	Gage
206	Small diameter on front protusion		1.0%	3.2	Gage
207	Poor workmanship		1.0%	3.2	Visual

NOTES:
(a) With each lot of material submitted

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.35	Container, Ammo, Metal, For Ctg, 105mm, HEAT-T-MP M456A2	1 OF 1	12551938
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Any component missing or damaged		0.40%	3.2	Visual
Minor 201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

4.5.8.1.1 Alternate air pressure test for unpainted cover assembly and upainted body assembly (Water Method). Add new paragraph 4.5.8.1.1 as follows:

"4.5.8.1.1 Alternate air pressure test for unpainted cover assembly and unpainted body assembly (Water Method). Subject the cover assembly and container body while under water, to the specified internal air pressure for the test time specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket. For the body assembly, apply the pressure when the body assembly is assembled to a master cover (or equivalent) and gasket.

The master cover and master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. No bubbles (other than surface bubbles) shall be permitted. A cover assembly or body assembly which does not meet the requirements shall be classed defective."

PAGE 40

4.5.10 Screw torque test. Add new paragraph 4.5.10 as follows:

"4.5.10 Screw torque test. The minimum applicable torque shall be applied to the screw. Any evidence of motion of the screw before reaching the minimum acceptable torque shall be cause for rejection of the container assembly being tested. Any container assembly which fails the screw torque test may be reworked and returned to the lot after passing the screw torque test."

Page 41

* 5.2 Packing. Delete "paragraph 2.3.1 of MIL-STD-1188" and substitute "ASTM D3951."

* 5.3 Marking. First sentence: Delete in its entirety and substitute "shipping marking, shall comply with the following instructions."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A748)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.