MILITARY SPECIFICATION
EJECTOR, PARACHUTE, CARTRIDGE ACTUATED: XM7
METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Ejector, Parachute, Cartridge Actuated: XM7 Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with Ballistically Deployed Troop Chest Reserve-Type Parachute System.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification For

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber O-Rings

DRAWINGS

Munitions Command

F10551542	- Ejector, Parachute, Cartridge Actuated, XM7 Metal Parts Assembly
C9257363	- Carton, Packing, Ammunition, Fiber, for Ejector, Parachute Cartridge Actuated, XM7
D9257364	- Box, Packing, Ammunition for Ejector, Parachute, Cartridge Actuated, XM7
IEL-10551542	- Inspection Equipment List for Ejector, Parachute, Cartridge Actuated, XM7 Metal Parts Assembly

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the currentversion before use.

2.1 (Cont'd)

(Copies of specifications, standards and drawings required by supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, N.Y. 10018).

3. REQUIREMENTS

3.1 General.-Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings, and in the referenced specifications.

3.2 Material.-The contractor shall be responsible for selecting from the classifications list contained in the raw material specification, the surface and physical condition of the raw material intended for use in manufacture.

3.3 Mechanical properties.-Mechanical properties required by the drawing shall be uniform throughout the part within specified tolerances. Mechanical properties for all alloy steel parts shall be achieved by quenching and tempering.

3.4 Hydrostatic pressure.-The outside tube shall withstand a constant internal pressure of 5000 pounds per square inch (psi), minimum for 15 seconds minimum, without application of any external load and shall show no evidence of leakage or mechanical failure (see 6.2).

3.5 Firing Pin Release.-The firing pin of the metal parts assembly, shall release from the cocked position when the application of an axial load of 15 to 30 pounds has withdrawn the sear pin.

3.6 Metal parts assembly.-Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled hand tight.

3.7 Protective finish.-Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of contoure configuration.

Source: https://assist.dla.mil -- Downloaded: 20260-22T20:36Z
Check the source to verify that this is the current version before use.

3.8 Workmanship.-The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.8.1 Metal defects.-All components shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.8.2 Burr.-No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.8.3 Foreign matter.-No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference is made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.-Inspection shall be in accordance with MIL-A-2550 except as specified herein.

4.2 First article sample.

4.2.1 Initial production sample.-At the beginning of regular production, a sample shall be submitted in accordance with contract requirements. The sample shall consist of 5 metal parts assemblies and 10 sets of unassembled components for visual and dimensional examination and tests. The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.-After inspection and provisional acceptance at source, the samples shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.1.2 Initial production sample failure.-Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.-Unless otherwise specified by the contracting officer, formation of lots and presentation of lots shall be in accordance with the "Submission of Product", provisions of MIL-STD-105.

4.3.1.2 Size of lot.-For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 5000 ejectors maximum, provided the homogeneity requirements of inspection lots have been retained.

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans and associated criteria in Table I and II. For an individual defect (single characteristic), the criteria in Table I shall be used. For total defects within a major or minor group, the criteria in Table II shall be used. All nonconforming material shall be rejected. The roughness comparison specimens prescribed in ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

Table I

Lot Size		Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination				
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

Table II

Total Allowable Defects per Sample Size

Sample Sizes for Major Defects	110	150	225	300
No. of Defects in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	6	8	11	14

Sample Sizes for Minor Defects	110	150	225	300
No. of Defects in Class				
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Sear, Dwg. C10551446 covering a detail of Dwg. F10551542

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Small outside diameter	Gage
102. Intermediate outside diameter	Gage
103. Thickness through flat at top of angle	Gage
104. Thickness through flat at bottom of angle	Gage
105. Location of hole in small diameter	Gage
106. Surface finish on intermediate diameter and angle	Gage
107. Metal defective	Visual
108. Foreign matter	Visual
109. Burrs or sharp corners	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Total length	Gage
202. Large outside diameter	Gage
203. Spherical radius on large outside diameter	Gage
204. Thickness of large outside diameter	Gage
205. Length of intermediate outside diameter	Gage
206. Hole diameter	Gage
207. Hole chamfer or radius (both side)	Gage
208. Angle	Gage
209. Length from notched end to shoulder	Gage
210. Width from bottom of angle to shoulder	Gage
211. Incorrect radii	Gage
212. Surface finish, except as otherwise specified	Visual

4.3.2.2 Pin, Safety, Dwg. C10551454 covering a detail of Dwg. F10551542

CRITICAL

None defined

MAJOR	
101. Diameter of wire	Gage
102. Profile incorrect	Visual
103. Metal defective	Visual
104. Protective finish inadequate or defective	Visual
105. Burr, edges or sharp corners	Visual
106. Foreign matter	Visual
MINOR	
201. Diameter of head, outside	Gage
202. Length between head and center loop	Gage
203. Radius of center loop	Gage
204. Length between end and small loop	Gage
205. Radius of small loop	Gage
206. Length from chamfered end to unchamfered end	Gage
207. Height to unchamfered end	Gage
208. Angle of unchamfered end	Gage
209. Length between head and chamfered end	Gage
210. Diameter at top of chamfered end	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.3 Spring, Dwg. C10551450 covering a detail of Dwg. F10551542

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Inside diameter, max.	Gage
102. Spring rate	Gage
103. Solid length, max.	Gage
104. Metal defective	Visual
105. Foreign matter	Visual
MINOR	
201. Total coils	Visual
202. Active coils	Visual
203. Free length	Gage
204. Closed ends ground	Visual
205. Final protective finish inadequate or defective	Visual
206. Heating requirements	Certification
207. Direction of helix	Visual

4.3.2.4 Tube, Inside Dwg. D10551444 covering a detail of Dwg. F10551542

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter min.	Gage
102. Minor thread diameter	Gage
103. True position of pitch diameter to intermediate inside diameter	Gage
104. True position of short cavity diameter to intermediate inside of diameter	Gage
105. True position of intermediate diameter to large outside diameter	Gage
106. True position of long outside diameter to large outside diameter	Gage
107. Large outside diameter	Gage
108. Angle, large outside diameter to small outside diameter	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the currentversion before use.

4.3.2.4 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
109. Long length outside diameter	Gage
110. Intermediate inside diameter	Gage
111. Short cavity diameter	Gage
112. Surface finish on long outside diameter	Visual
MINOR	
201. Pitch diameter max.	Gage
202. Length of effective thread	Gage
203. Length to bottom of thread cavity	Gage
204. Length to bottom of short cavity	Gage
205. Length to bottom of intermediate cavity	Gage
206. Length of large outside diameter	Gage
207. Total length	Gage
208. Small inside diameter	Gage
209. Part number missing incorrect or illegible	Visual
210. Radius and chamfers incorrect or missing	Visual
211. Final protective finish inadequate or defective	Visual
212. Surface finish except as otherwise specified	Visual
213. Burr	Visual
214. Foreign matter	Visual

4.3.2.5 Pin, Firing Dwg. C10551448 covering a detail of dwg. F10551542

CRITICAL

None defined

MAJOR	
101. Body diameter	Gage
102. Large outside diameter	Gage
103. Concentricity of body diameter to large outside diameter	Gage
104. Concentricity of tip to large outside diameter	Gage
105. Length of tip	Gage
106. Thickness of drilled shoulder	Gage
107. Thickness through flat at bottom of angle	Gage
108. Thickness through flat at top of angle	Gage
109. Tip contour spherical with radius tangent to dia	Gage
110. Surface finish on body and angle	Visual
111. Metal defective	Visual
112. Foreign matter	Visual
113. Burrs or sharp corners	Visual

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:36Z
Check the source to verify that this is the currentversion before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Total length	Gage
202. Tip diameter	Gage
203. Hole diameter (4 holes)	Gage
204. Hole location (4 holes)	Gage
205. Length from notched end to shoulder	Gage
206. Angle	Gage
207. Width from bottom of angle to shoulder	Gage
208. Incorrect radii	Gage
209. Surface finish, except as otherwise specified	Visual
210. Final protective finish inadequate or defective	Visual

4.3.2.6 Washer, Dwg. B10551453 covering a detail of Dwg. F10551542

CRITICAL

None defined

MAJOR	
101. True position of inside diameter to outside diameter	Gage
102. Outside diameter	Gage
103. Inside diameter	Gage
104. Thickness	Gage
105. Burrs or sharp edges	Visual
106. Metal defective	Visual
107. Foreign matter	Visual
108. Surface finish incorrect	Visual
MINRO	
201. Final protective finish inadequate or defective	Visual

4.3.2.7 Bar, T, Dwg. B10551451 covering a detail of Dwg. F10551542

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Pitch diameter, max.	Gage
102. Minor thread diameter, max.	Gage
103. Concentricity of u'cut diameter to pitch dia	Gage
104. Perpendicularity bottom of threaded hole to pitch diameter	Gage
105. Metal defective	Visual
106. Foreign matter	Visual
MINOR	
201. Pitch diameter, min.	Gage
202. Location of threaded hole	Gage
203. Depth of threaded hole	Gage
204. Width of u'cut hole	Gage
205. Total length	Gage
206. Width	Gage
207. Thickness	Gage
208. Radii incorrect	Gage
209. Profile angle	Gage
210. Location of profile angle	Gage
211. Diameter of u'cut groove	Gage
212. Chamfers incorrect	Gage
213. Surface finish of u'cut groove	Visual
214. Final protective finish inadequate	Visual
215. Part number missing incorrect or illegible	Visual

4.3.2.8 Tube, Outside, Dwg. 10551443 covering a detail of Dwg. F10551542

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter, min.	Gage
102. Major thread diameter	Gage
103. True position of pitch diameter to large inside dia	Gage
104. True position of large inside dia to small inside diameter	Gage
105. Small inside diameter	Gage
106. Large inside diameter	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
107. Wall thickness	Gage
108. Diameter of "o" ring groove	Gage
109. Outside diameter (Large)	Gage
110. Concentricity of "o" ring groove to small inside diameter	Gage
111. Width of "o" ring groove	
112. Metal defect	Visual
113. Burrs or sharp corners	Visual
114. Foreign matter	Visual
115. Surface finish of groove	Visual
MINOR	
201. Pitch diameter max.	Gage
202. Length of threads	Gage
203. Length of large outside diameter	Gage
204. Angle on beginning of threads	Gage
205. Length of small inside diameter	Gage
206. Angle of small inside diameter	Gage
207. Total length	Gage
208. Diameter, outside, small	Gage
209. Angle on large outside diameter	Gage
210. Final protective finish inadequate or defective	Visual
211. Part number missing, incorrect or illegible	Visual

4.3.2.9 Head, Dwg. D10551449 covering a detail of Dwg. F10551542

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter	Gage
102. Major thread diameter	Gage
103. True position of pitch diameter to large outside diameter	Gage
104. True position of pitch diameter to small inside diameter	Gage
105. True position of large outside diameter to small inside diameter	Gage
106. True position of intermediate inside diameter to small inside diameter	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
107. Large outside diameter, body	Gage
108. Small inside diameter	Gage
109. Intermediate, inside diameter	Gage
110. Inside boss diameter	Gage
111. Length to bottom of boss	Gage
112. Length of boss	Gage
113. Length to intermediate diameter cavity	Gage
114. Large inside diameter	Gage
115. Length across flats	Gage
116. Pin hole diameter	Gage
117. Location of pin holes	Gage
118. Large outside diameter on side with flats	Gage
119. Radius at both end of small bone	Gage
120. Large inside, depth min.	Gage
121. Large inside, diameter	Gage
122. Surface finished of inside diameters improper	Visual
123. Metal defects	Visual
MINOR	
201. Total length	Gage
202. Length to end of thread	Gage
203. Length to beginning of thread	Gage
204. Diameter, over flats	Gage
205. Location of flats	Gage
206. Radius, missing or improper	Gage
207. Burr or sharp corners	Visual
208. Surface finish inadequate	Visual
209. Foreign matter	Visual
210. Final protective finish	Visual

4.3.2.10 Buffer, Dwg. B10551452, covering a detail of Dwg. F10551542

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.10 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Total length	Gage
202. Width	Gage
203. Height	Gage
204. Radii	Gage

4.3.2.11 Tag, Dwg. B10551455 covering a detail of Dwg. F10551542

CRITICAL

None defined

MAJOR

None defined

MINOR	
201. Total length	Gage
202. Width	Gage
203. Marking missing, incorrect or illegible	Visual

4.3.2.12 Sear Assembly, Dwg. C10551445 covering a detail of Dwg. F10551542

CRITICAL

None defined

MAJOR

None defined

MINOR	
201. Inside diameter of loop	Gage
202. Length, sear end to sleeve	Gage
203. Cable, diameter	Gage
204. Sleeve, not crimped to cable	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.13 Metal Parts Assembly, Dwg. 10551542, less all components except Washer 10551453, Pin Firing 10551448

Defect	Method of Inspection
CRITICAL	
1. Protrusion of firing pin	Gage
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr	Visual
104. Foreign matter	Visual
MINOR	
None defined	

4.3.2.14 Metal Parts Assembly Dwg. 10551542

CRITICAL	
1. Any part missing	Visual
MAJOR	
101. Adherence of buffer to T bar	Visual
102. Lable, missing, incorrect or illegible	Visual
103. Safety pin and tag not in place	Visual
104. Metal defective	Visual
105. Marking missing, incorrect or illegible	Visual
106. Burr of sharp corner	Visual
107. Foreign matter	Visual

4.3.2.15 Packing in carton, Ammunition, Drawing C9257363

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Cut or damaged	Visual
203. Marking, missing, incorrect or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2.16 Packing in Wooden Box, Drawing C9257364

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Visual/Manual
203. Strapping missing, loose, broken or improperly assembled	Visual/Manual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual

4.3.3 Inspection testing.-The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness.-Fifty units from each heat treated lot of components shall be tested for compliance with the values noted on the applicable drawing. Failure of any unit to comply with drawing requirements shall be cause for rejection of the lot.

4.3.3.2 Hydrostatic pressure.-Each outside tube shall be subjected to a hydrostatic pressure test. Failure of any tube to comply with the requirements of 3.4 shall be cause for rejection of the tube.

4.3.3.3 Protective finish.-The number of units for protective finish tests shall be in accordance with the applicable MIL-Standard listed on the drawing. Failure of any sample to comply shall be cause for rejection of the lot.

4.3.3.4 Firing pin release.-Each partial assembly consisting of the following parts: Head 10551449, Sear Assembly 10551445, "o" ring MS29513-005, spring 10551450, firing pin 10551448 shall be subjected to the firing pin release test. Failure of any partial assembly to comply with the requirement of 3.5 shall be cause for rejection of the subassembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.4 Inspection equipment.-The examination and tests shall be made using equipment listed on IEL-10551542.

4.4. Test methods and procedures.

4.4.1 Hardness.-Prior to the application of protective finish, a hardness testing machine shall be used to determine the hardness values specified on the detail drawings.

4.4.2 Protective finish.-Test procedures for protective finish shall be in accordance with the MIL-Standard referenced on the component drawing.

4.4.3 Hydrostatic pressure.-Prior to the application of protective finish the tube and head subassembly shall be mounted in a device and subjected to an internal hydrostatic pressure in accordance with the requirements of 3.4. The testing device used shall internally seal the head and tubes at the prescribed seal surfaces without applying any axial lead other than that applied by the liquid pressure.

4.4.4 Firing pin release.-The subassembly shall be secured in a fixture and subjected to a pull applied to the sear pin in a longitudinal direction in conjunction with the fixture which registers the amount of pulls.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Level A.-Packing and marking shall be in accordance with Drawings C9257363 and C9257364.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number and date of this specification.

6.2 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1377-A491

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-J4000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.