MILITARY SPECIFICATION

FUZE, DEMOLITION KIT, M1134A3 WITH DETONATORS, PARTS FOR

This Specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing for one type of fuze designated as Fuze, Demolition Kit, M1134A3.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-I-13857	-	Impregnation of Metal Castings.
MIL-D-46253		Detonator,Electric T20E1, Parts for Loading, Assembling, and Packing.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-454	-	Standard General Requirements for Electronic Equipment
MIL-STD-1169	-	Packaging, Packing, and Marking for Shipment of Inert Ammunition Components.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

8799682	-	Carton, Packing, Ammunition for Fuze, Demolition Kit, M1134A2.
8799683	-	Container, Fiberboard, Ammunition for Fuze, Demolition Kit, M1134A3.
12597841	-	Fuze, Demolition Kit, M1134A3.

(Copies of specifications, standards, handbooks, drawings, publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Fuze assembly. The fuze assembly shall comply with all requirements specified on drawing (dwg.) 12597841, all associated drawings and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

3.3 Electrical resistance (continuity).

3.3.1 Unarmed position. The electrical resistance, between the external connector pins and the arming pin assembly, (fully inserted into the complete fuze) shall be an open circuit when measured as specified in 4.5.2.

3.3.2 Armed position. To indicate acceptable continuity, the electrical resistance between the pins of the filtered connector shall be no less than one (1) ohm nor greater than two and one half (2.5) ohms when the arming switch pin is sufficiently withdrawn to arm the fuze. The test shall be performed as specified in 4.5.2.

3.4 Non-arming and arming test. The testing shall be performed prior to insertion of the shear pin, as specified in 4.5.3.

3.5 Salt spray. The nut, arming switch pin, container assembly, and disconnect, arming switch pin shall be subjected to and pass the salt spray test when performed as specified in 4.5.4.

3.6 Torque test. The rotor spring shall meet the requirements on the applicable drawing when tested in accordance with 4.5.1.

3.7 First article. This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be clean and free of burrs, sharp edges, distortion, unblended radii, surface defects, chips, dirt, grease, rust, weld splatter, corrosion products, and other foreign material. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coatings shall be continuous except for a few slight scratches not exposing base metal. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provision of 4.3.2. The first article sample shall be in accordance with Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Nut				
	(Dwg. 9370100)				
	Examination for defects	5		3.2	4.4.2.1
	Salt spray	5-0-1		3.5	4.5.4
	Cover, lead cup				
	(Dwg. 9370097)				
	Examination for defects	5		3.2	4.4.2.2
	Cup, rotor, lead				
	(Dwg. 9370099)				
	Examination for defects	5		3.2	4.4.2.3
	Rotor				
	(Dwg. 12597844)				
	Examination for defects	5		3.2	4.4.2.4
	Cup, booster, lead				
	(Dwg. 9370114)				
	Examination for defects	5		3.2	4.4.2.5

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Container (Dwg. 12597849)				
	Examination for defects	5		3.2	4.4.2.6
	Container assembly (Dwg. 12597845)				
	Examination for defects	5		3.2	4.4.2.7
	Salt spray	5-0-1		3.5	4.5.4
	Tube center (Dwg. 12597847)				
	Examination for defects	5		3.2	4.4.2.8
	Guide, arming (Dwg. 12597852)				
	Examination for defects	5		3.2	4.4.2.9
	Disconnect, pin, arming switch (Dwg. 9370091)				
	Examination for defects	5		3.2	4.4.2.10
	Salt spray	5-0-1		3.5	4.5.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Center tube assembly (Dwg. 12597846)				
	Examination for defects	5		3.2	4.4.2.11
	Assembly, metal parts (prior to assembly of container and nut) (Dwg. 12597842)				
	Examination for defects	5		3.2	4.4.2.12
	Electrical continuity	5		3.3	4.5.2
	Assembly, metal parts (Dwg. 12597842)				
	Examination for defects	5		3.2	4.4.2.13
	Arming/Non-arming	5		3.4	4.5.3
	Ground plate (Dwg. 9370081)				
	Examination for defects	5		3.2	4.4.2.14

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Connector (Dwg. 9370080)				
	Examination for defects	5		3.2	4.4.2.15
	Pin, arming switch (Dwg. 12597848				
	Examination for defects	5		3.2	4.4.2.16
	Salt spray	5-0-1		3.5	4.5.4
	Spring, rotor (Dwg. 9370103)				
	Examination for defects	5		3.2	4.4.2.17
	Torque test	5		3.6	4.4.2.17
	Bushing, insulating (Dwg. 9370105)				
	Examination for defects	5		3.2	4.4.2.18
	Bar, stop (Dwg. 9370104)				
	Examination for defects	5		3.2	4.4.2.19
	Connector filtered (Dwg. 9370079)				
	Examination for defects	5		3.2	4.4.2.20

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lot shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Parts of only one lot number from one supplier.

b. T20E1 detonators from only one lot number from one supplier.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Nut				9370100
					NEXT HIGHER ASSEMBLY 12597842
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of either face with pitch diameter of thread		0.40%	3.2	Gage
102	Pitch diameter		0.40%	3.2	Gage
103	Minor diameter, min.		0.40%	3.2	Gage
104	Salt spray	5-0-1		3.5	4.5.4
Minor					
201	O.D.		0.65%	3.2	Gage
202	Location of wrench holes		0.65%	3.2	Gage
203	Diameter of wrench holes		0.65%	3.2	Gage
204	Thickness, min.		0.65%	3.2	Gage
205	Protective coating incomplete or inadequate		0.65%	3.2	Visual
206	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Cover, Lead Cup		9370097
			NEXT HIGHER ASSEMBLY 12597843

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Diameter, max.		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Cup, rotor, lead	1 OF 1	9370099
			NEXT HIGHER ASSEMBLY: 9370098

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	none defined				
Major					
101	Thickness through bottom		0.40%	3.2	Gage
102	Outside diameter, max.		0.40%	3.2	Gage
103	Length, max.		0.40%	3.2	Gage
Minor					
201	Diameter of flange		0.65%	3.2	Gage
202	Protective finish incomplete or inadequate		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Rotor				12597844
					NEXT HIGHER ASSEMBLY 12597843
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Contour		0.40%	3.2	Gage
102	Parallelism of external surfaces		0.40%	3.2	Gage
103	Location of all holes		0.40%	3.2	Gage
104	Diameter of lead assembly holes (2 places)		0.40%	3.2	Gage
105	Diameter of lead assembly counterbores, (2 places)		0.40%	3.2	Gage
106	Depth of lead assembly counterbore, min. (2 places)		0.40%	3.2	Gage
107	Diameter of pivot hole		0.40%	3.2	Gage
108	Diameter of arming pin hole		0.40%	3.2	Gage
109	Angle of arming pin hole		0.40%	3.2	Gage
110	Width of slots (2 places)		0.40%	3.2	Gage
111	Depth of slots (2 places)		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Protective finish incomplete or inadequate		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Cup, booster, lead	1 OF 1	9370114
			NEXT HIGHER ASSEMBLY: 9370113

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness through bottom		0.40%	3.2	Gage
102	Outside diameter, max.		0.40%	3.2	Gage
103	Length, max.		0.40%	3.2	Gage
Minor					
201	Diameter of flange		0.65%	3.2	Gage
202	Protective finish incomplete or inadequate		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Container		12597849
			NEXT HIGHER ASSEMBLY 12597846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
104	Perpendicularity of bottom surface to I.D.		0.40%	3.2	Gage
105	Diameter of large counterbore		0.40%	3.2	Gage
106	Diameter of small counterbore		0.40%	3.2	Gage
107	Diameter of counterbore, sidewall		0.40%	3.2	Gage
108	Depth of counterbore, sidewall		0.40%	3.2	Gage
109	Location of counterbore, sidewall		0.40%	3.2	Gage
110	Diameter, holes, bottom (2 places)		0.40%	3.2	Gage
111	Diameter counterbores bottom (2 places)		0.40%	3.2	Gage
112	Depth of counterbores bottom (2 places)		0.40%	3.2	Gage
113	Length of slot		0.40%	3.2	Gage
114	Width of slot		0.40%	3.2	Gage
115	Protective coating improper		0.40%	3.2	Gage
Minor					
201	Thickness, bottom		0.65%	3.2	Gage
202	Depth of holes, bottom (2 places)		0.65%	3.2	Gage
203	Diameter small hole, bottom		0.65%	3.2	Gage
204	Depth small hole, bottom		0.65%	3.2	Gage
205	Location small hole, bottom		0.65%	3.2	Gage
206	Diameter, thru hole, bottom		0.65%	3.2	Gage
207	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Container Assembly				12597845
					NEXT HIGHER ASSEMBLY 12597850
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Window, missing or defective		0.40%	3.2	Gage
102	Stake, window, missing or inadequate		0.40%	3.2	Gage
103	Adhesive, window, missing or improperly applied		0.40%	3.2	Gage
104	Salt spray	5-0-1		3.5	4.5.4
Minor					
201	Protective coating incomplete or inadequate		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.8	Tube, center				12597847
					NEXT HIGHER ASSEMBLY 12597846
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of center cavity		0.40%	3.2	Gage
102	Distance, base to forward face of front flange		0.40%	3.2	Gage
103	Diameter, rotor mounting surface		0.40%	3.2	Gage
104	Distance, base to forward edge, rotor mounting surface		0.40%	3.2	Gage
105	Diameter, container mounting surface (front)		0.40%	3.2	Gage
106	Diameter, "O" ring mounting surface (aft)		0.40%	3.2	Gage
107	Diameter, container mounting surface (aft)		0.40%	3.2	Gage
108	Distance, base to container mounting surface shoulder (aft)		0.40%	3.2	Gage
109	Surface finish "O" ring mounting surface		0.40%	3.2	Gage
110	Location, shear pin hole		0.40%	3.2	Gage
111	Location, locating pin hole		0.40%	3.2	Gage
112	Pitch diameter, set screw hole		0.40%	3.2	Gage
113	Minor diameter, set screw hole		0.40%	3.2	Gage
114	True position, set screw hole		0.40%	3.2	Gage
115	Location of holes, front flange		0.40%	3.2	Gage
116	Diameter of holes, front flange		0.40%	3.2	Gage
117	Depth of holes, front flange		0.40%	3.2	Gage
118	Pitch diameter, external thread		0.40%	3.2	Gage
119	Major dimeter, external thread, max.		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.8	Tube, center	2	2	12597847
				NEXT HIGHER ASSEMBLY 12597846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major	(Cont'd)				
120	Pitch diameter of switch mounting holes (4 places)		0.40%	3.2	Gage
121	Minor diameter of switch mounting holes (4 places)		0.40%	3.2	Gage
122	Depth diameter of switch mounting holes (4 places)		0.40%	3.2	Gage
123	Location, fuze positioning slot (external thread)		0.40%	3.2	Gage
124	Diameter arming guide hole, base		0.40%	3.2	Gage
125	Perpendicularity guide hole, base		0.40%	3.2	Gage
126	Pitch diameter, connector hole, base		0.40%	3.2	Gage
127	Minor diameter connector hole, base		0.40%	3.2	Gage
128	Impregnation test	1/			1/
Minor					
201	Outer diameter front flange		0.65%	3.2	Gage
202	Diameter of undercut forward of flange		0.65%	3.2	Gage
203	Distance, base to rear of rotor mounting surface		0.65%	3.2	Gage
204	Distance, base to container mounting surface (front)		0.65%	3.2	Gage
205	Distance, base to external thread		0.65%	3.2	Gage
206	Distance, base to edge of groove		0.65%	3.2	Gage
207	Width of groove		0.65%	3.2	Gage
208	Depth of groove		0.65%	3.2	Gage
209	Poor workmanship		1.0%	3.8	Visual

NOTES:
1/ Sampling, testing, and rejecting shall be in accordance with MIL-I-13857.

Source: https://assist.dla.mil -- 18 -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 12597852
4.4.2.9	Guide, arming				NEXT HIGHER ASSEMBLY 12597846
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Diameter		0.40%	3.2	Gage
103	Pitch diameter of thread		0.40%	3.2	Gage
104	Minor diameter of thread, min.		0.40%	3.2	Gage
105	Distance from arming pin surface to front of scarf groove, max.		0.40%	3.2	Gage
106	Distance from rear surface to rear of scarf groove, max.		0.40%	3.2	Gage
107	Radial distance from outside surface to top of scarf lip		0.40%	3.2	Gage
108	Concentricity of "O" ring groove with outside diameter		0.40%	3.2	Gage
109	Depth of groove on outside surface		0.40%	3.2	Gage
110	Distance from arming pin surface to forward end of slot on outside surface		0.40%	3.2	Gage
111	Distance from arming pin surface to rear end of slot on outside surface		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.09 (Cont'd)	Guide, arming				12597852
					NEXT HIGHER ASSEMBLY 12597846
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
114	Radial distance from outside surface to bottom of scarf groove		0.40%	3.2	Gage
Minor					
201	Length of thread		0.65%	3.2	Gage
202	Width of "O" ring groove		0.65%	3.2	Gage
203	Diameter of "O" ring groove		0.65%	3.2	Gage
204	Protective coating incomplete or inadequate		0.65%	3.2	Visual
205	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Disconnect, pin, arming switch	1 OF 2	9370091
			NEXT HIGHER ASSEMBLY 12597846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread, max.		0.40%	3.2	Gage
103	Diameter of shear pin hole, min.		0.40%	3.2	Gage
104	Diameter of non threaded length, max.		0.40%	3.2	Gage
105	Distance from threaded end to front of scarf groove, max.		0.40%	3.2	Gage
106	Total length		0.40%	3.2	Gage
107	Width of scarf groove, min.		0.40%	3.2	Gage
108	Radial distance from outside surface to top of scarf lip		0.40%	3.2	Gage
109	Concentricity of "O" ring groove with unthreaded diameter		0.40%	3.2	Gage
110	Distance from threaded end of scarf groove to shear pin hole		0.40%	3.2	Gage
111	Radial distance from outside surface to bottom of scarf groove		0.40%	3.2	Gage
112	Salt spray	5-0-1		3.5	4.5.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.10 (Cont'd.)	Disconnect, pin, arming switch		9370091
			NEXT HIGHER ASSEMBLY 12597846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Length of thread		0.65%	3.2	Gage
202	Distance from threaded end to front of "O" ring groove		0.65%	3.2	Gage
203	Distance from rear surface to rear of "O" ring groove		0.65%	3.2	Gage
204	Diameter of "O" ring groove		0.65%	3.2	Gage
205	Protective finish improper or inadequate		0.65%	3.2	Visual
206	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12597846
4.4.2.11	Center tube assembly				NEXT HIGHER ASSEMBLY 12597842
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Rotor not in full safe position		100%	3.2	Visual
Major					
101	Any component missing, loose or improperly assembled		0.40%	3.2	Visual/Manual
102	RTV sealant missing or improperly applied		0.40%	3.2	Visual
103	Thread sealing compound missing or improperly applied		0.40%	3.2	Visual
104	Locktite missing or improperly applied		0.40%	3.2	Visual
105	Set screw, arming guide, improperly positioned		0.40%	3.2	Visual
106	Detonator missing or improperly assembled (2)		0.40%	3.2	Visual
107	Bushing, insulating, missing (2)		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Assembly, metal parts, prior to assembly of container and nut	1 OF 1	12597842
			NEXT HIGHER ASSEMBLY: 12597841

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Rotor action not free		0.40%	3.2	Manual
102	Any component missing or improperly assembled		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.13	Assembly, Mpts	1	1	12597842
				NEXT HIGHER ASSEMBLY: 12597841

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Red warning stencil or decal missing or illegible		100%	3.2	Visual
2	Green safing indicator not visible		100%	3.3	Visual
Major					
101	Any part missing, improperly assembled, or damaged		0.40%	3.2	Visual
102	Nut more than hand tight		0.40%	3.2	Manual
Minor					
201	Protective finish incomplete or inadequate		0.65%	3.2	Visual
202	Dust cap(s) missing		0.40%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Ground plate				9370081
					NEXT HIGHER ASSEMBLY 9370079
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of holes		0.40%	3.2	Gage
102	Diameter of small end		0.40%	3.2	Gage
103	Plating missing or inadequate		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Connector				9370080
					NEXT HIGHER ASSEMBLY
					9370079
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of large thread		0.40%	3.2	Gage
102	Major diameter of large thread, max.		0.40%	3.2	Gage
103	Pitch diameter of small thread		0.40%	3.2	Gage
104	Major diameter of small thread, max.		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Pin, arming switch				12597848
					NEXT HIGHER ASSEMBLY
					12597846
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread, max.		0.40%	3.2	Gage
103	Large O.D.		0.40%	3.2	Gage
104	Surface finish, large O.D.		0.40%	3.2	Gage
105	Angle of taper, large O.D.		0.40%	3.2	Gage
106	Surface finish, taper, large O.D.		0.40%	3.2	Gage
107	Angle of taper of tip		0.40%	3.2	Gage
108	Length, tip		0.40%	3.2	Gage
109	Protective finish incomplete or inadequate		0.65%	3.2	Visual
110	Salt spray	5-0-1		3.5	4.5.4
Minor					
201	Length of thread		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Distance, tip to end or large O.D.		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	Spring, rotor		9370103
			NEXT HIGHER ASSEMBLY 12597846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Torque test	30-0-1		3.6	4.5.1
102	Inside diameter of coil, min.		0.40%	3.2	Gage
103	Outside diameter of coil, max.		0.40%	3.2	Gage
104	Length of legs		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Bushing, insulating				9370105
					NEXT HIGHER ASSEMBLY 12597846
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter of flange, max.		0.40%	3.2	Gage
102	Outside diameter of body, max.		0.40%	3.2	Gage
103	Diameter of hole		0.40%	3.2	Gage
Minor					
201	Thickness of flange, min.		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Bar, stop	1 OF 1	9370104
			NEXT HIGHER ASSEMBLY: 12597846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Overall length		0.65%	3.2	Gage
202	Height of ends		0.65%	3.2	Gage
203	Protective finish missing, improper or inadequate		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70736 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Connector, filtered	1 OF 1	9370079
			NEXT HIGHER ASSEMBLY: 12597846

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Filters not present		100%	3.2	Visual
Major					
101	Soldering not in compliance with MIL-STD-454	each lot		3.2	Certificate of compliance
102	Potting missing or incomplete		0.40%	3.2	Visual
103	Continuity check		0.40%	3.2	Gage
Minor					
201	Length of exposed filters, max.		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article Inspection Table I, the Quality Conformance Inspection Tables herein, as well as in the following paragraph.

4.4.3.1 Check test for deterioration of detonators (see MIL-D-46253). If the total time between original acceptance of any detonator lot and the assembly of that lot into the fuzes exceeds two years, or if the detonators have been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in MIL-D-46253 immediately before the detonator lot is assembled into the fuzes. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling the detonators into the fuzes (see 6.4).

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in Table I starting with 4.4.2.1. The contractor shall submit inspection equipment designs, for approval, in accordance with the terms of the contract. See section 6 of MIL-A-48078, and 6.3 and 6.4 herein.

4.5 Methods of inspection.

4.5.1 Rotor spring torque test. The springs shall be assembled to the applicable test fixture and the torque required to rotate the legs of the spring parallel to each other shall be recorded. Any spring which fails to comply with the specified drawing requirement shall be classified defective.

4.5.2 Electrical continuity test. The assembly shall be connected to the approved test fixture and the electrical resistance of the lead circuit shall be measured with the fuze first in the unarmed position and then with the fuze in the armed position. Any assembly which fails to comply with the specified requirement shall be classified defective and removed from the lot. This test shall be performed behind a suitable barricade.

4.5.3 Non-arming and arming test. The fuze less shear pin shall be assembled to the approved test fixture and a force between 20 and 30 pounds shall be applied to the arming pin disconnect in a direction so as to withdraw the pin from the assembly. If the arming pin disconnect does not withdraw sufficiently enough to allow the rotor to move to the armed position, the assembly shall be classified defective and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

After arming, the pin disconnect shall be re-inserted into the assembly. If the rotor fails to return to the fully unarmed position, the assembly shall be classified defective and removed from the lot. After the arming test, the shear pin shall be assembled to the fuze.

Warning: This test may be dangerous and should be performed behind a suitable barricade.

4.5.4 Salt spray test. After application of the protective coating specified on the applicable drawing, the samples shall be subjected to the salt spray test for the period specified on the applicable drawing. If one or more units of the sample show evidence of corrosion after testing, the lot of components represented by the sample shall be rejected.

5. PACKAGING

5.1 Packaging.

5.1.1 Assembled fuze. The assembled fuze shall be packaged in accordance with Dwg. 8799682.

5.2 Packing.

5.2.1 Assembled fuze. The packaged outer cartons shall be packed in accordance with Dwg. 8799683.

5.3 Marking. All marking shall be done in accordance with MIL-STD-1169.

5.4 Shipping. When component parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The parts covered by this specification are intended for use on a Demolition Fuze with other demolition items.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Cost of check test. The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the assemblies. The test shall be conducted at Government expense without cost to the contractor who loaded the detonator assemblies or to the contractor assembling the detonator assemblies into the fuzes, and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the detonator assembly lot was under the jurisdiction of either contractor.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, ARRADCOM or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Subject term (key word) listing.

Fuze
Demolition kit

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A382)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.