MILITARY SPECIFICATION

FUZE, ARTILLERY, ELECTRONIC, M767
LOADING, ASSEMBLING AND PACKING

This specification is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading, assembling and packing for the Fuze, Artillery, Electronic, M767.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

Preservation, Methods Of

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-P-60412 - Packaging, Packing and Marking for Shipment of Artillery Type and Rocket Fuzes, General Specification for

SPECIFICATION

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions, and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (see 6.8)

U.S. Army Armament Research, Development and Engineering Center (ARDEC).

8861213 - Box, Wirebound, Packing Ammunition for Artillery or Rocket Fuzes
8864492 - Box, Ammo, Metal, for Artillery Type and Rocket Fuzes
8886458 - Box, Pallet Type, Wirebound, Packing, Ammunition for Artillery Type and Rocket Fuzes (Within M2A1 Box)
11720206 - Cup, Booster (M767 E.T. Fuze only)
11720213 - Pellet, Booster (M767 E.T. Fuze only)
12551000 - Fuze, Electronic Time, M762
12551001 - Fuze, Artillery, Electronic, M767 Less Booster
12550756 - Sneak Circuit Analysis
12550850 - Fuze Assembly, M767

(Request for copies should be addressed to the Superintendent of Documents, Government Printing Offices, Washington, DC 20402).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the documents which are DOD adopted shall be those listed in the issue of documents not listed in the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODOSS shall be the issue of the nongovernment documents which is current on the date of the soliciation.

American Society for Testing and Materials (ASTM)

ASTM E29 - Standard Recommended Practice for Indicating Which Places of Figures Are to be Considered Significant in Specified Limiting Values

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:08Z
Check the source to verify that this is the currentversion before use.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelpha, Pennsylvania 19103)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts and assemblies. The parts and assemblies shall comply with all requirements specified on the drawings and with all requirements specified in applicable specifications.

3.3 Ballistic performance.

3.3.1 Premature bursts (see 6.4). There shall be no premature bursts in the gun bore, in flight or during handling.

3.3.2 Functioning (see 6.5).

3.3.2.1 Target impact functioning. The fuze, when set PD shall cause the projectile to function upon impact of the PD element when fired in the 105MM, L20A1/M119 Zone 5 at a 6" plywood target located 311 meters from the muzzle of the weapon.

3.3.2.2 Airburst functioning. The fuze, when set for airburst functioning shall cause the projectile to function at or about its intended functioning zone along the projectile trajectory.

3.3.3 Target non-function. The fuze when set PD shall not cause the projectile to function upon impact of the PD element when fired in the 155MM, M185/M109A3, Zone 7 at a 6" plywood target located 62 meters from the muzzle of the weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner and all manufacturing, processing and assembly operations shall be correctly performed. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, dirt, grease and oil (except where specifically required), rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

4.1.1 Responsiblilty for compliance. All items must meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contrator of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. Quality conformance inspection shall be conducted on this item:

a. Quality conformance inspection.

4.3 Quality conformance inspection.

4.3.1 Lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of complete fuze assemblies shall contain:

a. Metal parts of not more than one interfix from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

b. Booster pellets of not more than one interfix from one manufacturer.

4.3.2 Examination. See MIL-A-48078

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests tables, sampling plans for major defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70829 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 11720206
4.3.2.1	Cup, Booster		NEXT HIGHER ASSEMBLY 12551001

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Minor diameter of thread		0.40%	3.2	Gage
103	Cup cracked or otherwise damaged		0.40%	3.2	Visual
104	Inside depth, max.		0.40%	3.2	Gage
105	Thickness of cup at bottom		0.40%	3.2	Gage
106	Outside diameter, max.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70829 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.3.2.2	Pellet, Booster	1	1	11720213
				NEXT HIGHER ASSEMBLY: 12551001

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pellet cracked, chipped or broken		0.40%	3.2	Visual
102	Thickness		0.40%	3.2	Gage
103	Weight		0.40%	3.2	Gage
104	Outside diameter		0.40%	3.2	Gage
105	Radii		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70829 (AR)

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.3.2.3	Fuze, Artillery, Electronic, M767 Less Booster		1 1		12551001
					NEXT HIGHER ASSEMBLY 12550850
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Fuze damaged		0.40%	3.2	Visual
102	Output lead functioned		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual
202	Marking improper		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70829 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.3.2.4	Fuze, Artillery, Electronic, M767 prior to assembling Cup, Booster	1	1	12551001
				NEXT HIGHER ASSEMBLY 12550850

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Explosive material on booster cup threads		100%	3.2	Visual
Major					
101	Booster pellet missing		0.40%	3.2	Visual
102	Foreign matter in booster cup		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70829 (AR)

PARAGRAPH	TITLE		SHEET	OF	DRAWING NUMBER
4.3.2.5	Fuze, Artillery, Electronic, M767			1 1	12550850
					NEXT HIGHER ASSEMBLY: Final Assembly
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length below ogive, max.		0.40%	3.2	Gage
102	Booster cup cracked or otherwise defective		0.40%	3.2	Visual
103	Adhesive missing or excessive		0.40%	3.2	Visual
104	Fuze not set in ship position		0.40%	3.2	Visual
105	Booster cup fails disassembly torque		0.40%	3.2	Gage
106	Booster pellet loose (moves when shaken)		0.40%	3.2	Visual/Manual
107	Fuze threads damaged		0.65%	3.2	Visual
108	Fuze ogive damaged		0.65%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual
202	Marking missing, illegible or improper		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.6	Fuze, Artillery, Electronic, M767 Destructive Tests	1 OF 1	12550850
			NEXT HIGHER ASSEMBLY Final Assembly

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Target non-function test	10		3.4.3	4.4.1.3
2	Premature burst	30(a)		3.4.1	4.4.1
Major					
101	Target function	10		3.4.2.1	4.4.1.1
102	Airburst function	10		3.4.2.2	4.4.1.2

NOTES: (a) Samples for this test are the fuzes subjected to the target non-function, target function and airburst function tests.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70829 (AR)

PARAGRAPH	TITLE		SHEET	OF	DRAWING NUMBER
4.3.2.7	Fuze, Artillery, Electronic, M767		1	1	12550850
					NEXT HIGHER ASSEMBLY 8864492
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Barrier bag damaged		0.40%	3.2	Visual
102	Seal damaged		0.40%	3.4	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70829 (AR)

PARAGRAPH	TITLE		SHEET OF	DRAWING NUMBER
4.3.2.8	Fuze, artillery, electrinic, M767		1 1	8864492
				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged damaged		0.40%	3.2	Visual
102	Marking inadequate		0.40%	3.2	Visual
103	Strapping missing or loose		0.40%	3.2	Visual
104	Marking incomplete, misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.3.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and section 6 herein.

4.4. Methods of inspection.

4.4.1 Ballistic performance test.

4.4.1.1 Premature burst. Any premature burst during the entire ballistic test shall cause the lot to be rejected.

4.4.1.2 Target functioning. The fuze shall be assembled to a 105MM and fired at an adequately supported target as specified in 3.4.2.1. When fired, the fuze, projectile and charge shall be at a temperature of 70° ± 10°F. This may require temperature conditioning in accordance with 4.4.2. Observation of impact functioning is required and shall be noted on the ballistic records. If more than one fuze fails to function the lot shall be rejected.

4.4.1.3 Airburst functioning. The fuze shall be assembled to a 105MM, M1 projectile and set for 25.0 seconds. The fuze projectile shall be fired from a 105MM weapon with an M103 tube at Charge 7. When fired, the fuze, projectile and charge shall be at a temperature of 70° ± 10°F. This may require temperature conditioning in accordance with 4.4.2. All defects shall be recorded. A system of electric clocks or stopwatches shall be employed to measure the time to burst. These measurements shall be recorded to the neareat 0.01 seconds. If a round fails to function in flight observation shall be made to determine if the round functions on impact. If more than two (2) fuzes fail to function the lot shall be rejcted.

4.4.1.4 Target non-function test. The fuze shall be assembled to a 155MM, M185/M109A3, Zone 7 and fired at an adequately supported target as specified in 3.4.3. When fired, the fuze, projectile and charge shall be at a temperature of 70° ± 10°F. This may require temperature conditioning in accordance with 4.4.2. Observation of impact non-functioning is required and shall be noted on the ballistic records. If any fuze functions on target impact the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:08Z
Check the source to verify that this is the currentversion before use.

4.4.2 Temperature conditioning. The projectile with the fuze assembled to it, and the charge shall be placed in a temperature conditioning chamber. With the components in the chamber, start the test at ambient temperature. The chamber shall then be maintained at the desired temperature until a steady-state condition exists. After a steady-state temperature condition is reached, the components shall be saturated for twenty-four (24) hours minimum at that temperature.

5. PACKAGING.

5.1 Packaging.

5.1.1 Level A, B, and C. Packaging shall be in accordance with drawing 8864492 and MIL-P-60412.

5.2 Packing.

5.2.1 Level A. Packing shall be in accordance with drawing 8861213.

5.2.2 Level B and C. Packing shall be in accordance with drawing 8886458.

5.3 Marking.

5.3.1 Packaging, marking, level A, B, and C. Packaging and marking shall be in accordance with drawing 8864492.

5.3.2 Packing, marking.

5.3.2.1 Level A. Packing, marking shall be in accordance with drawing 8861213.

5.3.2.2 Level B and C. Packing, marking shall be in accordance with drawing 8886458.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in Artillery Systems.

6.2 Ordering data. See MIL-A-48078 (AR).

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required to Commander, ARDEC, AMSMC-QAR-R(D), Picatinny Arsenal, N.J. 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, DI-R-1714 will apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

6.4 Premature burst. A premature burst is a malfunction in which a fuze functions before safe separation. In the point detonating mode (PD), safe separation is defined by the minimum arming distance per 3.4.3.

6.5 Functioning. A function is evidenced by the detonation of the specified projectile. A projectile which does not function as intended is termed a dud.

6.5.1 Airburst dud. An airburst dud is a fuzed projectile set to function in the airburst mode but does not function in air. This is independent of whether or not the projectile functions upon subsequent impact.

6.5.2 Target dud. A target dud is a fuze which does not function on impact when it is intended.

6.6 Proving ground test summary.

TEST	WEAPON/ TUBE	CHARGE	DISTANCE/ SETTING	SAMPLE	ACCEPT/ REJECT
Non-Function	155/M804	7	62 Meters	10	0/1
Function	105MM/L20A1	5	311 Meters	10	1/2
Airburst	105MM/M103	7	25.0 Sec.	10	2/3

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.8 Subject term (key word) listing.

Airburst Functioning
Fuze, Ammunition
Fuze, Artillery
Fuze, Artillery Ammunition
Fuze, Artillery Projectile
Fuze, Electronic Time
Fuze, Electronic Time and Point Detonating
Fuze, Projectile
Premature Burst
Target Dud

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1390-A615)

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:08Z
Check the source to verify that this is the currentversion before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-70829 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:08Z
Check the source to verify that this is the current version before use.