MILITARY SPECIFICATION
INITIATOR, CARTRIDGE ACTUATED, XM107
METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Initiators, Cartridge Actuated, XM107, Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with an ejector for reserve parachute for paratroops.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATION

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber O-Rings
MIL-STD-639	- Surface Roughness Values Preferred for Army Ordnance Materiel
MIL-STD-1167	- Ammunition Data Card

DRAWINGS

Munitions Command

F-10535977	- Initiator, Cartridge Actuated, Metal Parts Assembly
C-8830984	- Container, Ammunition Fiber, M426 for Initiator, Cartridge Actuated, M27, M99, XM86, XM98 or XM107 with Cartridge
C8830985	- Box, Packing, Ammunition for Initiator, Cartridge Actuated, M27, M99, XM86, XM98 or XM107 in Fiber Container M426
IEL-10535977	- Index of Inspection Equipment List for Initiator, Cartridge Actuated, XM107, Metal Parts Assembly

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement function should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 General.- Materials, parts, and assemblies shall comply with the requirements on the applicable drawings and specifications.

3.2 First article sample.- Requirements for the submission of first article sample by the contractor shall be as specified in the contract.

3.3 Material.- The contractor shall be responsible for selecting from the classification list contained in the raw material specification, the surface and physical condition of the raw material intended for use in manufacture.

3.4 Mechanical properties.- Mechanical properties required by the drawings shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.5 Hydrostatic pressure.- The initiator chamber and cap shall withstand a hydrostatic pressure of 14,000 to 15,000 pounds per square inch (psi) for 15 seconds, minimum, without deformation or mechanical failure (see 6.1).

3.6 Firing pin release.- The firing pin of the metal parts assembly, less cotter pin, shall release from the cocked position when the application of an axial load of 15 to 30 pounds has withdrawn the initiator pin, .370 inches, minimum and .425 inches maximum.

3.7 Metal parts assembly.- Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled handtight.

3.8 Protective finish.- Protective finish shall be in accordance with the specifications and drawings and shall apply to all surfaces of the component regardless of contour.

3.9 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following.

3.9.1 Metal defects.- All components shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.9.2 Burr.- No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.9.3 Foreign matter.- No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample

4.2.1 Initial production sample.- At the beginning of regular production a sample shall be submitted in accordance with contract requirements and shall consist of five (5) assembled initiators and ten (10) sets of unassembled components for visual and dimensional examination. The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility as specified in the contract.

4.2.2 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions

4.3.1 Lot

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.- Unless otherwise specified by the procuring agency, a lot shall consist of 10,000 initiators maximum, exclusive of test samples provided the homogeneity requirements of inspection lots have been retained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans and criteria in Table I and II. For an individual defect (single characteristic), the criteria in Table I shall be used. For total defects within a major or minor group the criteria in Table II shall be used. All nonconforming material shall be rejected. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. The Ordnance Standard Finish Blocks prescribed in MIL-STD-639 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE I

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	-	-	-	-
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

TABLE II

Total Allowable Defects per Sample Size

Sample Sizes for Major Defects	110	150	225	300
No. of Defects in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over - 43	6	8	11	14
Sample Size for Minor Defects				
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over - 48	8	11	17	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.1 Chamber, Initiator, Drawing D10520407, covering a detail of Drawing F10535977.

Defect		Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Pitch diameter of large external thread, min.	Gage
102.	Major diameter of large external thread, min.	Gage
103.	Pitch diameter of small external thread, min.	Gage
104.	Major diameter of small external thread, min.	Gage
105.	Pitch diameter of internal thread, max.	Gage
106.	Minor diameter of internal thread, max.	Gage
107.	Concentricity of datum location with pitch diameter of small external thread	Gage
108.	Concentricity of pitch diameter of large thread with cavity	Gage
109.	Concentricity of large external thread pilot with large external thread	Gage
110.	Concentricity of counterbore with cavity, including perpendicularity with base of counterbore	Gage
111.	Diameter of counterbore	Gage
112.	Diameter of large thread pilot	Gage
113.	Depth of cavity	Gage
114.	Length to datum location	Gage
115.	Thickness of wall, min.	Gage
116.	Metal defective	Visual
117.	Protective finish, inadequate or defective	Visual
118.	Surface finish of cavity and angle of gas port improper	Visual
119.	Burr or sharp corner	Visual
120.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Pitch diameter of large external thread, max.	Gage
202. Pitch diameter of small external thread, max.	Gage
203. Pitch diameter of internal thread, min.	Gage
204. Diameter of small external thread relief	Gage
205. Diameter of small external thread pilot	Gage
206. Diameter of hole in gas port	Gage
207. Diameter of cavity	Gage
208. Diameter of chamfer at internal thread	Gage
209. Depth of counterbore	Gage
210. Depth of threaded hole	Gage
211. Length of large external thread	Gage
212. Length of gas port	Gage
213. Length of small thread relief	Gage
214. Length from face of gas port to small thread	Gage
215. Length of external thread pilot	Gage
216. Total length	Gage
217. Thickness of wall, max.	Gage
218. Marking missing, incorrect or illegible	Visual
219. Radius or chamfer missing or incorrect	Visual
220. Surface finish improper unless otherwise classified	Visual

4.3.2.2 Cap, Initiator, Drawing F10535978, covering a detail of Drawing F1053977.

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of small internal thread, max.	Gage
102. Minor diameter of small internal thread, max.	Gage
103. Pitch diameter of large internal thread, max.	Gage
104. Minor diameter of large internal thread, max.	Gage
105. Concentricity of pitch diameter of large internal thread (with midsection cavity, including perpendicularity with base of large cavity counterbore	Gage
106. Concentricity of pitch diameter of small internal thread with midsection cavity including perpendicularity with base of large cavity counterbore	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
107. Concentricity of hole between small cavity and boss cavity with midsection cavity, including perpendicularity with base of large cavity counterbore	Gage
108. Concentricity of undercut in large cavity with large internal thread	Gage
109. Concentricity of boss cavity with hole between small cavity and boss cavity	Gage
110. Concentricity of flange with hole between small cavity and boss cavity	Gage
111. Concentricity of body, large end with large internal thread	Gage
112. Concentricity of small cavity with midsection cavity	Gage
113. Concentricity of thread cavity with large internal thread	Gage
114. Diameter of hole between boss cavity and small cavity	Gage
115. Diameter of boss cavity	Gage
116. Diameter of large midsection cavity	Gage
117. Diameter of small midsection cavity	Gage
118. Diameter of undercut	Gage
119. Length of midsection cavity effective thread, min.	Gage
120. Thread damaged or not full	Visual
121. Metal defective	Visual
122. Protective finish inadequate or defective	Visual
123. Surface finish of thread undercut improper	Visual
124. Burr	Visual
125. Foreign matter	Visual
MINOR	
201. Pitch diameter small internal thread, min.	Gage
202. Pitch diameter large internal thread, min.	Gage
203. Pitch diameter set screw thread	Gage
204. Minor diameter set screw thread	Gage
205. Diameter of chamfer at base of large threaded cavity counterbore	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

	Defect	Method of Inspection
MINOR (Cont'd)		
206.	Diameter of boss flange	Gage
207.	Diameter of body	Gage
208.	Diameter of cotter pin holes	Gage
209.	Diameter of counterbore at base of large threaded cavity	Gage
210.	Depth from chamfer at base of large threaded cavity counterbore to base of midsection cavity	Gage
211.	Depth of large threaded cavity counterbore	Gage
212.	Depth to base of large threaded cavity counterbore	Gage
213.	Depth around internal boss	Gage
214.	Depth from base of counterbore of large threaded cavity to chamfer at base of large midsection cavity	Gage
215.	Total length	Gage
216.	Length of flats at small end	Gage
217.	Length across flats at small end	Gage
218.	Length of flange at small end	Gage
219.	Length of head	Gage
220.	Length from large threaded cavity counterbore to boss in small end	Gage
221.	Width of counterbore at base of large threaded cavity	Gage
222.	Location of set screw hole	Gage
223.	Location of cotter pin hole	Gage
224.	Radius or chamfer missing or incorrect	Visual
225.	Surface finish improper, except as otherwise classified	Visual

4.3.2.3 Pin, Initiator, Drawing C10520409, covering a detail of Drawing F10535977.

CRITICAL

None defined

MAJOR

101.	Concentricity of groove in head with body	Gage
102.	Concentricity of shoulder with body	Gage
103.	Symmetry of pin hole with body	Gage
104.	Diameter of undercut, min, if applicable	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
105. Width of undercut, max, if applicable	Gage
106. Diameter of body	Gage
107. Diameter of shoulder	Gage
108. Diameter of groove in body, min.	Gage
109. Width of head groove	Gage
110. Location of groove in head	Gage
111. Location of groove in body	Gage
112. Location of pull hole	Gage
113. Profile of end	Visual
114. Profile of head	Visual
115. Metal defective	Visual
116. Protective finish inadequate or defective	Visual
117. Surface finish of groove in head and face of shoulder, improper	Visual
118. Burr	Visual
119. Foreign matter	Visual
MINOR	
201. Diameter of groove in head	Gage
202. Diameter of groove in body	Gage
203. Diameter of pull hole	Gage
204. Length to groove in body	Gage
205. Total length	Gage
206. Width of flat at body groove end	Gage
207. Thickness of pull hole end	Gage
208. Marking missing, incorrect or illegible	Visual
209. Radius or chamfer missing or incorrect	Visual
210. Surface finish improper, except as otherwise classified	Visual

4.3.2.4 Seal, Drawing B10520415 covering a detail of Drawing F10535977

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

	Defect	Method of Inspection
MAJOR		
101.	Diameter, outside, min.	Gage
102.	Width, min.	Gage
103.	Thickness, min.	Gage
104.	Cut, cracked or split	Visual
105.	Flash	Visual
106.	Foreign matter	Visual
MINOR		
201.	Diameter, outside, max.	Gage
202.	Width, max.	Gage
203.	Thickness, max.	Gage

4.3.2.5 Housing, Firing Pin Drawing C10520410 covering a detail of Drawing F10535977.

CRITICAL		
1.	Diameter of striker hole, min.	Gage
MAJOR		
101.	Pitch diameter of thread, min.	Gage
102.	Major diameter of thread, min.	Gage
103.	Concentricity of striker hole with cavity	Gage
104.	Concentricity of cavity with pitch diameter of thread	Gage
105.	Concentricity of body with pitch diameter of thread	Gage
106.	Perpendicularity of face with body	Gage
107.	Diameter of body, min.	Gage
108.	Diameter of cavity	Gage
109.	Diameter of flange, min.	Gage
110.	Diameter of boss	Gage
111.	Diameter of undercut, min.	Gage
112.	Total length, max.	Gage
113.	Width of undercut	Gage
114.	Thickness of striker hole	Gage
115.	Location of thread	Gage
116.	Chamfer at striker hole	Gage
117.	Height of boss	Gage
118.	Metal defective	Visual
119.	Protective finish, inadequate or defective	Visual
120.	Surface finish of cavity, improper	Visual
121.	Burr	Visual
122.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Pitch diameter of thread, max.	Gage
202. Diameter of body, max.	Gage
203. Diameter of striker hole, max.	Gage
204. Diameter of flange, max.	Gage
205. Diameter of wrench holes	Gage
206. Depth of wrench holes	Gage
207. Total length, min.	Gage
208. Length of body to flange	Gage
209. Location of wrench holes	Gage
210. Marking missing, incorrect or illegible	Visual
211. Radius or chamfer, missing or incorrect, except as otherwise classified	Visual
212. Surface finish improper, except as otherwise classified	Visual

4.3.2.6 Pin, Firing, Drawing C10520411 covering a detail of Drawing F10535977

CRITICAL

None defined

MAJOR	
101. Concentricity of large cavity with body	Gage
102. Concentricity of striker with body	Gage
103. Concentricity of cavity with body	Gage
104. Symmetry of pin relief holes with small cavity	Gage
105. Symmetry of ball hole counterbore with ball hole	Gage
106. Diameter of striker	Gage
107. Diameter of body	Gage
108. Diameter of ball hole, max.	Gage
109. Diameter of ball hole counterbore	Gage
110. Diameter of pin relief holes, min.	Gage
111. Depth of ball counterbore, min.	Gage
112. Length of striker, min.	Gage
113. Location of ball hole counterbore	Gage
114. Metal defective	Visual
115. Protective finish inadequate or defective	Visual
116. Surface finish of body improper	Visual
117. Burr or sharp corner	Visual
118. Foreign matter	Visual
MINOR	
201. Diameter of large cavity	Gage
202. Diameter of small cavity	Gage
203. Diameter of ball hole, min.	Gage
204. Diameter of pin relief holes, max.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

Defect	Method of Inspection
MINOR (Cont'd)	
205. Depth of large cavity	Gage
206. Depth to bottom of small cavity	Gage
207. Depth of ball hole counterbore, max.	Gage
208. Length of striker, max.	Gage
209. Total length	Gage
210. Location of pin relief holes	Gage
211. Marking missing incorrect or illegible	Visual
212. Radius or chamfer missing or incorrect	Visual
213. Surface finish improper, except as otherwise classified	Visual

4.3.2.7 Spring, Initiator, Drawing B10520412, covering a detail of Drawing F1053977.

CRITICAL

None defined

MAJOR	
101. Load at specified height	Gage
102. Closed length, max.	Gage
103. Ends incorrect	Visual
104. Protective finish inadequate or defective	Visual
105. Burr	Visual
106. Foreign matter	Visual
MINOR	
201. Diameter, outside	Gage
202. Free length	Gage

4.3.2.8 Filter, Drawing C10520414, covering a detail of Drawing F10535977

CRITICAL

None defined

MAJOR	
101. Pitch diameter of thread, min.	Gage
102. Major diameter of thread, min.	Gage
103. Concentricity of thread with center hole and outside diameter	Gage
104. Symmetry of holes with outside diameter	Gage
105. Diameter of center hole	Gage
106. Diameter of holes	Gage
107. Depth of center hole	Gage
108. Depth of slot, max.	Gage
109. Location of holes	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
110. Angular location of holes	Gage
111. Nylon patch not properly located or fused	Manual or Visual
112. Number of holes incorrect	Visual
113. Metal defective	Visual
114. Protective finish inadequate or defective	Visual
115. Burr	Visual
116. Foreign matter	Visual
MINOR	
201. Pitch diameter of thread, max.	Gage
202. Diameter of undercut	Gage
203. Diameter of body	Gage
204. Depth of slot, min.	Gage
205. Total length	Gage
206. Length of body	Gage
207. Width of undercut, max.	Gage
208. Width of slot	Gage
209. Location of slot	Gage
210. Marking missing, incorrect or illegible	Visual
211. Chamfer missing or incorrect	Visual
212. Surface finish improper	Visual

4.3.2.9 Assembly, Drawing F10535977, less all drawings except C10520410, C10520411 and MS19060-S.

CRITICAL	
1. Firing pin protrusion	Gage
2. Steel ball missing	Gage
MAJOR	
101. Burr	Visual
102. Foreign matter	Visual
MINOR	
None defined	

4.3.2.10 Assembly, Drawing F10535977

CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.10 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Firing pin not cocked	Manual
102. Initiator pin not free to rotate	Manual
103. Any part missing, except as otherwise classified	Visual
104. Improper assembly	Visual
105. Cotter pin improperly inserted	Visual
106. O-ring not lubricated	Visual
107. Marking missing, incorrect or illegible	Visual
MINOR	
201. Shipping cap missing	Visual
202. Protective finish inadequate or defective	Visual

4.3.2.11 Container, Fiber, Drawing C8830984

CRITICAL

None defined

MAJOR

None defined

MINOR

201. Contents loose	Manual
202. Metal ends loose or distorted	Manual
203. Gap between body and cover, max.	Visual
204. Cut or damaged through all impregnated layers	Visual

4.3.2.12 Box, Packing, Drawing C8830985

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.3.2.12 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Manual and Visual
203. Strapping missing, loose, broken or improperly assembled	Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual

4.3.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness.- Fifty units from each heat treated lot of components shall be tested for compliance with the requirements specified on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.3.3.2 Hydrostatic pressure.- Each chamber and subassembly shall be subjected to the hydrostatic pressure test. Failure of any subassembly to comply with the requirements of 3.5 shall be cause for rejection of the subassembly.

4.3.3.3 Firing pin release.- The initiator pin of each partial assembly consisting of all parts except the cotter pin and chamber shall be subjected to the firing pin release test. Failure of any partial assembly to comply with the requirements of 3.6 shall be cause for rejection of the subassembly.

4.3.3.4 Protective finish.- The number of units for protective finish tests shall be in accordance with the applicable specifications. Failure of any sample to comply with the requirements of 3.8.

4.3.4 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-10535977.

4.4 Test methods and procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

4.4.1 Hardness.- A hardness tester shall be used to determine compliance with the requirements of the applicable drawing.

4.4.2 Hydrostatic pressure.- Prior to the application of protective finish, the chamber and cap subassembly shall be mounted in the device, using the fixture for properly sealing all openings and subjected to the hydrostatic pressure to determine compliance with the requirements of 3.5.

4.4.3 Firing pin release.- The subassembly shall be secured in the fixture. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture which registers the amount of pull.

4.4.4 Protective finish.- Test procedures for protective finish shall be in accordance with the specification referenced on the component drawing.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packing and marking shall be in accordance with Drawings C8830984 and C8830985.

5.2 Data cards.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A103

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA- N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.