MILITARY SPECIFICATION

MAGNETIC CORE

1. SCOPE

1.1 This specification covers special requirements, provides the quality assurance provisions, and the preparation for delivery criteria for one type of Magnetic Core used on the Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-S-60902(MU) - Soldering Electrical Connections for Nuclear Weapons Systems, Procedure for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspections by Attributes
MIL-STD-810 - Environmental Test Methods
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169(MU) - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8853940 - Operating Instructions
8853983 - Insulation Resistance Test Panel
8854004 - Operation Test Panel
8883539 - Bag, Packing for Repair Parts
9204037 - Magnetic Core
EL-9204037 - Equipment List

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publication required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. - The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. - The magnetic core shall comply with all requirements specified on Drawing (dwg) 9204037, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. - Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Insulation resistance. - The assembly shall have a value of insulation of not less than 10,000 megohms measured between circuitry as specified in table I when tested as specified in 4.4.1.

Table I

Between (plus)	To (minus)	Exceptions
Pin 1	All other pins and casing	Pin 4
Pin 2	All other pins and casing	Pin 3 and 8
Pin 9	All other pins and casing	Pin 5
Pin 10	All other pins and casing	Pin 6 and 7

3.5 Environmental testing. - The item shall comply with 3.4 and 4.3.3.1 before and after each environmental test when tested as specified in 4.4.2. Tests shall be conducted in the order specified.

3.5.1 Low temperature. - The item shall withstand exposure to a storage temperature of -65°F and shall comply with 3.4 and 4.3.3.1 while at -65°F when tested as specified in 4.4.2.1.

3.5.2 High temperature. - The item shall withstand exposure to a temperature of +160°F and shall comply with 3.4 and 4.3.3.1 while at +160°F when tested as specified in 4.4.2.2.

3.5.3 Temperature shock. - The item shall withstand sudden changes in temperature when tested as specified in 4.4.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

3.5.4 Humidity. - The item shall withstand exposure to a humid atmosphere when tested as specified in 4.4.2.4.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. - All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. - Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. - Parts shall be free from burrs.

3.6.4 Foreign matter. - Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. - The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.6.6 Electrical. - Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. - When the contract requires first article inspection, the contractor shall submit 24 complete assemblies (see dwg 9204037) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. - The first article inspection sample shall be subjected to the inspections and tests specified in table II. Tests shall be conducted in order specified in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

Table II

First article inspections and tests

Examination or Test	Contractors Inspection Permissable before Submission	Destruct.	Non Destruct.
1. Classification of characteristics (see 4.3.2.1)	X		X
2. Operation (see 4.3.3.1)	X		X
3. Insulation resistance (see 3.4)	X		X
4. Low temperature (see 3.5.1)	X		X
5. High temperature (see 3.5.2)	X		X
6. Temperature shock (see 3.5.3)	X		X
7. Humidity (see 3.5.4)		X	

4.2.3 Inspection equipment. - The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. - If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Product acceptance inspection.

4.3.1 Lot formation. - A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. - An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. - Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

Major characteristic table III

Lot size	Sample size
1- 155	100% inspection
156- 200	155
201- 250	175
251- 300	190
301- 350	200
351- 400	210
401- 450	220
451- 500	225
501- 550	230
551- 600	235
601- 650	240
651- 700	243
701- 750	247
751- 800	250
801- 900	254
901-1000	258
1001-1100	261
1101-1200	264
1201-1300	266
1301-1400	268
1401-1500	270
1501-1600	272

Minor characteristic table IV

Lot size	Sample size
1- 25	100% inspection
26- 30	25
31- 35	26
36- 40	27
41- 45	28
46- 50	29
51- 55	30
56- 60	31
61- 65	32
66- 70	33
71- 75	34
76- 85	35
86- 95	36
96- 110	37
111- 130	38
131- 156	39
157- 190	40
191- 240	41
241- 340	42
341- 520	43
521-1120	44
1121 and over	45

4.3.2.1 Classification of characteristics. - Critical, major, and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Magnetic core (see dwg 9204037).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Soldering in accordance with MIL-S-60902(MU).....Visual/Manual
102. Length, max.....Gage
103. Width, max.....Gage
104. Height, max.....Gage
105. Length of pins.....Gage
106. Location of pins.....Gage
107. Diameter of pins.....Gage
108. Material (see 3.1).....Visual
109. Windings loose on coil.....Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

110. Pins bent or damaged.....Visual
111. Workmanship (see 3.6).....Visual/Manual
112. Marking.....Visual

Minor: None defined.

4.3.2.1.2 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Packaging, packing and marking in accordance with MIL-STD-1169(MU).....Visual

Minor:
201. Workmanship (see 3.6).....Visual

4.3.2.1.3 Bag, packing, for repair parts (see dwg 8883539 covering dwg part number 8883539-3 and 5.2).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Material (see 3.1).....Visual
102. Length before packing, min.....*Measure
103. Width before packing, min.....*Measure
104. Objective evidence (see 6.2) available for heat seal test in accordance with MIL-P-116.....Visual
105. Properly packed.....Visual
106. No tear, split, or crack in bag.....Visual

*Measure with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.6).....Visual/Manual

4.3.2.1.4 Packing and marking for storage and shipments (see dwg 8808362 and section 5).

Categories	Characteristics	Method of Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

Critical: None defined.

Major:
101. Gross load weight, max.....*Measure
102. Contents tight in package.....Manual
103. Correctly packed.....Visual/Manual
104. Package material (see 3.1).....Visual

* Determine weight with a suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.6).....Visual/Manual

4.3.3 Testing. - All the tests specified in this paragraph shall be performed. Tests shall be performed in the order specified.

	Test	Test Classification
a.	Operation	Critical
b.	Insulation resistance	Critical
c.	High temperature	Major
d.	Low temperature	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Operation (see dwg 9204037). - Each magnetic core shall be tested as specified in 4.4.3 for peak power, voltage drop, output "one", output "zero" and frequency. If any magnetic core fails to comply with drawing requirements, the magnetic core shall be rejected and removed from the lot.

4.3.3.2 Insulation resistance (see 3.4). - Each magnetic core shall be tested in accordance with 4.4.1. If any magnetic core fails to comply with 3.4, the magnetic core shall be rejected and removed from the lot.

4.3.3.3 High temperature (see 3.5.2) and low temperature (see 3.5.1). - A sample shall be selected at random from each inspection lot in accordance with table V and tested in accordance with 4.4.2. If any magnetic core fails to comply with 3.5.1 and 3.5.2 the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

Table No. V

Lot Size	Sample Size for No Failures 100% Inspection
1- 25	25
26- 30	26
31- 35	27
36- 40	28
41- 45	29
46- 50	30
51- 55	31
56- 60	32
61- 65	33
66- 70	34
71- 75	35
76- 85	36
86- 95	37
96- 110	38
111- 130	39
131- 156	40
157- 190	41
191- 240	42
241- 340	43
341- 520	44
521-1120	45
1121 and over	

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. - Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment List (EL-9204037). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.

b. The code "CD" is listed in the "Part or Identifying Number" column on the EL.

4.3.4.2 Minor characteristics and tests. - Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. - The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

4.4.1 Insulation resistance (see 3.4). - Insulation resistance shall be measured utilizing the insulation resistance tester specified on test panel dwg 8853983. The potential shall be applied for a minimum of 5 seconds and the current shall be limited to 5 milliamperes as a safety measure.

4.4.2 Environmental testing (see 3.5).

4.4.2.1 Low temperature (see 3.5.1). - The item shall be tested in accordance with MIL-STD-810, Method 502.

4.4.2.2 High temperature (see 3.5.2). - The item shall be tested in accordance with MIL-STD-810, Method 501, Procedure II.

4.4.2.3 Temperature shock (see 3.5.3). - The item shall be tested in accordance with MIL-STD-810, Method 503.

4.4.2.4 Humidity (see 3.5.4). - The item shall be tested in accordance with MIL-STD-810, Method 507, Procedure I.

4.4.3 Operation (see 4.3.3.1). - Operation shall be performed utilizing the operation test panel dwg 8854004 and operating instructions dwg 8853940.

5. PREPARATION FOR DELIVERY

5.1 Production parts only.

5.1.1 Preservation and packaging. - Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. - The core shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. - The core shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. - The core shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. - Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts only.

5.2.1 Preservation and packaging. - Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. - The core shall be packaged in accordance with dwgs 8883539 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. - The core shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Levels A and C. - The core shall be packed in accordance with dwgs 8883539 and 8808362.

5.2.3 Marking. - Marking shall be as specified in accordance with dwgs 8883539 and 8808362, as applicable.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

6.1 Ordering data. - Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. - Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment. - The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

6.4 Supersession data. - This specification includes the requirements of Purchase Description PA-PD-1895, dated 26 July 1963.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1125-A028

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-M-50285(MU) Magnetic Core

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.