MILITARY SPECIFICATION

PRINTED CIRCUIT CARD, M1 AND M1A1 TANK, GENERAL SPECIFICATION FOR

This specification is approved for use by US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the general performance for printed circuit cards (PCC) used in the driver instrument panel, and the turret network box of the M1 and M1A1 Tank. The requirements of this specification together with those of the applicable detail specification constitute the complete requirements for each printed circuit card listed in 1.2.

1.2 Classification. Printed circuit cards shall be classified as follows:

Type I	-	Printed Circuit Card, Driver's Instrument Panel, DIP-A3.
Class 1		12282631 (for M1)
Class 2		12316386 (for M1A1)
Type II	-	Printed Circuit Card, Driver's Instrument Panel, DIP-A1
Class 1		12282607 (for M1)
Class 2		12337028 (for M1A1)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 1240
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

Type III - Printed Circuit Card, Turret Network Box, (TNB-A4)

Drawing No. 12282891 (for M1 and M1A1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS
MILITARY

MIL-P-62341/1A	- Printed Circuit Card Driver's Instrument Panel, DIP-A3.
MIL-P-62341/2A	- Printed Circuit Card Driver's Instrument Panel, DIP-A1.
MIL-P-62341/3A	- Printed Circuit Card Turret Network Box, TNB-A4.
MIL-R-5757/23	- Relays, Electrical, Hermetically Sealed, DPDT, 10 Amperes.
MIL-R-6106/19	- Relays, Electromagnetic, Permanent Magnetic Drive, 25 Amperes, SPDT, Hermetically Sealed.

STANDARDS
MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	- Marking for Shipment and Storage.
MIL-STD-202	- Electronic and Electrical Component Parts, Test Methods for Electronic and Electrical Component Parts.
MIL-STD-454	- Standard General Requirements for Electronic Equipment.
MIL-STD-750	- Test Methods for Semiconductor Devices.
MIL-STD-810	- Environmental Test Methods and Engineering Guidelines.
MIL-STD-45662	- Calibration Systems Requirements.
MS24171	- Relay, 200 Amp, 1 PST, N.O. Type II Non-Hermetically Sealed.
MS24187	- Relay, 50/25 Amp, 1 PDT, N.O./N.C. Type II, Non-Hermetically Sealed.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:33Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS
ARMY

11655194	- Process Specification for Soldering, Electrical Connections for Electrical and Electronics Equipment, General Requirements for.
12282631	- Printed Circuit Card DIP-A3 for M1.
12316386	- Printed Circuit Card DIP-A3 for M1A1.
12282607	- Printed Circuit Card DIP-A1 for M1.
12337028	- Printed Circuit Card DIP-A1 for M1A1.
12282891	- Printed Circuit Card Turret Network Box (TNB-A4) for M1 and M1A1.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

General Dynamics Land Systems Division

DEOS 2060	- Nuclear Hardening Criteria (U)

(Copies of General Dynamics DEOS 2060 should be obtained from the U.S. Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000.) Vendors requesting the nuclear hardening criteria, which is classified confidential, shall possess the proper security clearance and shall demonstrate a need to know.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. Unless otherwise specified (see 6.2), the contractor shall furnish printed circuit cards which shall be subjected to first article inspection (see 4.4 and 6.2). First article inspection samples, properly marked with identifying information shall be representative of the unit to be furnished to the Government. All subsequent assemblies delivered to the Government shall conform to these samples in all of their pertinent physical and performance attributes.

3.2 Detail specification. The individual item requirements shall be as specified herein and in accordance with the applicable detail specification. In the event of conflict between requirements of this specification and the detail specification, the latter shall govern.

3.3 Materials. Materials shall be as specified herein and in referenced specifications, standards, and drawings. Materials shall be free from defects which adversely affect performance or serviceability of the finished product (see 4.8.1).

3.4 Design and construction. The printed circuit card shall be constructed to the form and dimensions depicted on the applicable drawings and fabricated so that all component assemblies and parts are functionally and dimensionally interchangeable with like components furnished under the same part number. In addition to the provisions of this specification, the printed circuit card shall conform to the applicable detail specifications listed in 2.1.

3.4.1 Configuration. See applicable specification sheet.

3.4.2 Weight. See applicable specification sheet.

3.4.3 Soldering. Electrical connections shall be soldered in accordance with Drawing 11655194 (see 4.8.1).

3.4.4 Nuclear hardening. See applicable specification sheet.

3.5 Performance.

3.5.1 Circuit continuity. Except as otherwise specified in the applicable specification sheet, the resistance of continuous circuits shall not exceed 1.0 ohm. Continuous circuits are those which do not contain power utilizing elements (see 4.8.4.2).

3.5.2 Circuit isolation. Except as specified in the applicable specification sheet, the resistance between any two isolated circuits shall be 100 megohms at 100 volts (V) direct current (dc) (see 4.8.4.3).

3.5.3 Diode circuits. See applicable specification sheet.

3.5.4 Blocking diodes. See applicable specification sheet.

3.5.5 Resistors. See applicable specification sheet.

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:33Z
Check the source to verify that this is the current version before use.

3.5.6 Relay operation. See applicable specification sheet.

3.5.7 Transient voltage characteristics. See applicable specification sheet.

3.5.8 Time delay and latching circuit. See applicable specification sheet.

3.5.9 Fire warning circuit. See applicable specification sheet.

3.5.10 Environmental conditions.

3.5.10.1 Temperature.

3.5.10.1.1 Low temperature. The printed circuit card shall withstand storage in an ambient temperature of minus 70 degrees Fahrenheit (°F), and shall operate at temperatures down to minus 25°F (see 4.8.4.11.1).

3.5.10.1.2 High temperature. The printed circuit card shall withstand storage in an ambient temperature of 160°F and shall operate at temperatures up to 140°F (see 4.8.4.11.1).

3.5.10.2 Basic shock. The printed circuit card shall meet the performance requirements of 3.5.1 thru 3.5.9, during and after exposure to three shock impulses of 30 ± 3 gravity (g) intensity, 11 ± 0.2 milliseconds (ms) duration, half sine wave applied in each direction of three mutually perpendicular axes for a total of 18 impulses (see 4.8.4.11.2).

3.5.10.3 Gun firing shock. The printed circuit card shall meet the performance requirements of 3.5.1 thru 3.5.9, during and after exposure to three shock impulses of 100 ± 10 g intensity, 1.5 ± 0.2 ms duration, half sine wave form applied in each direction of three mutually perpendicular axes for a total of 18 shocks (see 4.8.4.11.3).

3.5.10.4 Vibration. The printed circuit card shall meet the performance requirements of 3.5.1 thru 3.5.9, during and after exposure to sinusoidal vibration in accordance with table I for a period of 60 minutes in each of the three mutually perpendicular axes. The vibration shall be imposed at a logarithmic sweep rate of 15 minutes per sweep cycle from 5 to 500 to 5 Hertz (Hz) (see 4.8.4.11.4).

TABLE I. Vibration levels.

Axis	Frequency (Hz)	Amplitude
Vertical	5 to 25 25 to 57 57 to 500	± 1.0 gravity (g) 0.030 inch Double Amplitude ± 5.0 g
Longitudinal and Latitudinal	5 to 25 25 to 44 44 to 500	± 1.0 g 0.030 inch Double Amplitude ± 3.0 g

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

3.5.10.5 Ballistic shock. The printed circuit card shall meet the performance requirements during and after subjection to shock impulses of 70 ± 7.0 g intensity, 0.5 ± 0.1 ms duration, half sine wave form applied in each direction of three mutually perpendicular axes (see 4.8.4.11.5).

3.6 Cross-reference to engineering and logistical support part number. Refer to table II for engineering and logistical support part number cross-reference interchangeability.

TABLE II. Cross-reference for part number interchangeability.

Engineering part number	Specification sheet part number
12282631 12316386	M62341/1A
12282607 12337028	M62341/2A
12282891	M62341/3A

3.7 Marking. Marking shall be in accordance with MIL-STD-130 and as shown on the applicable printed circuit card drawing (see 4.8.2).

3.8 Workmanship. Workmanship shall be in accordance with the workmanship requirements of MIL-STD-454, requirement 9 (see 4.8.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform or witness any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply wih all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection equipment. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the provision and maintenance of all inspection equipment necessary to assure that supplies and services conform to contract requirements. Inspection equipment must be capable of repetitive measurements to an accuracy of 10 percent of the measurement tolerance. Calibration of inspection equipment shall be in accordance with MIL-STD-45662.

4.2 Classification of inspection:

a. First article inspection (see 4.4).
b. Quality conformance inspections (see 4.5).
   1. Examination (see 4.5.2).
   2. Tests (see 4.5.3).
c. Control tests (see 4.6).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be conducted under the following conditions:

a. Air temperature 73 $\pm$ 18°F
b. Barometric pressure 28.5 + 2.0 inches of mercury (Hg)
   - 3.0
c. Relative humidity 50 $\pm$ 30 percent

4.4 First article inspection. Unless otherwise specified (see 6.2), the Government shall select printed circuit card produced under the production contract (see 6.2) for first article inspection. First article samples shall be numbered and inspected as specified in table III. Approval of the first article sample by the Government shall not relieve the contractor of his obligation to supply printed circuit card that are fully representative of those inspected as a first article sample. Any changes or deviation of the production units from the first article sample shall be subject to the approval of the contracting officer.

4.4.1 First article inspection failure. Test item deficiencies during, or as a result of, the first article test, shall be cause for rejection of the items until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiency. Any deficiency found during, or as a result of the first article test, shall be prima facie evidence that all items already produced prior to completion of the first article test are similarly deficient unless evidence satisfactory to the contracting officer is furnished by the contractor that they are not similarly deficient. Such deficiencies on all items shall be corrected by the contractor at no cost to the Government. The Government shall not final accept products until first article testing is completed to the satisfaction of the Government.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:33Z
Check the source to verify that this is the currentversion before use.

TABLE III. Classification of inspections.

Title	Requirement	Inspection	First article 1	First article 2	Quality conformance: Examination	Quality conformance: Acceptance (100%)	Control
Materials and construction	3.1 thru 3.4, 3.4.3, 3.4.4	4.8.1					
Defects (see table III and 4.5.2)	3.7, 3.8 and 3.4.1	4.8.2			X		
Weight	3.4.2	4.8.3	X	X			
Circuit continuity	3.5.1	4.8.4.2	X	X		X	
Circuit isolation	3.5.2	4.8.4.3	X	X		X	
Diode circuit characteristics	3.5.4	4.8.4.4	X	X		X	
Blocking diodes	3.5.5	4.8.4.5	X	X		X	
Resistors	3.5.6	4.8.4.6	X	X		X	
Relay operation	3.5.7	4.8.4.7	X	X		X	
Transient voltage	3.5.8	4.8.4.8	X	X		X	
Time delay and latching circuit	3.5.9	4.8.4.9	X	X		X	
Fire warning circuit	3.5.10	4.8.4.10	X	X		X	
Low temperature	3.5.10.1.1	4.8.4.11.1	X	X			X
High temperature	3.5.10.1.2	4.8.4.11.1	X	X			X
Basic shock	3.5.10.2	4.8.4.11.2	X	X			X
Gun firing shock	3.5.10.3	4.8.4.11.3	X	X			X
Vibration	3.5.10.4	4.8.4.11.4	X	X			X
Ballistic shock	3.5.10.5	4.8.4.11.5	X				X

4.5 Quality conformance inspection.

4.5.1 Sampling.

4.5.1.1 Lot formation. An inspection lot shall consist of all the printed circuit cards of one type and part number, from an identifiable production period, from one manufacturer, submitted at one time for acceptance.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:33Z
Check the source to verify that this is the current version before use.

4.5.1.2 Sampling for examination. Samples for quality conformance examination shall be selected in accordance with general inspection level II of MIL-STD-105. Before sampling may be initiated, the contractor shall establish by examination of at least 20 consecutively produced PCC that the process average percent defective, as defined in MIL-STD-105, is not greater than the specified AQLs.

4.5.2 Examination.

4.5.2.1 Acceptable quality level. Each sample selected in accordance with 4.5.1.2 shall be examined to determine conformance to the following acceptable quality levels (AQL).

Classification	AQL
Major	2.5
Minor	4.0

4.5.2.2 Classification of defects. For examination purposes, defects shall be classified as listed in table IV.

TABLE IV. Classification of defects.

Category	Defect	Method of examination
Critical	None	
Major	AQL 2.5% Defective	
101	Dimensions affecting interchangeability, out of tolerance (see 3.4).	SIE 1/
102	Improper, inadequate soldering (see 3.4.3).	Visual
103	Improper marking (see 3.7).	Visual
104	Faulty workmanship affecting function (see 3.8).	Functional
Minor	AQL 4.0% Defective	
201	Dimensions not affecting interchangeability, out of tolerance (see 3.4).	SIE 1/
202	Faulty workmanship affecting appearance (see 3.8).	Visual

1/ SIE = Standard Inspection Equipment.

4.5.3 Tests. Each PCC shall be subjected to the quality conformance tests specified in table III.

4.6 Control tests. Control tests shall be conducted at a rate of one PCC from each lot of 300 units consecutively produced, except that not more than one test shall be performed in a 3 month period, nor less than one test in a 6 month period. The printed circuit card shall be subjected to the tests specified in table III.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:33Z
Check the source to verify that this is the current version before use.

4.7 Failure. Failure of any PCC to pass any of the specified quality conformance or control tests shall be cause for the Government to refuse acceptance of the production quantity represented, until action taken by the contractor to correct defects and prevent recurrence has been approved by the Government.

4.8 Methods of inspection.

4.8.1 Materials and construction. Conformance to 3.1 through 3.4, 3.4.3, and 3.4.4 shall be determined by inspection of contractor records providing proof or certification that design, construction, processing, and materials conform to requirements. Applicable records shall include drawings, specifications, design data, receiving inspection records, processing and quality control standards, vendor catalogs and certifications, industry standards, test reports, and rating data.

4.8.2 Defects. Conformance to 3.4.1, 3.7, and 3.8 shall be determined by examination for the defects listed in table IV. Examination shall be visual, tactile, or by measurement with standard inspection equipment.

4.8.3 Weight. See applicable specification sheet.

4.8.4 Performance.

4.8.4.1 Test equipment. Performance tests shall be conducted using the following test equipment or its equivalent:

a. Oscilloscope, Hewlett Packard, model 895, 2 required.
b. Digital multimeter, John Fluke, model 8100.
c. Power supply, Hewlett Packard, model 6255A.

4.8.4.2 Circuit continuity. To determine conformance to 3.5.1, the printed circuit card shall be tested in accordance with MIL-STD-202, method 303.

4.8.4.3 Circuit isolation. To determine conformance to 3.5.2, the printed circuit card shall be tested in accordance with MIL-STD-202, method 302, test condition A.

4.8.4.4 Diode circuit characteristics. See applicable specification sheet.

4.8.4.5 Blocking diodes. See applicable specification sheet.

4.8.4.6 Resistors. See applicable specification sheet.

4.8.4.7 Relay operation. See applicable specification sheet.

4.8.4.8 Transient voltage characteristics. See applicable specification sheet.

4.8.4.9 Time delay and latching circuit. See applicable specification sheet.

Source: https://assist.dla.mil -- Downloaded: 202640-23T01:33Z
Check the source to verify that this is the current version before use.

4.8.4.10 Fire warning circuit. See applicable specification sheet.

4.8.4.11 Environmental conditions.

4.8.4.11.1 Temperature. To determine conformance to 3.5.10.1, the PCC shall be tested as follows:

a. Operation.

1. Low temperature. The printed circuit card shall be tested in accordance with MIL-STD-810, method 502, procedure II at minus 25°F.

2. High temperature. The printed circuit card shall be tested in accordance with MIL-STD-810, method 501, procedure II at 140°F.

b. Storage.

1. Low temperature. The printed circuit card shall be tested in accordance with MIL-STD-810, method 502, procedure I at minus 70°F to minus 80°F for 24 hours.

2. High temperature. The printed circuit card shall be tested in accordance with MIL-STD-810, method 501, procedure I at 160°F for 48 hours.

4.8.4.11.2 Basic shock. To determine conformance to 3.5.10.2, the printed circuit card shall be tested in accordance with MIL-STD-810, method 516, procedure I. The PCC shall be mounted using the installed interface configuration for its intended application (i.e. hard mounted to vehicle skin, bracket mounted, etc.) or equivalent. A total of three half sine wave shock pulses shall be applied in both directions along each of three mutually perpendicular axes. Unless otherwise specified in the applicable specification sheet, during exposure, monitor the PCC and verify that intermittent operation does not occur. At the conclusion of this test, examine the PCC for damage and subject it to the tests of 4.8.4.2 through 4.8.4.10.

4.8.4.11.2.1 First article. For first article test shock amplitude shall be 30 $\pm$ 3 g, 11 $\pm$ 1.1 ms.

4.8.4.11.2.2 Control test. For control testing the shock pulse shall be 25 $\pm$ 2.5 g, 11 $\pm$ 1.1 ms.

4.8.4.11.3 Gun firing shock. To determine conformance to 3.5.10.3, the printed circuit card shall be tested in accordance with MIL-STD-810, method 516, procedure IV. The PCC shall be mounted using the installed interface configuration for its intended application (i.e. hard mounted to vehicle skin, bracket mounted, etc.) or equivalent. A total of three half sine wave shock pulses shall be applied in both directions along each of three mutually perpendicular axes. During exposure, monitor the PCC and verify intermittent operation does not occur. At the conclusion of this test, examine the PCC for damage and subject it to the tests of 4.8.4.2 and 4.8.4.3.

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:33Z
Check the source to verify that this is the current version before use.

4.8.4.11.3.1 First article. For first article testing peak amplitude shall be 100 ± 10 g, 1.5 ± 0.2 ms.

4.8.4.11.3.2 Control tests. For control testing the peak amplitude shall be 75 ± 8 g, 1.5 ± 0.2 ms.

4.8.4.11.4 Vibration. To determine conformance to 3.5.10.4, the printed circuit card shall be tested in accordance with MIL-STD-810, method 514, procedure VIII. The PCC shall be mounted using the installed interface configuration for its intended application (i.e. hard mounted to vehicle skin, bracket mounted, etc.) or equivalent. During exposure, monitor the PCC and verify that intermittent operation does not occur and test in accordance with 4.8.4.5 once in each axis. At the conclusion of this test, the PCC shall be returned to room ambient temperature examined for damage, and subjected to the performance test of 4.8.4.2 through 4.8.4.6.

4.8.4.11.4.1 First article. The vibration schedule shall be in accordance with 3.5.10.4 for a total of 60 minutes in each of the three mutually perpendicular axes at an ambient temperature of 140°F.

4.8.4.11.4.2 Control test. For control testing the temperature shall be 73 ± 18°F and the exposure time shall be 90 minutes.

4.8.4.11.5 Ballistic shock. To determine conformance to 3.5.6.5, the printed circuit card shall be tested in accordance with MIL-STD-810, method 516, procedure I, except that conditions of 3.5.4.5 shall apply. At the conclusion of the test, the PCC shall be subjected to and pass the performance test of 4.8.4.2 and 4.8.4.3.

5. PACKAGING

5.1 Packaging requirements. Unit protection shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. The printed circuit card assemblies shall be packaged as specified in MIL-STD-2073-2, coded as follows: GX-1-XX-XX-XX-X-NS-A-2-39.

5.1.2 Level B and C. The printed circuit card assemblies shall be packaged the same as Level A, coded as follows: GX-1-XX-XX-XX-X-NS-(B or C)-F-39.

5.2 Marking. Marking shall be IAW the requirements of MIL-STD-129 for military levels of protection.

6. NOTES

6.1 Intended use. Printed circuit cards conforming to this specification are intended to provide electronic circuitry for the M1 Driver's Instrument Panel and the Turret Network Box, as follows.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.

Printed Circuit Card	Driver's Instrument Panel DIP-A3	Driver's Instrument Panel DIP-A1	Turret Network Box (TNB-A4)
Type I:			
Class 1	X		
Class 2		X	
Type II:			
Class 1	X		
Class 2		X	
Type III:			X

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Title, number, and date of the applicable detailed specifications.
c. Type and drawing number, title, and date (see 3.4).
d. If first article samples are not required (see 3.1).
e. If responsibility for inspection shall be other than as specified (see 4.1).
f. If responsibility for inspection equipment shall be other than as specified (see 4.1.1).
g. If inspection conditions shall be other than as specified (see 4.3).
h. If first article inspection is not required (see 4.4).
i. Selection of applicable level and packaging standard or packaging data sheet (see 5.1).

6.3 Recycled materials. The use of recycled materials which meet the requirements of the applicable material specification without jeopardizing the intended use of the item shall be encouraged (see 3.3).

6.4 Subject term (key word) listing.

Circuit, Card, Printed, M1 and M1A1 Tank.
Card, Circuit, Printed, M1 and M1A1 Tank.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - AT

Preparing activity:
Army - AT

(Project 1240-A860)

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:33Z
Check the source to verify that this is the current version before use.