MIL-R-51344B(MI)
1 July 1982
Superseding
MIL-R-51344A(MI)
17 February 1976

MILITARY SPECIFICATION

* ROCKET, INCENDIARY, 66MM, TPA,

4-ROUND CLIP, M74 OR M74A1

This specification is approved for use by the US Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of loaded clip and a launcher.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

	SPECIFICATION	
	FEDERAL	
*	QQ-S-781	Steel Strapping, Flat
	MILITARY	
	MIL-P-116	Preservation, Methods of
*	MIL-B-2427	Box, Ammunition Packing, Wood, Nailed
*	MIL-H-6088	Heat Treatment of Aluminum Alloys
	MIL-W-45205	Welding, Gas Metal - Arc and Gas Tungsten-Arc, Aluminum Alloys, Readily Weldable for Structures, Excluding Armor - Edgewood Arsenal Interim Appendix

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Missile Command, ATTN: DRSMI-RSDS, Redstone Arsenal, AL 35898, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC-1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

	MIL-B-46506	Boxes, Ammunition Packing, Wood, Wirebound

STANDARDS

Military

	MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
*	MIL-STD-129	Marking for Shipmnet and Storage
	MIL-STD-810	Environmental Test Methods
	MIL-STD-1168	Lot Numbering of Ammunition

* 2.1.2 Other government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

Army

	DL147-1-39	Rocket, Incendiary, 66MM, TPA, 4-Round Clip, M74
	IDL147-1-39	Rocket, Incendiary, 66MM, TPA, 4-Round Clip, M74, Inspection Data List
*	11508965	Rocket, Incendiary, 66MM, TPA, 4-Round Clip, M74A1
*	19-48-4138/70	Utilization Procedures for Boxed Ammunition and Components on 4-Way Entry Pallets (Defense Ammunition Center, Savanna, IL).

PUBLICATIONS

Army

Edgewood Arsenal Interim Appendix to Military Specification MIL-W-45205, Welding, Gas Metal-Arc and Gas Tungsten-Arc. Aluminum Alloys, Readily Weldable for Structures, Excluding Armor.

* (Copies of specifications, standards, drawings and publications required by suppliers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

* 2.3 Order of precedence. In the event a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials and components.

* 3.1.1 Materials. All materials cited on Drawing DL147-1-39,or 11508965 or on subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

* 3.1.2 Components. All components of the clip and rocket shall conform to the specifications and drawings listed on Drawing DL147-1-39, or 11508965 and subsidiary drawings.

* 3.2 Assembly. The clip and rocket shall be assembled in accordance with Drawing E147-1-39 or 11508965 (see 6.3).

* 3.3 Inner tube. The inner tube, Drawing D147-1-2 (M74) or inner tube assy D147-1-349 (M74A1), shall not leak or be permanently deformed when subjected to an internal hydrostatic pressure of 300 ±30 pounds per square inch gage (psig) when tested as specified in 4.4.4.1.

3.4 Warhead.

3.4.1 Fuze well assembly. The fuze well, Drawing C147-1-33, shall not leak when subjected to an internal air pressure of 100 ±10 psig when tested as specified in 4.4.4.2.

* 3.4.2 Case assembly. The case assembly, Drawing C147-1-29 (M74) or 11508966 (M74A1) shall not leak when subjected to an internal air pressure of 100 ± 10 psig when tested as specified in 4.4.4.3.

3.4.3 Cleaning. The case assembly (3.4.2) shall be thoroughly flushed internally with a suitable solvent and be free from contamination, clean and dry internally prior to filling.

* 3.4.4 Leakage. The filled and closed warhead, Drawing C147-1-30 (M74) or 11508967 (M74A1)shall not leak when submerged in water maintained at a temperature of 175° ± 5° F when tested as specified in 4.4.4.4.

* 3.4.5 Filling. The filled warhead shall contain 590 ± 20 grams of fill and the atmosphere in the dry box shall be clean, dry nitrogen and contain no more than 25 parts per million of oxygen and no more than 25 parts per million of water when tested as specified in 4.4.4.5 (see 6.3). The actual fill weight to be such that total rocket weight is 1338 ± 20 grams (M74) or 1408 ± 20 grams (M74A1) (see 3.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

* 3.4.6 Burst. The case assembly, Drawing D147-1-29 (M74) or 11508966 (M74A1) shall not burst when subjected to a minimum hydrostatic pressure of 1100 psi when tested as specified in 4.4.4.6 (see 6.3).

* 3.4.7 Artifically age. The case assembly, drawing 11508960 (M74A1) shall be artificially aged to T6 condition per MIL-H-6088 after welding.

* 3.5 Rocket. The rocket (dwg E147-1-150) (M74) or 11508964 (M74A1) shall weight 1338 ± 20 grams (M74) or 1408 ± 20 grams (M74A1).

* 3.6 Fuze assembly. The primacord shall withstand a pull of 8 + 0.1 pounds for a minimum of 5 seconds without movement in, or separation from, the retaining plug when tested in accordance with 4.4.4.7.

* 3.7 Manifold, primer, clip. The clip primer manifold, Drawing D147-1-3 (M74) or D147-1-350 (M74A1) shall have no overflow of 9205316 (RTV-102) sealant used around the M56 igniter. The face of the primer, locating pin holes, clip retainer slots and the manifold bore which accepts firing mechanism shall be clean and free of sealant when inspected as specified in 4.4.4.10.

3.8 Clip retainer. The clip retainer shall require a force of 10 ± 5 pounds to disengage it from the firing mechanism when tested as specified in 4.4.4.8.

* 3.9 Vibration. The loaded clip, Drawing E147-1-39, or 11508965 shall not be damaged and shall meet the requirements of 3.10 after testing as specified in 4.4.4.13.

3.10 Functioning. The rockets shall fire and impact on a target 200 meters from point of launch when tested as specified in 4.4.4.9. The target shall be 7-1/2 by 7-1/2 feet by 1 inch thick wood and the warheads shall disseminate ignited fuel for a minimum distance of 10 meters either side of impact point on target. Aiming point shall be the center of the target.

* 3.11 Rocket retainer. When assembled in accordance with Drawing E147-1-39, or 11508964 the maximum horizontal end play between warhead and inner tube shall be 3/16 inch when tested as specified in 4.4.4.11.

3.12 Bail. The bail, Drawing C147-1-11, shall readily snap back to its stowed position when released from its fully extended position. No interferance between parts is permitted when tested as specified in 4.4.4.12.

3.13 Preproduction. Prior to the start of regular production a preproduction sample of clip and rocket assemblies shall be produced in accordance with this specification for examination and test (see 4.3).

3.14 Workmanship. The clip and rocket assembly shall be free from foreign matter (dirt, oil or grease) and damage such as dents, cracks, burrs, or deformation which could affect its intended use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

* 4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)

(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of four clips containing 16 rockets shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

* 4.3.2.1 For examinations, inspections, and nondestructive tests. The sample clips, rockets and components shall be examined, inspected and tested in accordance with 4.4.3.5, 4.4.3.6, 4.4.4.13, and the applicable drawings. The AQL's do not apply or acceptance number is zero.

* 4.3.2.2 For ballistic tests. The sample clips, rockets and components shall be tested in accordance with 4.4.4.9.

* 4.3.3 Acceptance/rejection criteria. When any item of the preproduction sample fails to meet any of the requirements of Section 3, when examined, inspected and tested in accordance with 4.3.2, the sample shall be considered defective. The acceptance/rejection criteria shall be in accordance with Table 1. The supplier shall obtain written approval from the contracting officer prior to preceding with regular production. Accept/reject number (Table 1) refers to rockets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

* TABLE I

REQUIREMENTS	ACCEPT/REJECT NUMBER
Examinations, inspections, and nondestructive test	0/1 Defective
Functioning	
Hit Target	2/3 Defective
Warhead Burst	0/1 Defective
Fuel Dissemination	0/1 Defective

4.4 Quality conformance inspection.

4.4.1 Lotting.

(a) Rocket, 4 round clip, M74. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in any one interfix number of clips, no more than one interfix number from one manufacturer of the following components is permitted.

(1) Warhead, M235
* (2) Rocket motor, M54 or M123
* (3) Fuze, M434

(b) Warhead, M235. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in any one interfix number of warheads, no more than one interfix number from one manufacturer of the following components is permitted.

(1) Case assembly
(2) Thickened triethylaluminum

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive tests.

(a) Clips and rockets. Sampling shall be conducted in accordance MIL-STD-105.

(b) Components. Sampling shall be conducted in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

4.4.2.2 For destructive tests.

(a) Rockets and clips. Sampling shall be conducted in accordance with MIL-STD-105, inspection level S-4, based on number of rockets. Sufficient number of clips shall be selected to provide the required number of rockets.

(b) Case assembly. Sampling shall be conducted in accordance with Edgewood Arsenal Interim Appendix to MIL-W-45205.

* 4.4.3 Inspection procedures.

4.4.3.1 For examination and nondestructive tests.

* (a) Clips and rockets. The sample clips and rockets shall be examined, inspected, and tested in accordance with 4.4.3.6, the applicable drawings, and MIL-STD-105.

* (b) Components. The sample components shall be tested in accordance with 4.4.3.5.

4.4.3.2 For destructive tests.

* (a) The sample rockets and clips shall be tested in accordance with 4.4.4.9.

* (b) Case Assembly. The sample case assembly shall be tested in accordance with 4.4.4.6.

4.4.3.3 For critical defects. Each item in the lot shall be tested for the critical characteristics listed in the classification of defects.

* 4.4.3.4 Acceptance/Rejection criteria. When any item of the quality conformance sample fails to meet any of the requirements of section 3; when examined, inspected and/or tested in accordance with 4.4.4; the sample shall be considered defective. Unless otherwise stated in this document or the contract, the accept/reject number shall be in accordance with the AQL and MIL-STD-105. When 100% inspection is required, each item in the lot shall be tested for that defect and those items which are defective shall be rejected.

* 4.4.3.5 Components classification of defects. (See inspection data list IDL147-1-39 (M74) for inspection equipment required to perform the examinations and test specified in this section.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

* (a) Tube, inner (drawing D147-1-2 M74) or (drawing D147-1-349 M74A1)

Categories	Defects	Requirement	Test
Critical: 100% inspection			
1	Leakage	3.3	4.4.4.1

* (b) Fuze well (drawing C147-1-33).

Categories	Defects	Requirement	Test
Critical: 100% inspection			
1	Leakage	3.4.1	4.4.4.2

* (c) Case Assembly (drawing D147-1-29 M74 or (dwg 11508966 M74A1)

Categories	Defects	Requirement	Test
Critical: 100% inspection			
1	Leakage	3.4.2	4.4.4.3
2	Interior contamination	3.4.3	4.4.4.3
* 3	Artifically aged	3.4.7	4.4.4.14
Critical:	Sampling and accept/reject number per Edgewood Arsenal Interim Appendix to MIL-W-45205.		
* 4	Burst	3.4.6	4.4.4.6

* (d) Fuze assembly (drawing D147-1-174).

Categories	Defects	Requirement	Test
Critical	None defined		
Major:	AQL 0.10 percent defective		
101	Primacord Assembly Alignment	Note 6 of Dwg D147-1-174	
102	Open end of primacord not dipped in adhseive	Note 3 of Dwg D147-1-174	
103	Primacord cemented incorrectly	3.6	4.4.4.7
104	Fuze cover base deformed	Note 7 of Dwg D147-1-174	
105	Workmanship	3.14	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

* (e) Warhead, 66MM rocket, incendiary, TDA M235 (dwg C147-1-30, M74 or drawing 11508967, M74A1).

Categories	Defects	Requirement	Test
Critical: 100% Inspection			
1	Leakage	3.4.4	4.4.4.4
2	Filling Smoke	3.4.5	4.4.4.5
3	Not Marked with yellow band	Note 8 of Dwg 11508967	
Major: 100% Inspection			
101	Workmanship	3.14	Visual

* 4.4.3.6 Clip and Rockets Classification of Defects.

* (a) Preparation for delivery (Section 5).

Categories	Defects	Requirement	Test
Critical: None defined			
Major:	AQL 1.0 percent detective		
101	Not cleaned	5.1.1	MIL-P-116
* 102	Bag not sealed	5.1.1	MIL-P-116
103	Loose Pack	5.2	Visual
104	Seams and joints not sealed	5.2	MIL-B-46506
105	Container incorrect	5.2	MIL-B-46506
106	Strapping loose or missing	5.2	Visual
107	Vermiculite missing or excessive causing bulging of box	5.2	Visual
108	Marking illegible or incorrect	5.3	Visual
109	Bag ruptured	5.1.2	MIL-P-116
110	Clip wrap or cap missing or incorrect	5.1.2	Visual
111	Wet preservative	5.2	MIL-B-2427
112	Palletization incorrect	5.4	Dwg D147-1-158

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

* (b) Clip assembly (drawing D147-1-1, M74), or Rocket and Inner tube assembly drawings 11509031, M74A1).

Categories	Defects	Requirement	Tests
Critical:	None Defined		
Major: 100% Inspection			
* 101	Tube location incorrect	D147-1-1, M74 only	Gage
* 103	Workmanship	3.14	Visual

(c) Rocket incendiary, 66MM, TPA (Drawing E147-1-150 M74 or Drawing 11508964 M74A1).

Categories	Defects	Requirement	Tests
Critical:	None Defined		
Major: 100% Inspection			
101	Concentricity incorrect	Drawing	Gage
102	Dimension (7.880-7.942) incorrect	Drawing	Gage
103	Weight incorrect	3.5	Scale
104	Workmanship	3.14	Visual
* 105	Clip retainer pull force incorrect	3.8	4.4.4.8

* (d) Rocket incendiary, 66MM, TPA, 4-round clip (Drawing E147-1-39, M74 or drawing 11508965, M74A1).

Categories	Defects	Requirement	Tests
Critical:	None defined		
Major: 100% Inspection			
101	Excess RTV sealant	3.7	4.4.4.10
102	Rocket retainer end play incorrect	3.11	4.4.4.11
103	Bail extended and stowed position incorrect	3.12	4.4.4.12
104	Workmanship	3.14	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

4.4.4 Tests. Tests shall be conducted as follows: (See inspection data list IDL147-1-39 for inspection equipment required to perform the tests specified in this section.)

4.4.4.1 Inner tube. Subject the inner tube to the specified hydrostatic pressure employing a suitable fixture for a minimum period of 5 seconds. Check for leakage, release pressure, and check for deformation.

4.4.4.2 Fuze well. Subject the fuze well to the specified air pressure employing a suitable adapter. Submerge in water containing a wetting agent, and check for a minimum of 20 seconds for leakage.

4.4.4.3 Case assembly. Subject the case assembly to the specified air pressure employing a suitable adapter. Submerge in water containing a wetting agent, and check for a minimum period of 20 seconds for leakage. After cleaning per 3.4.3, the case assembly shall be examined for the precents of any foreign matter, corrosion or any other contamination that would be detrimental to the case assembly or the end item.

4.4.4.4 Leakage. Seal or plug the fuze well prior to submerging the filled warhead in water held at the specified temperature for a minimum period of 3 minutes. Bubbles shall indicate leakage. After removing from water, evidence of chalky white deposit or smoke indicates leakage.

4.4.4.5 Filling. Fill the warhead with the specified quantity of fill. Absence of smoke in the dry box atmosphere shall be considered sufficient evidence that specified condition exists.

4.4.4.6 Burst. Subject the case assembly to the specified hydrostatic pressure and test in accordance with Edgewood Arsenal Intermim Appendix to MIL-W-45206.

4.4.4.7 Fuze assembly. Apply the specified pull to the primacord and observe for any primacord movement in or separation from the retaining plug.

4.4.4.8 Clip retainer. Attach a spring gage tester to the clip retainer, and pull. Record the force required to effect separation from firing mechanism.

4.4.4.9 Functioning. Insert loaded clip into launcher and pull trigger. The specified number of sample rockets shall hit target, burst and disseminate fuel as required.

4.4.4.10 Manifold, primer, clip. After manifold cover is assembled and RTV sealant has permanently cured, visually inspect for specified requirements.

4.4.4.11 Rocket retainer. When the inner tube is securely held, pull warhead in direction of fire and measure separation to assure it does not exceed specified distance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

4.4.4.12 Bail. Pull the bail into fully extended position and release.

* 4.4.4.13 Vibration test. The test samples shall consist of two unpackaged loaded clip assemblies inserted into launchers in the carrying configuration and two loaded clip assemblies in their polystyrene containers. The above samples shall be tested in accordance with Method 514, table 514-I, equipment category (h), procedure XI, part 2, test type-bounce, loose cargo of MIL-STD-810, except that the time shall be 11 minutes of which 6 minutes shall be on one side and 5 minutes on the other side.

* 4.4.4.14 Hardness of case assemblies. Hardness of case assemblies shall be verified to the requirement of para 3.4.7 by one of the methods of MIL-H-6088.

* 5. PACKAGING.

* 5.1 Preservation. Preservation, packaging, packing, palletization and marking shall be Level A.

* 5.1.1 Level A. One rocket clip shall be wrapped and protected, placed in a heat sealed barrier bag, and then packaged in a molded polystyrene container as specified on drawing D147-1-151(M74) or 11508983 (M74A1). Before packaged in the container, the sealed barrier bag assembly shall be tested for leakage in accordance with the leak test requirements of MIL-P-116. The container shall then be packaged with the rocket clip nose down in a fiberboard box as specified on drawing C147-1-153 (M74) or 11508984 (M74A1).

* 5.2 Packing

* 5.2.1 Level A. Four rocket clips, packaged as specified in 5.1.1, shall be packed in wirebound boxes having inside dimensions of approximately 23 by 23 by 26-3/4 inches, length, width and depth respectively. The boxes shall conform to type I, class 2, grade A of MIL-B-46506 and the weight of contents is approximately 96 lbs. Filler pads of material conforming to weather-resistant class, type CF, grade V3C of PPP-F-320 shall be included, as necessary, to ensure a tight pack. The boxes shall be assembled and closed in accordance with 6.5 of MIL-B-46506 and to prevent pilferage, the boxes shall be strapped with one strap applied girthwise, approximately center of the box; over the sides, top and bottom and under sufficient tension to firmly grip the edges of the face material. The strapping shall be 3/8 by .020 inches and conform to type 1, class B of QQ-S-781. Prior to packing items in the treated shipping containers the preservation must be dry when tested for dyness in accordance with MIL-B-2427.

* 5.3 Marking. Marking shall be in accordance with MIL-STD-129. Interior package shall be marked in accordance with Drawing C147-1-153 for M74, or 11508984 for M74A1. Exterior containers shall be marked in accordance with Drawing D147-1-159 for M74 or Drawing 11509039 for M74A1.

* 5.4 Palletization. When specified in the contract or order, rocket clips packed in accordance with 5.2, shall be palletized in accordance with Drawing 19-48-4138/70.

6. NOTES

* 6.1 Intended use. This item is intended to neutralize hard, soft or jungle-type targets and is a component of the M202 launcher.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
* (b) Launcher, M202 (will be Government furnished when required).
(c) Palletization, if required.
(d) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.

(2) Name and address of test facility and shipping instructions when testing is performed by the Government.

(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Cautuion. Due to the hazards attending the testing of items with high pressures, live firing and filling, suppliers are hereby advised to take all necessary precautions to protect personnel while filling testing.

* 6.4 Changes to previous issue. The margins of this specification are marked to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-MI

Review Activity:
Army-EA

Preparing Activity:
Army-MI

Project No. 1340-A618

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Msl Cmd -
ATTN: DRSMI-RSDS
Redstone Arsenal, AL 35898

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-R-51344B(MI) ROCKET, INCENDIARY, 66MM, TPA 4-ROUND CLIP, M74 or M74A1

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.