MIL-W-48846(PA)
9 June 1975
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

WARHEAD SECTION METAL COMPONENTS

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of metal components entitled Warhead Section Metal Components which are used on the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8846005	- Static Probe Protector Assembly.
8846007	- Band Assembly.
8846035	- Intermediate Plate.
8846050	- Nose Section Weldment Assembly.
8846074	- Transponder Weldment Assembly.
8846117	- Band, Intermediate Section.
8846120	- Band, End Section.
8846137	- Warhead Section Weldment.
8846262	- Bracket, Fail-Safe.
8846266	- Bracket, Arm-Safe.
8846272	- Bracket, Connector.
8846328	- Warhead Weldment Assembly.
EL-8855806	- Equipment Lists.

FSC: 1115

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The metal components shall comply with all requirements specified on the drawings (dwg) 8846005, 8846007, 8846035, 8846050, 8846074, 8846137 and 8846328, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwgs 8846005, 8846007, 8846035, 8846050, 8846074, 8846137 and 8846328) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

90

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Static probe protector assembly (see dwg 8846005).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Stabilizer block missing or not securely in place	Visual
	102. Stabilizer channel missing or not securely in place	Visual
	103. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Location of centerline of channel stabilizer (9.13)	Gage
	202. Diameter across channel stabilizer (5.06)	Gage
	203. Length of channel stabilizer (3.81)	Gage
	204. Deformation in any area	Visual
	205. Marking missing, misleading, or unidentifiable	Visual
	206. Foreign matter in assembly unless removable	Visual
	207. Painting defective to extent it shows primer coat or bare metal	Visual
	208. Evidence of poor workmanship (see 3.4)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Band intermediate section and end sections (see dwg 8846117).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Total length	Gage
202.	Width of band	Gage
203.	Angle of band	Gage
204.	Evidence of poor workmanship (see 3.4)	Visual

4.3.2.1.3 Band assembly (see dwg. 8846007).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Band assembly mounting holes improperly drilled	Gage
102.	Band assembly mounting holes improperly located	Gage
103.	Band assembly mounting holes improperly bumped	Gage
104.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Deformation in any area	Visual
202.	Evidence of poor workmanship (see 3.4)	Visual
203.	Markings missing, misleading, or unidentifiable	Visaul
204.	Painting defective to extent it shows primer coat or bare metal	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

95

4.3.2.1.4 Intermediate plate assembly (see dwg 8846035).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Mounting holes improperly located	Gage
102.	Mounting holes improperly drilled	Gage
103.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Outside diameter	Gage
202.	Thickness of plate	Gage
203.	Deformation in any area	Visual
204.	Evidence of poor workmanship (see 3.4)	Visual
205.	Painting defective to extent it shows primer coat or bare metal	Visual

4.3.2.1.5 Nose section weldment assembly (see dwg. 8846050).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Hoist point hole improperly located	Gage
102.	Hoist point hole improperly tapped	Gage
103.	Hoist point hole improperly counterbored	Gage
104.	Mounting holes at station 18 improperly located	Gage
105.	Mounting holes at station 18 improperly tapped	Gage
106.	Mounting holes at station 87.5 improperly drilled	Gage
107.	Mounting holes at station 87.5 improperly located	Gage

95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

108.	Lifting eye adapter holes improperly located	Gage
109.	Lifting eye adapter holes improperly tapped	Gage
110.	Transponder bracket assembly missing or loose	Visual
111.	Fail safe bracket assembly missing or loose	Visual
112.	Plug mounting angle bracket missing or loose	Visual
113.	Harness mounting angle brackets missing or loose	Visual
114.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Total length	Gage
202.	Location of mounting ring on cone	Gage
203.	Location of first reinforcing ring	Gage
204.	Location of second reinforcing ring	Gage
205.	Location of door flare	Gage
206.	Evidence of poor workmanship (see 3.4)	Visual
207.	Foreign matter in Nose Section unless removable	Visual
208.	Markings missing, misleading, or unidentifiable	Visual
209.	Painting defective to extent it shows primer coat or bare metal	Visual

4.3.2.1.6 Transponder weldment assembly (see dwg 8846074).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

95

Minor:

201. Location of centerline of transponder support from face to bracket.....Gage
202. Length of transponder support.....Gage
203. Deformation in any area.....Visual
204. Evidence of poor workmanship (see 3.4).....Visual
205. Foreign matter in assembly unless removable.....Visual
206. Painting defective to extent it shows primer coat or bare metal.....Visual
207. End plate not flat.....Visual

4.3.2.1.7 Warhead section weldment (see dwg 8846137).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101. Mounting holes at station 87.5 improperly located.....Gage
102. Mounting holes at station 87.5 improperly tapped.....Gage
103. Mounting holes at station 150 improperly located.....Gage
104. Mounting holes at station 150 improperly drilled.....Gage
105. Door frame mounting holes improperly located.....Gage
106. Door frame mounting holes improper size.....Gage
107. Mounting holes at station 136 improperly located.....Gage
108. Mounting holes at station 136 improperly tapped.....Gage
109. P5 connector bracket missing or loose (see 8846272).....Visual
110. Launcher lug station 150 missing or loose .....Visual
111. Fail-safe bracket missing or loose (see 8846262).....Visual
112. Arm-safe bracket missing or loose (see 8846266).....Visual
113. Cable clips missing or loose.....Visual
114. Objective evidence relative to material missing or improper (see 3.1).....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:

201.	Diameter of warhead section	Gage
202.	Diameter of bulkhead flange	Gage
203.	Diameter of pilot	Gage
204.	Diameter of warhead section at weld	Gage
205.	Diameter of reinforcing ring	Gage
206.	Location of door fastener	Gage
207.	Total length	Gage
208.	Location of lifting hoist connector	Gage
209.	Clearance around arm and safe door	Gage
210.	Location of warhead ring support	Gage
211.	Evidence of poor workmanship (see 3.4)	Visual
212.	Deformation in any area	Visual
213.	Foreign matter in assembly	Visual
214.	Painting defective to extent it shows primer coat or bare metal	Visual

4.3.2.1.8 Warhead weldment assembly (see dwg 8846328).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Warhead weldment flange mounting holes improperly drilled	Gage
102.	Warhead weldment flange mounting holes improperly located	Gage
103.	Tapped holes improperly located	Gage
104.	Tapped holes improperly tapped	Gage
105.	Reinforcing bars missing or not securely in place	Visual
106.	Dowel pins missing or not securely in place	Visual
107.	Dowel pins improperly located	Visual
108.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Total length from mounting flange to cartridge shell	Gage
202.	Height of locating dowel	Gage
203.	Location of mounting holes	Gage
204.	Deformation in any area	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

205. Evidence of poor workmanship (see 3.4).....Visual
206. Yellow orientating strip missing or improperly located.....Visual
207. Painting defective to extent it shows primer coat or bare metal.....Visual

4.3.2.1.9 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Preparation, packaging, and packing not in accordance with MIL-STD-1169	Visual
	102. Marking not in accordance with MIL-STD-1169	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.4)	Visual

4.3.3 Testing. There are no tests applicable to this specification.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8855806). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The metal components shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The metal components shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Levels A and C. The metal components shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description X-PA-PD-2125 dated 7 March 1962.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1115-A059

☆ U. S. GOVERNMENT PRINTING OFFICE: 1975-603-766/0665

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

6065 S/S

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.