INCH-POUND

MIL-PRF-914A
AMENDMENT 2
11 August 2000
SUPERSEDING
AMENDMENT 1
19 December 1997

PERFORMANCE SPECIFICATION

RESISTORS NETWORKS, FIXED, FILM, SURFACE MOUNT,
NONESTABLISHED RELIABILITY, AND ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-914A, dated 3 July 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I, delete and substitute.

"TABLE I. Characteristics.

Test or condition	Characteristics						Units
	R	V	H	K	M	C 1/	
Resistance-temperature characteristic (see 3.13)	±25	±50	±50	±100	±300	±50	ppm/°C
Tracking to the reference element	±5	±5	2/	2/	2/	±5	
Maximum ambient temperature at rated wattage (see 3.6)	70	70	70	70	70	70	°C
Maximum ambient temperature at zero power derating (see figure 1)	125	125	125	125	125	125	
Maximum ambient temperature at rated wattage (see 3.6)	70	70	70	70	70	70	Maximum percent change in resistance (0.01 ohm additional allowed for measure-ment error). When applicable maximum percent change in resistance ratio.
Maximum ambient temperature at zero power derating (see figure 1)	125	125	125	125	125	125	
Thermal shock (see 3.8) and Power conditioning (see 3.9) ΔR ΔRatio	±.25 ±.03	±.25 ±.03	±.50 3/	±.70 3/	±.70 3/	±.25 ±.03	
Thermal shock (see 3.8) ΔR ΔRatio	±.15 ±.03	±.15 ±.03	±.25 3/	±.50 3/	±.50 3/	±.15 ±.03	
Low temperature operation (see 3.14) ΔR ΔRatio	±.10 ±.02	±.10 ±.02	±.10 3/	±.25 3/	±.50 3/	±.10 ±.02	

See footnotes at end of table.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:53Z
Check the source to verify that this is the current version before use.

TABLE I. Characteristics – Continued.

Test or condition		Characteristics R	V	H	K	M	C 1/	Units
Short-time overload (see 3.15)	ΔR ΔRatio	±.10 ±.02	±.10 ±.02	±.10 3/	±.25 3/	±.50 3/	±.10 ±.02	Maximum percent change in resistance (0.01 ohm additional allowed for measure-ment error). When applicable maximum percent change in resistance ratio.
Terminal strength (see 3.17)	ΔR ΔRatio	±.10 ±.03	±.10 ±.03	±.25 3/	±.25 3/	±.25 3/	±.10 ±.03	
Resistance to bonding exposure (see 3.20)	ΔR ΔRatio	±.25 ±.02	±.25 ±.02	±.25 3/	±.25 3/	±.25 3/	±.25 ±.02	
Moisture resistance (see 3.21)	ΔR ΔRatio	±.20 ±.02	±.20 ±.02	±.40 3/	±.50 3/	±.50 3/	±.20 ±.02	
Shock, specified pulse (see 3.22)	ΔR ΔRatio	±.25 ±.03	±.25 ±.03	±.25 3/	±.25 3/	±.25 3/	±.25 ±.03	
Vibration, high frequency (see 3.23)	ΔR ΔRatio	±.25 ±.03	±.25 ±.03	±.25 3/	±.25 3/	±.25 3/	±.25 ±.03	
Life (see 3.24.1)	ΔR ΔRatio	±.50 ±.03	±.50 ±.03	±.50 3/	±.50 3/	±2.0 3/	±.50 ±.03	
FR level		±2.0	±2.0	±2.0	±2.0	±2.0	±2.0	
High temperature Exposure (see 3.25)	ΔR ΔRatio	±.10 ±.03	±.10 ±.03	±.20 3/	±.50 3/	±1.0 3/	±.10 ±.03	
Low temperature storage (see 3.26)	ΔR ΔRatio	±.10 ±.02	±.10 ±.02	±.10 3/	±.25 3/	±.50 3/	±.10 ±.02	
Steady-state humidity (see 3.28)	ΔR ΔRatio	±.20 ±.02	±.20 ±.02	±.40 3/	±.50 3/	±.50 3/	±.20 ±.02	
Insulation resistance (see 3.19)		10,000	10,000	10,000	10,000	10,000	10,000	megohms
Resistance, tolerance and, when applicable, resistance ratio accuracy (see table VIII) 4/		B D F	B D F	B D F	D F G J	F G J	B D F	± percent

1/ Hermetically sealed resistor network (see 3.27).
2/ Not applicable.
3/ Delta ratio are not applicable.
4/ See 3.10.3.

PAGE 20

4.5h, delete “P” and substitute “M”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:53Z
Check the source to verify that this is the current version before use.

PAGE 41

6.2c, delete and substitute.

"c. Packaging requirements (e.g., Electrostatic discharge (ESD) sensitivity) (see 5.1)."

PAGE 42

A.3.1, delete "P" and substitute "M".

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 19
NASA - NA

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5905-1589)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:53Z
Check the source to verify that this is the current version before use.