INCH-POUND
MIL-DTL-55302/1E
22 October 2008
SUPERSEDING
MIL-DTL-55302/1D
3 February 2003

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, PIN CONTACTS, RIGHT-ANGLE, FOR PRINTED WIRING BOARDS (.150 SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.






FIGURE 1. Connectors, plug (.100 spacing).


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:43Z
Check the source to verify that this is the current version before use.



HOLE GRID FOR 12 & 28 CONTACTS
COMPONENT SIDE



HOLE GRID FOR 7, 17 & 23 CONTACTS
COMPONENT SIDE



ARRANGEMENT FOR 12 & 28 CONTACTS

Dash no.	No. of contacts	A ±.005	B basic	C ref	D ref
01	7	.800	.650	.450	.300
02	12	1.200	1.050	.850	.750
03	17	1.550	1.400	1.200	1.050
04	23	2.000	1.850	1.650	1.500
05	28	2.400	2.250	2.050	1.950

FIGURE 1. Connectors, plug (.100 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:43Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.002	.05	.044	1.12	.100	2.54	.200	5.08	.750	19.05	1.850	46.99
.004	.10	.050	1.27	.120	3.05	.205	5.21	.800	20.32	1.950	49.53
.005	.13	.0515	1.308	.121	3.07	.245	6.22	.850	21.59	2.000	50.80
.007	.18	.0525	1.334	.122	3.10	.250	6.35	1.050	26.67	2.050	52.07
.009	.23	.055	1.40	.129	3.28	.255	6.48	1.200	30.48	2.250	57.15
.012	.30	.065	1.65	.140	3.56	.265	6.73	1.400	35.56	2.400	60.96
.026	.66	.079	2.01	.150	3.81	.300	7.62	1.500	38.10		
.028	.71	.080	2.03	.173	4.39	.450	11.43	1.550	39.37		
.039	.99	.084	2.13	.187	4.75	.650	16.51	1.650	41.91		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm) on three place decimals and ±2° on angles.
4. These connectors mate with connectors specified in MIL-DTL-55302/2 and are primarily for use with single-sided, double sided, or multilayered printed wiring boards.
5. Positional tolerances of guide pins shall apply at datum plane X.
6. Pad(s) suitable for printed circuit board support ate required. Dimensions and location(s) are optional.
7. The termination side and the side opposite mating face of the plug may be open or solid construction.

FIGURE 1. Connectors, plug (.100 spacing) - Continued.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Material:
Guide pins and guide bushing: Brass composition B, 60,000 to 70,000 PSI tensile, as specified in ASTM B134/B134M, or FC brass as specified in ASTM B16/B16M.

Plating:
Guide pins and guide bushings: Gold over copper, type II, class 1.27, grade C, in accordance with ASTM B488.

Contact: Gold in accordance with ASTM B488, type II, grade C, class 1.27, over nickel plating in accordance with appendix A of MIL-DTL-38999, class 2, 50 to 150 microinches.

Contact identification: Shall be alphabetical and sequential in the pattern indicated, using upper case characters followed by lower case characters.

Pin size: 23.

Wire size: 22.

Current rating: 5 amperes, maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:43Z
Check the source to verify that this is the current version before use.

Mating and unmating: The maximum insertion force, in pounds shall not exceed a value equal to 0.5 times the number of contacts, and the withdrawal force, in pounds, shall be a minimum of 0.11 times the number of contacts, and shall not exceed the measured insertion force.

Contact resistance: The average resistance of all contact pairs measured shall not exceed .010 ohm, and no individual contact pair shall have a resistance exceeding .020 ohm.

Dielectric withstanding voltage:

Sea level: 1,000 volts rms, 60 Hz, ac.
High altitude: 500 volts rms, 60 Hz, ac.

Part or Identifying Number (PIN): M55302/1-(dash number on figure 1).

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/2
MIL-DTL-38999
ASTM B16/B16M
ASTM B134/B134M
ASTM B488

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy - EC
Air Force - 85
DLA – CC

Preparing activity:
DLA - CC

(Project 5935-2008-056)

Review activities:
Army – AT, AV, MI
Navy – AS, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:43Z
Check the source to verify that this is the current version before use.