INCH-POUND

MIL-C-60251A(AR)
AMENDMENT 3
11 March 1991
SUPERSEDING
AMENDMENT 2
24 July 1984

MILITARY SPECIFICATION

CARTRIDGE, 7.62MM, NATO, BALL, M80 OVERHEAD FIRE APPLICATION

This Amendment forms a part of Military Specification MIL-C-60251A(MU), dated 5 March 1971, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

Delete "AMCR 715-505, Volume 3" wherever it appears in the specification and substitute "SCATP-7.62".

PAGE 2

* 2.1 In Paragraph 2.1 add:

"9362607 - Packing and Marking for Box, Wirebound for Cartridge, 7.62mm"

PAGE 3

3.9 Delete "4 hours" and substitute "4 to 5 hours."

3.10 Delete the word "ambient" and substitute the word "room".

PAGE 8

4.3.3.1, Table II: Delete the heading "Ambient Temperature" and substitute "70 $\pm$ 2°F".

PAGE 11

4.3.3.2, Table III: Change defect numbers from "3, 4, 5, 6 and 7" to "4, 5, 6, 7 and 8" respectively. Then insert new defect number 3 as follows:

"3. Hangfire 7/ 0 -"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:23Z
Check the source to verify that this is the current version before use.

Delete defect number 3.c. and substitute the following:

"3.c. Escape of gas around primer cup 6/ 56 132"

Delete "3.c(1) and 3.c(2)" from the total of defects and substitute "3.c."

Change total of defects from "3.c and 4.a91)" to "4.c and 5.a(1)" respectively.

PAGE 12

4.4.3.2 Add footnotes 6/ and 7/ to Table III as follows:

"6/ The total number of cases in which the escape of gas is 50% or more around the primer cup shall not exceed 18 for the first sample nor more than 41 for the cumulative sample.

7/ For definition of a hangfire, see SCATP-7.62 paragraph 10.6.2."

PAGE 13

4.4.8.2: Delete "for not less than 4 hours" and substitute "for 4 to 5 hours."

4.4.8.3 Add new section 4.4.8.3 as follows:

"4.4.8.3 Room temperature tests. The test sample shall be conditioned for not less than 2 hours at 68°F to 70°F (room temperature) and fired at that temperature."

4.4.9 Delete the word "ambient" and substitute the word "room".

PAGE 14

* 5. Delete "paragraph 5" in its entirety and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Preservation and packing.

5.1.1 Packing, Level A. The cartridges shall be packed in accordance with drawing 9362607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:23Z
Check the source to verify that this is the current version before use.

5.1.2 Marking. Markings shall be in accordance with Dwg 9362607.

5.2 Shipping. When cartridges from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections or deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AD64)

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T00:23Z
Check the source to verify that this is the current version before use.