INCH-POUND

MIL-D-63123B(AR)
AMENDMENT 2
04 January 1994
SUPERSEDING
AMENDMENT 1
22 October 1990

MILITARY SPECIFICATION

DISPENSER ASSEMBLY

This amendment forms a part of Military Specification MIL-D-63123B(AR), dated 17 December 1979, and is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Department and Agencies of the Department of Defense.

PAGE 1

* 2.1.1 Standards, Military: Delete "MIL-STD-810C" and substitute "MIL-STD-810".

PAGE 2

2.1.2: Add the following drawing under *INSPECTION EQUIPMENT* DRAWINGS:

"12589959 - BALLAST, FLARE"

PAGE 3

3.3.3 Output: Delete" 5.0 ± .75 amperes DC" and substitute "5.25 ± 1.0 amperes DC".

* 3.4.1 Helicopter vibration.

Line 3: Delete "MIL-STD-810C" and substitute "MIL-STD-810, Method 514.4, Category 7C".

Line 4: Delete the following: "The dispenser shall be vibrated ... flares for this test".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:16Z
Check the source to verify that this is the current version before use.

* 3.4.2 Transportation vibration, line 3: Delete "MIL-STD-810C" and substitute "MIL-STD-810, Method 514.4, Basic Transportation, Category I".

PAGE 6

* 3.4.3 Humidity, line 2: Delete "MIL-STD-810C .... Procedure I, (10 days)" and substitute "MIL-STD-810, Method 507.3, Procedure III".

* 3.4.4 High temperature, line 2: Delete "MIL-STD-810C, Test Method 501.1" and substitute "MIL-STD-810, Test Method 501.3, Procedure II, Induced".

* 3.4.5 Low temperature, line 2: Delete "MIL-STD-810C, Test Method 502.1" and substitute "MIL-STD-810, Test Method 502.3, Procedure II, Severe Cold".

PAGE 29

* 4.5.2 High temperature, line 2: Delete "MIL-STD-810C, Test Method 501.1" and substitute "MIL-STD-810, Test Method 501.3, Procedure II, Induced".

* 4.5.3 Low temperature, line 2: Delete "MIL-STD-810C, Test Method 502.1" and substitute "MIL-STD-810, Test Method 502.3, Procedure II, Severe Cold".

4.5.4 Helicopter vibration.

* Line 2: Delete "MIL-STD-810C .... Procedure IIC, ..." and substitute "MIL-STD-810, Method 514.4, Category 7C, ...".

Line 4: Delete "...with thirty (30) inert flares..." and substitute "...with thirty (30) ballast flares, Dwg. 12589959, (Preferred) or with thirty (30) inert flares...".

* 4.5.5 Transportation vibration, line 2: Delete "MIL-STD-810C 5 and 6 HZ)" and substitute "MIL-STD-810, Method 514.4, Basic Transportation, Category I".

PAGE 30

* 4.5.6 Humidity, line 2: Delete "MIL-STD-810C .... (10 days)" and substitute "MIL-STD-810, Method 507.3, Procedure III".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1095-A271)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.