INCH-POUND

MIL-T-55155/6B

19 March 1990


SUPERSEDING
MIL-T-55155/6A
27 October 1971

MILITARY SPECIFICATION SHEET

TERMINALS, FEEDTHRU (INSULATED), STYLE FT06

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-55155



PART NUMBER 1/	DIMENSIONS							
	A	B	C +.002 -.000	D	E	F	G	H
M55155/06--01	.193	.025	.125	.050	.150	.063	.030	.015 x 45°
M55155/06--02	.367	.050	.148	.085	.172	.110	.063	

FIGURE 1. CONFIGURATION AND DIMENSIONS.


AMSC N/A FSC 5940


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:30Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.015 inch on decimals and ± 3° on angles.
3. Drawing depicts only general design characteristics and is not intended to limit specific manufacturing processes.
4. Terminals should have no less than .040 inch of the insulated portion protruding beyond the mounting panel or board.





PART NUMBER 1/	DIMENSIONS			
	A		B	
	MAX	MIN	MAX	MIN
M55155/06--01	.115	.111	.140	.135
M55155/06--02	.138	.134	.165	.160

FIGURE 2. TEST MOUNTING HOLE.

NOTES:

1. Dimensions are in inches.
2. For panels less than 0.040 inch thick, the countersink angle shall be 82°.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:30Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Insulation material: Polytetrafluoroethylene.

Test mounting: Terminals shall be mounted for testing in the hole specified on figure 2. The hole shall be made in 14 to 16 B and S gage sheet metal.

Dielectric withstanding voltage:

	Volts ac (rms) (min)
At atmospheric pressure:	1,500
At reduced barometric pressure:	650

Pull: 8 pounds, min.

Torque: 3 ounce-inches, min.

Type of mounting: Compression.

TABLE I. Substitutability data.

Part Number in MIL-T-55155/6B 1/	Part Number in MIL-T-55155/6A 2/
M55155/06--01	FT06-B01
M55155/06--02	FT06-B02

1/ The complete part number shall include the symbol for the insulation color (first dash) and symbol for the conductor material and finish (second dash).

2/ The complete number included the symbol for the insulation color.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:30Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS
Air Force - 99
DLA-GS

User activities:
Army - AV
Navy - MC
Air Force -

Preparing activity:
Army - ER

(Project 5940-1099-06)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:30Z
Check the source to verify that this is the current version before use.