MILITARY SPECIFICATION

CONNECTOR, PLUG, ELECTRICAL CONNECTOR, RECEPTACLE, ELECTRICAL (HEAVY DUTY, WATERPROOF)

This supplement forms a part of Military Specification MIL-C-27699 and has been approved by the Department of Defense for use of the Departments of the Army, the Navy, and the Air Force.

2.01 Scope. This supplement lists the MS military standards which form a part of this specification.

MS Number	*Nomenclature*
MS27155	— Connector, Plug, Electrical — 3 Conductor, Type I, Style S, Class 1 (200 VDC; 45 A).
MS27156	— Connector, Plug, Electrical — 3 Conductor, Type I, Style P, Class 1 (200 VDC; 45 A).
MS27157	— Connector, Receptacle, Electrical — 3 Conductor, Type I, Style S (200 VDC; 45 A).
MS27158	— Connector, Receptacle, Electrical — 3 Conductor, Type I, Style P (200 VDC; 45 A).
MS27159	— Connector, Plug, Electrical — 3 Conductor, Type I, Style S, Class 1 (500 VDC; 200 A).
MS27160	— Connector, Plug, Electrical — 3 Conductor, Type I, Style P, Class 1 (500 VDC; 200 A).
MS27161	— Connector, Receptacle, Electrical — 3 Conductor, Type I, Style S (500 VDS; 200 A).
MS27162	— Connector, Receptacle, Electrical — 3 Conductor, Type I, Style P (500 VDC; 200 A).
MS27163	— Connector, Plug, Electrical — 4 Conductor, Type I, Style S, Class 1 (500 VDC; 60 A).
MS27164	— Connector, Plug, Electrical — 4 Conductor, Type I, Style P, Class 1 (500 VDC; 60 A).
MS27165	— Connector, Receptacle, Electrical — 4 Conductor, Type I, Style S, (500 VDC; 60 A).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:43Z
Check the source to verify that this is the current version before use.

MS Number	*Nomenclature*
MS27166	— Connector, Receptacle, Electrical — 4 Conductor, Type I, Style P (500 VDC; 60 A).
MS27167	— Connector, Plug, Electrical — 19 Conductor, Type I, Style S, Class 1 (200 VDC; 30 A).
MS27168	— Connector, Plug, Electrical — 19 Conductor, Type I, Style P, Class 1 (200 VDC; 30 A).
MS27169	— Connector, Receptacle, Electrical — 19 Conductor, Type I, Style S (200 VDC; 30 A).
MS27170	— Connector, Receptacle, Electrical — 19 Conductor, Type I, Style P (200 VDC; 30 A).
MS27171	— Connector, Plug, Electrical — 21 Conductor, Type I, Style S, Class 1 (200 VDC; 45 A, 30 A).
MS27172	— Connector, Plug, Electrical — 21 Conductor, Type I, Style P, Class 1 (200 VDC; 45 A, 30 A).
MS27173	— Connector, Receptacle, Electrical — 21 Conductor, Type I, Style S (200 VDC; 45 A, 30 A).
MS27174	— Connector, Receptacle, Electrical — 21 Conductor, Type I, Style P (200 VDC; 45 A, 30 A).
MS27175	— Connector, Plug, Electrical — 28 Conductor, Type I, Style S, Class 1 (200 VDC; 30 A).
MS27176	— Connector, Plug, Electrical — 28 Conductor, Type I, Style P, Class 1 (200 VDC; 30 A).
MS27177	— Connector, Receptacle, Electrical — 28 Conductor, Type I, Style S (200 VDC; 30 A).
MS27178	— Connector, Receptacle, Electrical — 28 Conductor, Type I, Style P (200 VDC; 30 A).
MS27179	— Connector, Plug, Electrical — 38 Conductor, Type I, Style S, Class 1 (200 VDC; 30 A).
MS27180	— Connector, Plug, Electrical — 38 Conductor, Type I, Style P, Class 1 (200 VDC; 30 A).
MS27181	— Connector, Receptacle, Electrical — 38 Conductor, Type I, Style S (200 VDC; 30 A).
MS27182	— Connector, Receptacle, Electrical — 38 Conductor, Type I, Style P (200 VDC; 30 A).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:43Z
Check the source to verify that this is the current version before use.