INCH POUND

MIL-DTL-60517B
14 September 2004
SUPERSEDING
MIL-I-60517A
30 March 1990

DETAIL SPECIFICATION

INITIATOR, CARTRIDGE ACTUATED, M27 METAL PARTS ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M27 Cartridge Actuated Initiator Metal Parts Assembly (see 6.1)

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-A-2550	Ammunition, General Specification for

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-413	Visual Inspection Guide for Elastomeric O-rings

Comments, suggestions, or questions on this document should be addressed to Commander, Indian Head Division, Naval Surface Warfare Center, Technical Information Branch (Code 4230), 101 Strauss Avenue, Indian Head, Maryland 20640-5035, or emailed to amanda.penn@navy.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

AMSC N/A FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

(Copies of these documents are available online at http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DRAWINGS

NAVAL ORDNANCE STATION, INDIAN HEAD (GAGE CODE 19200 and 19203)

10520551	Initiator, Cartridge Actuated, M27, Metal Parts Assembly
8830984	Box, Fiberboard (inner) packing, Ammunition for Initiator, Cartridge Actuated M27, M86, M87, M99, or XM107
8830985	Box, Packing, Ammunition, for Initiator, Cartridge Actuated M27, M86, M87, M98, M99, or XM017
9241155	Box, Fiberboard (Outer) Alternative Packing, Ammunition, for Initiator, Cartridge Actuated M27, M86, M87, M98, M99, or XM107

(Application for copies should be addressed to Commanding Officer, Naval Surface Warfare Center, Indian Head, Technical Information Branch (Code 4230), Indian Head, MD 20640.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR QUALITY

ASQ A8402	Quality Management and Quality Assurance – Vocabulary
ASQ Z1.4	Sampling Procedures and Tables for Inspection by Attributes

(Application for copies should be addressed to the American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 53201-4606.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First Article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection (see 4.4 and 6.3).

3.2 Materials. All materials used in the manufacture of the initiators shall conform strictly to the specifications referred to on the respective drawings unless specific approval in writing covering a departure there from has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

3.2.1 Raw materials. The contractor shall be responsible for selecting from the classification list contained in the raw material specification the surface and physical condition of the raw material intended for use in manufacture.

3.3 Hardness and other physical properties. Physical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.4 Hydrostatic pressure. The initiator chamber and cap shall withstand a hydrostatic pressure of 14,00 to 15,00 pounds per square inch (psi) for 15 seconds, minimum, without deformation or mechanical failure (see 6.4.1).

3.5 Firing pin release. The firing pin of the metal parts assembly initiator, less safety pin and cartridge, shall release from the cocked position when the application of an axial load of 15 to 30 pounds has withdrawn the initiator pin 0.370 inch, minimum, and 0.425 inch, maximum (see 4.3.3).

3.6 Initiator pin security. Application of an axial load of 200 to 220 pounds to the initiator pin of the metal parts assembly shall not withdraw the initiator pin past the safety pin. Load application shall cause no permanent deformation of the safety pin.

3.7 Protective finish. Protective finish shall be in accordance with the applicable specifications and shall apply to all surfaces of the component regardless of contour configuration.

3.8 Residual magnetism. The metal parts assembly shall not deflect the indicator of the compass more than five degrees in either direction using procedures in 4.6.6.

3.9 Metal parts assembly. Parts shall be combined to produce an assembly, which conforms to the requirements of the metals parts assembly drawing. All threaded joints shall be assembled hand tight.

3.10 Workmanship. The requirements for workmanship are as specified on the applicable drawings, referenced specification, and the following:

3.10.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.10.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.10.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Conformance inspection.

4.1.1 Quality assurance terms and definitions. Reference shall be made to ASQ A8402 to define the quality assurance terms used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection. Inspection shall be in accordance with MIL-A-2550.

4.2 Classification of Characteristics. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformation inspection (see 4.5)

4.3 Inspection conditioning. Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: Room ambient 20 to 25 °C (68 to 77 °F)
b. Altitude: Sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psia.

4.4 First article inspection. At the beginning of regular production, the supplier shall submit a first article sample to a Government approved facility for evaluation. The sample shall consist of 5 metal parts assemblies, 9 sets of unassembled parts, and 1 set of unassembled parts without plating or final protective finish. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, must be the same as will be used in regular production and shall be obtained from the same source of supply. After inspection and provisional acceptance at source, the first article sample shall be inspected for all requirements of the drawings and specifications. The Government reserves the right to require new first article samples until such time as an acceptable sample is submitted (see 6.3).

4.5 Quality conformance inspection.

4.5.1 Lot.

4.5.1.1 Submission of product. The product shall be submitted in accordance with ASQ Z1.4.

4.5.1.2 Size of lot. For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 1200 assemblies, maximum, provided the homogeneity requirements of inspection lots have been retained.

4.5.2 Examination. One-hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirements is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability. All nonconforming material shall be rejected.

4.5.2.1 Chamber, Initiator, Drawing 10520407, covering a detail of Drawing 10520551.

Characteristic	Defect	Method of Inspection
Critical		
None Defined		
Major		
101	Pitch diameter of large external thread, min	Gage
102	Major diameter of large external thread, min	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

103	Pitch diameter of small external thread, min	Gage
104	Major diameter of small external thread, min	Gage
105	Pitch diameter of internal thread, max	Gage
106	Minor diameter of internal thread, max	Gage
107	Concentricity of datum location with pitch diameter of small external thread	Gage
108	Concentricity of pitch diameter of large thread with cavity	Gage
109	Concentricity of large external thread pilot with large external thread	Gage
110	Concentricity of counterbore with cavity, including perpendicularity with base of counterbore	Gage
111	Diameter of counterbore	Gage
112	Diameter of large thread pilot	Gage
113	Depth of cavity	Gage
114	Length of datum location	Gage
115	Thickness of wall, min	Gage
116	Metal defective	Visual
117	Protective finish, inadequate or defective	Visual
118	Surface finish of cavity and angle of gas port, improper	Visual
119	Burr	Visual
120	Foreign matter present	Visual
Minor		
201	Pitch diameter of large external thread, max	Gage
202	Pitch diameter of small external thread, max	Gage
203	Pitch diameter of internal thread, min	Gage
204	Diameter of small external relief	Gage
205	Diameter of small external thread pilot	Gage
206	Diameter of hole in gas port	Gage
207	Diameter of cavity	Gage
208	Depth of counterbore	Gage
209	Length of gas port	Gage
210	Length of small thread relief	Gage
211	Length from face of gas port to small thread	Gage
212	Length of external thread pilot	Gage
213	Thickness of wall, max	Gage
214	Depth of threaded hole	Measure
215	Diameter of chamfer at internal thread	Measure
216	Total length	Measure
217	Length of large external thread	Measure
218	Marking missing, incorrect or illegible	Visual
219	Radius or chamfer, missing or incorrect	Visual
220	Surface finish improper, except as otherwise classified	Visual

4.5.2.2 Cap, Initiator, Drawing 10520552, covering a detail of Drawing 10520551.

Critical

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

Major		
101	Pitch diameter of small internal thread, max	Gage
102	Minor diameter of small internal thread, max	Gage
103	Pitch diameter of large external thread, max	Gage
104	Minor diameter of large external thread, max	Gage
105	Concentricity of pitch diameter of large internal thread with midsection cavity, including perpendicularity with base of counterbore of large cavity	Gage
106	Concentricity of pitch diameter of small internal thread with midsection cavity, including perpendicularity with base of counterbore of large cavity	Gage
107	Concentricity of hole between small cavity and boss cavity with midsection cavity, including perpendicularity with base of counterbore of large cavity	Gage
108	Concentricity of undercut in large cavity with large internal thread	Gage
109	Concentricity of boss cavity with hole between small cavity and boss cavity	Gage
110	Concentricity of flange with hole between small cavity and boss cavity	Gage
111	Concentricity of body, large end with large internal thread	Gage
112	Concentricity of small cavity with midsection cavity	Gage
113	Concentricity of thread with large internal thread	Gage
114	Symmetry of thickness of mounting lugs with body, large end	Gage
115	Symmetry of length of mounting lugs with body, large end	Gage
116	Variation of centerline of mounting holes with small hole between boss cavity and small cavity	Gage
117	Diameter of large cavity rear of undercut	Gage
118	Diameter of small cavity	Gage
119	Diameter of boss cavity, max	Gage
120	Diameter of hole between small cavity and boss cavity, max	Gage
121	Diameter of undercut at large internal thread	Gage
122	Diameter of safety pin hole, max	Gage
123	Diameter of flange	Gage
124	Length of effective small interior thread, min	Gage
125	Length of small interior thread, max	Gage
126	Width of undercut behind large interior thread	Gage
127	Location of safety pin hole	Gage
128	Height of boss	Gage
129	Metal defective	Visual
130	Protective finish, inadequate or defective	Visual
131	Burr	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

132	Foreign matter present	Visual
Minor		
201	Pitch diameter of set screw thread	Gage
202	Minor diameter of set screw thread	Gage
203	Pitch diameter of small internal thread, min	Gage
204	Pitch diameter of large internal thread, min	Gage
205	Diameter of body, small end	Gage
206	Diameter of body, large end	Gage
207	Diameter of groove, small end	Gage
208	Diameter of chamfer, large internal thread	Gage
209	Diameter of chamfer, small internal thread	Gage
210	Diameter of midsection cavity	Gage
211	Diameter of boss cavity, min	Gage
212	Diameter of hole between boss cavity and small cavity, max	Gage
213	Diameter of safety pin hole, min	Gage
214	Diameter of mounting hole	Gage
215	Depth from base of large cavity rear of undercut to base midsection cavity	Gage
216	Depth from base of large cavity rear undercut to face of internal boss	Gage
217	Depth to bottom of large cavity rear of undercut	Gage
218	Depth of large cavity rear of undercut	Gage
219	Total length	Gage
220	Length of body, large end	Gage
221	Width of groove, small end	Gage
222	Width across flat	Gage
223	Thickness of mounting flange	Gage
224	Location of set screw hole	Gage
225	Location of groove, small end	Gage
226	Location of small cavity	Gage
227	Location of mounting holes	Gage
228	Location of flats	Gage
229	Length from rear flange to shoulder	Measure
230	Width of flange	Measure
231	Safety pin hole obstructed	Visual
232	Marking missing, incorrect or illegible	Visual
233	Radius or chamfer, missing or incorrect	Visual
234	Surface finish, improper	Visual

4.5.2.3 Pin, Initiator, Drawing 10520553, covering a detail of Drawing 10520551.

Critical		
None Defined		
Major		
101	Concentricity of groove in head with body	Gage
102	Concentricity of shoulder with body	Gage
103	Symmetry of pull hole with body	Gage
104	Diameter of undercut, min, if applicable	Gage
105	Width of undercut, max, if applicable	Gage
106	Diameter of body	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

107	Diameter of shoulder	Gage
108	Diameter of groove in body, min	Gage
109	Width of head groove	Gage
110	Location of groove in head	Gage
111	Location of groove in body	Gage
112	Location of pull hole	Gage
113	Profile of end	Visual
114	Profile of head	Visual
115	Metal defective	Visual
117	Protective finish, inadequate or defective	Visual
118	Surface finish of groove in head and face of shoulder, improper	Visual
119	Burr	Visual
120	Foreign matter present	Visual
Minor		
201	Diameter of groove in head	Gage
202	Diameter of groove in body	Gage
203	Diameter of pull hole	Gage
204	Length to groove in body	Gage
205	Width of flat at body groove end	Gage
206	Thickness of pull hole end	Gage
207	Total length	Measure
208	Marking missing, incorrect or illegible	Visual
209	Radius or chamfer, missing or incorrect	Visual
210	Surface finish, improper, except as otherwise classified	Visual

4.5.2.4 Seal Drawing 10520415, covering a detail of Drawing 10520551.

Critical		
None defined		
Major		
101	Diameter, outside, min	Gage
102	Width, min	Gage
103	Thickness, min	Gage
104	Cut, cracked or split	Visual
105	Flash	Visual
106	Foreign matter present	Visual
Minor		
201	Diameter, outside, max	Gage
202	Width, max	Gage
203	Thickness, max	Gage

4.5.2.5 Housing, Firing, Pin, Drawing 10520410, covering a detail of Drawing 10520551.

Critical		
1	Diameter of striker hole, min	Gage
Major		
101	Pitch diameter of thread, min	Gage
102	Major diameter of thread, min	Gage
103	Concentricity of striker hole with cavity	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

104	Concentricity of cavity with body	Gage
105	Concentricity of pitch diameter of thread with body	Gage
106	Perpendicularity of face with body	Gage
107	Diameter of body, min	Gage
108	Diameter of cavity	Gage
109	Diameter of flange, min	Gage
110	Diameter of boss	Gage
111	Diameter of undercut, min	Gage
112	Total length, max	Gage
113	Width of undercut	Gage
114	Thickness of striker hole	Gage
115	Location of thread	Gage
116	Chamfer at striker hole	Gage
117	Height of boss	Visual
118	Metal defective	Visual
119	Protective finish, inadequate or defective	Visual
120	Surface finish of cavity, improper	Visual
121	Burr	Visual
122	Foreign matter present	Visual
Minor		
201	Pitch diameter of thread, max	Gage
202	Diameter of body, max	Gage
203	Diameter of striker hole, max	Gage
204	Diameter of flange, max	Gage
205	Diameter of wrench holes	Gage
206	Depth of wrench holes	Gage
207	Total length, min	Gage
208	Length of body to flange	Gage
209	Location of wrench holes	Gage
210	Marking missing, incorrect or illegible	Visual
211	Radius or chamfer, missing or incorrect, except as otherwise classified	Visual
212	Surface finish, improper, excepts as otherwise classified	Visual

4.5.2.6 Pin, Firing, Drawing 10520411, covering a detail of Drawing 10520551.

Critical		
None Defined		
Major		
101	Concentricity of large cavity with body	Gage
102	Concentricity of striker with body	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

103	Concentricity of cavity with body	Gage
104	Symmetry of pin relief holes with small cavity	Gage
105	Symmetry of ball hole counterbore with ball holes	Gage
106	Diameter of striker	Gage
107	Diameter of body	Gage
108	Diameter of ball hole, max	Gage
109	Diameter of ball hole counterbore	Gage
110	Diameter of pin relief holes, min	Gage
111	Depth of ball counterbore, min	Gage
112	Length of striker, min	Gage
113	Location of ball hole counterbore	Visual
114	Metal defective	Visual
115	Protective finish, inadequate or defective	Visual
116	Surface finish of body, improper	Visual
117	Burr	Visual
118	Foreign matter present	Visual
Minor		
201	Diameter of large cavity	Gage
202	Diameter of small cavity	Gage
203	Diameter of ball hole, min	Gage
204	Diameter of pin relief holes, max	Gage
205	Depth of large cavity	Gage
206	Depth to bottom of small cavity	Gage
207	Depth of ball hole counterbore, max	Gage
208	Length of striker, max	Gage
209	Total length	Gage
210	Location of pin relief holes	Gage
211	Marking missing, incorrect or illegible	Visual
212	Radius or chamfer, missing or incorrect	Visual
213	Surface finish, improper, except as otherwise classified	Visual

4.5.2.7 Spring, Initiator, Drawing 10520412, covering a detail of Drawing 10520551.

Critical		
None defined		
Major		
101	Load at specified height	Gage
102	Closed length, max	Gage
103	Ends incorrect	Visual
104	Protective finish, inadequate or defective	Visual
105	Burr	Visual
106	Foreign matter present	Visual
Minor		
201	Diameter outside	Gage
202	Free length	Gage

4.5.2.8 Pin, Safety, Drawing 10522817, covering a detail of Drawing 10520551.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

Critical

None defined

Major

101	Diameter of wire	Gage
102	Profile, incorrect	Visual
103	Metal defective	Visual
104	Protective finish, inadequate or defective	Visual
105	Burr	Visual
106	Foreign matter present	Visual

Minor

201	Diameter of head, outside	Measure
202	Length between high and low ends	Measure
203	Total length	Measure
204	Location of center loop	Measure
205	Radius of center loop, incorrect	Measure

4.5.2.9 Filter, Drawing 10520414, covering a detail of Drawing 10520551.

Critical

None Defined

Major

101	Pitch diameter of thread, min	Gage
102	Major diameter of thread, min	Gage
103	Concentricity of thread with center hole and outside diameter	Gage
104	Symmetry of hole with outside diameter	Gage
105	Diameter of center hole	Gage
106	Diameter of holes	Gage
107	Depth of center hole	Gage
108	Depth of slot, max	Gage
109	Location of holes	Gage
110	Angular location of holes	Gage
111	Nylon patch not properly located or fused	Manual/Visual
112	Number of holes, incorrect	Visual
113	Metal defective	Visual
114	Protective finish, inadequate or defective	Visual
115	Burr	Visual
116	Foreign matter present	Visual

Minor

201	Pitch diameter of thread, max	Gage
202	Diameter of undercut	Gage
203	Diameter of body	Gage
204	Depth of slot, min	Gage
205	Total length	Gage
206	Length of body	Gage
207	Width of undercut, max	Gage
208	Width of slot	
209	Location of slot	Gage
210	Marking missing, incorrect or illegible	Visual
211	Chamfer, missing or incorrect	Visual
212	Surface finish, improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

4.5.2.10 Assembly, Drawing 10520551, less all drawings except 10520410, 10520411, 10520552, and MS19060-3.

Critical		
1	Firing pin protrusion	Gage
2	Steel ball missing	Gage
Major		
101	Burr	Visual
102	Foreign matter present	Visual
Minor		
None defined		

4.5.5.11 Assembly, Drawing 10520551.

Critical		
None defined		
Major		
101	Firing pin cocked	Manual
102	Initiator pin not free to rotate	Manual
103	Any part missing, except as otherwise classified	Visual
104	Improper assembly	Visual
105	Safety pin improperly inserted	Visual
106	O-ring not lubricated	Visual
107	Marking missing, incorrect or illegible	Visual
Minor		
201	Protective cap missing	Visual
202	Protective finish inadequate or defective	Visual

4.5.2.12 Box, Fiberboard (inner Ammunition Packing, Drawing 8830984.

Critical		
None defined		
Major		
None defined		
Minor		
201	Contents loose	Manual
202	Box damaged	Visual
203	Sealing strip missing, incorrectly applied	Visual
204	Marking missing, incorrect or illegible	Visual
205	Cut damaged or improperly sealed bag	Visual

4.5.2.13 Box, Ammunition, Packing, Drawing 8830985.

Critical		
None defined		
Major		
None defined		
Minor		
201	Contents loose	Manual
202	Strapping missing, loose, broken, or improperly assembled	Manual/Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

203	Contents of box exposed	Visual
204	Box damaged	Visual
205	Marking missing, incorrect or illegible	Visual
206	Number of units incorrect	Visual

4.5.2.14 Box, Fiberboard (Outer) Alternative, Ammunition Packing, Drawing 9241155.

Critical

None defined

Major

None defined

Minor

201	Contents loose	Manual
202	Box broken or damaged	Visual
203	Number of units contained incorrect	Visual
204	Marking missing, incorrect or illegible	Visual
205	Tape incomplete	Visual

4.5.3 Inspection testing. The following tests shall be performed in accordance with the provision of 4.6.

4.5.3.1 Hardness. Fifty units from each heat-treated lot of components shall be tested for compliance with the requirements on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.5.3.2 Hydrostatic pressure. Each chamber and cap shall be subjected to the hydrostatic pressure test. Failure of any cap or chamber subassembly to comply with the requirements of 3.4 shall be cause for rejection of the subassembly.

4.5.3.3 Firing pin release. The initiator pin of each partial assembly, consisting of all parts except the safety pin, cartridge and chamber, shall be subjected to the firing-pin release test. Failure of any partial assembly to comply with the requirements of 3.5 shall be cause for rejection of the subassembly.

4.5.3.4 Initiator pin security. The initiator pin of each subassembly, consisting of all parts except the chamber, shall be subjected to the initiator pin security test. Failure of any subassembly to comply with the requirements of 3.6 shall be cause for rejection of the subassembly.

4.5.3.5 Protective finish. The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.5.3.6 Residual magnetism. Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any unit in the inspection sample to comply with the requirements of 3.8 shall be cause for rejection of assembly.

4.6 Test methods and procedures.

4.6.1 Hardness. Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the requirements of the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

4.6.2 Hydrostatic pressure. Prior to the application of protective finish, the cap and chamber shall be mounted in the device, using a fixture for properly sealing all openings and subjected to the internal hydrostatic pressure to determine compliance with the requirements.

4.6.3 Firing pin release. The subassembly shall be secured in the fixture. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture, which registers the amount of pull.

4.6.4 Initiator pin security. The subassembly shall be secured in the fixture with the safety pin in place. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with a fixture, which registers the amount of pull. The test shall be performed with the safety pin in both positions.

4.6.5 Protective finish. Test procedures for protective finish shall be in accordance with the applicable specification referenced on the component drawing.

4.6.6 Residual magnetism. The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater the 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90-degree rotation of the assembly for 4 full passes.

4.7 Inspection of packaging. The sampling and inspection of the packing and container marking shall be in accordance with the requirements of section 5.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contractor order (see 6.2). When actual packaging of material needs to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department of Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may helpful but is not mandatory.)

6.1 Intended use. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems. The assembly was designed for use in military aircraft and has no commercial application.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. If first article is necessary (see 3.1 and 6.3)
d. The responsible for inspection activity (see 4.1)
e. Any special inspection conditions (see 4.3)
f. Level of marking and packing (see 5.1 and 6.4)

6.3 First article. When a first article inspection is required, the terms should be a first article sample. The first article should consist of 5 metal parts assemblies, 9 sets of unassembled parts, 1 set of unassembled parts without plating or final protective finish. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first article. Invitations for bids should provided that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Contract packaging, packing and marking. The following requirements should be specified in the contract.

6.4.1 Packing and marking level. Packing and marking should be Level A or B, as specified by the contracting activity.

6.4.1.1 Level A. Level A should be in accordance with Drawings 8830984 and 8830985 or SPI F00-138-3770.

6.4.1.2 Level B. Level B should be in accordance with Drawings 8830984 and 9241155 or SPI F00-138-3770.

6.4.1.3 Lot numbers. Lot numbers should be in accordance with MIL-STD-1168.

6.5 Definitions.

6.5.1 Mechanical failure. Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

6.6 Subject term (key word) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes. These changes were authorized by Indian Head ECP 045220I018.

Custodian:
Navy-OS
Air Force-99

Preparing activity
Navy - OS
(Project 1377-0229)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.

Review activity:
Air Force-70

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:40Z
Check the source to verify that this is the current version before use.