METRIC

MIL-PRF-55365/8G
22 February 2008
SUPERSEDING
MIL-PRF-55365/8F
23 October 2006

PERFORMANCE SPECIFICATION SHEET

# CAPACITORS, CHIP, FIXED, TANTALUM, POLARIZED ESTABLISHED RELIABILITY, NON-ESTABLISHED RELIABILITY AND HIGH RELIABILITY, STYLE CWR11 (METRIC)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-55365.





FIGURE 1. Style CWR11 (molded) capacitors.

AMSC N/A
FSC 5910

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

| Dimensions | | | | | | |
|---|---|---|---|---|---|---|
| Case code | H | $H_2$ (min) | L | P ±0.3 (0.12) | W | $W_2$ ±0.1 (.004) (see note 4) |
| A | 1.6 ±.2 (.063 ±.008) | 0.7 (.028) | 3.2 ±.2 (.126 ±.008) | 0.8 (.031) | 1.6 ±.2 (0.063 ±.008) | 1.2 (.047) |
| B | 1.9 ±.2 (.075 ±.008) | 0.7 (.028) | 3.5 ±.2 (.138 ±.008) | 0.8 (.031) | 2.8 ±.2 (.110 ±.008) | 2.2 (.087) |
| C | 2.5 ±.3 (.098 ±.012) | 1.0 (.039) | 6.0 ±.3 (.236 ±.012) | 1.3 (.051) | 3.2 ±.3 (.126 ±.012) | 2.2 (.087) |
| D | 2.8 ±.3 (.110 ±.012) | 1.0 (.039) | 7.3 ±.3 (.287 ±.012) | 1.3 (.051) | 4.3 ±.3 (.169 ±.012) | 2.4 (.094) |

NOTES:
1. Dimensions are in millimeters. Inch equivalents are given in parenthesis for general information only.
2. These capacitors are designed for mounting by dip or wave soldering, reflow soldering, thermo-compression bonding, or other conventional means.
3. The anode (+) terminal shall be indicated by a marking on the case or by bevel on anode end.
4. Applicable to solderable surfaces only. The configuration of the nonsolderable area is optional.
5. Solderable surfaces are only those surfaces designated as such. Termination edges are not considered solderable.
6. For solder coated terminations, add an additional 0.38 mm (.015 inch) to the tolerances for “L”, “W”, “H”, “P”, “$W_2$”, and “$H_2$” for each case size.

FIGURE 1. Style CWR11 (molded) capacitors - Continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Termination finish: In accordance with MIL-PRF-55365.

DC rated voltage: See table I. Above +85°C, voltage derating is required (see MIL-PRF-55365).

Operating temperature range: -55°C to +125°C.

Product level designator: In accordance with MIL-PRF-55365.

DC leakage (DCL): See table I.

Capacitance: See table I.

Capacitance tolerance: ±5 percent (J), ±10 percent (K), or ±20 percent (M).

Dissipation factor (DF): See table I.

Equivalent series resistance (ESR) at 100 kHz: In accordance with MIL-PRF-55365. See table I.

Resistance to soldering heat: In accordance with MIL-PRF-55365.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Stability at low and high temperatures: In accordance with MIL-PRF-55365.

| | | | |
|---|---|---|---|
| Step 1 (+25°C): | DCL | - | See table I. |
| | Capacitance | - | Within tolerance of table I value. |
| | DF | - | See table I. |
| | ESR | - | See table I. |
| Step 2 (-55°C): | ΔCapacitance | - | Shall not exceed ±10 percent of initial measurement. |
| | DF | - | See table I. |
| Step 3 (+25°C): | DCL | - | See table I. |
| | ΔCapacitance | - | Shall not exceed ±5 percent of initial +25°C measurement. |
| | DF | - | See table I. |
| Step 4 (+85°C): | DCL | - | See table I. |
| | ΔCapacitance | - | Shall not exceed ±10 percent of initial +25°C measurement. |
| | DF | - | See table I. |
| Step 5 (+125°C): | DCL | - | See table I. |
| | ΔCapacitance | - | Shall not exceed 15 percent of initial +25°C measurement. |
| | DF | - | See table I. |
| Step 6 (+25°C): | DCL | - | See table I. |
| | ΔCapacitance | - | Shall not exceed ±5 percent of initial +25°C measurement. |
| | DF | - | See table I. |
| | ESR | - | See table I. |

Life: Method 108 of MIL-STD-202.

2,000 hours:

| | | | |
|---|---|---|---|
| At 25°C: | DCL | - | See table I. |
| | ΔCapacitance | - | Within ±5 percent of initial measured value. |
| | DF | - | See table I. |
| At 85°C: | DCL | - | See table I. |
| At 125°C: | DCL | - | See table I. |

* 10,000 hours:

| | | | |
|---|---|---|---|
| At 25°C: | DCL | - | 200 percent of initial requirement. |
| | ΔCapacitance | - | Within ±5 percent of initial measured value. |
| | DF | - | See table I. |
| At 85°C: | DCL | - | 200 percent of initial requirement. |
| At 125°C: | DCL | - | 200 percent of initial requirement. |

Solderability will be in accordance with MIL-PRF-55365 except that following steam aging; test samples may have a 30 minute bake out at 150°C prior to solder dipping.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE I. Style CWR11 characteristics.

| Part or identifying number (PIN) 1/ | DC rated voltage (+85°C) | Cap. (nom) | DC Leakage (max) | | | Dissipation factor (max) | | | Max ESR 100 kHz | Case size |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | +25°C | +85°C | +125°C | +25°C | +85°C +125°C | -55°C | +25°C | |
| | Volts | µF | µA | µA | µA | % | % | % | Ohms | |
| CWR11C-225--- | 4 | 2.2 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 8.0 | A |
| CWR11C-475--- | 4 | 4.7 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 8.0 | A |
| CWR11C-685--- | 4 | 6.8 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 5.5 | B |
| CWR11C-106--- | 4 | 10.0 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 4.0 | B |
| CWR11C-156--- | 4 | 15.0 | 0.6 | 6.0 | 7.2 | 6 | 9 | 9 | 3.5 | B |
| CWR11C-336--- | 4 | 33.0 | 1.3 | 13.0 | 15.6 | 6 | 9 | 9 | 2.2 | C |
| CWR11C-686--- | 4 | 68.0 | 2.7 | 27.0 | 32.4 | 6 | 9 | 9 | 1.1 | D |
| CWR11C-107--- | 4 | 100.0 | 4.0 | 40.0 | 48.0 | 8 | 12 | 12 | 0.9 | D |
| CWR11D-155--- | 6 | 1.5 | 0.5 | 5.0 | 6 | 6 | 9 | 9 | 8.0 | A |
| CWR11D-225--- | 6 | 2.2 | 0.5 | 5.0 | 6 | 6 | 6 | 9 | 8.0 | A |
| CWR11D-335--- | 6 | 3.3 | 0.5 | 5.0 | 6 | 6 | 9 | 9 | 8.0 | A |
| CWR11D-475--- | 6 | 4.7 | 0.5 | 5.0 | 6 | 6 | 9 | 9 | 5.5 | B |
| CWR11D-685--- | 6 | 6.8 | 0.5 | 5.0 | 6 | 6 | 6 | 9 | 4.5 | B |
| CWR11D-106--- | 6 | 10.0 | 0.6 | 6.0 | 7.2 | 6 | 9 | 9 | 3.5 | B |
| CWR11D-156--- | 6 | 15.0 | 0.9 | 9.0 | 10.8 | 6 | 6 | 9 | 3.0 | C |
| CWR11D-226--- | 6 | 22.0 | 1.4 | 14.0 | 16.8 | 6 | 9 | 9 | 2.2 | C |
| CWR11D-476--- | 6 | 47.0 | 2.8 | 28.0 | 33.6 | 6 | 6 | 9 | 1.1 | D |
| CWR11D-686--- | 6 | 68.0 | 4.3 | 43.0 | 51.6 | 6 | 9 | 9 | 0.9 | D |
| CWR11F-105--- | 10 | 1.0 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 10.0 | A |
| CWR11F-155--- | 10 | 1.5 | 0.5 | 5.0 | 6.0 | 6 | 6 | 9 | 8.0 | A |
| CWR11F-225--- | 10 | 2.2 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 8.0 | A |
| CWR11F-335--- | 10 | 3.3 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 5.5 | B |
| CWR11F-475--- | 10 | 4.7 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 4.5 | B |
| CWR11F-685--- | 10 | 6.8 | 0.7 | 7.0 | 8.4 | 6 | 9 | 9 | 3.5 | B |
| CWR11F-156--- | 10 | 15.0 | 1.5 | 15.0 | 18.0 | 6 | 6 | 9 | 2.5 | C |
| CWR11F-336--- | 10 | 33.0 | 3.3 | 33.0 | 39.6 | 6 | 9 | 9 | 1.1 | D |
| CWR11F-476--- | 10 | 47.0 | 4.7 | 47.0 | 56.4 | 6 | 9 | 9 | 0.9 | D |
| CWR11H-684--- | 15 | 0.68 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 12.0 | A |
| CWR11H-105--- | 15 | 1.0 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 10.0 | A |
| CWR11H-155--- | 15 | 1.5 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 8.0 | A |
| CWR11H-225--- | 15 | 2.2 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 5.5 | B |
| CWR11H-335--- | 15 | 3.3 | 0.5 | 5.0 | 6.0 | 6 | 8 | 9 | 5.0 | B |
| CWR11H-475--- | 15 | 4.7 | 0.7 | 7.0 | 8.4 | 6 | 9 | 9 | 4.0 | B |
| CWR11H-106--- | 15 | 10.0 | 1.6 | 16.0 | 19.2 | 6 | 8 | 9 | 2.5 | C |
| CWR11H-226--- | 15 | 22.0 | 3.3 | 33.0 | 39.6 | 6 | 8 | 9 | 1.1 | D |
| CWR11H-336--- | 15 | 33.0 | 5.3 | 53.0 | 63.6 | 6 | 9 | 9 | 0.9 | D |
| CWR11J-474--- | 20 | 0.47 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 14.0 | A |
| CWR11J-684--- | 20 | 0.68 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 12.0 | A |
| CWR11J-105--- | 20 | 1.0 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 10.0 | A |
| CWR11J-155--- | 20 | 1.5 | 0.5 | 5.0 | 6.0 | 6 | 9 | 9 | 6.0 | B |
| CWR11J-225--- | 20 | 2.2 | 0.5 | 5.0 | 6.0 | 6 | 8 | 9 | 5.0 | B |
| CWR11J-335--- | 20 | 3.3 | 0.7 | 7.0 | 8.4 | 6 | 9 | 9 | 4.0 | B |

See footnote at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

TABLE I. Style CWR11 characteristics - Continued.

| PIN 1/ | DC rated voltage (+85°C) | Cap. (nom) | DC Leakage (max) | | | Dissipation factor (max) | | | Max ESR 100 kHz | Case size |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | +25°C | +85°C | +125°C | +25°C | +85°C +125°C | -55°C | +25°C | |
| | Volts | µF | µA | µA | µA | % | % | % | Ohms | |
| CWR11J-475--- | 20 | 4.7 | 1.0 | 10.0 | 12.0 | 6 | 8 | 9 | 3.0 | C |
| CWR11J-685--- | 20 | 6.8 | 1.4 | 14.0 | 16.8 | 6 | 9 | 9 | 2.4 | C |
| CWR11J-156--- | 20 | 15.0 | 3.0 | 30.0 | 36.0 | 6 | 8 | 9 | 1.1 | D |
| CWR11J-226--- | 20 | 22.0 | 4.4 | 44.0 | 52.8 | 6 | 9 | 9 | 0.9 | D |
| CWR11K-334--- | 25 | 0.33 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 15.0 | A |
| CWR11K-474--- | 25 | 0.47 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 14.0 | A |
| CWR11K-684--- | 25 | 0.68 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 7.5 | B |
| CWR11K-105--- | 25 | 1.0 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 6.5 | B |
| CWR11K-155--- | 25 | 1.5 | 0.5 | 5.0 | 6.0 | 6 | 8 | 9 | 6.5 | B |
| CWR11K-225--- | 25 | 2.2 | 0.6 | 6.0 | 7.2 | 6 | 9 | 9 | 3.5 | C |
| CWR11K-335--- | 25 | 3.3 | 0.9 | 9.0 | 10.8 | 6 | 8 | 9 | 3.5 | C |
| CWR11K-475--- | 25 | 4.7 | 1.2 | 12.0 | 14.4 | 6 | 9 | 9 | 2.5 | C |
| CWR11K-685--- | 25 | 6.8 | 1.7 | 17.0 | 20.4 | 6 | 9 | 9 | 1.4 | D |
| CWR11K-106--- | 25 | 10.0 | 2.5 | 25.0 | 30.0 | 6 | 8 | 9 | 1.2 | D |
| CWR11K-156--- | 25 | 15.0 | 3.8 | 38.0 | 45.6 | 6 | 9 | 9 | 1.0 | D |
| CWR11M-104--- | 35 | 0.10 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 24.0 | A |
| CWR11M-154--- | 35 | 0.15 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 21.0 | A |
| CWR11M-224--- | 35 | .22 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 18.0 | A |
| CWR11M-334--- | 35 | .33 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 15.0 | A |
| CWR11M-474--- | 35 | .47 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 10.0 | B |
| CWR11M-684--- | 35 | .68 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 8.0 | B |
| CWR11M-105--- | 35 | 1.0 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 6.5 | B |
| CWR11M-155--- | 35 | 1.5 | 0.5 | 5.0 | 6.0 | 6 | 8 | 9 | 4.5 | C |
| CWR11M-225--- | 35 | 2.2 | 0.8 | 8.0 | 9.6 | 6 | 8 | 9 | 3.5 | C |
| CWR11M-335--- | 35 | 3.3 | 1.2 | 12.0 | 14.4 | 6 | 8 | 9 | 2.5 | C |
| CWR11M-475--- | 35 | 4.7 | 1.7 | 17.0 | 20.4 | 6 | 8 | 9 | 1.5 | D |
| CWR11M-685--- | 35 | 6.8 | 2.4 | 24.0 | 28.8 | 6 | 9 | 9 | 1.3 | D |
| CWR11N-104--- | 50 | .10 | 0.5 | 5.0 | 12 | 6 | 8 | 8 | 22.0 | A |
| CWR11N-154--- | 50 | .15 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 17.0 | B |
| CWR11N-224--- | 50 | .22 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 14.0 | B |
| CWR11N-334--- | 50 | .33 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 12.0 | B |
| CWR11N-474--- | 50 | .47 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 8.0 | C |
| CWR11N-684--- | 50 | .68 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 7.0 | C |
| CWR11N-105--- | 50 | 1.0 | 0.5 | 5.0 | 6.0 | 4 | 6 | 6 | 6.0 | C |
| CWR11N-155--- | 50 | 1.5 | 0.8 | 8.0 | 9.6 | 6 | 8 | 9 | 4.0 | D |
| CWR11N-225--- | 50 | 2.2 | 1.1 | 11.0 | 13.2 | 6 | 8 | 9 | 2.5 | D |
| CWR11N-335--- | 50 | 3.3 | 1.7 | 17.0 | 20.4 | 6 | 9 | 9 | 2.0 | D |
| CWR11N-475--- | 50 | 4.7 | 2.4 | 24.0 | 28.8 | 6 | 9 | 9 | 1.5 | D |

1/ Complete PIN shall include additional symbols to indicate termination finish, capacitance tolerance, product level, and, if applicable, surge current option letter. If optional surge current is not required, the last "-" shall be deleted.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

Marking: In accordance with MIL-PRF-55365, to be marked on top of case as follows: Print orientation is optional.

Case code A

| | | |
|---|---|---|
| J | (+) | polarity stripe, J = JAN |
| 105X | - | capacitance in picofarad code<br>manufacturer's identifier |

Case codes B, C, and D

| | | |
|---|---|---|
| J | (+) | polarity stripe, J = JAN |
| 105 | - | capacitance in picofarad code |
| 35X | - | rated voltage; manufacturer's identifier |

Alternate case code A marking

| | | |
|---|---|---|
| X | (+) | polarity stripe, X = manufacturer's identifier |
| 105J | - | capacitance in picofarad code; J = JAN |

At the option of the manufacturer, the lot date code may be marked on the top of the case for any case code.

NOTES:

Reference documents. In addition to MIL-PRF-55365, this specification sheet references the following documents.

MIL-STD-202

(Copies of these documents are available online at http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094).

Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA – NA

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2008-009)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.