MILITARY
SPECIFICATION

MIL-R-55044(SigC)
Amendment 2
10 August 1959

REPEATER, TELEPHONE TA-287( )/G

---

1. Paragraph 3.3.8 Ringing Signal. - Replace with the following:

3.3.8 Ringing Signal. - A chain of Repeaters TA-287( )/G each separated by 6 miles of Wire WD-1/TT shall be capable of transmitting a 20 cycle ringing signal over the equivalent of 18 miles of Wire WD-1/TT. The ringing signal shall be supplied by a band operated Telephone Set TA-312( ) through both local and common battery circuits to a telephone switchboard located at the end of the simulated 18 miles line.

2. Paragraph 4.7.8 Ringing Signal.- Replace with the following:

4.7.8 Ringing Signal.- Connect a Field Telephone TA-312( ) to the simulated line and ring a signal to a Switchboard SB-22/PT over the following circuit. Starting from a Field Telephone TA-312( ) through 6 miles of WD-1/TT Field Wire, or simulated equivalent, to a Repeater TA-287( )/G through 6 miles of Field Wire WD-1, to another Repeater TA-287( )/G and through 6 miles of field wire, terminating in a Switchboard SB-22/PT. Values per mile loop of the WD-1( )/TT field wire are as follows: D.C. Resistance; 220 ohms, Capacitance, .05 MF dry, 0.12 MF wet, Inductance, 1.5 MH wet or dry.

FSC 5805

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.