NOT MEASUREMENT SENSITIVE

MIL-T-62059B(AT)
11 September 1991
SUPERSEDING
MIL-T-62059A(AT)
12 March 1982

MILITARY SPECIFICATION

TRAILER, CARGO: WITH HYDRAULIC LIFT BODY, 2,000 POUND PAYLOAD, 2 WHEEL, COMMERCIAL

This specification is approved for use by the US Amy Tank-Automotive Command, Department of the Amy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a two-wheel commercial, hydraulic lift cargo type trailer having a minimum load carrying capacity of 2,000 pounds under normal operating conditions. Trailers procured under this specification are commercial items which are warranted by the manufacturer as specified in acquisition documents.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal, (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

* FED-STD-297 - Rustproofing of Commercial (Non-tactical) Vehicles.

MILITARY

MIL-STD-1223 - Non-Tactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* DEPARTMENT OF DEFENSE

Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

Federal Motor Vehicle Safety Standards.

* (Application for copies of DoT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)

Standards Manual

(Application for copies of the ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

SAE, INC.
SAE Standards and Recommended Practices.

J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
J588	- Turn Signal Lamps.
J682	- Rear Wheel Splash and Stone Throw Protection.
J1067	- Seven-Conductor Jacketed Cable for Truck and Trailer Connections.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

* (Application for copies of Tire and Rim Association publications should be addressed to the Tire and Rim Association Inc., 175 Montrose West Ave., Copley, OH 44321.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order Of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.4, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be the manufacturer's standard or optional items, which meet or exceed the requirements of this specification. All vehicle items shall be as represented and rated in the manufacturer's technical data. Special or mounted equipment shall be as represented in the equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be on file in the engineering offices of the procuring activity, prior to delivery of the items.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

* 3.1.1.1 Treatment and painting. The vehicle shall be treated and painted in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate service (see 6.2), the exterior color shall be in accordance with MIL-STD-1223.

* 3.1.1.2 Marking and data plates. As specified by the procuring activity for the appropriate military service (see 6.2), identification marking and data plates shall be in accordance with MIL-STD-1223. When specified (see 6.2), concealed markings shall be furnished.

* 3.1.1.3 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297.

* 3.1.1.4 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher unless they are independent. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the chassis manufacturer's standard matching hardware.

3.2 General design.

* 3.2.1 Federal Motor Vehicle Safety Standards. The vehicle shall comply with all Federal Motor Vehicle Safety Standards applicable to the type of trailer furnished and in effect on the date of manufacture.

* 3.2.2 Dissimilar metals. All dissimilar metals used throughout the vehicle shall be insulated from one another to prevent galvanic or electrolytic action.

3.2.3 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the appropriate engineering office of the procuring activity.

* 3.2.4 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.5 Prohibited materials. Asbestos materials shall not be used in any form in any part of the vehicle. No item, part or assembly shall contain radioactive materials in which the specific activity is greater than 0.002 microcurie per gram or activity per item equals or exceeds 0.01 microcuries.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

3.3 Performance. Vehicle performance requirements, as specified in 3.3.1 through 3.8.4.2, shall be met by the trailer when fully equipped, completely serviced, with payload uniformly distributed over the trailer load area, and when towed by a towing vehicle over improved and unimproved, hard, uneven terrain. The vehicle shall show no evidence of failure or malfunction of trailer, trailer components, attachments, and accessories.

* 3.3.1 Towing speed and tracking ability. When transporting the rated payload, while being towed over dry, level, smooth, improved, and prepared hard-surfaced roads at sustained speeds to 60 miles per hour (mph), and over dry unimproved and gravel roads at speeds up to 10 mph, the trailer shall follow the towing vehicle without exceeding the tracking deviations as specified in Federal Motor Carrier Safety Regulation 393.70(a).

3.3.2 Turning ability. When coupled to a towing vehicle operating in its minimum turning circle, the trailer shall follow without cramping. The trailer shall be capable of moving through an angle of not less than 60 degrees in relation to the towing vehicle without interference between vehicles. The angle shall be measured between the longitudinal axis of the trailer and the longitudinal axis of the towing vehicle at the coupling device.

3.3.3 Suspension systems. The axle, springs, accessories and components of the suspension system shall withstand the imposed loads without evidence of permanent set, part failure or malfunctioning under the operating conditions specified.

3.3.4 Brakes. The service brakes of the trailer, in conjunction with the towing vehicle (truck-trailer combination), under all conditions of loading, shall control, decelerate, and stop the vehicle combination in accordance with Federal Motor Carrier Safety Regulation 393.52.

3.3.4.1 Parking brakes. The parking brakes shall hold the fully loaded trailer on a dry, hard surfaced grade of not less than 30 percent when uncoupled from the towing vehicle, resting on the landing leg and running gear, and headed up and down the incline. The parking brake lever shall have sufficient moment arm to require not more than 30 pounds of effort for application and release.

3.3.4.2 Automatic actuation. The trailer shall be equipped with an automatically actuated device to apply the vehicle brakes upon breakaway from the towing vehicle. The breakaway system shall conform to Federal Motor Carrier Safety Regulation 393.43.

3.4 Payload and distribution. The minimum payload shall be 2,000 pounds. Requirements shall be met with the payload uniformly distributed over the loadspace.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

3.4.1 Gross vehicle weight. The gross vehicle weight shall consist of the weight of the chassis and the body with all attachments and a payload uniformly distributed in the vehicle body load area.

3.5 Dimensions. Trailer dimensions shall be as specified in table I. (See 3.3.2 for clearance between towing vehicle and trailer.)

TABLE I. Dimensions.

Feature	Dimension
Overall length	Minimum practicable
Overall width	96 inches, maximum
Overall height	Minimum practicable
Body length, (inside):	
Length	96 inches, minimum
Width	60 inches, minimum
Height (platform to ground)	18 inches, minimum
Ground clearance	9 inches, minimum

3.6 Suspension. The trailer shall be equipped with an individual wheel, spring suspension system having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded with specified payload. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted.

3.7 Axle. The trailer shall be provided with stub type independent axles. Axle rating shall be at least equal to the load imposed on the axles, measured at the ground with vehicle loaded with specified payload. The axles shall be provided with means for positive wheel alinement.

* 3.8 Wheels, rims, tires and tubes. The trailer shall be equipped with single wheels and tires. The rim size and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of tires furnished. Except when tube type tires are specified in acquisition documents, multi-piece rims shall not be furnished. Tire and rim sizes shall be the same for all wheels on the vehicle.

* 3.8.1 Tires. Steel belted radial tires shall be furnished. Tires shall be tubeless truck type with highway tread. Tires shall be of the rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the trailer fully loaded with specified payload. Tires shall conform to the Tire and Rim Association or to the European Tyre and Rim Technical Organisation recommendations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

3.8.2 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished.

3.8.3 Spare tire assembly. When specified (see 6.2), an inflated spare tire mounted on the spare wheel or rim shall be furnished. The spare tire shall be of the same size, tread design and ply rating as the tires furnished on the trailer.

* 3.8.4 Carrier for spare tire assembly. When specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. Carrier design shall enable safe removal or mounting of a spare wheel assembly using only the tools specified in 3.8.5. The carrier shall enable the safe removal and installation of the spare tire assembly from and to the vehicle and carrier without personnel positioning themselves or any part of their body under the spare tire assembly.

3.8.5 Tools. When specified (see 6.2), the vehicle shall be furnished with tools required for exchanging mounted tire assembly with the spare assembly, and shall include at least a jack, jack handle and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.9 Service brakes. Unless inertia brakes are specified (see 3.9.1), the trailer shall be equipped with a 12-volt electric brake system. Brake linings shall be of nonasbestos material. The system shall include a manual controller kit for mounting on the dash of the towing vehicle, a controller kit for synchronizing the trailer electric brakes with the brakes of the towing vehicle, and an emergency breakaway kit. Kits shall be complete with all necessary parts (except storage battery for breakaway kit) and installation instructions. Unless otherwise specified, the synchronizing controlled shall be for use with hydraulic brake equipped towing vehicles. When specified (see 6.2), the synchronizing controller shall be for use with air brake equipped towing vehicles. The kits shall be boxed, marked as to contents and securely attached to the trailer for shipment.

3.9.1 Inertia brakes. When specified (see 6.2), the trailer shall be furnished with an inertia (surge) applied hydraulic brake system in lieu of electric brakes. The inertia brake actuator, mounted on the tow bar, shall include a master cylinder, an accumulator chamber and a hold-off spring to prevent brake applications due to road shook or trailer pitching. The system shall provide for modulated brake applications, shall be protected against the entrance of foreign matter, shall include breakaway features conforming to Federal Motor Carrier Safety Regulation 393.43(d), and shall enable the trailer to be backed up without continued application of the trailer brakes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

3.9.2 Parking brakes. Manually applied parking brakes shall be furnished. Parking brakes shall conform to Federal Motor Carrier Safety Regulation 393.41. When brake cables are used, the cables shall be corrosion-resistant steel. Provisions shall be made for slack adjustment. Lubrication fittings shall be provided.

3.10 Coupling device and towbar. The trailer shall be furnished with a 2-inch ball coupling device with automatic latch which secures the trailer when the ball is engaged on the towing vehicle. A split hitch arm assembly shall be provided. The hitch arm assembly shall permit the trailer body to be lowered to ground level and raised to hauling position without uncoupling the trailer from the towing vehicle. Means shall be provided to lock the split hitch arm assembly in a longitudinal plane, when the trailer is in travel position. Safety chains shall be provided. Chains shall conform to Federal Motor Carrier Safety Regulation 393.70(d).

3.11 Load leveler. A load leveling system which maintains the trailer body in level position on the transverse plane while being lowered or raised, regardless of weight distribution in the cargo body, shall be provided.

3.12 Landing leg. The trailer shall be equipped with a retractable landing leg with caster type landing wheel, with cranking handle (rigid or swivel type) permanently installed. The landing leg shall have a vertical range of adjustment. The landing leg shall permit the operator to lower the cargo body to ground level. When the cargo body is in its maximum travel position, the landing leg shall have sufficient vertical adjustment to permit the operator to couple the coupling device to the towing vehicle when the top of the 2-inch ball of the towing device of the towing vehicle is 17.75 inches above ground level. The landing leg and related parts shall withstand, without permanent deformation, the combined static and dynamic forces due to the proportionate weight of the gross weight and impacts during coupling and uncoupling operations. The landing leg shall operate freely, and shall be protected from malfunctioning by the accumulation of foreign matter. When placed in travel position, the landing leg shall remain positively looked to provide ground clearance in the course of normal towing operations. The landing leg wheel, and any rotating components of the landing leg, shall be fitted with anti-friction bearings. Means shall be provided to lubricate the landing leg assembly and the wheel.

3.13 Lighting. The electrical lighting system shall be 12-volts. All vehicle lights, reflectors, and wiring (including electric brakes) shall conform to Federal Motor Carrier Safety Regulations 393.15, 393.19, 393.20, 393.22, 393.23, 393.25, 393.26 (a, b, c and d), and 393.27 through 393.33. Lights and reflectors shall not be mounted on vehicle bumpers.

3.13.1 Electrical receptacle. A trailer electrical receptacle with a spring-loaded cover assembly shall be installed on the forward end of the drawbar. The receptacle shall conform to SAE J560, with conductors connected and color-coded as specified in SAE J560.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

3.13.2 Brake wiring. Electric brakes shall be wired to the auxiliary circuit of the SAE J560 seven-conductor electrical connector. All wiring shall be properly mounted and secured with clamps. Wiring shall be heavy-wall thermoplastic insulated cable and shall be enclosed in conduit.

3.13.3 Electrical cable. Unless otherwise specified (see 6.2), a coiled electrical cable conforming to SAE J1067, with a cable plug at each end conforming to SAE J560, shall be provided. Both plugs shall be equipped with a grip for withdrawing from connector sockets. Stowage provisions shall have an anti-theft feature. Means of hanging the cable with the plugs pointing down shall be provided. The cable, when fully extended, shall be not less than 3 feet longer than the distance from the trailer electrical receptacle to the ball hitch.

3.1.3.4 Turn signals. Turn signals conforming to SAE J588 shall be furnished.

3.14 Trailer body and frame.

3.14.1 Body and frame construction. The trailer shall be equipped with a body and frame of all steel welded construction, with each main frame member in one piece without splices or joints. A sufficient number of full-width crossmembers shall be furnished to assure stability with the trailer fully loaded. All parts of the chassis frame, where welding is required, shall be electrically welded. Body floor and side panels shall be of adequate gage and construction so as to support trailer payload specified without evidence of deformation or permanent set. The body side and front panels shall be flanged outward into a box section at the top. The front panel shall be provided with 2 tie down devices. Each side panel shall be provided with 4 tie down devices. Tie down devices shall be welded to the cargo body and located near the upper top of each panel.

3.14.2 Tailgate. A tailgate shall be furnished. The tailgate shall be hinged at the floor level of the cargo body. The inside surface of the tailgate shall be covered with safety steel tread plate. When the tailgate is in closed position, the height of the tailgate shall be the same as the side panels. The tailgate degree of travel shall be not less than 10 degrees and not more than 15 degrees below horizontal measured to the face of the tailgate and without chains. The tailgate shall accept a rolling load equal to the specified payload without evidence of deformation or permanent set. The tailgate shall be so constructed that the approach ramp shall be not more than 0.375 inch above the ground surface. The tailgate shall have a ramp angle of 10 degrees, plus or minus 1 degree, below the longitudinal plane of the trailer body floor. The tailgate shall be provided with a latch and corrosion resistant safety chains covered with a heavy protective boot. Chains shall be of a length to support the tailgate in horizontal position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

3.14.3 Hydraulic pump. The trailer shall be provided with a hand operated pump hydraulic lift unit. The hydraulic lift unit shall be capable of lowering the cargo body to ground level and raising the cargo body not less than 16 inches to travel position. The hydraulic lift unit shall elevate the cargo body, with rated payload, from ground level to travel position in not more than 35 seconds. Means shall be provided to retain the body in travel position. Guards shall be provided to prevent damage to the hydraulic system. Raising and lowering of the cargo body loaded with the specified payload shall not require more than 20 pound-feet of torque applied to the pump lever. The hand operated hydraulic pump shall be provided with built-in reservoir and shall be completely sealed to prevent dirt from entering the system. The hydraulic cylinder system shall be provided with external seals to wipe plungers clean and keep out foreign matter. When specified (see 6.2), an electric hydraulic pump shall be furnished.

3.14.4 Body mounting. The body shall be mounted in accordance with manufacturer's standard commercial practice.

3.14.5 Fenders. The vehicle shall have fenders over the wheels. The fenders shall have inside shields and shall have sufficient crown to control mud and water from splashing on the chassis and trailer body.

* 3.14.6 Tarpaulin and bows. When specified (see 6.2), the trailer shall be furnished with stake pockets, bows, tarpaulin and tie down ropes. Not less than five bows shall be furnished. The bows shall be of the knockdown type constructed of metal or of hardwood and metal components and shall provide an inside height of not less than 60 inches, measured from the floor to inside of the tarpaulin at the center. The tarpaulin shall cover the body, with bows in place, mid extend down the exterior sides, front, and rear to at least 3 inches below the top edge of the body panels. The front and rear tarpaulin sections shall be the roll tip type. The tarpaulin shall be fabricated from waterproof and fireproof number 8 cotton duck. When specified (see 6.2), the tarpaulin shall be fabricated from vinyl coated nylon or polyester material not less than 18 ounces weight per square yard.

3.14.7 Controls and operating mechanisms. All controls and operating mechanisms shall be located for easy maintenance and replacement and shall be identified as to their function.

3.15 Lubrication. All moving parts normally requiring lubrication shall be provided with suitable means for such lubrication. Lubrication fittings shall be standard commercial type with a surface-check ball.

* 3.16 Mud flaps. Mud flaps shall be provided to the rear of the wheels in accordance with SAE J682. A metal strip not less than 0.125 inch thick and not less than 1 inch wide, extending the entire width of the mud flap, shall be installed to prevent the bolt heads or bolt nuts from damaging the mud flap. As an alternate method of attaching the mud flaps, tabs or clips with minimum surface contact dimensions of 1 inch high by 1.25 inch wide by 0.094 inch thick, shall be furnished at each bolt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

3.17 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service each vehicle for operational use including at least the following: adjustment of the brake systems; alinement of wheels; inflation of all tires; and complete lubrication of chassis, and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point.

3.18 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examination and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformity with the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.3.1 Vehicle weight. The fully equipped first production vehicle shall be weighed to determine curb weight and distribution of curb weight on the coupling device and axles. The loads imposed on the coupling device and axles shall be calculated, with the vehicle loaded, to ascertain that the suspension, axles and tires furnished are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The first production vehicle shall be road tested, fully equipped, and fully loaded by the contractor to assure the vehicle will operate in accordance with contractual requirements. Unless otherwise specified (see 6.2), the road test shall be for a distance of 1000 miles. Approximately half the mileage shall be on paved streets or highways at speeds up to 55 mph and half shall be on gravel or dirt roads at speeds up to those deemed safe. At least five sudden stops shall be made from a speed of not less than 20 mph. Tracking ability shall be observed to verify conformance to 3.3.1; turning ability shall be observed to verify conformance to 3.3.2. After the test the trailer shall be examined for evidence of misalinement, binding or other malfunction.

4.3.3 Test failure. The vehicle shall successfully complete the entire test. Failure of the vehicle to successfully complete the test shall be cause for nonacceptance of any of the contract quantity, pending correction of deficiencies and evidence of corrective action which shall prevent the recurrence of similar deficiencies in the contract quantity. Failure of the vehicle to successfully complete the test shall not constitute an excusable delay in meeting scheduled deliveries. The equipment shall be closely monitored throughout the test for interference with towing operations, and for instability as evidenced by poor tracking or uncontrollable sideslipping, skidding, swerving, or tilting. The equipment also shall be closely monitored for loosening of parts, interference between parts, leakage of fluids or lubricants, overheating of components, and for damage, permanent distortion, or excessive wear of parts and components. The equipment shall be disassembled to the extent necessary for inspection for unusual wear or damage to components. Substitution of a new trailer or replacement of a major component may require complete retest at the discretion of the Government representatives. Rejection of the test trailer shall be for damage or deficiencies, including but not limited to the following:

(a) Damage caused by collision
(b) Failure of any major component
(c) Vibration due to misalinement of wheels or frame
(d) Vibration due to the type of construction or mounting
(e) Evidence of abnormal tire wear due to misalinement or unbalance
(f) Failure of any vehicular safety device, such as brakes and electrical circuits

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

(g) Evidence of structural weakness in any part of the vehicle, vehicle components, accessories or welds
(h) Loose mountings of parts or accessories due to workmanship or vehicular operation.

4.3.4 Elevating platform test. The elevating platform shall be lowered and raised not less than 10 times, under the following conditions:

(a) With evenly distributed payload and coupled to the towing vehicle
(b) With evenly distributed payload, uncoupled from towing vehicle and resting on trailer landing leg.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting the performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.17 have been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The trailers covered by this specification are intended for general nontactical use by the Government for general purpose cargo handling.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
* (b) Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.

(c) Identification of appropriate military service for painting (see 3.1.1.1).
(d) Identification of appropriate military service for marking (see 3.1.1.2).
(e) Concealed marking, if required (see 3.1.1.2).
(f) Rustproofing, if required (see 3.1.1.3).
(g) Spare wheel or rim, if required (see 3.8.2).
(h) Spare tire assembly, if required (see 3.8.3).
(i) A carrier for a spare tire assembly, if required (see 3.8.4).
(j) Tools, if required (see 3.8.5).
(k) An air brake synchronizing controller for electric brakes, if required, in lieu of a hydraulic synchronizing controller (see 3.9).
(1) Inertia brake system, if required, in lieu of electric brakes (see 3.9.1).
(m) If an electrical cable is not required (see 3.13).
(n) Electric hydraulic pump, if required in lieu of manual pump (see 3.14.3).
(o) Stake pockets, tarpaulin, bows and tie downs, if required (see 3.14.6).
* (p) Vinyl coated nylon tarpaulin, if required (see 3.14.6).
(q) Road test mileage, if not 1,000 miles (see 4.3.2).

* 6.3 Subject term (key word) listing.

Coupling device
Hydraulic pump
Inertia brake
Landing leg
Load leveler
Synchronizing controller

6.4 Identification of changes. The margins of this document are marked with asterisks (*) to indicate where changes (additions, modifications, corrections and deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the previous issue.

Custodian:
Army - AT

Preparing activity:
Army - AT

Project No. 2330-0016

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:12Z
Check the source to verify that this is the current version before use.