MIL-C-25674C (USAF)
7 April 1980
SUPERSEDING
MIL-C-25674B (USAF)
7 November 1963

MILITARY SPECIFICATION

CONVERTER, LIQUID OXYGEN TYPE ME-3

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of liquid oxygen converter with a capacitance gaging element. The converter is designated Type ME-3. The converter does not include warming coils.

2. APPLICABLE DOCUMENTS

*2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-V-9050	Valve, Oxygen, Aircraft, Pressure Relief
MIL-C-25516	Connectors, Electrical, Miniature, Coaxial, Environmental Resistant Type, General Specification for
MIL-C-25666	Converter, Liquid Oxygen, Capacitance Type Gaging, General Specification for

STANDARDS

MILITARY

MIL-STD-831	Test Reports, Preparation of

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

FSC 1660

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:58Z
Check the source to verify that this is the current version before use.

DRAWINGS

AIR FORCE

58J3535	Capacitance Chart - 25 Liter Liquid Oxygen Converter

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

*3.1 Qualification. Converters furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (See 4.3 and 6.3).

3.2 General Specification. - The requirements of MIL-C-25666 shall apply as requirements of this specification with the exceptions and additions called out herein. When the two specifications conflict, this specification shall govern.

3.3 Design. - The converter shall conform to the dimensions and general design shown on figures 1 and 2. The converter shall have a minimum capacity of 25 liters of liquid oxygen measured at 1 atmosphere plus at least 3 percent of this volume to allow for the change in liquid density at the operating pressure. The converter shall be designed for an operating pressure of 300 psig.

3.3.1 Schematic Diagram. - The converter shall be designed in accordance with the schematic diagram shown on figure 3.

3.3.2 Design strength. The converter shall be designed to satisfy the dynamic force requirements specified in MIL-C-25666. When subjected to the acceleration test, the following exceptions to the values for G levels shall apply:

Vertical (down)	9.0G
Vertical (up)	3.0G
Lateral	4.0G

3.3.3 Relief valves. The relief valves shall conform to the performance requirements of types III and IV of MIL-V-9050 and shall be of such size and shape to fit the overall dimensions specified for the converter.

Source: https://assist.dla.mil -- Downloaded: 20260-20T06:58Z
Check the source to verify that this is the current version before use.

3.3.4 Weight. The weight of the complete converter shall not exceed 38 pounds.

3.3.5 Shock and shock safety. The requirements of 3.5.17 and 3.5.18 of MIL-C-25666 shall not apply as requirements of this specification.

3.3.6 Overpressure safety device. Safety discs or other secondary overpressure devices, as specified in 3.6.6 of MIL-C-25666 shall not be required for this converter. The design of this converter incorporates two pressure relief valves, which satisfies 3.6.6 of MIL-C-25666.

3.4 Performance.

3.4.1 Permanent volumetric expansion. The converter shall meet the performance requirements for Permanent Volumetric Expansion of MIL-C-25666 when subjected to a pneumatic or hydrostatic expansion pressure of 500 psig.

3.4.2 Evaporation loss. The evaporation loss of the converter shall not exceed 4 pounds of oxygen when the converter is tested as specified.

3.4.3 Final assembly pressure. The pressure used for the Final Assembly Pressure test shall be 320 psig.

3.4.4 Filling time. Filling time shall not exceed 10 minutes when the converter is tested as specified.

3.4.5 Buildup time. Buildup time shall not exceed 10 minutes when the converter is tested as specified.

3.4.6 Sensing element calibration. The capacitance sensing element shall have characteristics which provide for a linear relationship between electrical capacitance and volume of liquid oxygen sensed. The relationship shall be as shown on figure 4, using either the equations or the referenced drawing to determine tolerances. An example of use of the equations is as follows: At the 10 - liter test point, suppose the actual quantity of liquid oxygen is 10.1 liters. The measured capacitance must be between C maximum (max) and C minimum (min).

C min = 5.715 x 10.1 + 300.5 = 358.2 micromicrofarad (uuf)
C max = 5.875 x 10.1 + 306.5 = 365.8 micromicrofarad (uuf)

Source: https://assist.dla.mil -- Downloaded: 202610-20T06:58Z
Check the source to verify that this is the currentversion before use.

3.4.7 Delivery rate. The converter shall deliver constant gas flows up to 150 liters of gaseous oxygen per minute for not less than 2 hours with the operating pressure remaining between 295 and 315 psig after the first 15 minutes of operation. An intermittent increase or decrease of pressure by an additional 5 psig is allowable provided these variances do not exceed a 2-minute interval for any one pressure cycle.

3.4.8 Extreme temperature operation. The operating pressure shall remain between 295 and 320 psig after the first 15 minutes of flow at the low temperature and between 290 and 315 psig after the 15 minutes of flow at the high temperature. An intermittent increase or decrease of pressure by an additional 5 psig is allowable provided these variances do not exceed a 2-minute interval for any one pressure cycle.

3.4.9 Vibration. After the converter is vibrated in accordance with the procedure specified in MIL-C-25666 to a Wo value of 0.15 G^2/Hertz, the evaporation loss shall not exceed 4.5 pounds of oxygen in the buildup condition.

*3.4.10 Sensing element capacitance. The capacitance of the sensing element of the empty converter shall be 303.5 ± 2.5 uuf.

3.5 Marking of ports. Ports shall be marked as shown on figure 2.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirement as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling, inspecting, and testing procedures. Sampling, inspecting, and testing procedures shall be in accordance with MIL-C-25666.

4.3 Qualification testing.

4.3.1 Qualification test samples. The contractor shall subject two or more converters to the qualification tests specified in 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 20260-20T06:58Z
Check the source to verify that this is the current version before use.

4.3.2 Qualification test report. After the contractor completes the qualification tests, he shall prepare a qualification test report in accordance with MIL-STD-831 and shall furnish three complete copies of the report to the qualifying activity.

4.3.3 Qualification test sample for the qualifying activity. Along with the qualification test report, the contractor shall submit one converter. The sample may be a tested sample, except that it shall not be subjected to the test for gunfire specified in MIL-C-25666.

5. PACKAGING.

5.1 Preservation - packaging. The preservation - packaging of the converter shall be as specified in MIL-C-25666.

6. NOTES.

*6.1 Intended use. The converter covered by this specification is intended for use on C-141 airplanes.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Selection of applicable levels of preservation-packaging and packing.

*6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in the applicable Qaulified Products List whether or not such products have actually been so listed by that date. The attention of the contractors is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is Hq AFLC/CASO/LODS Federal Center, Battle Creek, MI 49016 and information pertaining to qualification of products may be obtained from that activity.

*6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 202610-20T06:58Z
Check the source to verify that this is the current version before use.

6.5 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible.

Custodian:
Air Force - 99


Preparing Activity:
Air Force - 99

Reviewer:
Air Force - 11

Project 1660 - F399

International interest (see MIL-C-25666)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:58Z
Check the source to verify that this is the current version before use.




FULL LEG DESIGN OPTIONAL

DIMENSIONS IN INCHES
UNLESS OTHERWISE SPECIFIED,
TOLERANCES:
DECIMALS ±.016

FIGURE 1 CONVERTER ASSEMBLY

Source: https://assist.dla.mil -- Downloaded: 202640-20T06:58Z
Check the source to verify that this is the current version before use.



TYPE OF MOUNTING BASE OPTIONAL TO CONTRACTOR
EITHER THREE MOUNTING LEGS OR A MOUNTING RING.

DIMENSIONS IN INCHES
UNLESS OTHERWISE SPECIFIED,
TOLERANCES: FRACTIONS ± 1/32
DECIMALS ~
ANGLES ± 1°

FIGURE 2. CONVERTER DESIGN

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:58Z
Check the source to verify that this is the current version before use.





FIGURE 3 SCHEMATIC DIAGRAM OF CONVERTER WITH CAPACITANCE GAGING ELEMENT

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:58Z
Check the source to verify that this is the current version before use.



CALCULATION OF MAXIMUM AND MINIMUM CAPACITANCES

FOR VALUES LESS THAN 5 LITERS	FOR VALUES GREATER THAN 5 LITERS
C MIN. = 5.6L + 301.0	C MIN. = 5.715L + 300.5
C MAX. = 6.0L + 306.0	C MAX. = 5.875L + 306.5

C = CAPACITANCE IN UUF

L = EXACT QUANTITY OF LIQUID OXYGEN AT TEST POINT IN LITERS.

CALIBRATION LIMITS, BASED ON THE ABOVE EQUATIONS, ARE SHOWN IN DIRECT READING GRAPH FORM ON DRAWING 38J3535.

FIGURE 4 CALCULATION OF CAPACITANCES

Source: https://assist.dla.mil -- Downloaded: 202610-20T06:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

HQ AFLC CASO/LODSAB
Federal Center
Battle Creek, MI 49016

Source: https://assist.dla.mil -- Downloaded: 202610-20T06:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-20T06:58Z
Check the source to verify that this is the current version before use.