INCH-POUND

MIL-DTL-25666/7 (USAF)
15 September 1995
SUPERSEDING
MIL-C-25674D (USAF)
01 April 1983

DETAIL SPECIFICATION

CONVERTER, LIQUID OXYGEN TYPE ME-3

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of liquid oxygen converter with a capacitance gauging element. It provides storage and pressurization of 25 liters of liquid oxygen to 300 pounds per square inch gauge (psig), nominal pressure and does not include warming coils. The converter is designated type ME-3.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are needed to meet the requirements specified in sections 3, 4, and 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3, 4, and 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index for Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-V-9050	Valve, Oxygen, Aircraft, Pressure Relief
MIL-C-25516	Connectors, Electrical, Miniature, Coaxial, Environmental Resistant Type, General Specification for
MIL-DTL-25666	Converter, Liquid Oxygen, Capacitance Type Gauging, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use improving this document should be addressed to: OC-ALC/TICLA, 3001 Staff Drive, Tinker AFB, OK 73145-5990 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1660
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-129 Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, and standards are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Ave, Philadelphia, PA 19111-5094)

2.3 Order of Precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this documents takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. Converters furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (See 4.2 and 6.3).

3.2 Design. The converter shall conform to the dimensions and general design shown on figures 1 and 2. The converter shall have a minimum capacity of 25 liters of liquid oxygen measured at 1 atmosphere plus at least 3 percent of this volume to allow for the change in liquid density at the operating pressure. The converter shall be designed for an operating pressure of 300 psig.

3.2.1 Schematic Diagram. The converter shall be designed in accordance with the schematic diagram shown on figure 3.

3.2.2 Design strength. The converter shall be designed to satisfy the dynamic force requirements specified in MIL-DTL-25666. When subjected to the acceleration test, the following exceptions to the values for G levels shall apply:

Vertical (down)	9G
Vertical (up)	3G
Lateral	4G

3.2.3 Relief valves. The relief valves shall conform to the performance requirements of types III and IV of MIL-V-9050 and shall be of such size and shape to fit the overall dimensions specified for the converter.

3.2.4 Weight. The weight of the complete converter shall not exceed 38 pounds.

3 2.5 Marking of ports. Ports shall be marked as shown on figure 2.

3.2.6 Overpressure safety device. Safety discs or other secondary overpressure devices, as specified in MIL-DTL-25666 shall not be required for this converter. The design of this converter incorporates two pressure relief valves.

3.3 Performance.

3.3.1 Final assembly pressure. The pressure used for the final assembly pressure test shall be 320 psig.

3.3.2 Filling time. Filling time shall not exceed 10 minutes when the converter is tested as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.

3.3.3 Evaporation loss.

3.3.3.1 Vent condition. The evaporation loss of the essentially full converter in the vent condition shall not exceed 4 pounds of oxygen when tested as specified in MIL-DTL-25666.

3.3.3.2 Buildup condition. The evaporation loss of the essentially full converter in the buildup condition shall not exceed 4 pounds of oxygen when tested as specified in MIL-DTL-25666.

3.3.4 Buildup time. Buildup time shall not exceed 10 minutes when the converter is tested as specified in MIL-DTL-25666.

3.3.5 Capacitance. The capacitance of the sensing element of the empty converter shall be 303.5 ±2.5 picofarad (pf) when tested as specified in MIL-DTL-25666.

3.3.6 Inner vessel pressure.

3.3.6.1 Inner vessel. The inner vessel shall meet the performance requirements for the inner vessel pressure test specified in MIL-DTL-25666 when subjected to a pressure of 500 psig.

3.3.6.2 Permanent volumetric expansion. The converter shall meet the performance requirements for permanent volumetric expansion as specified in MIL-DTL-25666 when subjected to a pneumatic or hydrostatic pressure of 500 psig .

3 3.7 Delivery rate.

3.3.7.1 Constant flow. The converter shall deliver a flow of gaseous oxygen up to 150 liters per minute for not less than 2 hours with the operating pressure remaining between 295 and 315 psig after the first 15 minutes of flow. The pressure shall be allowed to drop to 205 psig during the final 30 minutes of the 2 hour period. The flow at the specified rate shall be initiated within 10 minutes after the converter has reached the operating pressure. An intermittent increase or decrease of pressure by an additional 5 psig is allowable provided these variances do not exceed a 2 minute interval for any one pressure cycle. The full test procedure is specified in MIL-DTL-25666.

3.3.8 Calibration. The capacitance sensing element shall have characteristics which provide for a linear relationship between electrical capacitance and volume of liquid oxygen sensed. The relationship shall be as shown on figure 4, using either the equations or the referenced drawing to determine tolerances. An example of use of the equations is as follows: At the 10 - liter test point, suppose the actual quantity of liquid oxygen is 10.1 liters. The measured capacitance must be between C maximum (max) and C minimum (min).

C min = 5.715 x 10.1 + 300.5 = 358.2 pf
C max = 5.875 x 10.1 + 306.5 = 365.8 pf

3.3.8.1 Equations. The following equations shall be used to calculate the maximum and minimum capacitances:

Values less than 5 liters	Values greater than 5 liters
C min = 5.6L + 301.0	C min = 5.715L + 300.5
C max = 6.0L + 306.0	C max = 5.875L + 306.5

C = Capacitance in PF
L = Exact quantity in liters of liquid at test point

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.

3.3.9 Operating temperature. The operating pressure shall remain between 295 and 320 psig after the first 15 minutes of flow at the low temperature and between 290 and 315 psig after the first 15 minutes of flow at the high temperature. An intermittent increase or decrease of pressure by an additional 5 psig is allowable provided these variances do not exceed a 2-minute interval for any one pressure cycle.

3.3.10 Vibration.

3.3.10.1 Vibration. The converter shall not exhibit physical evidence of damage after completion of the vibration tests as specified in MIL-DTL-25666.

3.3.10.2 Vibration - resonance. The converter shall not exhibit physical evidence of damage after completion of the resonance portion of the vibration test specified in MIL-DTL-25666.

3.3.10.3 Vibration - cycling. The converter shall not exhibit physical evidence of damage after completion of the cycling portion of the vibration test specified (see 4.4.1).

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2)

b. Conformance inspection (see 4.3).

4.2 Qualification inspection. The qualification inspection shall consist of all the inspection methods specified in MIL-DTL-25666.

4.3 Conformance inspection. The conformance inspection shall consist of the individual tests and the sampling plans and tests specified in MIL-DTL-25666.

4.4 Vibration.

4.4.1 Vibration - cycling. The converter shall be vibrated under the cycling conditions specified herein for the applicable periods listed in table I. The frequency shall be cycled between 5 to 500 cps or as specified in the applicable associated specification and return in a 15 minute cycle at an applied double amplitude of 0.036 inch or an applied acceleration of ±10G which ever is the lower G value. The rate of change of frequency shall be logarithmic (see 3.3.10.3).

5. PACKAGING

5.1 Packaging. Packaging requirements shall be as specified in the contract or order (see 6.2).

5.2 Marking. Unless otherwise specified (see 6.2), marking shall be in accordance with MIL-STD-129.

6. NOTES.

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The 25 liter, 300 psig converter covered by this specification is intended for use on C-130, C-135, and C-141 aircraft.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Products List QPL 25666 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from, OC-ALC/TICLA, 3001 Staff Drive, Tinker AFB, OK 73145-3037.


6.4 Subject term (key word) listing.

Breathing oxygen
Capacitance
Container, inner
Container, outer
Delivery rate
Dewar
Element, sensing
Evaporation loss
Gunfire
Life support
LOX
Valve, fill-buildup-vent
Valve, pressure closing
Valve, pressure relief
Vibration


6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.

TABLE I. Range curve for converter vibration



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.




FULL LEG DESIGN OPTIONAL

DIMENSIONS IN INCHES
UNLESS OTHERWISE SPECIFIED,
TOLERANCES:
DECIMALS ±.016

FIGURE 1. Converter assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.



TYPE OF MOUNTING BASE OPTIONAL TO CONTRACTOR
EITHER THREE MOUNTING LEGS OR A MOUNTING RING.

DIMENSIONS IN INCHES
UNLESS OTHERWISE SPECIFIED,
TOLERANCES: FRACTIONS ± 1/32
DECIMALS ~
ANGLES ± 1°

FIGURE 2. Bottom view

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.





FIGURE 3. Schematic diagram

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.



Liquid oxygen (liters)	Nominal capacitance (pf)
0	303.5
5	332.5
10	361.5
15	390.4
20	419.4
25	448.4

FIGURE 4. Relationship between capacitance and volume of oxygen sensed

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.

Custodian:
Air Force - 99

Reviewer:
Air Force - 11

Preparing Activity:
Air Force - 71

Agent:
Air Force - 99

Project 1660-F687

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-DTL-25666/7	950915

3. DOCUMENT TITLE
CONVERTER, LIQUID OXYGEN TYPE ME-3

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

OC-ALC/TICLA ATTN: H. Edwards 3001 Staff Drive, Ste 1AE1/101A Tinker AFB, OK 73145-5990	b. TELEPHONE (Include Area Code) (1) Commercial (405) 736-5960	(2) AUTOVON 336-5960
	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-Feb-20 06:56Z
Check the source to verify that this is the current version before use.